



FCC

CANADA



IC-F52D-UL


LMR for Haz. Loc. CL I Div 1 Grp C D, CL II Div 1 Grp E F G, CL III. CL I Div 2 Grp A B C D. T3C. Tamb=-20°C to +60°C. INTRINSICALLY SAFE when used with Model BP-292UL battery pack.  
⚠ Use with UL Listed ICOM batteries and ACC. See Instruction Manual.



FCC ID:AFJ395100

Contains

FCC ID:AFJ381500




SERIAL NO.

0 0 0 0 0 0 0 0


Icom Inc.

MADE IN JAPAN



Model:IC-F52D-UL


LMR for Haz. Loc. CL I Div 1 Grp C D, CL II Div 1 Grp E F G, CL III. CL I Div 2 Grp A B C D. T3C. Tamb=-20°C to +60°C. INTRINSICALLY SAFE when used with Model BP-292UL battery pack.  
⚠ Use with UL Listed ICOM batteries and ACC. See Instruction Manual.



IC: 202D-395100

HVIN: 395100-02

Contains IC: 202D-381500




SERIAL NO.


0 0 0 0 0 0 0 0

Icom Inc.

MADE IN JAPAN




Restricted to occupational use to satisfy FCC RF exposure limits. See user manual for operating requirements.



Restricted to occupational use to satisfy FCC RF exposure limits. See user manual for operating requirements.



UL certification has not been obtained, UL Listing mark  is not printed. The contents may change after obtaining the certification.

See Pictures.pdf for serial plates photographs.