

FCC TEST REPORT

Under :

FCC 15 Subpart C, Paragraph 15.231

Prepared For :

Forcome(Shanghai) Co., Ltd.

Building 109, No. 255, South Sizhuan Road, Shanghai 201612, China

FCC ID: 2AEZB-27880
EUT: XT2009Wireless Remote Control Search Light
Model: #27880

June 2, 2015 Issue Date:
Original Report Report Type:
<i>Eric Guo</i> Test Engineer: Eric Guo
<i>Apollo Liu</i> Review By: Apollo Liu / Manager

The test report consists 24 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Ke Mei Ou Laboratory Corporation. The test result in the report only applied to the tested sample.

TABLE OF CONTENTS

1. General Information	3
1. 1 Notes	3
1. 2 Testing Laboratory	3
1. 3 Details of Applicant	3
1. 4 Application Details	3
1. 5 Test Item	3
1. 6 Test Standards	3
2. Technical Test	4
2. 1 Summary of Test Results	4
3. EUT Modifications	4
4. Conducted Power Line Test	5
4. 1 Test Equipment	5
4. 2 Test Procedure	5
4. 3 Test Setup	5
4. 4 Configuration of The EUT	6
4. 5 EUT Operating Condition	7
4. 6 Conducted Power Line Emission Limits	7
4. 7 Conducted Power Line Test Result	7
5. Radiated Emission Test	8
5. 1 Test Equipment	8
5. 2 Test Procedure	8
5. 3 Radiated Test Setup	8
5. 4 Configuration of the EUT	9
5. 5 EUT Operating Condition	9
5. 6 Radiated Emission Limit	9
5. 7 Radiated Emission Test Result	10
6. Technical Characteristic	11
6. 1 Band Edge	11
6.1.1 Test Equipment	11
6.1.2 Test Procedure	11
6.1.3 Radiated Test Setup	11
6.1.4 Configuration of The EUT	12
6.1.5 EUT Operating Condition	12
6.1.6 Band Edge FCC 15.231 Limit	12
6.1.7 Band Edge Test Result	12
6. 2 Calculation of Average Factor	13
6. 3 Manually Operated Transmitter Deactivation	15
6. 4 Antenna Requirement	16
7. Photos of Testing	17
7. 1 EUT Test Photographs	17
7. 2 EUT Detailed Photographs	18
8. FCC ID Label	23
9. Test Equipment	24

1. General Information

1.1 Notes

The test results of this report relate exclusively to the test item specified in 1.5. The KMO Lab does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the KMO Lab.

1.2 Testing Laboratory

Ke Mei Ou Laboratory Co., Ltd.

ANSI-ASQ National Accreditation Board/ACLASS ISO/IEC 17025 Accredited Lab for telecommunication standards. The Registration Number is AT-1532. The testing quality system meets with ISO/IEC-17025 requirements, This approval results is accepted by MRA of ILAC.

FCC Test Site Registration Number: 962205

IC Test Site Registration Number: 4986A-2

Internet: www.kmolab.com

1.3 Details of Applicant

Name : Forcome(Shanghai) Co., Ltd.

Address : Building 109, No. 255, South Sizhuan Road, Shanghai 201612, China

1.4 Application Details

Date of Receipt of Application : April 27, 2015
Date of Receipt of Test Item : April 27, 2015
Date of Test : May 12~June 2, 2015

1.5 Test Item

Manufacturer : Same as applicant
Address : Same as applicant
Trade Name : ULTRA-TOW
Model No.(Base) : #27880
Model No.(Extension) : XT2009
Description : XT2009Wireless Remote Control Search Light

Additional Information

Frequency : 433.920MHz
Transmission Range : N/A
Number of Channels : 1
Antenna : Internal PCB
Power Supply : DC 9V(Power by battery)
Extreme Temp. Tolerance : N/A

1.6 Test Standards

Title 47 CFR, FCC Part 15, including: 15.203, 15.205, 15.207, 15.209, 15.231a, 15.231b and 15.231c.

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

2. Technical Test

2.1 Summary of Test Results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.203	Antenna Requirement	PASS	Complies
FCC Part 15, Paragraph 15.207	Conducted Test	N/A	Owing to the DC operation of EUT, this test item is not performed.
FCC Part 15 Subpart C Paragraph 15.231(a)	Periodic Operation Characteristics	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.231(b) Limit	Field Strength of Fundamental	PASS	Complies
FCC Part 15, Subpart C Paragraph 15.231(b) Limit & Paragraph 15.209, Paragraph 15.205(b)	Radiated Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.231(c) Limit	Measured 20 dB Bandwidth	PASS	Complies.

3. EUT Modifications

No modification by test lab.

4. Conducted Power Line Test


4.1 Test Equipment

Please refer to Section 9 this report.

4.2 Test Procedure

The EUT was tested according to ANSI C63.4 - 2003. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm / 50 uHenry as specified by section 5.1 of ANSI C63.4 - 2003. cables and peripherals were moved to find the maximum emission levels for each frequency.

4.3 Test Setup



For the actual test configuration, Please refer to the related items – Photos of Testing.

4. 4 Configuration of the EUT

The EUT was configured according to ANSI C63.4-2003. EUT was used DC 9V. Press any key of the EUT. Once the button releasing, the transmission will be stopped within 3 second. The EUT transmitted continuously and the duty cycle of transmitting was set to worst case condition, which provided by manufacturer during all the tests. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model #	FCC ID
XT2009Wireless Remote Control Search Light	Same as applicant	#27880	2AEZB-27880

B. Internal Devices

Device	Manufacturer	Model #	FCCID / DoC
N/A			


C. Peripherals

Device	Manufacturer	Model # Serial #	FCC ID/ DoC	Cable
N/A				

4.5 EUT Operating Condition

Operating condition is according to ANSI C63.4 - 2003.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.



4.6 Conducted Power Line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHz)	Class A QP/AV	Class B QP/AV
0.15 – 0.5	79/66	66-56/56-46
0.5 – 5.0	73/60	56/46
5.0 - 30	73/60	60/50

NOTE : In the above table, the tighter limit applies at the band edges.

4.7 Conducted Power Line Test Result

Owing to the DC operation of EUT, this test item is not performed.

5. Radiated Emission Test


5.1 Test Equipment

Please refer to Section 9 this report.

5.2 Test Procedure

1. The EUT was tested according to ANSI C63.4 - 2003.
2. The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
3. The frequency spectrum from 9 kHz to 25 GHz was investigated. All readings from 9 kHz to 150 kHz are quasi-peak values with a resolution bandwidth of 200 Hz. All readings from 150 kHz to 30 MHz are quasi-peak values with a resolution bandwidth of 9 KHz. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. All readings are above 1 GHz , peak values with a resolution bandwidth of 1 MHz . Measurements were made at 3 meters.
4. The emissions from the EUT were measured continuously at every azimuth by rotating the turntable. The Receiving antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency. Emissions below 30MHz were measured with a loop antenna while emission above 30MHz were measured using a broadband E-field antenna.
5. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4 - 2003.

5.3 Radiated Test Setup



For the actual test configuration , please refer to the related items – Photos of Testing.

5.4 Configuration of the EUT

Same as section 4.4 of this report

5.5 EUT Operating Condition

Same as section 4.5 of this report.

5.6 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below :

A. FCC Part 15 Subpart C Paragraph 15.231(b) Limit

Calculation of Radiated Emissions limits for FCC Part 15.231b (260-470MHz)

Field Strength of Fundamental / Harmonic Frequencies:

The calculation involves a linear interpolation of 3750 to 12500 uV/m over 260 - 470 MHz, where field strength of the fundamental frequency (f_0) when, 260 ≤ f_0 ≤ 470 MHz, can be found by: $41.6667(f_0) - 7083.3333$, where f_0 is in MHz.

Field Strength of Spurious / Harmonic Frequencies:

The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

where $f_0 = 433.920$ MHz

Fundamental: $41.6667(433.920) - 7083.3333 = 10996.681164$ uV/m

Fundamental Frequency (MHz)	Field Strength of Fundamental (3m)		Field Strength of Harmonics (3m)	
	uV/m	dBuV/m	uV/m	dBuV/m
433.920	10996.681164	80.83	-	60.83

- Note:**
- (1) RF Voltage (dBuV) = 20 log RF Voltage (uV)
 - (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
 - (3) The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency (MHz)	Distance (m)	Field Strength (dBuV/m)
30 - 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

- Note:**
- (1) RF Voltage (dBuV) = 20 log RF Voltage (uV)
 - (2) In the Above Table, the tighter limit applies at the band edges.
 - (3) Distance refers to the distance in meters between the measuring instrument antenna and the

A. Fundamental Radiated Emission Data

Freq. (MHz)	Emission Peak (dBuV/m)	Calculated Average Level (dBuV/m)	HORIZ / VERT	Limits (dBuV/m)	Margin (dB)
433.920	69.99	62.29	HORIZ	80.83	-18.54
433.920	67.97	60.27	VERT	80.83	-20.56

B. General Radiated Emission Data & Harmonics Radiated Emission Data

Freq. (MHz)	Emission Peak (dBuV/m)	Calculated Average Level (dBuV/m)	HORIZ / VERT	Limits (dBuV/m)	Margin (dB)
867.960	65.81	58.11	HORIZ	60.83	-2.72
867.960	64.33	56.63	VERT	60.83	-4.20
1301.800	43.54	35.84	HORIZ	60.83	-24.99
1301.800	42.78	35.08	VERT	60.83	-25.75
	-	-	HORIZ	-	-
	-	-	VERT	-	-

Report #: KSZ2015042701J

6. Technical Characteristic

6.1 Band Edge


6.1.1 Test Equipment

Please refer to Section 9 this report.

6.1.2 Test Procedure

1. The EUT was tested according to ANSI C63.4 - 2003.
2. The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
3. The frequency spectrum from 9 kHz to 25 GHz was investigated. All readings from 9 kHz to 150 kHz are quasi-peak values with a resolution bandwidth of 200 Hz. All readings from 150 kHz to 30 MHz are quasi-peak values with a resolution bandwidth of 9 KHz. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. All readings are above 1 GHz , peak values with a resolution bandwidth of 1 MHz . Measurements were made at 3 meters.
4. The emissions from the EUT were measured continuously at every azimuth by rotating the turntable. The Receiving antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency. Emissions below 30MHz were measured with a loop antenna while emission above 30MHz were measured using a broadband E-field antenna.
5. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4 - 2003.

6.1.3 Radiated Test Setup



For the actual test configuration , please refer to the related items – Photos of Testing

6.1.4 Configuration of The EUT

Same as section 4 . 4 of this report

6.1.5 EUT Operating Condition


Same as section 4 . 5 of this report.

6.1.6 Band Edge FCC 15.231 Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. Bandwidth is determined at the points 20dB down from the modulated carrier.
 $B.W(20dBc) \text{ Limit} = 0.25\% \times f \text{ (MHz)} = 0.25\% \times 433.920\text{MHz} = 1.0848\text{MHz}$
From the plot, the bandwidth is observed to be 0.492MHz, at 20dBc where the bandwidth limit is 1.0848MHz.

6.1.7 Band Edge Test Result

Product	: XT2009Wireless Remote Control	Test Mode	: Normal
	Search Light		
Test Item	: Band Edge Data	Temperature	: 25 °C
Test Voltage	: DC 9V	Humidity	: 56%RH
Test Result	: PASS		



Date: 2.JUN.2015 14:20:50

- Note:**
- (1) The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.
 - (2) The average measurement was not performed when the peak measured data under the limit of average detection.

6.2 Calculation of Average Factor

For a graphical presentation of the data bursts being transmitted from the transmitter, refer to below figures for the amount of time that the transmitter is active. Figures are provided that show the On-time of the transmitter that occurs when a key is held down continuously, and also over a 150 milliseconds (worst case) period. In the 150 millisecond window, with 141.6ms packet length, and 141.6 ms between packets with each packet consisting of 126 bits we will obtain a total of 1 packet transmitted during the 141.6 ms interval. If all bits are high and each bit is 0.456ms long, the On-time for a burst is; $0.456\text{ms} \times 126 \text{ bits} = 57.456\text{ms}$.


The duration of one cycle = 141.6ms

Effective period of the cycle = 57.456ms

DC = $57.456\text{ms} / 141.6\text{ms} = 0.41$


Averaging Factor = $20 \times \log(\text{DC}) = -7.7\text{dB}$

Duty Cycle Detail, Over a 150 ms Interval




Date: 2.JUN.2015 14:26:49

Duty Cycle Detail, Over a 3.0 ms Interval



Date: 2.JUN.2015 14:28:54

Duty Cycle Detail, Over a 3.0 ms Interval




Date: 2.JUN.2015 14:29:29

6.3 Manually Operated Transmitter Deactivation

15.231(a) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Transmitter Turn-Off Release Time, Upon Momentary Activation of Push Switch
(Showing release time less than 3 second)



6.4 Antenna Requirement



An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

The EUT's antenna is a trace on the PCB. The EUT meets the requirements of this section.

7. Photos of Testing


7.1 EUT Test Photographs


Radiated Emission test view




7.2 EUT Detailed Photographs

EUT top view






EUT bottom view







EUT inside whole view



Main board component side



Main board solder side




8. FCC ID Label

FCC ID: 2AEZB-27880

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The Label must not be a stick-on paper label. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Proposed Label Location on EUT



9. Test Equipment

The following test equipments were used during the radiated & conducted emission test:

Equipment/ Facilities	Manufacturer	Model #	Serial No.	Due Date
Turntable	Innco systems GmbH	CT-0801	KMO-SZ114	NCR
Antenna Tower	Innco systems GmbH	MM4000-PP	KMO-SZ115	NCR
Controller	Innco systems GmbH	CO2000	KMO-SZ116	NCR
Pre-Amplifier	Agilent	87405C	KMO-SZ155	Dec.6, 2015
Pre-Amplifier	Com-Power	PAM-840	KMO-SZ156	Dec.6, 2015
Horn Antenna	Com-Power	AH-840	KMO-SZ157	Dec.6, 2015
EMI Test Receiver	Rohde & Schwarz	ESPI7	KMO-SZ002	June 27, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP40	KMO-SZ003	June 27, 2015
Signal Generator	FLUKE	PM5418+Y/C	KMO-SZ020	May 27, 2016
Loop Antenna	Rohde & Schwarz	HFH2-Z2	KMO-SZ004	Jan. 30, 2016
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	KMO-SZ005	Sep.18, 2015
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	KMO-SZ006	Sep.18, 2015
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9120D	KMO-SZ007	Sep.18, 2015
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9120D	KMO-SZ008	Sep.18, 2015
AMN	Rohde & Schwarz	ESH3-Z5	KMO-SZ009	June 27, 2015
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	KMO-SZ077	Nov.29, 2015
ISN	SCHWARZBECK	NTFM 8158 CAT3	KMO-SZ070	Nov.19, 2015
ISN	SCHWARZBECK	NTFM 8158 CAT5	KMO-SZ071	Nov.19, 2015
ISN	SCHWARZBECK	NTFM 8158 CAT6	KMO-SZ072	Nov.19, 2015
KMO Shielded Room	KMO	KMO-001	KMO-SZ036	NCR
Coaxial Cable with N-Connectors	SCHWARZBECK	AK9515H	KMO-SZ037	Sep.18, 2015
AC Power Source / Analyzer	Agilent	6813B	KMO-SZ166	July 22, 2015
Digital Radio Communication Tester	Rohde & Schwarz	CMD60	KMO-SZ169	April 10, 2016
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	KMO-SZ170	April 10, 2016
Program Control Telephone Exchanger	Excelltel	CDX8000-M	KMO-SZ221	NCR
3m Anechoic Chamber	KMO	KMO-3AC	KMO-3AC-1	Nov.12, 2016
Temperature Chamber	TABAI	PSL-4GTW	N/A	Feb.10, 2016