

Standalone SAR test exclusion considerations

RF feautre	Mode	Transmitting Frequency(MHz)	Test separation distance (mm)	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) ^{Note1,2}	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
BT	BDR(1Mbps)	2 480.00	5.0	-0.10	5.35	3.427 7	1.08	3.00
BT	EDR(2,3Mbps)	2 480.00	5.0	-0.10	4.35	2.722 7	0.86	3.00
BLE	GFSK(1Mbps)	2 480.00	5.0	-0.10	0.00	1.000 0	0.31	3.00

Note1. For bluetooth(BDR, EDR), the max tune-up power was based on time-averaged power.

Max Time Avg. Power = Max Burst Avg. Power + Duty facor

Duty facotr = $10 \times \log (TX_{on\ time} / Tx_{on+off\ time}) = 10 \times \log (2.88ms/3.75ms) = -1.15\ dB$

Note2. Please refer to the operation description for Max tune-up power.

KDB 447498 D01 clasue 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separationn distances $\leq 50\ mm$

$[(\max. \text{ power of channel, including tune-up tolerance, mW }) / (\min. \text{ test separation distance, mm })] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1g SAR and ≤ 7.5 for 10g extremity SAR

Sample Calculation

$$= [(3.4277\text{mW} / 5\text{mm})] \times [\sqrt{2.48\text{GHz}}] = 1.08$$

Note. The calculation result was rounded to two decimal place for comparison.

Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required