





FCC Part 15.247 TEST REPORT

For

IONE ELECTRONIC TECHNOLOGY CO., LTD. TAIWAN BRANCH

8F-2, #75, sec 1, Hsin Tai Wu Rd., Hsi Chih District, New Taipei City, Taiwan, R.O.C.(Far East World Center-Bldg. A)

FCC ID: 2APDTTS-A05BT-ANC

Report Type	Original Report
Product Name:	TUNE IN - Streaming
Model Name:	TS-A05BT-ANC
Report Number :	RXZ190624003-00A
Report Date :	2019/10/21
Reviewed By :	Zeus Chen Zeus Cher

Prepared By:

Bay Area Compliance Laboratories Corp.(Linkou Laboratory)

No. 6, Wende 2Rd., Guishan Dist., Taoyuan City 33382, Taiwan (R.O.C.)

Tel: +886 (3)3961072; Fax: +886 (3) 3961027

www.bacl.com.tw

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Revision History

Revision	Report Number	Issue Date	Description
1.0	RXZ190624003-00A	2019/10/21	Original Report

TABLE OF CONTENTS

1	GEN	IERAL INFORMATION	5
	1.1	PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
	1.2	OPERATION CONDITION OF EUT.	
	1.3	OBJECTIVE AND TEST METHODOLOGY	
	1.4	Measurement Uncertainty	
	1.5	TEST FACILITY	6
2	SYS	TEM TEST CONFIGURATION	7
	2.1	TEST CHANNELS AND DESCRIPTION OF WORST TEST CONFIGURATION	7
	2.2	SUPPORT EQUIPMENT LIST AND EXTERNAL CABLE LIST	7
	2.3	BLOCK DIAGRAM OF TEST SETUP	
	2.4	DUTY CYCLE	8
3	SUN	MMARY OF TEST RESULTS	9
4	FCC	§15.247(I), §1.1307, § 2.1093 - RF EXPOSURE	10
_	4.1	APPLICABLE STANDARD	
	4.1	RF Exposure Evaluation Result	
5	FCC	§15.203 - ANTENNA REQUIREMENTS	11
	5.1	Applicable Standard	
	5.2	Antenna List and Details	11
6	FCC	§15.207 - AC LINE CONDUCTED EMISSIONS	12
	6.1	Applicable Standard	12
	6.2	EUT SETUP AND TEST PROCEDURE	
	6.3	TEST EQUIPMENT LIST AND DETAILS	13
	6.4	TEST ENVIRONMENTAL CONDITIONS	
	6.5	TEST DATA AND TEST PLOT	14
7	FCC	§15.209, §15.205, §15.247(D) – SPURIOUS EMISSIONS	16
	7.1	Applicable Standard	16
	7.2	EUT SETUP AND TEST PROCEDURE	18
	7.3	TEST EQUIPMENT LIST AND DETAILS	
	7.4	TEST ENVIRONMENTAL CONDITIONS	
	7.5	TEST RESULT	20
8	FCC	§15.247(A)(2) – 6 DB EMISSION BANDWIDTH	24
	8.1	APPLICABLE STANDARD	24
	8.2	TEST PROCEDURE	
	8.3	TEST EQUIPMENT LIST AND DETAILS	
	8.4	TEST ENVIRONMENTAL CONDITIONS	
	8.5	TEST RESULTS	
9	FCC	§15.247(B) (3) – MAXIMUM OUTPUT POWER	26
	9.1	Applicable Standard	
	9.2	TEST PROCEDURE	
	9.3	TEST EQUIPMENT LIST AND DETAILS	
	9.4 9.5	TEST ENVIRONMENTAL CONDITIONS	
10) FCC	§15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	
	10.1	Applicable Standard	
	10.2	TEST PROCEDURE	-
	10.3	TEST EQUIPMENT LIST AND DETAILS	
	10.4 10.5	TEST ENVIRONMENTAL CONDITIONS	
		§15.247(E) – POWER SPECTRAL DENSITY	
		• · · · · · · · · · · · · · · · · · · ·	

Bay Area Compliance Laboratories Corp.(Linkou Laboratory)

11.1	APPLICABLE STANDARD	31
	TEST PROCEDURE	
11.3	TEST EQUIPMENT LIST AND DETAILS	31
11.4	TEST ENVIRONMENTAL CONDITIONS	31
11.5	TEST RESULTS	32

1 General Information

1.1 Product Description for Equipment under Test (EUT)

Applicant	IONE ELECTRONIC TECHNOLOGY CO., LTD. TAIWAN BRANCH 8F-2, #75, sec 1, Hsin Tai Wu Rd., Hsi Chih District, New Taipei City, Taiwan, R.O.C.(Far East World Center-Bldg. A)
Manufacturer IONE ELECTRONIC TECHNOLOGY CO., LTD. TAIWAN BRAM 8F-2, #75, sec 1, Hsin Tai Wu Rd., Hsi Chih District, New Ta Taiwan, R.O.C.(Far East World Center-Bldg. A)	
Product (Equipment)	TUNE IN - Streaming
Model Name	TS-A05BT-ANC
Frequency Range	2402 - 2480 MHz
Number of Channels	40 Channels
Output Power	-2.22 dBm (0.0006 W)
Modulation Type	GFSK
Related Submittal(s)/Grant(s)	FCC Part 15.247 DSS with FCC ID: 2APDTTS-A05BT-ANC
Received Date	Jun. 24, 2019
Date of Test	July. 12, 2019 ~ Oct 21, 2019

^{*}All measurement and test data in this report was gathered from production sample serial number: 190624003(Assigned by BACL, LinKou).

1.2 Operation Condition of EUT

	AC 120 V/60 Hz Adapter By Power Cord.
Power Operation (Voltage Range)	 □ DC Type □ DC Power Supply: 5Vdc to connector port □ Battery ☑ External from USB Cable 5Vdc □ External DC Adapter
	☐ Host System

Page 5 of 32

1.3 Objective and Test Methodology

The Objective of this Test Report was to document the compliance of the IONE ELECTRONIC TECHNOLOGY CO., LTD. TAIWAN BRANCH. Appliance (Model: TS-A05BT-ANC) to the requirements of the following Standards:

- -Part 2, Subpart J, Part 15, Subparts A and C, section 15.247 of the Federal Communication Commission's rules.
- ANSI C63.10-2013 of t American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
- -KDB 558074 D01 15.247 Meas Guidance v05r02.

1.4 Measurement Uncertainty

Parameter	Expanded Measurement uncertainty	
RF output power with Power Meter	± 0.55 dB	
Occupied Channel Bandwidth	± 4.54 Hz	
RF Conducted test with Spectrum	± 1.45 dB	
AC Power Line Conducted Emission	± 2.66 dB	
Radiated Below 1G	± 3.57 dB	
Radiated Above 1G-18G	± 4.29 dB	
Radiated Above 18G-40G	± 4.67 dB	

1.5 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Linkou) to collect test data is located on

No.6, Wende 2Rd., Guishan Dist., Taoyuan City 33382, Taiwan (R.O.C.).

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database. The FCC Registration No.: 0027578244. Designation No.: TW3546. The Test Firm Registration No.: 181430.

Page 6 of 32

2 System Test Configuration

2.1 Test Channels and Description of Worst Test Configuration

The system was configured for testing in testing mode which was provided by manufacturer.

No special accessory, No modification was made to the EUT and No special equipment used during test.

For BLE, there are totally 40 channels.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404		-
2	2406	-	
3	2408	37	2476
		38	2478
19	2440	39	2480

For BLE: Channel 0, 19 and 39 were tested.

The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the Peak power and PSD across all date rates bandwidths, and modulations.

Modulation Used for Conformance Test					
Configuration NTX Data Rate Worst Data Rate					
BLE mode	1	125 kbps-1 Mbps	1 Mbps		

Worst Case of Power Setting					
EUT Exercise Software QRCT3					
Configuration	NTX	Low CH Mid CH High CH			
BLE mode	1	Default	Default	Default	


2.2 Support Equipment List and External Cable List

No.	Description	Manufacturer	Model Number
Α	Notebook PC	DELL	Latitude E6410
В	Adapter	MI	A1718 (Apple)

No.	c. Cable Description Shielding Type		Length (m)	From	То
1	USB Cable	Non-Shielded	1.0	EUT	Adapter
2	USB Cable	Non-Shielded	1.0	EUT	NB

Page 7 of 32

2.3 Block Diagram of Test Setup




2.4 Duty Cycle

According to KDB 558074 D01 15.247 Meas Guidance v05:

All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum power transmission duration, T, are required for each tested mode of operation.

Configuration	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Factor (dB)
BLE mode	0.384	0.626	61.00	2.15



*Note: Duty Factor = 10*log (1/Duty cycle)

Page 8 of 32

Report No.: RXZ190624003-00A

3 Summary of Test Results

FCC Rules	Description of Test	Result
§15.247(i), §1.1307, § 2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247(a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Page 9 of 32

4 FCC§15.247(i), §1.1307, § 2.1093 - RF Exposure

4.1 Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·

 $[Vf(GHz)] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

4.2 RF Exposure Evaluation Result

RF Exposure Evaluation:

Frequency (MHz)	Tunp-up	Power	Evaluation Distrance (mm)	SAR Excluion Result	Extremity SAR Exclusion Limit
(2)	(dBm)	(mW)	()	nesure	(1g SAR)
2402-2480	-1.00	0.794	5	0.2528	7.5

Result: SAR evaluation is not necessary.

Page 10 of 32

5 FCC §15.203 - Antenna Requirements

5.1 Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna does not exceed 6dBi

5.2 Antenna List and Details

Brand	Antenna Type	Antenna Gain	Result
YAGEO	Chip Antenna	1.69 dBi	Compliance

The EUT has an internal antenna arrangement, which was permanently attached, fulfill the requirement of this section.

Page 11 of 32

6 FCC §15.207 - AC Line Conducted Emissions

6.1 Applicable Standard


According to FCC §15.207 and §15.407(b)(6),

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Francisco (BALLE)	Conducted Limit (dBuV)				
Frequency (MHz)	Quasi-Peak	Average			
0.15-0.5	66 to 56 Note 1	56 to 46 ^{Note 2}			
0.5-5	56	46			
5-30	60	50			

Note 1: Decreases with the logarithm of the frequency. Note 2: A linear average detector is required

6.2 EUT Setup and Test Procedure



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits

Page 12 of 32

Report No.: RXZ190624003-00A

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz. During the conducted emission test, the EMI test receiver was set with the following configurations

Frequency Range	Receiver RBW
150 kHz - 30 MHz	9 kHz

During the conducted emission test, the adapter was connected to the outlet of the LISN. Maximizing procedure was performed on the six (6) highest emissions of the EUT. All data was recorded in the Quasi-peak and average detection mode.

6.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.	
Conduction Room						
LISN	Rohde & Schwarz	ENV216	100010	2019/09/02	2020/09/01	
EMI Test Receiver	Rohde & Schwarz	ESR3	102430	2019/03/27	2020/03/26	
Pulse Limiter	SCHWARZBECK	VSTD 9561-F	00432	2019/08/28	2020/08/27	
RF Cable	EMCI	EMCCFD300-BM- BM-8000	180526	2019/08/08	2020/08/07	
Software	Audix	e3 v9	E3LK-03	N.C.R	N.C.R	

^{*}Statement of Traceability: The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).


6.4 Test Environmental Conditions

Temperature:	25 ℃	Relative Humidity:	50 %
ATM Pressure:	1010 hPa	Test Engineer:	David Hsu
Test Date:	2019-10-21		

Page 13 of 32

6.5 Test Data and Test Plot

Mode: AC 120 V/60 Hz, Line



		Read			Limit	0ver	
	Freq	Level	Level	Factor	Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dBuV	——dB	
1	0.168	19.88	39.82	19.94	65.07	-25.25	QP
2	0.168	4.75	24.69	19.94	55.07	-30.38	Average
3	0.252	15.48	35.42	19.94	61.70	-26.28	QP
4	0.252	1.11	21.05	19.94	51.70	-30.65	Average
5	0.338	12.12	32.07	19.95	59.25	-27.18	QP
6	0.338	0.77	20.72	19.95	49.25	-28.53	Average
7	0.508	12.21	32.17	19.96	56.00	-23.83	QP
8	0.508	7.75	27.71	19.96	46.00	-18.29	Average
9	6.294	15.27	35.32	20.05	60.00	-24.68	QP
10	6.294	7.49	27.54	20.05	50.00	-22.46	Average
11	19.511	12.65	32.82	20.17	60.00	-27.18	QP
12	19.511	3.28	23.45	20.17	50.00	-26.55	Average


Note:

Level = Read Level + Factor

Over Limit (Margin) = Level – Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

Mode: AC 120V/60 Hz, Neutral



		Read			Limit	0ver	
	Freq	Level	Level	Factor	Line	Limit	Remark
	MHz	dBuV	dBuV	——dB	dBuV	——dB	
1	0.169	19.57	39.52	19.95	65.01	-25.49	QP
2	0.169	3.11	23.06	19.95	55.01	-31.95	Average
3	0.250	14.62	34.56	19.94	61.76	-27.20	QP
4	0.250	-0.87	19.07	19.94	51.76	-32.69	Average
5	0.330	8.59	28.54	19.95	59.45	-30.91	QP
6	0.330	-3.83	16.12	19.95	49.45	-33.33	Average
7	0.433	7.15	27.12	19.97	57.20	-30.08	QP
8	0.433	-3.94	16.03	19.97	47.20	-31.17	Average
9	6.097	13.89	33.98	20.09	60.00	-26.02	QP
10	6.097	4.84	24.93	20.09	50.00	-25.07	Average
11	20.630	9.53	29.85	20.32	60.00	-30.15	QP
12	20.630	0.64	20.96	20.32	50.00	-29.04	Average

Note:

Level = Read Level + Factor

Over Limit (Margin) = Level – Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

7 FCC §15.209, §15.205, §15.247(d) – Spurious Emissions

7.1 Applicable Standard

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1MHz.

As Per FCC §15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	13.36-13.41	399.9-410	4.5-5.15
0.495-0.505	16.42-16.423	608-614	5.35-5.46
2.1735-2.1905	16.69475-16.69525	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6

Page 16 of 32

Report No.: RXZ190624003-00A

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3


^{**} Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c).


Page 17 of 32

Report No.: RXZ190624003-00A

7.2 EUT Setup and Test Procedure



Radiated Above 1G



Radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part 15.209 and FCC 15.247 Limits.

The system was investigated from 30 MHz to 26.5 GHz. During the radiated emission test, the EMI test receiver was set with the following configurations measurement method 6.3 in ANSI C63.10.

Frequency Range	RBW	VBW	Detector	Duty cycle	Measurement method
30-1000 MHz	120 kHz	/	QP	-	QP
	1 MHz	3 MHz	PK	-	PK
Above 1 GHz	1 MHz	3 MHz	RMS	>98%	Ave
	1 MHz	1/T	PK	<98%	Ave

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations. All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Page 18 of 32

7.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
		966A Roon	n		
Bilog Antenna/6 dB Attenuator	SUNOL SCIENCES & EMEC /EMCI	JB3/N-6-06	A111513/AT-N0668	2019/03/29	2020/03/28
Horn Antenna	ETS-Lindgren	3115	00109141	2019/07/05	2020/07/04
Horn Antenna	ETS-Lindgren	3160-09	00123852	2019/07/11	2020/07/10
Preamplifier	A.H. Systems	PAM-0118P	478	2019/03/28	2020/03/27
Preamplifier	A.H. Systems	PAM-1840VH	174	2019/02/18	2020/02/17
Signal and Spectrum Analyzer	Rohde & Schwarzr	FSV40	101434	2019/04/17	2020/04/16
Microflex Cable (1m)	EMCI	EMC106-SM-SM-2000	93D0127	2019/05/05	2020/05/04
Microflex Cable (2m)	MTJ	H0919	MFR64639 226389-002	2019/05/05	2020/05/04
Microflex Cable (8m)	UTIFLEX	UFA210A-1-3149- 300300	160309-1	2019/05/05	2020/05/04
Turn Table	Chaintek	T-200-S-1	003501	N.C.R	N.C.R
Antenna Tower	Chaintek	MBD-400-1	003504	N.C.R	N.C.R
Controller	Chaintek	3000-1	003507	N.C.R	N.C.R
Software	Audix	e3 v9	E3LK-01	N.C.R	N.C.R
		Conducted Ro	oom		
Signal Analyzer 40GHZ	Rohde & Schwarz	FSV40-N	102248	2019/09/11	2020/09/10
Cable	MTJ	MT40S	620620-MT40S-100	2018/12/28	2019/12/27

^{*}Statement of Traceability: The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

7.4 Test Environmental Conditions

Temperature:	25.6 ℃	Relative Humidity:	46 %	
ATM Pressure:	1014hPa	Test Engineer:	Boris Kao / Boris Kao	
Radiated Test Date:	2019-10-18 to 2019-10-19	Conducted Test Date:	2019-07-12	


Page 19 of 32

7.5 Test Result

BLE Mode:

Transmitting mode (Pre-scan with three orthogonal axis, and worse case as X axis)

Below 1G (30 MHz-1 GHz) test the output power worst mode



Result = Reading + Correct Factor

Margin = Result - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported

Above 1G (1 GHz-26.5 GHz)

BLE mode:


	Low CH													
Horizontal					Vertical									
Freq	Level		Over Limit	Read Level	Factor	Remark		Freq	Level	Limit Line	Over Limit		Factor	Remark
MHz 2361.204 2361.204 2401.800 2401.800	25.08 36.37 90.67	54.00 74.00	dB -28.92 -37.63	32.78 44.07 98.29	-7.70 -7.70	Average Peak Average		MHz 2333.460 2333.460 2401.800 2401.800	23.29 37.42 84.33	74.00		31.07	-7.78 -7.78 -7.62	Average Peak Average
4804.000 4804.000 7206.000 7206.000	54.46 45.25	74.00 54.00	-9.62 -19.54 -8.75 -20.67	53.84 40.00	0.62 5.25	Average Peak Average Peak		4804.000 4804.000 7206.000 7206.000	48.07 42.39	74.00 54.00	-16.99 -25.93 -11.61 -21.77	47.45 37.14	0.62 5.25	Average Peak Average Peak

	Middle CH													
Horizontal								,	Vertica	al				
Freq	Level	Limit Line	Over Limit		Factor	Remark		Freq	Level	Limit Line			Factor	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		-	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	
2360.160	24.67	54.00	-29.33	32.38	-7.71	Average		2333.560	25.03	54.00	-28.97	32.81	-7.78	Average
2360.160	35.36	74.00	-38.64	43.07	-7.71	Peak		2333.560	37.11	74.00	-36.89	44.89	-7.78	Peak
2439.960	93.30			100.82	-7.52	Average		2439.960	87.51			95.03	-7.52	Average
2439.960	93.99			101.51	-7.52	Peak		2439.960	88.23			95.75	-7.52	Peak
2488.410	25.75	54.00	-28.25	33.08	-7.33	Average		2487.650	23.78	54.00	-30.22	31.11	-7.33	Average
2488.410	36.80	74.00	-37.20	44.13	-7.33	Peak		2487.650	34.74	74.00	-39.26	42.07	-7.33	Peak
4880.000	44.73	54.00	-9.27	43.92	0.81	Average		4880.000	40.35	54.00	-13.65	39.54	0.81	Average
4880.000	53.01	74.00	-20.99	52.20	0.81	Peak		4880.000	47.62	74.00	-26.38	46.81	0.81	Peak
7320.000	50.08	54.00	-3.92	44.38	5.70	Average		7320.000	42.91	54.00	-11.09	37.21	5.70	Average
7320.000	56.50	74.00	-17.50	50.80	5.70	Peak		7320.000	50.51	74.00	-23.49	44.81	5.70	Peak

	High CH													
	Horizontal					Vertical								
Freq	Level	Limit Line			Factor	Remark		Freq	Level	Limit Line			Factor	Remark
MHz 2479.780 2479.780 2483.620 2483.620	95.12 95.40 27.42		-26.58	102.47 102.75 34.76	-7.35 -7.35 -7.34	Average Peak Average		MHz 2479.750 2479.750 2483.800 2483.800	89.08 24.27	54.00		95.71 96.43 31.61	-7.35 -7.35 -7.34	Average Peak Average
4960.000 4960.000 7440.000 7440.000	51.93 43.30	54.00 74.00 54.00 74.00	-22.07 -10.70	51.12 37.24	0.81 6.06	Average Peak Average Peak		4960.000 4960.000 7440.000 7440.000	39.24 47.06 40.59 49.36	74.00 54.00	-14.76 -26.94 -13.41 -24.64	46.25	0.81 6.06	Average Peak Average Peak

Page 21 of 32

Above 1G (1 GHz-26.5 GHz): The worst mode



Level = Read Level + Factor


Over Limit = Level - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported

Conducted Spurious Emissions:

Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result					
BLE mode									
Low	2402	39.73	≥ 20	Compliance					
Mid	2440	38.35	≥ 20	Compliance					
High	2480	38.79	≥ 20	Compliance					



8 FCC §15.247(a)(2) – 6 dB Emission Bandwidth

8.1 Applicable Standard

According to FCC §15.247(a) (2),

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2 Test Procedure

According to ANSI C63.10-2013, the steps for the first option are as follows:

- (1) Set RBW = 100 kHz. (2) Set the VBW ≥ [3 × RBW]. (3) Detector = peak. (4) Trace mode = max hold.
- (5) Sweep = auto couple. (6) Allow the trace to stabilize. (7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.				
Conducted Room									
Signal Analyzer 40GHZ	Rohde & Schwarz	FSV40-N	102248	2019/09/11	2020/09/10				
Cable	MTJ	MT40S	620620-MT40S-100	2018/12/28	2019/12/27				

^{*}Statement of Traceability: The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).


8.4 Test Environmental Conditions

Temperature:	25.6 ° C Relative Humidity:		46 %	
ATM Pressure:	1010hPa	Test Engineer:	Boris Kao	
Conducted Test Date:	2019-07-12	-	-	

Page 24 of 32

8.5 Test Results

Channel	Frequency 6 dB BW 6dB Limit (MHz) (MHz) (MHz)			Result					
BLE mode									
Low	2402	0.735	> 0.5	Compliance					
Middle	2440	0.735	> 0.5	Compliance					
High	2480	0.741	> 0.5	Compliance					



9 FCC §15.247(b) (3) – Maximum Output Power

9.1 Applicable Standard

According to FCC §15.247(b) (3),

Systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

9.2 Test Procedure

- (1) Place the EUT on a bench and set it in transmitting mode.
- (2) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to measuring equipment. (3). Add a correction factor to the display.

9.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.				
Conducted Room									
Power Sensor	Agilent	U2021XA	MY54250014	2018/11/12	2019/11/11				
Cable	MTJ	MT40S	620620-MT40S-100	2018/12/28	2019/12/27				

^{*}Statement of Traceability: The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

9.4 Test Environmental Conditions

Temperature:	25.6°C	Relative Humidity:	46 %		
ATM Pressure:	1010hPa	Test Engineer:	Boris Kao		
Conducted Test Date:	2019-07-12	-	-		

Page 26 of 32

9.5 Test Results

Channel	Frequency (MHz)	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (W)	Limit (dBm)	Result		
BLE mode:							
Low	Low 2402 -2.29 0.0006 30 Compliance						
Middle	2440	-2.23	0.0006	30	Compliance		
High	2480	-2.22	0.0006	30	Compliance		

Page 27 of 32

10 FCC §15.247(d) – 100 kHz Bandwidth of Frequency Band Edge

10.1 Applicable Standard

According to FCC §15.247(d),

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

10.2 Test Procedure

- (1) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- (2) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- (3) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- (4) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Page 28 of 32

10.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Conducted Room					
Signal Analyzer 40GHZ	Rohde & Schwarz	FSV40-N	102248	2019/09/11	2020/09/10
Cable	MTJ	MT40S	620620-MT40S-100	2018/12/28	2019/12/27

^{*}Statement of Traceability: The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).


10.4 Test Environmental Conditions

Temperature:	25.6°C	Relative Humidity:	46 %
ATM Pressure:	1010hPa	Test Engineer:	Boris Kao
Conducted Test Date:	2019-07-12	-	-

Page 29 of 32

10.5 Test Results

Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result	
BLE mode					
Low	2402	44.78	≥ 20	Compliance	
High	2480	46.73	≥ 20	Compliance	



11 FCC §15.247(e) - Power Spectral Density

11.1 Applicable Standard

According to FCC §15.247(e),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

11.2 Test Procedure

According to ANSI C63.10-2013,

- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth. (3) Set the RBW to 3 kHz ≤ RBW ≤ 100 kHz.
- (4) Set the VBW \geq [3 × RBW]. (5) Detector = peak. (6) Sweep time = auto couple.
- (7) Trace mode = max hold. (8) Allow trace to fully stabilize.
- (9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- (10) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

11.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.	
Conducted Room						
Signal Analyzer 40GHZ	Rohde & Schwarz	FSV40-N	102248	2019/09/11	2020/09/10	
Cable	MTJ	MT40S	620620-MT40S-100	2018/12/28	2019/12/27	

^{*}Statement of Traceability: The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

11.4 Test Environmental Conditions


Temperature: 25.6°C		Relative Humidity:	46 %
ATM Pressure:	1010hPa	Test Engineer:	Boris Kao
Conducted Test Date:	2019-07-12	-	-

Page 31 of 32

Report No.: RXZ190624003-00A

11.5 Test Results

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Result	
BLE mode					
Low	2402	-17.32	8	Compliance	
Middle	2440	-16.83	8	Compliance	
High	2480	-16.15	8	Compliance	



---- END OF REPORT ----

Page 32 of 32