

Applicant: Eastern Times Technology Co.,Ltd

Product: REDRAGON LOW-PROFILE WITH G KEYS WIRELESS

**KEYBOARD** 

Model No.: K653-RGB-PRO, K653W-RGB-PRO, ET-8822

Trademark: REDRAGON

Test Standards: FCC Part 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10 & FCC Part 15 Subpart C,

Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Terry long

Terry Tang

Manager

Dated: October 27, 2023


Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

## SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com



Report No.: TW2308322-02E Page 2 of 35

Date: 2023-10-27



## **Special Statement:**

## FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

## Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

## A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

CAB identifier: CN0033

Date: 2023-10-27



# Test Report Conclusion

(		O	n	t	e	n	t
	$\overline{}$	v	11		·		·

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test	8
5.2	Test Method and Test Procedure	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition	9
5.5	Conducted Emission Limit.	9
5.6	Test Result	9
6.0	Radiated Emission test	12
6.1	Test Method and Test Procedure	12
6.2	Configuration of the EUT	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit	13
6.5	Test Result	15
7.0	Band Edge	23
7.1	Test Method and Test Procedure	23
7.2	Radiated Test Setup	23
7.3	Configuration of the EUT	23
7.4	EUT Operating Condition	23
7.5	Band Edge Limit	23
7.6	Band Edge Test Result.	24
8.0	Antenna Requirement	28
9.0	20dB bandwidth measurement	29
10.0	FCC ID Label	33
11.0	Photo of Test Setup and EUT View	34

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2023-10-27



#### 1.0 General Details

#### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189 For 3m Anechoic Chamber

#### 1.2 Applicant Details

Applicant: Eastern Times Technology Co.,Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town, Dongguan City,

Guangdong, China.

Telephone: --Fax: --

#### 1.3 Description of EUT

Product: REDRAGON LOW-PROFILE WITH G KEYS WIRELESS KEYBOARD

Manufacturer: Eastern Times Technology Co.,Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town,

Dongguan City, Guangdong, China.

Trademark: REDRAGON

Model Number: K653-RGB-PRO

Additional Model Name K653W-RGB-PRO, ET-8822

Rating: Input: DC5V, 710mA or DC3.7V, 360mA

Battery: DC3.7V, 1900mAh Li-ion battery

Hardware Version: 8822-A V1

Software Version: E359

Serial No.: RDK653- RGB-PRO23051501002

Operation Frequency: 2402-2480MHz

Modulation Type: GFSK Number of Channels: 79 Channel Separation: 1MHz

Antenna Designation PCB antenna with gain 2.34dB maximum (Get from the antenna specification)

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2308322-02E Page 5 of 35

Date: 2023-10-27



1.4 Submitted Sample: 2 Samples

1.5 Test Duration

2023-08-25 to 2023-10-27

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty =6.0dB

Occupied Channel Bandwidth Uncertainty = 5%

Conducted Emissions Uncertainty = 3.6dB

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by

Print Name: Andy Xing

Page 6 of 35

Report No.: TW2308322-02E

Date: 2023-10-27



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2023-07-14	2024-07-13
LISN	R&S	EZH3-Z5	100294	2023-07-14	2024-07-13
LISN	R&S	EZH3-Z5	100253	2023-07-14	2024-07-13
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2023-07-14	2024-07-13
Loop Antenna	EMCO	6507	00078608	2022-07-18	2025-07-17
Spectrum	R&S	FSIQ26	100292	2023-07-14	2024-07-13
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2022-07-18	2025-07-17
Horn Antenna	R&S	BBHA 9120D	9120D-631	2022-07-18	2024-07-17
Power meter	Anritsu	ML2487A	6K00003613	2023-07-14	2024-07-13
Power sensor	Anritsu	MA2491A	32263	2023-07-14	2024-07-13
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2022-07-18	2025-07-17
9*6*6 Anechoic			N/A	2022-07-26	2025-07-25
EMI Test Receiver	RS	ESVB	826156/011	2023-07-14	2024-07-13
EMI Test Receiver	RS	ESCS 30	834115/006	2023-07-14	2024-07-13
Spectrum	HP/Agilent	E4407B	MY50441392	2023-07-14	2024-07-13
Spectrum	RS	FSP	1164.4391.38	2023-07-14	2024-07-13
RF Cable	Zhengdi	ZT26-NJ-NJ-8M/FA		2023-07-14	2024-07-13
RF Cable	Zhengdi	7m		2023-07-14	2024-07-13
Pre-Amplifier	Schwarebeck	BBV9743	#218	2023-07-14	2024-07-13
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2023-07-14	2024-07-13
LISN	SCHAFFNER	NNB42	00012	2023-07-14	2024-07-13
ESPI Test Receiver	R&S	ESPI 3	100379	2023-07-14	2024-07-13
LISN	R&S	EZH3-Z5	100294	2023-07-14	2024-07-13

## 2.2 Automation Test Software

#### For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

#### For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 7 of 35

Report No.: TW2308322-02E

Date: 2023-10-27



#### 3.0 Technical Details

## 3.1 Summary of test results

	The EUT has	been tested	l according to	the following	specifications:
--	-------------	-------------	----------------	---------------	-----------------

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.203	Antenna Requirement	Pass	Complies
FCC Part 15, Paragraph 15.207	Conducted Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	Pass	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	Pass	Complies
FCC Part 15.215(c)	20dB bandwidth	Pass	Complies

#### 3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249, ANSI C63.4:2014 and ANSI C63.10:2013

## 4.0 EUT Modification


No modification by SHENZHEN TIMEWAY TESTING LABORATORIES

Date: 2023-10-27



#### 5.0 Power Line Conducted Emission Test

#### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

#### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum from 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



## 5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

79 channels are provided to the EUT

## A. EUT

Device	Manufacturer	Model	FCC ID
REDRAGON			
LOW-PROFILE WITH G	Eastern Times Technology	K653-RGB-PRO,	TUVET 0022 A
KEYS WIRELESS	Co.,Ltd	K653W-RGB-PRO, ET-8822	TUVET-8822A
KEYBOARD			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2308322-02E Page 9 of 35

Date: 2023-10-27



#### B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

## C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	KEYU	KA23-0502000DEU	Input: 100-240V~, 50/60Hz, 0.35A;
			Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (d	lB μV)
(MHz)	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	66.0~56.0*	56.0~46.0*
$0.50 \sim 5.00$	56.0	46.0
5.00 ~ 30.00	60.0	50.0

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

#### 5.6 Test Results:

Date: 2023-10-27



## A: Conducted Emission on Live Terminal (150kHz to 30MHz)


## **EUT Operating Environment**

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

**EUT set Condition: Charging + Communication by BT** 

**Results: Pass** 

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1578	46.60	9.78	56.38	65.58	-9.20	QP	Р
2	0.1578	9.48	9.78	19.26	55.58	-36.32	AVG	Р
3	0.1773	41.04	9.77	50.81	64.61	-13.80	QP	Р
4	0.1773	8.11	9.77	17.88	54.61	-36.73	AVG	Р
5	0.2631	30.25	9.75	40.00	61.33	-21.33	QP	Р
6	0.2631	9.28	9.75	19.03	51.33	-32.30	AVG	Р
7	16.5525	22.56	10.47	33.03	60.00	-26.97	QP	Р
8	16.5525	14.39	10.47	24.86	50.00	-25.14	AVG	Р

Date: 2023-10-27



## B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)


**EUT Operating Environment** 

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

**EUT set Condition: Charging + Communication by BT** 

**Results: Pass** 

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1734	42.25	9.77	52.02	64.80	-12.78	QP	Р
2	0.1734	18.20	9.77	27.97	54.80	-26.83	AVG	Р
3	0.2436	38.80	9.75	48.55	61.97	-13.42	QP	Р
4	0.2436	11.60	9.75	21.35	51.97	-30.62	AVG	Р
5	0.5049	26.48	9.77	36.25	56.00	-19.75	QP	Р
6	0.5049	2.85	9.77	12.62	46.00	-33.38	AVG	Р
7	15.9558	18.56	10.44	29.00	60.00	-31.00	QP	Р
8	15.9558	9.55	10.44	19.99	50.00	-30.01	AVG	Р

Date: 2023-10-27



#### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 9kHz to 25 GHz was investigated. The frequency spectrum is set as follows:


Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
ADOVE IGHZ	Peak	1MHz	10Hz	Average

(Note: for Fundamental frequency radiated emission measurement, RBW=3MHz, VBW=10MHz). Measurements were made at 3 meters.

- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

#### **Block diagram of Test setup**


For radiated emissions from 9kHz to 30MHz




Date: 2023-10-27



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of the EUT
  Same as section 5.3 of this report
- 6.3 EUT Operating Condition

  Same as section 5.4 of this report.
- 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

## A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency	Field Stre	ength of Fundamental (3m)	Field Strength of Harmonics (3m)			
(MHz)	mV/m	dBuV/m	uV/m	dBuV/m		

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2308322-02E Page 14 of 35

Date: 2023-10-27



					· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)
2400-2403.3	50	1 34 (Average)	114 (1 cak)	500	J4 (Average)	/4 (1 Cak)

Note:

- 1. RF Field Strength  $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

## B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB $\mu$ V/m)
0.009-0.490	3	20log(2400/F(kHz)) +40log (300/3)
0.490-1.705	3	20log(24000/F(kHz)) +40log (30/3)
1.705-30	3	69.5
30-80	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage  $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK. For fundamental measurement, PK detector used.
- 5. Battery fully charged was used during the test.

Report No.: TW2308322-02E Page 15 of 35

Date: 2023-10-27




#### 6.5 Test result

## A Fundamental & Harmonics Radiated Emission Data

Please refer to the following test plots for details: Low Channel-2402MHz

#### Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2402	93.79	-3.57	114.0	-20.21	Peak	88.00	100	Horizontal	Pass
1**	2402	84.32	-3.57	94.0	-9.69	AV	88.00	100	Horizontal	Pass
2	4802.799	53.83	3.12	74.0	-21.17	Peak	93.00	100	Horizontal	Pass

Report No.: TW2308322-02E Page 16 of 35

Date: 2023-10-27



### Vertical



	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
Ī	1	2402	83.52	-3.57	114.0	-30.48	Peak	190.00	100	Vertical	Pass


Report No.: TW2308322-02E Page 17 of 35

Date: 2023-10-27



Please refer to the following test plots for details: Middle Channel-2441MHz

#### **Horizontal**




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2441	93.84	-3.57	114.0	-20.16	Peak	90.00	100	Horizontal	Pass
1**	2441	84.51	-3.57	94.0	-9.49	AV	90.00	100	Horizontal	Pass
2	4883.529	52.93	3.20	74.0	-21.07	Peak	90.00	100	Horizontal	Pass

Report No.: TW2308322-02E Page 18 of 35

Date: 2023-10-27



### Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2441	82.69	-3.57	114.0	-31.31	Peak	201.00	100	Vertical	Pass


Report No.: TW2308322-02E Page 19 of 35

Date: 2023-10-27



Please refer to the following test plots for details: High Channel-2480MHz

#### Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2480	93.74	-3.57	114.0	-20.26	Peak	100.00	100	Horizontal	Pass
1**	2480	84.25	-3.57	94.0	-9.75	AV	100.00	100	Horizontal	Pass
2	4960.010	52.59	3.36	74.0	-21.41	Peak	94.00	100	Horizontal	Pass

Report No.: TW2308322-02E Page 20 of 35

Date: 2023-10-27



## Vertical



Ν	0.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1		2480	83.22	-3.57	114.0	-30.78	Peak	0.00	100	Vertical	Pass

Note: (1) Emission Level = Reading Level + Antenna Factor + Cable Loss-Amplifier

- (2) Margin=Emission-Limits
- (3) According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (4) For test purpose, keep EUT continuous transmitting
- (5) For emission above 18GHz and Below 30MHz, It is only the floor noise and less than the limit for more than 20dB. No necessary to take down.
- (6) the measured PK value less than the AV limit.

Report No.: TW2308322-02E Page 21 of 35

Date: 2023-10-27




# B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

**Results:** Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Margin	Detector	Table	Height	Antenna	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(Degree)	(cm)		
1	132.552	32.88	-17.02	43.5	10.62	Peak	254.00	100	Horizontal	Pass
2	203.489	41.04	-13.46	43.5	2.46	Peak	0.00	119	Horizontal	Pass
2*	203.489	37.72	-13.46	43.5	5.78	QP	0.00	119	Horizontal	Pass
3	231.467	40.46	-12.60	46.0	5.54	Peak	150.00	100	Horizontal	Pass
4	425.904	30.87	-8.21	46.0	15.13	Peak	146.00	100	Horizontal	Pass
5	666.161	32.80	-4.50	46.0	13.20	Peak	304.00	100	Horizontal	Pass
6	998.545	37.84	-1.18	54.0	16.16	Peak	295.00	100	Horizontal	Pass

Report No.: TW2308322-02E Page 22 of 35

Date: 2023-10-27




## Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Margin	Detector	Table	Height	Antenna	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(Degree)	(cm)		
1	151.462	29.52	-16.95	43.5	13.98	Peak	249.00	100	Vertical	Pass
2	188.070	31.64	-14.46	43.5	11.86	Peak	25.00	100	Vertical	Pass
3	342.747	27.13	-9.68	46.0	18.87	Peak	308.00	100	Vertical	Pass
4	407.478	32.58	-8.54	46.0	13.42	Peak	308.00	100	Vertical	Pass
5	938.420	35.50	-1.76	46.0	10.50	Peak	322.00	100	Vertical	Pass
6	995.394	40.98	-1.26	54.0	13.02	Peak	340.00	100	Vertical	Pass

Date: 2023-10-27




#### 7. Band Edge

#### 7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) Set Spectrum as RBW=1MHz, VBW=3MHz and Peak detector used for PK value. RBW=1MHz, VBW=10Hz and Peak detector used for AV value.
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

## 7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

## 7.3 Configuration of the EUT

Same as section 5.3 of this report

## 7.4 EUT Operating Condition

Same as section 5.4 of this report.

#### 7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2308322-02E Page 24 of 35

Date: 2023-10-27



#### 7.6 Test Result



Page 25 of 35 Report No.: TW2308322-02E

Date: 2023-10-27



Product:		duct: REDRAGON LOW-PROFILE WITH G KEYS WIRELESS KEYBOARD				Detector		Vertical		
	Mode	le Keeping Transmitting				Test Voltage		DC3.7V		
Teı	mperature	24 deg. C,			Humid	ity	56% RH			
Te	st Result:		Pas	SS						
Part 1	.5C Class B 1GHz-18GHz -	2			<u>'</u>		<u>'</u>			
90	0-								M1	
80	0-								$\bigcap$	
70	0-							/	<b>—</b>	
60	0-								V.	
00							M4			
50	0-					N	13	M2	— \ 	
50		المراجعة	و معامل العالم العام	والمستعدد والمستعد والمستعدد والمستع	والمالية والمراوي ومراولة المراولة المراولة	المال ولينانيه ايريا دوور	13	M2 •	1	Militar Maria
40	O-	h Lades beneva karibis dirikse dingenterbedi	والمراجع المراجع المرا	derrichen gewent ziehnen der der	والمالية والمالية والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة وا		13	M2 •	\	Add so the law
30	O-	h finisa human disestis di della di septembri	بيغانية اللهيد	eri karakan kanakan ka	والمالية والمورد المراب والمالية والمالية والمالية والمالية والمالية والمالية والمالية والمالية والمالية والم	. Land John Market Market	13	M2 •		Malantalu
40	O-	No. of the Internal Society of Artificial Imperior Parts	. محل میشود است	and a desired subject to the subject	والمتابعة والمراجعة المتابعة المتابعة	المال المساور		M2 °		Malanhalu
30		h Laten benemen da verske drivite i de nya dewik ki	, we all his life to be seen	tti farika kankilika kunduka	والمنافعة المراجعة المالينية المالينية	. augustus de la	13	M2 •		<sup>N</sup> eljalositisku.
40 30 20 10		No. of the Second Section of the Section of the Second Section of the S	, a d lle palage, dese	en to de a markintant and	والمالية والمراجعة المالية الم	الاستحابيس	13	M2 •		SECOND STATES
40 30 20 10		h finisa henema dinashin Araka di mendenda di	e, say al liber de l'anni de l		Frequency (MHz)		13	M2 °		SECOND STATES
40 30 20 10		Results	Factor		Mill demonstration of the Prop. A. Market 1887	Detector	Table	M2 •	ANT	2
40 30 20 10	0	Results (dBuV/m)	and any and all the second and any and any		Frequency (MHz)		Table (o)	Height (cm)	ANT	2
40 30 20 10	0- 0- 0- 0- 0- 0- 2350		Factor	Limit	Frequency (MHz)  Over Limit			_	ANT	2
40 30 20 10 0.0	Frequency (MHz)	(dBuV/m)	Factor (dB)	Limit (dBuV/m)	Frequency (MHz)  Over Limit (dB)	Detector	(0)	(cm)		verdi
40 30 20 10 0.0	Frequency (MHz)	(dBuV/m) 83.50	Factor (dB) -3.57	Limit (dBuV/m) 74.0	Frequency (MHz)  Over Limit (dB)  9.50	Detector Peak	(o) 188.00	(cm) 100	Vertical	Verdi N/A Pass
40 30 20 10 0.0	Frequency (MHz) 2401.722 2400.147	(dBuV/m) 83.50 58.37	Factor (dB) -3.57	Limit (dBuV/m) 74.0	Frequency (MHz)  Over Limit (dB)  9.50  -15.63	Detector Peak Peak	(o) 188.00 188.00	(cm) 100 100	Vertical Vertical	2. Verdi

Report No.: TW2308322-02E Page 26 of 35

Date: 2023-10-27



	Product:	Product: KEYS WIRELESS KI			AGON LOW-PROFILE WITH G 'S WIRELESS KEYBOARD		Polarity		Horizontal		
	Mode		Keeping Transmitting			Т	Test Voltage		DC3.7V		
	Temperature			24 deg. C,			Humidity		56% RH		
	Test Result:			Pass							
C Part 1.0E	15C Class B 1GHz-18GHz +2-	: -2		M1		1					
	90-		الران	,							
	80-		Jahr Market	ra-							
	70-			**	lu						
	60-		7								
	50-	أنزلو	"		Whe						
	40-	- کلم العل			M2						
	30-	elanter hambotter ha			W.	William William	ntifeles descriptions	and the first of the parties of the		A CONTRACTOR	
	20-										
	20-										
	10-										
					2483.5 Frequency (MHz)					2500	
ı	0.0	Results	Factor	Limit	Frequency (MHz)	Detector	Table (o)	Height	ANT	2500	
ı	0.0-	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Frequency (MHz)		Table (o)	Height (cm)	ANT		
No.	0.0- 2470 Frequency				Over Limit (dB)		Table (o) 93.00		ANT Horizontal	1	
	Frequency (MHz)	(dBuV/m)	(dB)	(dBuV/m)	Over Limit (dB)	Detector	` ,	(cm)		Verdic	

Page 27 of 35

Report No.: TW2308322-02E

Date: 2023-10-27



]	Product:		REDRAGON LOW-PROFILE WITH G				tor		Vertical	
 Mode		KEYS WIRELESS KEYBOARD								
	Mode	Keeping Transmitting				Test Vol	ltage		DC3.7V	
Te	mperature		24 deg	g. C,		Humic	lity	56% RH		
Te	est Result:		Pas	SS						
	rt 15C Class B 1GHz-18GHz	: -2								
	90-		M1							
level (dBuV/m)	60 - 50 - 40 - 30 - 20 -		/	M2	**************************************	mpy-like; and special seconds.	de de la constitución de la cons	والمراوية والمتحاولة و	hidleridanda hadil	allow a display displaying
level (dBuV/m)	40	Material and a state of proceedings	/	M2	THE PROPERTY OF THE PROPERTY O		although the and the last		distantia manda di sandi	2500
	30 - 20 - 2470	Resulte	Fostor	Fi	requency (MHz)	A Construction of Construction	and the second	end dermitte de anne de preferencies	The second se	2500
	50- 40- 30- 20- 10- 2470	Results	Factor	Limit	requency (MHz)  Over Limit	Detector	Table	Height	ANT	2500
No.	50- 40- 30- 20- 10- 0.0- 2470 Frequency (MHz)	(dBuV/m)	(dB)	Limit (dBuV/m)	requency (MHz)  Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	2500 Verdid
(w//\ngp)  ava  No.	50- 40- 30- 20- 10- 2470			Limit	requency (MHz)  Over Limit	A Construction of Construction	Table	Height	The second se	(1) (1) (1)

Note: The PK emission level less than the AV limit. No necessary to record the AV emission level.

Report No.: TW2308322-02E Page 28 of 35

Date: 2023-10-27



## 8.0 Antenna Requirement

## **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a PCB antenna with gain 2.34dBi maximum. It fulfills the requirement of this section.

Test Result: Pass

Date: 2023-10-27



Page 29 of 35

#### 9.0 20dB Bandwidth Measurement

## **Test Configuration**



## **Test Procedure**

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### Limit

N/A

Page 30 of 35


Report No.: TW2308322-02E

Date: 2023-10-27



#### **Test Result**

GFSK			
Product:	REDRAGON LOW-PROFILE WITH G KEYS WIRELESS KEYBOARD	Test Mode:	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	1.224MHz		



Date: 10.SEP.2023 14:37:34

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 31 of 35

Report No.: TW2308322-02E

Date: 2023-10-27



GFSK			
Product:	REDRAGON LOW-PROFILE WITH G	Test Mode:	Voor transmitting
Product.	KEYS WIRELESS KEYBOARD	rest wiode.	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	1.170MHz		



Date: 10.SEP.2023 14:30:08


Page 32 of 35

Report No.: TW2308322-02E

Date: 2023-10-27



GFSK			
Product:	REDRAGON LOW-PROFILE WITH G	Test Mode:	Voor trongmitting
Product:	KEYS WIRELESS KEYBOARD	rest wrode:	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	1.080MHz		



Date: 10.SEP.2023 14:20:00

Report No.: TW2308322-02E Page 33 of 35

Date: 2023-10-27




#### 10.0 FCC ID Label

#### FCC ID: TUVET-8822A

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### Mark Location:



Page 34 of 35

Report No.: TW2308322-02E

Date: 2023-10-27



#### 11.0 Photo of testing

#### 11.1 Conducted test View



Date: 2023-10-27



#### Radiated emission test view



## 11.2 Photographs – EUT

Please refer test report TW2308322-01E

## -- End of the report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.