

FCC ID: 2AQBD-60233

RF Exposure Evaluation

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)	
and the state of the second	(A) Limits	for Occupational/Controlled I	Exposures	the first of the second	
0.3–3.0	614	1.63	*(100)		
3.0–30	1842/f	4.89/f	*(900/f²)	C C C C SIM NO	
30–300	61.4	0.163	1.0° che	The 6 the sta	
300–1500	the start of the	State of the state of	f/300	THE STIME 6 OF THE	
1500–100,000	oc the resting the oc	All is the of the state of	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	6	
ING CO CTELESTIC ING	(B) Limits for	General Population/Uncontro	lled Exposure	S S A THE THE A	
0.3–1.34	614	4 1.63 (100)		5 30 AP 510	
1.34–30	824/f	2.19/f	*(180/f ²) 30		
30–300	27.5	0.073 0 0.02		30 S	
300–1500	a an the the the a	o che che che che che che	f/1500	30	
1500–100,000	ING CONTRACTION		5 ¹⁰ 1.0 5 1.0	30 John M	

Limits for Maximum Permissible Exposure (MPE)

f = frequency in MHz

Friis transmission formula: Pd = (Pout*G)/(4*pi*r²)

Where

- Pd = power density in mW/cm², Pout = output power to antenna in mW;
- G = gain of antenna in linear scale, Pi = 3.1416;
- \mathbf{R} = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, and highest channel individually.



Shenzhen QC Testing Laboratory Co., Ltd.

Test Result of RF Exposure Evaluation

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm ²)	Power Density At 20 cm (mW/cm ²)	Test Results
2412	20.00	16.29	16±1	50.12	1.51	p 61 ()	0.0151	Pass
2437	20.00	o 15.00 <	15±1	39.81	<u> </u>	A C C	0.0120	Pass
2462	20.00	15.86	15±1	39.81	1.51	Star of	0.0120	Pass

For 2.4G Wi-Fi Antenna gain=1.8dBi

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.