

FCC PART 15.407

TEST REPORT

For

Shenzhen Jingwah Information Technology Co., Ltd.

4F, Bldg 4, Jinghua Square, No.1 Huafa North Road, Shenzhen, China

FCC ID: RBD-S4005L

Report Type: Original Report	Product Type: Smart Phone
Report Number: RGMA190103002-00E	
Report Date: 2019-04-08	
Reviewed By: RF Engineer	Rocky Kang <i>Rocky Kang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	11
SUPPORT EQUIPMENT LIST AND DETAILS	12
EXTERNAL I/O CABLE.....	12
BLOCK DIAGRAM OF TEST SETUP	12
SUMMARY OF TEST RESULTS.....	13
TEST EQUIPMENT LIST	14
FCC §1.1307(b) & §2.1093 - RF EXPOSURE.....	16
APPLICABLE STANDARD	16
TEST RESULT	16
FCC §15.203 – ANTENNA REQUIREMENT	17
APPLICABLE STANDARD	17
ANTENNA CONNECTOR CONSTRUCTION	17
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	18
APPLICABLE STANDARD	18
EUT SETUP.....	18
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
TEST RESULTS SUMMARY	19
TEST DATA	19
§15.205 & §15.209 & §15.407(B) (1), (2), (3), (4),(6),(7) – UNDESIRABLE EMISSION	22
APPLICABLE STANDARD	22
EUT SETUP	22
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	23
TEST PROCEDURE	23
CORRECTED AMPLITUDE & MARGIN CALCULATION	24
TEST RESULTS SUMMARY	24
TEST DATA	24
§15.407(B) (1), (2), (3), (4) –OUT OF BAND EMISSION	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41
FCC §15.407(a) (1) – 26 dB & 6dB EMISSION BANDWIDTH.....	62
APPLICABLE STANDARD	62

TEST PROCEDURE	62
TEST DATA	62
FCC §15.407(a) (1) (2)(3) – CONDUCTED TRANSMITTER OUTPUT POWER.....	102
APPLICABLE STANDARD	102
TEST PROCEDURE	102
TEST DATA	103
FCC §15.407(a) (1) (2) (3) - POWER SPECTRAL DENSITY	107
APPLICABLE STANDARD	107
TEST PROCEDURE	107
TEST DATA	108

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Smart Phone
Tested Model	S4005L
Multiple Model [#]	A4000-PB
Frequency Range	5150-5250MHz; 5250-5350 MHz; 5470-5725 MHz; 5725-5850 MHz;
Transmit Power	5150-5250 MHz: 8.42dBm 5250-5350 MHz: 9.12dBm 5470-5725 MHz: 8.87dBm 5725-5850 MHz: 9.48dBm
Modulation Technique	OFDM
Antenna Specification	5150-5250MHz :-4.64 dBi 5250-5350 MHz :-4.18 dBi 5470-5725 MHz :-3.03 dBi 5725-5850 MHz :-3.26 dBi
Voltage Range	DC 3.7 V battery or DC 5.0V from adapter
Date of Test	2019-01-06 to 2019-04-02
Sample serial number	A4000181200001
Received date	2019-01-03
Sample/EUT Status	Good condition
Adapter information	Model: TPA-95A050100UU Input: AC 100-240V, 60/80Hz, 0.16A Output: DC 5V, 1000mA

Notes: This series products model: A4000-PB and S4005L are identical; they have the same or similar appearance, structure, PCB, Material and function to the testing products, Model S4005L was selected for fully testing, the detailed information can be referred to the attached declaration which was stated and guaranteed by the applicant.

Objective

This type approval report is prepared on behalf of *Shenzhen Jingwah Information Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS&DSS and Part 22H&24E&27 PCE submissions with FCC ID: RBD-S4005L.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Radiated Emissions	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±3 °C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The device support 802.11a/n20/n40/ac20/ac40 modes.

For 5150-5250MHz Band, 6 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240

For 5250-5350MHz Band, 6 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300
54	5270	62	5310
56	5280	64	5320

For 5470-5725MHz Band, 16 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	120	5600
102	5510	124	5620
104	5520	126	5630
108	5540	128	5640
110	5550	132	5660
112	5560	134	5670
116	5580	136	5680
118	5590	140	5700

For 5725-5850MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785
151	5755	159	5795
153	5765	161	5805
/	/	165	5825

EUT Exercise Software


“RFtest tool” software was used. Test frequencies and power level were configured as below:

U-NII	Mode	Channel Number	Frequency (MHz)	Rate (Mbps)	Power Level
5150 – 5250MHz	802.11 a	CH36	5180	54	12
		CH40	5200	54	12
		CH48	5240	54	12
	802.11 n20	CH36	5180	MCS0	12
		CH40	5200	MCS0	12
		CH48	5240	MCS0	12
	802.11 n40	CH38	5190	MCS0	12
		CH46	5230	MCS0	12
	802.11 ac20	CH36	5180	MCS0	12
		CH40	5200	MCS0	12
		CH48	5240	MCS0	12
	802.11 ac40	CH38	5190	MCS0	12
		CH46	5230	MCS0	12
5250 – 5350MHz	802.11 a	CH52	5260	54	12
		CH56	5280	54	12
		CH64	5320	54	12
	802.11 n20	CH52	5260	MCS0	12
		CH56	5280	MCS0	12
		CH64	5320	MCS0	12
	802.11 n40	CH54	5270	MCS0	12
		CH62	5310	MCS0	12
	802.11 ac20	CH52	5260	MCS0	12
		CH56	5280	MCS0	12
		CH64	5320	MCS0	12
	802.11 ac40	CH54	5270	MCS0	12
		CH62	5310	MCS0	12

U-NII	Mode	Channel Number	Frequency (MHz)	Rate (Mbps)	Power Level
5470 – 5725MHz	802.11 a	CH100	5500	54	12
		CH120	5600	54	12
		CH140	5700	54	12
	802.11 n20	CH100	5500	MCS0	12
		CH120	5600	MCS0	12
		CH140	5700	MCS0	12
	802.11 n40	CH102	5510	MCS0	12
		CH118	5590	MCS0	12
	802.11 ac20	CH100	5500	MCS0	12
		CH120	5600	MCS0	12
		CH140	5700	MCS0	12
	802.11 ac40	CH102	5510	MCS0	12
		CH118	5590	MCS0	12
		CH134	5670	MCS0	12
5725 – 5850MHz	802.11 a	CH149	5745	54	14
		CH157	5785	54	14
		CH165	5825	54	14
	802.11 n20	CH149	5745	MCS0	14
		CH157	5785	MCS0	14
		CH165	5825	MCS0	14
	802.11 n40	CH151	5755	MCS0	15
		CH159	5795	MCS0	15
	802.11 ac20	CH149	5745	MCS0	15
		CH157	5785	MCS0	14
		CH165	5825	MCS0	14
	802.11 ac40	CH151	5755	MCS0	15
		CH159	5795	MCS0	15


Duty cycle
5150-5250 MHz

802.11a mode




Date: 16.JAN.2019 20:13:25

802.11n20 mode




Date: 16.JAN.2019 20:13:03

802.11n40 Mode




Date: 16.JAN.2019 20:15:15

802.11ac20 Mode



Date: 16.JAN.2019 20:12:41

802.11ac40 Mode



Date: 16.JAN.2019 20:16:34

Band	Duty Cycle (%)	T(ms)	1/T(kHz)	VBW Setting	10log(1/x)
802.11a	100	-	-	10Hz	-
802.11n20	100	-	-	10Hz	-
802.11n40	100	-	-	10Hz	-
802.11ac20	100	-	-	10Hz	-
802.11ac40	100	-	-	10Hz	-

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Un-detachable DC Cable	1.5	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) (1) & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b) (1), (2), (3), (4),(7)	Undesirable Emission& Restricted Bands	Compliance
§15.407(b) (1), (2), (3), (4)	Out Of Band Emission	Compliance
§15.407(a) (1), (5),(e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliance
§15.407(a)(1),(2), (3)	Conducted Transmitter Output Power	Compliance
§15.407 (a)(1), (2), (3)	Power Spectral Density	Compliance

DFS report please refer to RGMA190305002-RF issued by Bay Area Compliance Laboratories Corp. (Dongguan).

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2018-12-21	2019-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-11-12	2019-11-12
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Unknown	Conducted Emission Cable	78652	UF A210B-1-0720-504504	2018-11-12	2019-11-12
Radiated Emission Test					
A.H.System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
Agilent	Spectrum Analyzer	8564E	3943A01781	2019-01-04	2020-01-04
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2019-01-11	2020-01-11
UTiFLEX MICRO-C0AX	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-07-11	2021-07-10
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2018-11-19	2019-05-21
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-03	2017-12-29	2020-12-28
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2018-08-03	2019-08-03

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2018-12-24	2019-12-24
Agilent	USB Wideband Power Meter	U2021XA	MY54250003	2018-06-23	2019-06-23
Ducommun technologies	RF Cable	RG-214	3	Each Time	
WEINSCHTEL	3dB Attenuator	N/A	N/A	Each Time	

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1307(b) and §2.1093.

Test Result

Compliance, please refer to the SAR report: RGMA190103002-20A.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is -4.64 dBi for 5150-5250MHz, -4.18 dBi for 5250-5350MHz, -3.03 dBi for 5470-5725MHz, -3.26 dBi for 5725-5850MHz, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-01-06.

EUT operation mode: Transmitting (worst case is 802.11a mode 5180 MHz)

AC 120V/60 Hz, Line:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.289500	41.1	19.8	60.5	19.4	QP
0.317230	39.0	19.8	59.8	20.8	QP
0.470830	35.0	19.8	56.5	21.5	QP
0.786270	34.9	19.8	56.0	21.1	QP
0.876950	34.2	19.7	56.0	21.8	QP
0.972370	32.9	19.8	56.0	23.1	QP
0.289500	35.4	19.8	50.5	15.1	Ave.
0.317230	32.9	19.8	49.8	16.9	Ave.
0.470830	25.5	19.8	46.5	21	Ave.
0.786270	25.3	19.8	46.0	20.7	Ave.
0.876950	24.9	19.7	46.0	21.1	Ave.
0.972370	25.4	19.8	46.0	20.6	Ave.

AC120V, 60 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.286500	45.4	19.8	60.6	15.2	QP
0.297470	46.3	19.8	60.3	14	QP
0.317170	44.2	19.8	59.8	15.6	QP
0.501410	34.2	19.8	56.0	21.8	QP
1.012970	33.5	19.8	56.0	22.5	QP
1.042250	34.0	19.8	56.0	22	QP
0.286500	39.6	19.8	50.6	11	Ave.
0.297470	41.3	19.8	50.3	9	Ave.
0.317170	38.4	19.8	49.8	11.4	Ave.
0.501410	22.2	19.8	46.0	23.8	Ave.
1.012970	27.2	19.8	46.0	18.8	Ave.
1.042250	27.8	19.8	46.0	18.2	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

§15.205 & §15.209 & §15.407(B) (1), (2), (3), (4),(6),(7) – UNDESIRABLE EMISSION

Applicable Standard

FCC §15.407 (b) (1), (2), (3), (4), (6), (7); §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.


KDB 789033 D02 General UNII Test Procedures New Rules v02r01, clause G),


$E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{m}]) + 104.77$, where E = field strength and d = distance at which field strength limit is specified.

For FCC §15.407 (b) (1), (2), (3), $d=1\text{m}$, non-Restricted bands limit $= -27 - 20 \cdot \log(1) + 104.77 = 77.7 \text{ dB}\mu\text{V}/\text{m}$

EUT Setup

Below 1 GHz:



Above 1 GHz:

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure**Radiated Spurious Emission**

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to ANSI C63.10-2013: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dB μ V/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dB μ V/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2019-01-14.

EUT operation mode: Transmitting

30 MHz – 1 GHz: (worst case is 802.11a mode 5180 MHz)



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
50.602875	21.46	130.0	V	43.0	-19.7	40.00	18.54
53.475500	21.39	100.0	V	96.0	-19.8	40.00	18.61
216.013875	35.41	135.0	H	63.0	-13.9	46.00	10.59
311.991375	34.86	102.0	H	109.0	-10.7	46.00	11.14
839.972125	35.99	107.0	H	352.0	5.9	46.00	10.01
936.017875	35.60	124.0	H	17.0	8.3	46.00	10.40

5150-5250 MHz:

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11a									
5180 MHz									
5120.00	27.70	PK	239	1.5	H	41.60	69.30	83.5	14.20
5120.00	13.86	Ave.	239	1.5	H	41.60	55.46	63.5	8.04
5350.00	27.33	PK	114	2.4	H	42.06	69.39	83.5	14.11
5350.00	13.90	Ave.	114	2.4	H	42.06	55.96	63.5	7.54
10360.00	40.02	PK	327	2.1	H	21.69	61.71	77.7	15.99
5200 MHz									
10400.00	39.20	PK	235	1.1	H	21.79	60.99	77.7	16.71
5240 MHz									
5150.00	27.13	PK	185	2.2	H	41.43	68.56	83.5	14.94
5150.00	13.80	Ave.	185	2.2	H	41.43	55.23	63.5	8.27
5350.00	24.79	PK	61	2.4	H	42.06	66.85	83.5	16.65
5350.00	13.89	Ave.	61	2.4	H	42.06	55.95	63.5	7.55
10480.00	41.02	PK	234	1.1	H	21.49	62.51	77.7	15.19
802.11n20									
5180 MHz									
5140.00	27.84	PK	218	1.7	H	41.60	69.44	83.5	14.06
5140.00	13.90	Ave.	218	1.7	H	41.60	55.50	63.5	8.00
5350.00	27.40	PK	194	1.2	H	42.06	69.46	83.5	14.04
5350.00	13.79	Ave.	194	1.2	H	42.06	55.85	63.5	7.65
10360.00	40.26	PK	181	1.0	H	21.69	61.95	77.7	15.75
5200 MHz									
10400.00	40.36	PK	153	2.4	H	21.79	62.15	77.7	15.55
5240 MHz									
5150.00	27.40	PK	136	1.0	H	41.43	68.83	83.5	14.67
5150.00	13.93	Ave.	136	1.0	H	41.43	55.36	63.5	8.14
5350.00	27.10	PK	356	2.3	H	42.06	69.16	83.5	14.34
5350.00	13.57	Ave.	356	2.3	H	42.06	55.63	63.5	7.87
10480.00	40.10	PK	283	1.3	H	21.49	61.59	77.7	16.11

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5190 MHz									
5150.00	27.41	PK	185	2.2	H	41.43	68.84	83.5	14.66
5150.00	13.80	Ave.	185	2.2	H	41.43	55.23	63.5	8.27
5350.00	27.33	PK	226	1.9	H	42.06	69.39	83.5	14.11
5350.00	13.76	Ave.	226	1.9	H	42.06	55.82	63.5	7.68
10380.00	39.79	PK	183	2.1	H	21.69	61.48	77.7	16.22
5230 MHz									
5150.00	27.33	PK	306	1.0	H	41.43	68.76	83.5	14.74
5150.00	13.90	Ave.	306	1.0	H	41.43	55.33	63.5	8.17
5350.00	27.46	PK	290	2.5	H	42.06	69.52	83.5	13.98
5350.00	13.92	Ave.	290	2.5	H	42.06	55.98	63.5	7.52
10460.00	40.40	PK	52	1.1	H	21.39	61.79	77.7	15.91
802.11ac20									
5180 MHz									
5150.00	27.92	PK	148	1.8	H	41.43	69.35	83.5	14.15
5150.00	13.96	Ave.	148	1.8	H	41.43	55.39	63.5	8.11
5350.00	27.58	PK	136	2.3	H	42.06	69.64	83.5	13.86
5350.00	13.85	Ave.	136	2.3	H	42.06	55.91	63.5	7.59
10360.00	47.37	PK	274	2.2	H	21.69	69.06	77.7	8.6
5200 MHz									
10400.00	46.82	PK	256	1.7	H	21.79	68.61	77.7	9.09
5240 MHz									
5150.00	27.84	PK	27	1.3	H	41.43	69.27	83.5	14.23
5150.00	13.80	Ave.	27	1.3	H	41.43	55.23	63.5	8.27
5350.00	27.69	PK	251	2.1	H	42.06	69.75	83.5	13.75
5350.00	13.79	Ave.	251	2.1	H	42.06	55.85	63.5	7.65
10480.00	45.58	PK	279	1.2	H	21.49	67.07	77.7	10.63
802.11ac40									
5190 MHz									
5150.00	27.86	PK	129	1.8	H	41.43	69.29	83.5	14.21
5150.00	13.74	Ave.	129	1.8	H	41.43	55.17	63.5	8.33
5350.00	26.87	PK	308	1.1	H	42.06	68.93	83.5	14.57
5350.00	13.56	Ave.	308	1.1	H	42.06	55.62	63.5	7.88
10380.00	45.19	PK	191	1.6	H	21.69	66.88	77.7	10.82
5230 MHz									
5150.00	27.80	PK	261	1.7	H	41.43	69.23	83.5	14.27
5150.00	13.80	Ave.	261	1.7	H	41.43	55.23	63.5	8.27
5350.00	27.45	PK	83	1.9	H	42.06	69.51	83.5	13.99
5350.00	13.69	Ave.	83	1.9	H	42.06	55.75	63.5	7.75
10460.00	45.79	PK	244	2.0	H	21.39	67.18	77.7	10.52

5250-5350 MHz

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11a									
5260 MHz									
5150.00	31.70	PK	143	2.2	H	41.43	73.13	83.5	10.37
5150.00	15.60	Ave.	143	2.2	H	41.43	57.03	63.5	6.47
5350.00	30.22	PK	224	1.6	H	42.06	72.28	83.5	11.22
5350.00	15.03	Ave.	224	1.6	H	42.06	57.09	63.5	6.41
10520.00	39.05	PK	144	2.0	H	21.49	60.54	77.7	17.16
5280 MHz									
10560.00	39.10	PK	284	2.2	H	21.94	61.04	77.7	16.66
5320 MHz									
5150.00	29.90	PK	169	1.6	H	41.43	71.33	83.5	12.17
5150.00	15.02	Ave.	169	1.6	H	41.43	56.45	63.5	7.05
5350.00	29.61	PK	17	1.9	H	42.06	71.67	83.5	11.83
5350.00	14.89	Ave.	17	1.9	H	42.06	56.95	63.5	6.55
10640.00	39.93	PK	154	1.2	H	22.04	61.97	83.5	21.53
10640.00	25.60	Ave.	154	1.2	H	22.04	47.64	63.5	15.86
802.11n20									
5260 MHz									
5150.00	29.94	PK	259	1.3	H	41.43	71.37	83.5	12.13
5150.00	15.16	Ave.	259	1.3	H	41.43	56.59	63.5	6.91
5350.00	28.79	PK	292	2.4	H	42.06	70.85	83.5	12.65
5350.00	14.90	Ave.	292	2.4	H	42.06	56.96	63.5	6.54
10520.00	39.84	PK	296	1.5	H	20.91	60.75	77.7	16.77
5280 MHz									
10560.00	39.90	PK	23	1.1	H	21.94	61.84	77.7	15.68
5320 MHz									
5150.00	29.60	PK	217	1.6	H	41.43	71.03	83.5	12.47
5150.00	15.01	Ave.	217	1.6	H	41.43	56.44	63.5	7.06
5350.00	29.12	PK	92	2.4	H	42.06	71.18	83.5	12.32
5350.00	14.97	Ave.	92	2.4	H	42.06	57.03	63.5	6.47
10640.00	40.10	PK	22	1.5	H	22.04	62.14	83.5	21.36
10640.00	25.70	Ave.	22	1.5	H	22.04	47.74	63.5	15.76

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5270 MHz									
5150.00	29.66	PK	90	2.2	H	41.43	71.09	83.5	12.41
5150.00	15.06	Ave.	90	2.2	H	41.43	56.49	63.5	7.01
5352.00	29.50	PK	247	2.0	H	42.06	71.56	83.5	11.94
5352.00	14.90	Ave.	247	2.0	H	42.06	56.96	63.5	6.54
10540.00	40.30	PK	274	1.9	H	21.49	61.79	77.7	15.91
5310 MHz									
5150.00	29.14	PK	93	1.6	H	41.43	70.57	83.5	12.93
5150.00	14.99	Ave.	93	1.6	H	41.43	56.42	63.5	7.08
5352.00	29.30	PK	192	1.5	H	42.06	71.36	83.5	12.14
5352.00	14.56	Ave.	192	1.5	H	42.06	56.62	63.5	6.88
10620.00	39.60	PK	227	1.4	H	22.04	61.64	83.5	21.86
10620.00	26.10	Ave.	227	1.4	H	22.04	48.14	63.5	15.36
802.11ac20									
5260 MHz									
5150.00	29.65	PK	157	1.7	H	41.43	71.08	83.5	12.42
5150.00	15.03	Ave.	157	1.7	H	41.43	56.46	63.5	7.04
5352.00	29.25	PK	223	1.9	H	42.06	71.31	83.5	12.19
5352.00	15.01	Ave.	223	1.9	H	42.06	57.07	63.5	6.43
10520.00	39.74	PK	336	2.1	H	21.49	61.23	77.7	16.47
5280 MHz									
10560.00	40.01	PK	97	1.1	H	21.94	61.95	77.7	15.75
5320 MHz									
5150.00	29.74	PK	12	1.5	H	41.43	71.17	83.5	12.33
5150.00	14.95	Ave.	12	1.5	H	41.43	56.38	63.5	7.12
5350.00	29.16	PK	357	2.2	H	42.06	71.22	83.5	12.28
5350.00	14.55	Ave.	357	2.2	H	42.06	56.61	63.5	6.89
10640.00	39.74	PK	150	1.3	H	22.04	61.78	83.5	21.72
10640.00	26.35	Ave.	150	1.3	H	22.04	48.39	63.5	15.11
802.11ac40									
5270 MHz									
5150.00	29.30	PK	235	2.0	H	41.43	70.73	83.5	12.77
5150.00	14.89	Ave.	235	2.0	H	41.43	56.32	63.5	7.18
5350.00	29.36	PK	161	1.6	H	42.06	71.42	83.5	12.08
5350.00	14.99	Ave.	161	1.6	H	42.06	57.05	63.5	6.45
10540.00	39.90	PK	334	1.2	H	20.91	60.81	77.7	16.89
5310 MHz									
5150.00	29.45	PK	329	2.3	H	41.43	70.88	83.5	12.62
5150.00	14.80	Ave.	329	2.3	H	41.43	56.23	63.5	7.27
5350.00	29.33	PK	61	1.7	H	42.06	71.39	83.5	12.11
5350.00	14.75	Ave.	61	1.7	H	42.06	56.81	63.5	6.69
10620.00	40.11	PK	17	2.2	H	22.04	62.15	83.5	21.35
10620.00	26.33	Ave.	17	2.2	H	22.04	48.37	63.5	15.13

5470-5745 MHz

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11a									
5500 MHz									
5460.00	29.30	PK	74	1.7	H	42.36	71.66	83.5	11.84
5460.00	14.68	Ave.	74	1.7	H	42.36	57.04	63.5	6.46
5730.00	28.90	PK	345	2.5	H	42.78	71.68	77.7	6.02
11000.00	40.30	PK	1	1.5	H	22.24	62.54	83.5	20.96
11000.00	26.65	Ave.	1	1.5	H	22.24	48.89	63.5	14.61
5600 MHz									
11200.00	40.23	PK	109	1.2	H	22.48	62.71	83.5	20.79
11200.00	26.30	Ave.	109	1.2	H	22.48	48.78	63.5	14.72
5700 MHz									
5460.00	28.01	PK	274	2.2	H	42.36	70.37	83.5	13.13
5460.00	14.65	Ave.	274	2.2	H	42.36	57.01	63.5	6.49
5730.00	28.95	PK	344	2.4	H	42.78	71.73	77.7	5.97
11400.00	39.85	PK	271	1.6	H	23.33	63.18	83.5	20.32
11400.00	26.24	Ave.	271	1.6	H	23.33	49.57	63.5	13.93
802.11n20									
5500 MHz									
5460.00	28.35	PK	287	1.8	H	42.36	70.71	83.5	12.79
5460.00	14.20	Ave.	287	1.8	H	42.36	56.56	63.5	6.94
5730.00	28.60	PK	169	1.2	H	42.78	71.38	77.7	6.32
11000.00	40.06	PK	51	2.2	H	22.24	62.30	83.5	21.20
11000.00	26.30	Ave.	51	2.2	H	22.24	48.54	63.5	14.96
5600 MHz									
11200.00	39.56	PK	135	1.2	H	22.48	62.04	83.5	21.46
11200.00	25.77	Ave.	135	1.2	H	22.48	48.25	63.5	15.25
5700 MHz									
5460.00	28.56	PK	40	1.3	H	42.36	70.92	83.5	12.58
5460.00	14.36	Ave.	40	1.3	H	42.36	56.72	63.5	6.78
5730.00	28.71	PK	299	1.3	H	42.78	71.49	77.7	6.21
11400.00	39.90	PK	205	2.1	H	23.33	63.23	83.5	20.27
11400.00	25.89	Ave.	205	2.1	H	23.33	49.22	63.5	14.28

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5510 MHz									
5460.00	28.40	PK	98	1.5	H	42.36	70.76	83.5	12.74
5460.00	14.32	Ave.	98	1.5	H	42.36	56.68	63.5	6.82
5730.00	28.55	PK	40	2.3	H	42.78	71.33	77.7	6.37
11020.00	40.35	PK	290	1.0	H	22.24	62.59	83.5	20.91
11020.00	26.50	Ave.	290	1.0	H	22.24	48.74	63.5	14.76
5590 MHz									
5460.00	28.35	PK	45	1.0	H	42.36	70.71	83.5	12.79
5460.00	14.80	Ave.	45	1.0	H	42.36	57.16	63.5	6.34
5730.00	28.70	PK	14	2.3	H	42.78	71.48	77.7	6.22
11180.00	40.16	PK	232	1.5	H	22.48	62.64	83.5	20.86
11180.00	26.45	Ave.	232	1.5	H	22.48	48.93	63.5	14.57
802.11ac20									
5500 MHz									
5460.00	29.02	PK	96	2.1	H	42.36	71.38	83.5	12.12
5460.00	15.06	Ave.	96	2.1	H	42.36	57.42	63.5	6.08
5730.00	28.40	PK	43	2.4	H	42.78	71.18	77.7	6.52
11000.00	40.20	PK	262	2.0	H	22.24	62.44	83.5	21.06
11000.00	26.13	Ave.	262	2.0	H	22.24	48.37	63.5	15.13
5600 MHz									
11200.00	40.33	PK	80	1.6	H	22.48	62.81	83.5	20.69
11200.00	26.20	Ave.	80	1.6	H	22.48	48.68	63.5	14.82
5700 MHz									
5460.00	28.61	PK	299	2.0	H	42.36	70.97	83.5	12.53
5460.00	15.06	Ave.	299	2.0	H	42.36	57.42	63.5	6.08
5730.00	28.35	PK	244	1.4	H	42.78	71.13	77.7	6.57
11200.00	40.28	PK	56	2.4	H	22.48	62.76	83.5	20.74
11200.00	26.37	Ave.	56	2.4	H	22.48	48.85	63.5	14.65
802.11ac40									
5510 MHz									
5460.00	28.35	PK	90	2.2	H	42.36	70.71	83.5	12.79
5460.00	14.77	Ave.	90	2.2	H	42.36	57.13	63.5	6.37
5730.00	28.50	PK	237	2.3	H	42.78	71.28	77.7	6.42
11020.00	40.50	PK	255	1.1	H	22.24	62.74	83.5	20.76
11020.00	26.30	Ave.	255	1.1	H	22.24	48.54	63.5	14.96
5590 MHz									
5460.00	28.44	PK	190	2.5	H	42.36	70.80	83.5	12.70
5460.00	14.80	Ave.	190	2.5	H	42.36	57.16	63.5	6.34
5730.00	28.61	PK	296	1.7	H	42.78	71.39	77.7	6.31
11180.00	40.31	PK	174	1.4	H	22.48	62.79	83.5	20.71
11180.00	26.41	Ave.	174	1.4	H	22.48	48.89	63.5	14.61

5725-5850 MHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11a									
5745 MHz									
5725.00	27.68	PK	234	1.8	H	42.78	70.46	131.7	61.24
5720.00	27.80	PK	234	1.8	H	42.78	70.58	120.3	49.72
5650.00	27.74	PK	4	1.7	H	42.78	70.52	77.7	7.18
5850.00	27.36	Ave.	4	1.7	H	42.87	70.23	131.7	61.47
11490.00	40.79	PK	127	1.2	H	24.17	64.96	83.5	18.54
11490.00	26.30	Ave.	127	1.2	H	24.17	50.47	63.5	13.03
5785 MHz									
11570.00	40.38	PK	34	1.9	H	23.10	63.48	83.5	20.02
11570.00	25.89	Ave.	34	1.9	H	23.10	48.99	63.5	14.51
5825 MHz									
5850.00	27.49	PK	13	1.6	H	42.87	70.36	131.7	61.34
5855.00	27.50	PK	13	1.6	H	42.87	70.37	120.3	49.93
5925.00	27.61	PK	215	1.9	H	42.97	70.58	77.7	7.12
5725.00	27.00	PK	215	1.9	H	42.78	69.78	131.7	61.92
11650.00	40.05	PK	197	1.8	H	22.37	62.42	83.5	21.08
11650.00	26.10	Ave.	197	1.8	H	22.37	48.47	63.5	15.03

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11n20									
5745 MHz									
5725.00	27.60	PK	242	2.0	H	42.78	70.38	131.7	61.32
5720.00	28.10	PK	242	2.0	H	42.78	70.88	120.3	49.42
5650.00	28.06	PK	57	1.8	H	42.78	70.84	77.7	6.86
5850.00	27.95	Ave.	57	1.8	H	42.87	70.82	131.7	60.88
11490.00	39.97	PK	346	1.8	H	24.17	64.14	83.5	19.36
11490.00	25.89	Ave.	346	1.8	H	24.17	50.06	63.5	13.44
5785 MHz									
11570.00	40.62	PK	113	1.5	H	23.10	63.72	83.5	19.78
11570.00	26.32	Ave.	113	1.5	H	23.10	49.42	63.5	14.08
5825 MHz									
5850.00	28.45	PK	113	1.7	H	42.87	71.32	131.7	60.38
5855.00	28.20	PK	113	1.7	H	42.87	71.07	120.3	49.23
5925.00	27.90	PK	55	2.4	H	42.97	70.87	77.7	6.83
5725.00	27.84	PK	55	2.4	H	42.78	70.62	131.7	61.08
11650.00	39.90	PK	99	1.4	H	22.37	62.27	83.5	21.23
11650.00	26.18	Ave.	99	1.4	H	22.37	48.55	63.5	14.95

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5755 MHz									
5725.00	28.90	PK	194	1.1	H	42.78	71.68	131.7	60.02
5720.00	28.76	PK	194	1.1	H	42.78	71.54	120.3	48.76
5650.00	27.54	PK	103	2.1	H	42.78	70.32	77.7	7.38
5850.00	28.10	Ave.	103	2.1	H	42.87	70.97	131.7	60.73
11510.00	40.37	PK	167	2.2	H	24.17	64.54	83.5	18.96
11510.00	25.90	Ave.	167	2.2	H	24.17	50.07	63.5	13.43
5795 MHz									
5850.00	28.90	PK	139	1.6	H	42.87	71.77	131.7	59.93
5855.00	28.46	PK	139	1.6	H	42.87	71.33	120.3	48.97
5925.00	27.31	PK	311	2.1	H	42.97	70.28	77.7	7.42
5725.00	28.05	PK	311	2.1	H	42.78	70.83	131.7	60.87
11590.00	40.28	PK	162	1.9	H	23.10	63.38	83.5	20.12
11590.00	26.08	Ave.	162	1.9	H	23.10	49.18	63.5	14.32

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11ac20									
5745 MHz									
5725.00	29.35	PK	104	1.2	H	42.78	72.13	131.7	59.57
5720.00	28.40	PK	104	1.2	H	42.78	71.18	120.3	49.12
5650.00	27.67	PK	268	1.9	H	42.78	70.45	77.7	7.25
5850.00	28.36	Ave.	268	1.9	H	42.87	71.23	131.7	60.47
11590.00	39.35	PK	131	1.3	H	23.10	62.45	83.5	21.05
11590.00	25.48	Ave.	131	1.3	H	23.10	48.58	63.5	14.92
5785 MHz									
11570.00	39.48	PK	230	1.1	H	23.10	62.58	83.5	20.92
11570.00	25.68	Ave.	230	1.1	H	23.10	48.78	63.5	14.72
5825 MHz									
5850.00	28.79	PK	164	1.1	H	42.87	71.66	131.7	60.04
5855.00	28.59	PK	164	1.1	H	42.87	71.46	120.3	48.84
5925.00	28.05	PK	289	1.3	H	42.97	71.02	77.7	6.68
5725.00	28.31	PK	289	1.3	H	42.78	71.09	131.7	60.61
11650.00	39.87	PK	123	1.5	H	22.37	62.24	83.5	21.26
11650.00	25.71	Ave.	123	1.5	H	22.37	48.08	63.5	15.42

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11ac40									
5755 MHz									
5725.00	28.99	PK	16	2.0	H	42.78	71.77	131.7	59.93
5720.00	28.65	PK	16	2.0	H	42.78	71.43	120.3	48.87
5650.00	27.41	PK	358	1.2	H	42.78	70.19	77.7	7.51
5850.00	27.60	Ave.	358	1.2	H	42.87	70.47	131.7	61.23
11510.00	39.47	PK	214	1.0	H	24.17	63.64	83.5	19.86
11510.00	25.64	Ave.	214	1.0	H	24.17	49.81	63.5	13.69
5795 MHz									
5850.00	29.65	PK	189	1.3	H	42.87	72.52	131.7	59.18
5855.00	29.20	PK	189	1.3	H	42.87	72.07	120.3	48.23
5925.00	27.54	PK	261	1.6	H	42.97	70.51	77.7	7.19
5725.00	27.34	PK	261	1.6	H	42.78	70.12	131.7	61.58
11590.00	39.84	PK	279	2.0	H	23.10	62.94	83.5	20.56
11590.00	25.70	Ave.	279	2.0	H	23.10	48.80	63.5	14.70

Note:

Corrected Amplitude = Corrected Factor + Reading



Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor

Margin = Limit- Corr. Amplitude



All other spurious emissions are 20 dB below the limit or are on the system noise floor level.

Peak



Pre-scan with 802.11a 5745MHz
Horizontal





Vertical



Average Horizontal



Vertical



§15.407(B) (1), (2), (3), (4) –OUT OF BAND EMISSION

Applicable Standard

FCC §15.407 (b) (1), (2), (3), (4);

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27dBm/MHz.


For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.

For transmitters operating in the 5.725–5.825 GHz band: All emissions shall be limited to a level of –27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The Resolution bandwidth is set to 1MHz, The Video bandwidth is set to ≥ 1 MHz, report the peak value out of the operating band.
3. Repeat above procedures until all frequencies measured were complete.
4. when necessary, provided the measured energy is integrated to show the total power over 1 MHz.



Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2019-01-16 to 2019-04-02.

EUT operation mode: Transmitting


5150 – 5250 MHz:

802.11a mode, Band Edge, Left Side




Date: 16.JAN.2019 18:44:14

802.11a mode, Band Edge, Right Side




Date: 16.JAN.2019 18:45:52

802.11n20 mode, Band Edge, Left Side




Date: 16.JAN.2019 18:47:59

802.11n20 mode, Band Edge, Right Side




Date: 16.JAN.2019 18:47:03

802.11n40 mode, Band Edge, Left Side




Date: 16.JAN.2019 19:04:12

802.11n40 mode, Band Edge, Right Side




Date: 16.JAN.2019 19:05:18

802.11ac20 mode, Band Edge, Left Side




Date: 16.JAN.2019 18:50:35

802.11ac20 mode, Band Edge, Right Side




Date: 16.JAN.2019 18:52:12

802.11ac40 mode, Band Edge, Left Side



Date: 16.JAN.2019 19:01:31


802.11ac40 mode, Band Edge, Right Side



Date: 16.JAN.2019 19:00:30


5250 – 5350 MHz:

802.11a mode, Band Edge, Left Side




Date: 2.APR.2019 21:30:48

802.11a mode, Band Edge, Right Side




Date: 2.APR.2019 21:31:14

802.11n20 mode, Band Edge, Left Side




Date: 2.APR.2019 21:30:15

802.11n20 mode, Band Edge, Right Side




Date: 2.APR.2019 21:29:34

802.11n40 mode, Band Edge, Left Side




Date: 2.APR.2019 21:26:03

802.11n40 mode, Band Edge, Right Side




Date: 2.APR.2019 21:26:41

802.11ac20 mode, Band Edge, Left Side




Date: 2.APR.2019 21:28:36

802.11ac20 mode, Band Edge, Right Side




Date: 2.APR.2019 21:29:10

802.11ac40 mode, Band Edge, Left Side



Date: 2.APR.2019 21:27:28


802.11ac40 mode, Band Edge, Right Side



Date: 2.APR.2019 21:26:59


5470 – 5745 MHz:

802.11a mode, Band Edge, Left Side




Date: 18.MAR.2019 22:17:17

802.11a mode, Band Edge, Right Side




Date: 2.APR.2019 21:19:13

802.11n20 mode, Band Edge, Left Side




Date: 18.MAR.2019 22:15:56

802.11n20 mode, Band Edge, Right Side




Date: 2.APR.2019 21:19:57

802.11n40 mode, Band Edge, Left Side




Date: 18.MAR.2019 22:08:32

802.11n40 mode, Band Edge, Right Side




Date: 2.APR.2019 21:22:39

802.11ac20 mode, Band Edge, Left Side




Date: 18.MAR.2019 22:13:13

802.11ac20 mode, Band Edge, Right Side




Date: 2.APR.2019 21:20:40

802.11ac40 mode, Band Edge, Left Side



Date: 18.MAR.2019 22:11:24


802.11ac40 mode, Band Edge, Right Side



Date: 2.APR.2019 21:22:06


5725 – 5850 MHz:

802.11a mode, Band Edge, Left Side




Date: 16.JAN.2019 19:19:53

802.11a mode, Band Edge, Right Side




Date: 16.JAN.2019 19:21:39

802.11n20 mode, Band Edge, Left Side




Date: 16.JAN.2019 19:13:25

802.11n20 mode, Band Edge, Right Side




Date: 16.JAN.2019 19:14:07

802.11n40 mode, Band Edge, Left Side




Date: 16.JAN.2019 19:22:43

802.11n40 mode, Band Edge, Right Side




Date: 16.JAN.2019 19:23:49

802.11ac20 mode, Band Edge, Left Side




Date: 16.JAN.2019 19:16:07

802.11ac20 mode, Band Edge, Right Side




Date: 16.JAN.2019 19:14:44

802.11ac40 mode, Band Edge, Left Side



Date: 16.JAN.2019 19:27:11

802.11ac40 mode, Band Edge, Right Side



Date: 16.JAN.2019 19:27:57

FCC §15.407(a) (1) – 26 dB & 6dB EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2019-01-14 and 2019-03-18.


EUT operation mode: Transmitting

Test Result: Pass; please refer to the following tables and plots.

5150 MHz - 5250 MHz:


Frequency (MHz)	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Remark
802.11a			No transmitted signal in the 99% bandwidth extends into the U-NII-2A band
5180	20.256	17.308	
5200	20.321	17.308	
5240	20.128	17.115	
802.11n20			
5180	20.321	17.949	
5200	20.256	17.885	
5240	20.256	17.885	
802.11n40			
5190	40.897	36.410	
5230	40.897	36.410	
802.11ac20			
5180	20.256	17.885	
5200	20.256	17.949	
5240	20.256	17.885	
802.11ac40			
5190	40.897	36.410	
5230	40.769	36.410	

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz




Date: 14.JAN.2019 19:35:30


802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz



Date: 14.JAN.2019 19:37:39


802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz

Date: 14.JAN.2019 19:38:44

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz


Date: 14.JAN.2019 19:54:03

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz




Date: 14.JAN.2019 19:44:23

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz




Date: 14.JAN.2019 19:42:15

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5190 MHz




Date: 14.JAN.2019 20:02:34

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz




Date: 14.JAN.2019 20:01:15

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz




Date: 14.JAN.2019 19:55:06


802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz



Date: 14.JAN.2019 19:56:20


802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz

Date: 14.JAN.2019 19:57:24

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5190 MHz

Date: 14.JAN.2019 19:58:54

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz




Date: 14.JAN.2019 19:59:50

5250 MHz - 5350 MHz:


Frequency (MHz)	26dB bandwidth (MHz)	99% Bandwidth (MHz)
802.11a		
5260	20.26	17.24
5280	20.13	17.12
5320	20.26	17.31
802.11n20		
5260	20.26	17.95
5280	20.26	17.95
5320	20.26	17.88
802.11n40		
5270	40.77	36.41
5310	40.90	36.54
802.11ac20		
5260	20.26	17.88
5280	20.26	17.95
5320	20.26	17.88
802.11ac40		
5270	40.90	36.41
5310	40.90	36.54

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5260 MHz




Date: 18.MAR.2019 19:55:13


802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5280 MHz



Date: 18.MAR.2019 19:56:13


802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5320 MHz

Date: 18.MAR.2019 19:57:14

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5260 MHz


Date: 18.MAR.2019 19:53:35

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5280 MHz




Date: 18.MAR.2019 19:52:03


802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5320 MHz




Date: 18.MAR.2019 19:50:04

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5270 MHz


Date: 18.MAR.2019 19:17:09

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5310 MHz


Date: 18.MAR.2019 19:18:37

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5260 MHz


Date: 18.MAR.2019 19:45:51

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5280 MHz

Date: 18.MAR.2019 19:47:31


802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5320 MHz

Date: 18.MAR.2019 19:49:08

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5270 MHz

Date: 18.MAR.2019 19:44:26

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5310 MHz




Date: 18.MAR.2019 19:20:23

5470 MHz – 5745 MHz:


Frequency (MHz)	26dB bandwidth (MHz)	99% Bandwidth (MHz)
802.11a		
5500	20.26	17.12
5600	20.26	17.31
5700	20.26	17.31
802.11n20		
5500	20.32	17.88
5600	20.26	17.95
5700	20.26	17.88
802.11n40		
5510	40.64	36.41
5590	40.90	36.41
5670	40.90	36.41
802.11ac20		
5500	20.32	17.88
5600	20.26	17.88
5700	20.26	17.88
802.11ac40		
5510	40.64	36.41
5590	40.90	36.54
5670	40.90	36.41

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5500 MHz




Date: 18.MAR.2019 21:48:57


802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5600 MHz



Date: 18.MAR.2019 21:52:59


802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5700 MHz

Date: 18.MAR.2019 21:55:45

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5500 MHz


Date: 18.MAR.2019 21:33:02

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5600 MHz




Date: 18.MAR.2019 21:34:46

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5700 MHz




Date: 18.MAR.2019 21:37:04

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5510 MHz




Date: 18.MAR.2019 21:29:55


802.11 n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5590 MHz



Date: 18.MAR.2019 21:27:23


802.11 n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5670 MHz

Date: 18.MAR.2019 21:26:01

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5500 MHz


Date: 18.MAR.2019 21:46:47

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5600 MHz




Date: 18.MAR.2019 21:41:04


802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5700 MHz



Date: 18.MAR.2019 21:38:40


802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5510 MHz

Date: 18.MAR.2019 21:19:25

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5590 MHz

Date: 18.MAR.2019 21:23:42

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5670 MHz




Date: 18.MAR.2019 21:24:42

5725 MHz – 5850 MHz:


Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Remark
802.11a				No transmitted signal in the 99% bandwidth extends into the U-NII-2C band
5745	16.442	16.987	0.5	
5785	16.394	16.859	0.5	
5825	16.442	16.859	0.5	
802.11n20				
5745	17.644	17.756	0.5	
5785	17.596	17.756	0.5	
5825	17.644	17.692	0.5	
802.11n40				
5755	36.442	36.154	0.5	
5795	36.346	36.154	0.5	
802.11ac20				
5745	17.644	17.692	0.5	
5785	17.644	17.692	0.5	
5825	17.644	17.756	0.5	
802.11ac40				
5755	36.442	36.026	0.5	
5795	36.346	36.154	0.5	

802.11a mode, 6dB Emission Bandwidth, 5745 MHz




Date: 14.JAN.2019 21:00:12

802.11a mode, 6dB Emission Bandwidth, 5785 MHz




Date: 14.JAN.2019 21:02:21

802.11a mode, 6dB Emission Bandwidth, 5825 MHz




Date: 14.JAN.2019 21:04:45

802.11n20 mode, 6dB Emission Bandwidth, 5745 MHz




Date: 14.JAN.2019 20:37:24

802.11n20 mode, 6dB Emission Bandwidth, 5785 MHz




Date: 14.JAN.2019 20:38:43

802.11n20 mode, 6dB Emission Bandwidth, 5825 MHz




Date: 14.JAN.2019 20:39:54

802.11n40 mode, 6dB Emission Bandwidth, 5755 MHz




Date: 14.JAN.2019 20:28:53

802.11n40 mode, 6dB Emission Bandwidth, 5795 MHz




Date: 14.JAN.2019 20:27:39

802.11ac20 mode, 6dB Emission Bandwidth, 5745 MHz




Date: 14.JAN.2019 20:51:58

802.11ac20 mode, 6dB Emission Bandwidth, 5785 MHz




Date: 14.JAN.2019 20:50:12

802.11ac20 mode, 6dB Emission Bandwidth, 5825 MHz




Date: 14.JAN.2019 20:43:18

802.11ac40 mode, 6dB Emission Bandwidth, 5755 MHz




Date: 14.JAN.2019 20:24:59

802.11ac40 mode, 6dB Emission Bandwidth, 5795 MHz




Date: 14.JAN.2019 20:26:25

802.11a mode, 99% Occupied Bandwidth, 5745 MHz




Date: 14.JAN.2019 20:17:38

802.11a mode, 99% Occupied Bandwidth, 5785 MHz




Date: 14.JAN.2019 20:18:10

802.11a mode, 99% Occupied Bandwidth, 5825 MHz




Date: 14.JAN.2019 20:19:06

802.11n20 mode, 99% Occupied Bandwidth, 5745 MHz




Date: 14.JAN.2019 20:16:54

802.11n20 mode, 99% Occupied Bandwidth, 5785 MHz




Date: 14.JAN.2019 20:16:17

802.11n20 mode, 99% Occupied Bandwidth, 5825 MHz




Date: 14.JAN.2019 20:15:36

802.11n40 mode, 99% Occupied Bandwidth, 5755 MHz




Date: 14.JAN.2019 20:20:56

802.11n40 mode, 99% Occupied Bandwidth, 5795 MHz




Date: 14.JAN.2019 20:22:03

802.11ac20 mode, 99% Occupied Bandwidth, 5745 MHz




Date: 14.JAN.2019 20:13:47

802.11ac20 mode, 99% Occupied Bandwidth, 5785 MHz




Date: 14.JAN.2019 20:14:31

802.11ac20 mode, 99% Occupied Bandwidth, 5825 MHz




Date: 14.JAN.2019 20:15:06

802.11ac40 mode, 99% Occupied Bandwidth, 5755 MHz



Date: 14.JAN.2019 20:23:37

802.11ac40 mode, 99% Occupied Bandwidth, 5795 MHz



Date: 14.JAN.2019 20:22:45

FCC §15.407(a) (1) (2)(3) – CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2019-01-13.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the following tables.

5150 MHz – 5250 MHz(this is a client device)

Frequency (MHz)	Output Power (dBm)	Limit (dBm)
802.11a		
5180	8.20	24
5200	8.15	
5240	8.00	
802.11n20		
5180	8.31	24
5200	8.19	
5240	7.92	
802.11n40		
5190	8.16	24
5230	8.07	
802.11ac20		
5180	8.21	24
5200	8.28	
5240	8.16	
802.11ac40		
5190	8.42	24
5230	7.86	

5250 MHz – 5350 MHz:

Frequency (MHz)	Output Power (dBm)	Limit (dBm)
802.11a		
5260	8.94	24
5280	8.95	
5320	8.65	
802.11n20		
5260	8.90	24
5280	9.12	
5320	9.02	
802.11n40		
5270	8.65	24
5310	8.73	
802.11ac20		
5260	8.88	24
5280	8.62	
5320	8.58	
802.11ac40		
5270	8.94	24
5310	8.79	

5470 MHz – 5725 MHz:

Frequency (MHz)	Output Power (dBm)	Limit (dBm)
802.11a		
5500	8.83	24
5600	8.44	
5700	8.11	
802.11n20		
5500	8.87	24
5600	8.64	
5700	8.13	
802.11n40		
5510	8.81	24
5590	8.47	
5670	8.05	
802.11ac20		
5500	8.87	24
5600	8.44	
5700	8.06	
802.11ac40		
5510	8.76	24
5590	8.61	
5710	8.04	

5725 MHz – 5850 MHz:

Frequency (MHz)	Output Power (dBm)	Limit (dBm)
802.11a		
5745	8.55	30
5785	8.72	
5825	8.54	
802.11n20		
5745	8.18	30
5785	8.37	
5825	8.50	
802.11n40		
5755	8.87	30
5795	9.34	
802.11ac20		
5745	8.08	30
5785	8.63	
5825	8.70	
802.11ac40		
5755	8.94	30
5795	9.48	

FCC §15.407(a) (1) (2) (3) - POWER SPECTRAL DENSITY**Applicable Standard**

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth ($< 1 \text{ MHz}$, or $< 500 \text{ kHz}$) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $\text{VBW} \geq 3 \text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500 \text{ kHz/RBW})$ to the measured result, whereas $\text{RBW} (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz/RBW})$ to the measured result, whereas $\text{RBW} (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2019-01-16 and 2019-03-18.

EUT operation mode: Transmitting


Test Result: Pass

Please refer to the following tables and plots.

5150 MHz – 5250 MHz


Frequency (MHz)	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a		
5180	-1.24	11
5200	-1.34	
5240	-1.21	
802.11n20		
5180	-1.57	11
5200	-1.48	
5240	-1.56	
802.11n40		
5190	-4.26	11
5230	-4.26	
802. 11ac20		
5180	-1.62	11
5200	-1.41	
5240	-1.58	
802. 11ac40		
5190	-4.13	11
5230	-4.38	

802.11a mode, Power Spectral Density, 5180 MHz




Date: 16.JAN.2019 20:08:46

802.11a mode, Power Spectral Density, 5200 MHz




Date: 16.JAN.2019 20:09:21

802.11a mode, Power Spectral Density, 5240 MHz




Date: 16.JAN.2019 20:09:53

802.11n20 mode, Power Spectral Density, 5180 MHz




Date: 16.JAN.2019 20:03:17

802.11n20 mode, Power Spectral Density, 5200 MHz




Date: 16.JAN.2019 20:03:51

802.11n20 mode, Power Spectral Density, 5240 MHz




Date: 16.JAN.2019 20:04:24

802.11n40 mode, Power Spectral Density, 5190 MHz




Date: 16.JAN.2019 20:02:34

802.11n40 mode, Power Spectral Density, 5230 MHz




Date: 16.JAN.2019 20:02:07

802.11ac20 mode, Power Spectral Density, 5180 MHz




Date: 16.JAN.2019 20:05:44

802.11ac20 mode, Power Spectral Density, 5200 MHz




Date: 16.JAN.2019 20:05:20

802. 11ac20 mode, Power Spectral Density, 5240 MHz




Date: 16.JAN.2019 20:04:47

802. 11ac40 mode, Power Spectral Density, 5190 MHz



Date: 16.JAN.2019 20:01:03

802.11ac40 mode, Power Spectral Density, 5230 MHz




Date: 16.JAN.2019 20:01:39

5250 MHz – 5350 MHz:


Frequency (MHz)	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a		
5260	-2.42	11
5280	-2.50	
5320	-2.28	
802.11n20		
5260	-2.31	11
5280	-2.36	
5320	-2.99	
802.11n40		
5270	-5.55	11
5310	-5.67	
802. 11ac20		
5260	-1.97	11
5280	-2.47	
5320	-3.02	
802. 11ac40		
5270	-5.22	11
5310	-5.08	

802.11a mode, Power Spectral Density, 5260 MHz




Date: 18.MAR.2019 20:01:02

802.11a mode, Power Spectral Density, 5280 MHz




Date: 18.MAR.2019 20:00:21

802.11a mode, Power Spectral Density, 5320 MHz




Date: 18.MAR.2019 19:58:24

802.11n20 mode, Power Spectral Density, 5260 MHz




Date: 18.MAR.2019 20:03:24

802.11n20 mode, Power Spectral Density, 5280 MHz




Date: 18.MAR.2019 20:04:26

802.11n20 mode, Power Spectral Density, 5320 MHz




Date: 18.MAR.2019 20:05:04

802.11n40 mode, Power Spectral Density, 5270 MHz




Date: 18.MAR.2019 20:11:31

802.11n40 mode, Power Spectral Density, 5310 MHz




Date: 18.MAR.2019 20:10:51

802.11ac20 mode, Power Spectral Density, 5260 MHz




Date: 18.MAR.2019 20:06:50

802.11ac20 mode, Power Spectral Density, 5280 MHz




Date: 18.MAR.2019 20:06:14

802.11ac20 mode, Power Spectral Density, 5320 MHz




Date: 18.MAR.2019 20:05:41

802.11ac40 mode, Power Spectral Density, 5270 MHz



Date: 18.MAR.2019 20:09:04

802.11ac40 mode, Power Spectral Density, 5310 MHz




Date: 18.MAR.2019 20:09:49

5470 MHz – 5725 MHz:


Frequency (MHz)	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a		
5500	-1.98	11
5600	-2.48	
5700	-3.65	
802.11n20		
5500	-2.69	11
5600	-3.13	
5700	-3.67	
802.11n40		
5510	-5.42	11
5590	-5.50	
5670	-6.06	
802. 11ac20		
5500	-2.46	11
5600	-2.88	
5700	-3.70	
802. 11ac40		
5510	-5.40	11
5590	-5.60	
5670	-6.31	

802.11a mode, Power Spectral Density, 5500 MHz




Date: 18.MAR.2019 21:59:25

802.11a mode, Power Spectral Density, 5600 MHz




Date: 18.MAR.2019 21:58:03

802.11a mode, Power Spectral Density, 5700 MHz




Date: 18.MAR.2019 21:57:07

802.11n20 mode, Power Spectral Density, 5500 MHz




Date: 18.MAR.2019 22:00:04

802.11n20 mode, Power Spectral Density, 5600 MHz




Date: 18.MAR.2019 22:01:05

802.11n20 mode, Power Spectral Density, 5700 MHz




Date: 18.MAR.2019 22:01:36

802.11n40 mode, Power Spectral Density, 5510 MHz




Date: 18.MAR.2019 22:07:06

802.11n40 mode, Power Spectral Density, 5590 MHz




Date: 18.MAR.2019 22:06:16

802.11n40 mode, Power Spectral Density, 5670 MHz




Date: 18.MAR.2019 22:05:47

802.11ac20 mode, Power Spectral Density, 5500 MHz




Date: 18.MAR.2019 22:03:22

802.11ac20 mode, Power Spectral Density, 5600 MHz




Date: 18.MAR.2019 22:02:26

802.11ac20 mode, Power Spectral Density, 5700 MHz




Date: 18.MAR.2019 22:01:59

802.11ac40 mode, Power Spectral Density, 5510 MHz




Date: 18.MAR.2019 22:04:09

802.11ac40 mode, Power Spectral Density, 5590 MHz



Date: 18.MAR.2019 22:05:01

802.11ac40 mode, Power Spectral Density, 5670 MHz




Date: 18.MAR.2019 22:05:25

5725 MHz – 5850 MHz:


Frequency (MHz)	Power Spectral Density (dBm/500kHz)	Limit (dBm/500kHz)
802.11a		
5745	-3.36	30
5785	-3.39	
5825	-3.59	
802.11n20		
5745	-2.98	30
5785	-3.29	
5825	-4.06	
802.11n40		
5755	-6.41	30
5795	-6.20	
802.11ac20		
5745	-2.98	30
5785	-3.25	
5825	-3.52	
802. 11ac40		
5755	-5.80	30
5795	-5.81	

802.11a mode, Power Spectral Density, 5745 MHz




Date: 16.JAN.2019 19:52:26

802.11a mode, Power Spectral Density, 5785 MHz




Date: 16.JAN.2019 19:53:01

802.11a mode, Power Spectral Density, 5825 MHz




Date: 16.JAN.2019 19:53:32

802.11n20 mode, Power Spectral Density, 5745 MHz




Date: 16.JAN.2019 19:39:17

802.11n20 mode, Power Spectral Density, 5785 MHz




Date: 16.JAN.2019 19:38:51

802.11n20 mode, Power Spectral Density, 5825 MHz




Date: 16.JAN.2019 19:38:09

802.11n40 mode, Power Spectral Density, 5755 MHz




Date: 16.JAN.2019 19:54:10

802.11n40 mode, Power Spectral Density, 5795 MHz




Date: 16.JAN.2019 19:54:45

802.11ac20 mode, Power Spectral Density, 5745 MHz




Date: 16.JAN.2019 19:39:17

802.11ac20 mode, Power Spectral Density, 5785 MHz




Date: 16.JAN.2019 19:51:16

802.11ac20 mode, Power Spectral Density, 5825 MHz




Date: 16.JAN.2019 19:51:43

802.11ac40 mode, Power Spectral Density, 5755 MHz



Date: 16.JAN.2019 19:56:02

802.11ac40 mode, Power Spectral Density, 5795 MHz



Date: 16.JAN.2019 19:55:15

***** END OF REPORT *****