



SAR Test Report

For

Applicant Name: Imin Technology Pte Ltd
Address: 11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943
EUT Name: Quest Handheld
Model Number: Quest-Handheld

Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Report Number: BTF240808R01201
Test Standards: FCC 47 CFR§2.1093 IEC/IEEE 62209-1528: 2020
IEEE C95.1-2019 KDB447498 D01 KDB865664 D01
KDB865664 D02 KDB941225 D01 KDB941225 D05
KDB248227 D01 KDB941225 D06 KDB648474 D04
KDB690783 D01

FCC ID: 2AYD5-QSTHNHLD
Test Conclusion: Pass
Test Date: 2024-08-06 to 2024-08-15
Date of Issue: 2024-08-16

Prepared By: Zoey Zhang
Zoey Zhang / Test Engineer

Prepared By: Amenda Zhong
Amenda Zhong / Project Engineer

Date: 2024-08-16

Approved By: Ryan.CJ
Ryan.CJ / EMC Manager

Date: 2024-08-16

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2024-08-16	Original
Note:		Once the revision has been made, then previous versions reports are invalid.

Table of Contents

1. Introduction	4
1.1 Identification of Testing Laboratory	4
1.2 Identification of the Responsible Testing Location	4
1.3 Laboratory Condition	4
1.4 Announcement	4
2. Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Equipment under Test Ancillary Equipment	5
2.6 Technical Information	5
3. Summary of Test Results	7
3.1 Test Standards	7
3.2 Device Category and SAR Limit	7
3.3 Test Result Summary	8
3.4 Test Uncertainty	9
4. Measurement System	11
4.1 Specific Absorption Rate (SAR) Definition	11
4.2 MVG SAR System	11
5. System Verification	16
5.1 Purpose of System Check	16
5.2 System Check Setup	16
6. TEST POSITION CONFIGURATIONS	17
6.1 Head Exposure Conditions	17
6.2 Body-worn Position Conditions	22
6.3 Hotspot Mode Exposure Position Conditions	23
6.4 Product Specific 10g Exposure Consideration	23
7. Measurement Procedure	24
7.1 Measurement Process Diagram	24
7.2 SAR Scan General Requirement	25
7.3 Measurement Procedure	26
7.4 Area & Zoom Scan Procedure	26
8. Conducted RF Output Power	27
8.1 GSM	27
8.2 WCDMA	28
8.3 LTE	29
8.4 Wi-Fi	46
8.5 Bluetooth	48
8.6 NFC	48
9. Test Exclusion Consideration	49
9.1 SAR Test Exclusion Consideration Table	49
10. Test Result	49
11. SAR Measurement Variability	54
12. Simultaneous Transmission	55
12.1 Simultaneous Transmission Mode Considerations	55
12.2 Sum SAR of Simultaneous Transmission	55
13. Test Equipment List	56
ANNEX A Simulating Liquid Verification Result	57
ANNEX B System Check Result	57
ANNEX C SAR Dipole Calibrations	58
ANNEX D Test Data	81
ANNEX E SAR Test Setup Photos	123
ANNEX F EUT External and Internal Photos	124
ANNEX G Calibration Information	124

1. Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
FCC Registration Number	518915
Designation Number	CN1330

1.3 Laboratory Condition

Ambient Temperature:	21°C to 25°C
Ambient Relative Humidity:	48% to 59%
Ambient Pressure:	100 kPa to 102 kPa

1.4 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Product Information

2.1 Application Information

Company Name:	Imin Technology Pte Ltd
Address:	11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943

2.2 Manufacturer Information

Company Name:	Touch Dynamic
Address:	Touch Dynamic, 121 Corporate Blvd, South Plainfield, New Jersey, 07080

2.3 Factory Information

Company Name:	Jiangxi Neostra Electronic Co. Ltd
Address:	279 Shenzhen Road, Jinggangshan economic and Technological Development Zone, Ji' an, Jiangxi
Company Name:	Neosta Technology Sdn. Bhd.
Address:	No.78, Jln I-Park SAC 5, Taman Perindustrian i-ParkSAC, 81400 Senai, Johor, Malaysia

2.4 General Description of Equipment under Test (EUT)

EUT Name	Quest Handheld
Under Test Model Name	Quest-Handheld

2.5 Equipment under Test Ancillary Equipment

Ancillary Equipment 1	Rechargeable Battery	
	Capacity	2500mAh
	Rated Voltage	7.6V

2.6 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EGPRS 850/1900 3G Network WCDMA/HSDPA/HSUPA Band 2/5 4G Network FDD LTE Band 2/4/5/7/12/14/17/25/26/66 TDD LTE Band 41 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) BT (EDR+BLE) NFC
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	GSM, WCDMA, LTE, WLAN, Bluetooth, NFC		
Frequency Range	GSM 850	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 7	TX: 2500 ~ 2570 MHz	RX: 2620 ~ 2690 MHz
	LTE Band 12	TX: 698 ~ 716 MHz	RX: 728 ~ 746 MHz
	LTE Band 14	TX: 788 ~ 798 MHz	RX: 758 ~ 768 MHz
	LTE Band 17	TX: 704 ~ 716 MHz	RX: 734 ~ 746 MHz
	LTE Band 25	TX: 1850 ~ 1915 MHz	RX: 1930 ~ 1995 MHz
	LTE Band 26 part 90	TX: 814.7 ~ 823.3 MHz	RX: 859.7 ~ 868.3 MHz
	LTE Band 26 part 22	TX: 824.7 ~ 848.3 MHz	RX: 869.7 ~ 893.3 MHz
	LTE Band 66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2200 MHz
	LTE Band 41	2496 ~ 2690 MHz	
	802.11b/g/n(HT20)	2412 ~ 2462 MHz	
	802.11a /802.11n(HT20) /802.11ac(VHT20)	5150 ~ 5250 MHz 5250 ~ 5350 MHz 5470 ~ 5725 MHz 5725 ~ 5850 MHz	
	Bluetooth	2402 ~ 2480 MHz	
	NFC	13.56 MHz	
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna BT: PIFA Antenna NFC: PIFA Antenna		
Hotspot Function	Support		
Power Reduction	Not Support		
Exposure Category	General Population/Uncontrolled exposure		
EUT Stage	Portable Device		
Product	Type		
	☐ Production unit	☒ Identical prototype	
Note: this device doesn't support voice call function, so we don't need to test head.			

3. Summary of Test Results

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	IEC/IEEE 62209-1528: 2020	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)
3	IEEE C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
4	KDB447498 D01	General RF Exposure Guidance v06
5	KDB865664 D01	SAR measurement 100MHz to 6GHz v01r04
6	KDB865664 D02	RF Exposure Reporting v01r02
7	KDB941225 D01	3G SAR Procedures v03r01
8	KDB941225 D05	SAR for LTE Devices v02r05
9	KDB248227 D01	802.11 Wi-Fi SAR v02r02
10	KDB941225 D06	Hotspot Mode v02r01
11	KDB648474 D04	Handset SAR v01r03
12	KDB690783 D01	SAR Listings on Grant v01r03

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment- related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as follows:

<Highest Reported standalone SAR>

Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)
Hotspot(Body) 1-g SAR (0 mm Gap)	GSM 850	0.647	PCB	1.087
	GSM 1900	0.422		
	WCDMA Band II	0.575		
	WCDMA Band V	0.700		
	LTE Band 2	0.797		
	LTE Band 4	0.655		
	LTE Band 5	0.706		
	LTE Band 7	0.747		
	LTE Band 12	0.200		
	LTE Band 14	1.019		
	LTE Band 17	0.141		
	LTE Band 25	0.459		
	LTE Band 26 Part 90	0.988		
	LTE Band 26 Part 22	0.699		
	LTE Band 41	1.087		
	LTE Band 66	0.646		
	WLAN 2.4 GHz	0.498	DTS	
	WLAN 5.2 GHz	0.247	NII	
	WLAN 5.4 GHz	0.293		
	WLAN 5.6 GHz	0.262		
	WLAN 5.8 GHz	0.234		

This device is in compliance with Specific Absorption Rate(SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC47 CFR part 2(2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEC/IEEE 62209-1528: 2020.

<Highest Reported Simultaneous SAR>

Exposure Position	Simultaneous Configuration	Highest Reported Simultaneous Transmission SAR (W/kg)	Limit (W/kg)	Verdict
Hotspot(Body) 1-g SAR (0 mm Gap)	LTE Band 41 + 2.4G WIFI	1.585	1.6	Pass

3.4 Test Uncertainty

3.4.1 Measurement uncertainty evaluation for SAR test

Measurement uncertainty evaluation for SAR test (300MHz to 6GHz)

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+- %)	10 g Ui (+-%)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	√3	√0.5	√0.5	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	√3	√0.5	√0.5	2.41	2.41	∞
Boundary effect	1.0	R	√3	1	1	0.58	0.58	∞
Linearity	4.7	R	√3	1	1	2.71	2.71	∞
System detection limits	1.0	R	√3	1	1	0.58	0.58	∞
Modulation response	3.0	R	√3	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	√3	1	1	0.00	0.00	∞
Integration Time	1.4	R	√3	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	√3	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	√3	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	√3	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	√3	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	√3	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device Holder Uncertainty	3.0	N	1	1	1	3.00	3.00	7
Output power Variation - SAR drift measurement	5.0	R	√3	1	1	2.89	2.89	∞
SAR scaling	2.0	R	√3	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	√3	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4.0	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	√3	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	√3	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		k				20.95	20.69	

* This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.4.2 Measurement uncertainty evaluation for system check

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10 g)	1g Ui (+- %)	10 g Ui (+- %)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient Conditions - Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR drift measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Dist.	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		k				20.32	20.06	

4. Measurement System

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
 ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 MVG SAR System

4.2.1 SAR system diagram



4.2.2 Robot



A standard high precision 6-axis robot (Denso) with teaches pendant with Scanning System

- It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.

4.2.3 E-Field Probe

For the measurements, the Specific Dosimetric SSE2 E-Field Probe with following specifications is used:

- Dynamic range: 0.01-100 W/kg
- Tip diameter: 2mm for SSE2
- Distance between probe tip and sensor centre: 1mm for SSE2
- Distance between sensor centre and the inner phantom surface: 2mm for $f \geq 4\text{GHz}$.
- Probe linearity: $<0.25\text{dB}$.
- Axial Isotropy: $<0.25\text{dB}$.
- Spherical Isotropy: $<0.50\text{dB}$.
- Calibration range: 150 to 6000 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line: less than 20° .



4.2.4 Phantoms

SAM Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The probe scanning of the E-Field is done in the 2 halves of the normalized head. The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size. It enables the dosimetric evaluation of left and right-hand phone usage and includes an additional flat phantom part for the simplified body performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



SAM Phantom

The thickness of the phantom amounts to $2\text{ mm} \pm 0.2\text{ mm}$. The materials for the phantom do not affect the radiation of the device under test (DUT) : $\epsilon_r' < 5$
The head is filled with tissue simulating liquid. The hand do not have to be modeled.

TWIN SAM phantom

	Mechanical	Electrical	
Overall thickness	$2 \pm 0.2\text{ mm}$ (except ear area)	Relative permittivity	3.4
Dimensions	1000 mm(L) x 500 mm(W) x 200 mm(H)	Loss tangent	0.02
Maximum volume	27 L		
Material	Fiberglass based		

ELLIPTICAL Phantom

The phantom is for Body performance check filled with tissue-equivalent liquid to a depth of at least 150 mm, whose shell material is resistant to damage or reaction with tissue-equivalent liquid chemicals.




ELLI Phantom

The shape of the phantom is an ellipse with length $600\text{ mm} \pm 5\text{ mm}$ and width $400\text{ mm} \pm 5\text{ mm}$.
The phantom shell is made of low-loss and low-permittivity material, having loss tangent $\tan \delta \leq 0.05$ and relative permittivity:
 $\epsilon_r' \leq 5$ for $f \leq 3\text{ GHz}$
 $3 \leq \epsilon_r' \leq 5$ for $f > 3\text{ GHz}$
The thickness of the bottom-wall of the flat phantom is 2.0 mm with a tolerance of $\pm 0.2\text{ mm}$.

Technical & mechanical characteristics

Shell thickness	$2\text{ mm} \pm 0.2\text{ mm}$
Filling volume	25 L
Dimensions	600 mm x 400 mm x 200 mm
Permittivity	4.4
Loss tangent	0.017

4.2.5 Device Holder



System Material	Permittivity	Loss tangent
Delrin	3.7	0.005

(The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.)

System Material	Permittivity	Loss tangent
PMMA	2.9	0.028


4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.


Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

5. System Verification

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. The setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup



6. TEST POSITION CONFIGURATIONS

According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEC IEEE 62209-1528:2020 using the SAM phantom illustrated as below.

6.1.1 Definition of the cheek position

The cheek position is established using steps a) to j) as follows.

- (a) Configure the DUT for voice operation, if necessary. For example, for a DUT with a flip.a)swivel, or slide cover piece, open the cover if this is consistent with voice operation. If the DUT can also be used with the cover closed, both configurations shall be tested.
- (b) Define two imaginary lines on the DUT, the vertical centreline and the horizontal line, relative to the DUT in vertical orientation as shown in Figure 15.
- (c) The vertical centreline passes through two points on the front side of the DUT: the midpoint of the width w of the DUT at the level of the acoustic output (Point A in Figure 15), and the midpoint of the width w_t at the bottom of the DUT (Point B). The horizontal line is perpendicular to the vertical centerline, and passes through the centre of the acoustic output (Figure 15). The two lines intersect at Point A. Note that for many DUTs, Point A coincides with the centre of the acoustic output. However, the acoustic output could be located elsewhere on the horizontal line. Also note that the vertical centreline is not necessarily parallel to the front face of the DUT, especially for clamshell DUTs, DUTs with flip cover pieces, and other irregularly shaped DUTs.
- (d) Position the DUT close to the surface of the phantom such that Point A is on the (virtual) extension of the line passing through points RE (right-ear ear reference point) and LE left-ear ear reference point) on the phantom (see Figure 16a) and Figure 16b)). The plane determined by the vertical centreline and the horizontal line of the DUT shall be parallel to the sagittal plane of the phantom.
- (e) Translate the DUT towards the phantom along the line passing through RE and LE until the DUT touches the ear (see Figure 16c)).
- (f) Rotate the DUT around the (virtual) LE-RE Line until the DUT vertical centreline is in the)reference plane(see Figure 16d)).
- (g) Rotate the DUT around its vertical centreline until the plane established by the DUT vertical centreline and horizontal line is parallel to the N-F line (see Annex G), and then translate the DUT towards the phantom along the LE-RE line until DUT Point A touches the ear at the ERP (ear reference point) (see Figure 16e))
- (h) While keeping Point A on the line passing through RE and LE and maintaining the DUT in contact with the pinna, rotate the DUT about the N-F line until any point on the DUT is in contact with a phantom point below the pinna (cheek) (see Figure 16f)). The physical angles of rotation shall be documented.
- (i) While keeping DUT Point A in contact with the ERP rotate the DUT around a line perpendicular to the plane established by the DUT vertical centreline and horizontal line and passing through DUT Point A, until the DUT vertical centreline is in the reference plane(see Figure 16g)).

- (j) Verify that the cheek position is correct as follows:
- 1) the N-F line is in the plane established by the DUT vertical centreline and horizontal line;
 - 2) DUT Point A touches the pinna at the ERP
 - 3) the DUT vertical centreline is in the reference plane.





Figure 15 - Vertical and horizontal reference lines and reference points A and B on two example device types: a full touch-screen smart phone (left) and a DUT with a keypad (right)




NOTE The reference points for the right-ear ear reference point (RE), left-ear ear reference point (LE), and mouth (M), which establish the reference plane for DUT positioning, are indicated. This device position shall be maintained for the sagittal phantom test set-up shown in Figure G.4.

a) Phone position 1 – cheek position




b) One possible DUT position against the head after applying 7.2.4.2.2 c)




NOTE The black arrows show the direction of translation of the DUT for 7.2.4.2.2 d).

c) DUT position after applying 7.2.4.2.2 d)




NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 e).

d) DUT position after applying 7.2.4.2.2 e)



NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 f).


e) DUT position after applying 7.2.4.2.2 f)



NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 g)

f) DUT position after applying 7.2.4.2.2 g)

© IEC/IEEE 2020



NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 h).

g) DUT position after applying 7.2.4.2.2 h)

Figure 16 – Cheek position of the DUT on the left side of SAM where the device position shall be maintained for the phantom test set-up

6.1.2 Definition of the tilt position

The tilt position is established using steps a) through d) as follows.

- (a) Repeat steps a) through j) of 7.2.4.2.2 to place the DUT in the cheek position)(see Figure 16).
- (b) While maintaining the orientation of the DUT, move the DUT away from the pinna along the line passing through RE and LE far enough to allow a rotation of the DUT away from the cheek by 15°.
- (c) Rotate the DUT around the horizontal line by 15°(see Figure 17).
- (d) While maintaining the orientation of the DUT, move the DUT towards the phantom on a line passing through RE and LE until any part of the DUT touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g. an extended antenna in contact with the back of the head phantom, the angle of the DUT shall be reduced. In this case, the tilt position is obtained if any part of the DUT is in contact with the pinna and a second point on the DUT is in contact with the phantom, e.g. the antenna in contact with the back of the head.



Key

- M Mouth reference point
- LE Left-ear ear reference point
- RE Right-ear ear reference point

This device position shall be maintained for the phantom test set-up.


Figure 17 – Tilt position of the DUT on the left side of SAM

6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.


Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance ≤ 5 mm to support compliance.



6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



6.4 Product Specific 10g Exposure Consideration


According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

7. Measurement Procedure

7.1 Measurement Process Diagram

Body SAR



IEC

7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEC/IEEE 62209-1528: 2020.

Table 3 – Area scan parameters

Parameter	DUT transmit frequency being tested	
	$f \leq 3 \text{ GHz}$	$3 \text{ GHz} < f \leq 10 \text{ GHz}$
Maximum distance between the measured points (geometric centre of the sensors) and the inner phantom surface (z_{M1} in Figure 20 in mm)	5 ± 1	$\delta \ln(2)/2 \pm 0,5^a$
Maximum spacing between adjacent measured points in mm (see O.8.3.1) ^b	20, or half of the corresponding zoom scan length, whichever is smaller	$60/f$, or half of the corresponding zoom scan length, whichever is smaller
Maximum angle between the probe axis and the phantom surface normal (α in Figure 20) ^c	5° (flat phantom only) 30° (other phantoms)	5° (flat phantom only) 20° (other phantoms)
Tolerance in the probe angle	1°	1°
^a δ is the penetration depth for a plane-wave incident normally on a planar half-space.		
^b See Clause O.8 on how Δx and Δy may be selected for individual area scan requirements.		
^c The probe angle relative to the phantom surface normal is restricted due to the degradation in the measurement accuracy in fields with steep spatial gradients. The measurement accuracy decreases with increasing probe angle and increasing frequency. This is the reason for the tighter probe angle restriction at frequencies above 3 GHz.		

Table 4 – Zoom scan parameters

Parameter	DUT transmit frequency being tested	
	$f \leq 3 \text{ GHz}$	$3 \text{ GHz} < f \leq 10 \text{ GHz}$
Maximum distance between the closest measured points and the phantom surface (z_{M1} in Figure 20 and Table 3, in mm)	5	$\delta \ln(2)/2^a$
Maximum angle between the probe axis and the phantom surface normal (α in Figure 20)	5° (flat phantom only) 30° (other phantoms)	5° (flat phantom only) 20° (other phantoms)
Maximum spacing between measured points in the x- and y-directions (Δx and Δy , in mm)	8	$24/f^b$
For uniform grids: Maximum spacing between measured points in the direction normal to the phantom shell (Δz_1 in Figure 20, in mm)	5	$10/(f-1)$
For graded grids: Maximum spacing between the two closest measured points in the direction normal to the phantom shell (Δz_1 in Figure 20, in mm)	4	$12/f$
For graded grids: Maximum incremental increase in the spacing between measured points in the direction normal to the phantom shell ($R_z = \Delta z_2/\Delta z_1$ in Figure 20)	1,5	1,5
Minimum edge length of the zoom scan volume in the x- and y-directions (L_z in O.8.3.2, in mm)	30	22
Minimum edge length of the zoom scan volume in the direction normal to the phantom shell (L_n in O.8.3.2 in mm)	30	22
Tolerance in the probe angle	1°	1°
^a δ is the penetration depth for a plane-wave incident normally on a planar half-space.		
^b This is the maximum spacing allowed, which might not work for all circumstances.		

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8. Conducted RF Output Power

8.1 GSM

Mode: GSM850		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH128	CH190	CH251		CH128	CH190	CH251
			824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GPRS (GMSK)	1Tx slot	31.50	31.25	31.16	31.28	-9.03	22.22	22.13	22.25
	2Tx slots	31.50	31.13	31.18	31.27	-6.02	25.11	25.16	25.25
	3Tx slots	31.50	31.24	31.25	31.22	-4.26	26.98	26.99	26.96
	4Tx slots	31.50	31.17	31.20	31.18	-3.01	28.16	28.19	28.17
EGPRS (8PSK)	1Tx slot	31.50	31.12	31.15	31.30	-9.03	22.09	22.12	22.27
	2Tx slots	31.50	31.29	31.17	31.13	-6.02	25.27	25.15	25.11
	3Tx slots	31.50	31.22	31.17	31.18	-4.26	26.96	26.91	26.92
	4Tx slots	31.50	31.16	31.19	31.21	-3.01	28.15	28.18	28.20
Mode: GSM1900		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH512	CH661	CH810		CH512	CH661	CH810
			1850.2MHz	1880.0MHz	1909.8MHz		1850.2MHz	1880.0MHz	1909.8MHz
GPRS (GMSK)	1Tx slot	30.00	29.54	29.48	29.57	-9.03	20.51	20.45	20.54
	2Tx slots	30.00	29.59	29.58	29.46	-6.02	23.57	23.56	23.44
	3Tx slots	30.00	29.57	29.53	29.42	-4.26	25.31	25.27	25.16
	4Tx slots	30.00	29.53	29.53	29.52	-3.01	26.52	26.52	26.51
EGPRS (8PSK)	1Tx slot	29.50	29.45	29.49	29.49	-9.03	20.42	20.46	20.46
	2Tx slots	29.50	29.44	29.41	29.48	-6.02	23.42	23.39	23.46
	3Tx slots	30.00	29.41	29.53	29.44	-4.26	25.15	25.27	25.18
	4Tx slots	30.00	29.45	29.56	29.41	-3.01	26.44	26.55	26.40
Note: 1) Division Factors To average the power, the division factor is as follows: 1Tx-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB 2Tx-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB 3Tx-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB 4Tx-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB									

8.2 WCDMA

Mode		Maximum Tune-up(dBm)	WCDMA Band II		
			Conducted Power (dBm)		
			CH9262	CH9400	CH9538
			1852.4	1880.0	1907.6
RMC 12.2K		23.50	23.04	23.11	23.05
HSDPA	Subtest-1	22.50	22.30	22.21	22.32
	Subtest-2	22.50	22.39	22.25	22.32
	Subtest-3	22.50	22.23	22.25	22.30
	Subtest-4	22.50	22.34	22.30	22.23
HSUPA	Subtest-1	22.50	22.26	22.23	22.26
	Subtest-2	22.50	22.29	22.37	22.26
	Subtest-3	22.50	22.28	22.40	22.27
	Subtest-4	22.50	22.25	22.28	22.20
	Subtest-5	22.50	22.31	22.38	22.21
Mode		Maximum Tune-up(dBm)	WCDMA Band V		
			Conducted Power (dBm)		
			CH4132	CH4183	CH4233
			826.4	836.6	846.6
RMC 12.2K		23.00	22.98	22.75	22.86
HSDPA	Subtest-1	22.50	22.39	22.30	22.39
	Subtest-2	22.50	22.43	22.41	22.36
	Subtest-3	22.50	22.39	22.36	22.39
	Subtest-4	22.50	22.38	22.48	22.33
HSUPA	Subtest-1	22.50	22.46	22.49	22.48
	Subtest-2	22.50	22.44	22.45	22.38
	Subtest-3	22.50	22.30	22.49	22.48
	Subtest-4	22.50	22.44	22.44	22.42
	Subtest-5	22.50	22.44	22.35	22.37
Per KDB 941225 D01, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/2$ dB higher than the primary mode (RMC12.2kbps) or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.					

8.3 LTE

Band 2

LTE-FDD Band 2				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		18607	18900	19193
					1850.7MHz	1880.0MHz	1909.3MHz
1.4MHz	QPSK	1	0	23.50	23.49	23.09	22.71
			2	24.00	23.61	23.17	22.82
			5	23.50	23.48	23.08	22.73
		3	0	23.50	23.40	23.07	22.76
			2	23.50	23.42	23.11	22.77
			3	23.50	23.38	23.10	22.75
		6	0	23.00	22.52	22.11	21.82
	16QAM	1	0	22.50	22.17	21.83	21.47
			2	22.50	22.31	21.97	21.58
			5	22.50	22.18	21.85	21.43
		3	0	22.50	22.16	21.94	21.56
			2	22.50	22.16	21.87	21.55
			3	22.50	22.16	21.89	21.51
		6	0	21.50	21.36	20.90	20.79
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18615	18900	19185
					1851.5MHz	1880.0MHz	1908.5MHz
3MHz	QPSK	1	0	24.00	23.57	23.67	23.47
			7	24.50	24.09	23.70	23.48
			14	24.50	24.03	23.72	23.28
		8	0	23.50	23.10	22.75	22.45
			4	23.50	23.16	22.77	22.40
			7	23.50	23.09	22.80	22.44
		15	0	23.00	22.97	22.70	22.14
	16QAM	1	0	23.00	22.73	22.50	22.22
			7	23.00	22.69	22.52	22.47
			14	23.00	22.73	22.71	22.18
		8	0	22.00	21.91	21.83	21.45
			4	22.00	21.97	21.70	21.43
			7	22.00	21.99	21.80	21.37
		15	0	22.00	21.87	21.61	20.70
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18625	18900	19175
					1852.5MHz	1880.0MHz	1907.5MHz
5MHz	QPSK	1	0	24.50	24.01	23.07	22.85
			13	24.50	24.14	23.16	22.96
			24	24.50	24.04	22.94	22.88
		12	0	23.00	22.97	21.73	21.86
			6	23.00	22.67	21.86	21.84
			13	23.00	22.60	22.27	21.94
		25	0	22.50	22.39	22.20	21.90
	16QAM	1	0	23.00	22.82	22.04	21.93
			13	23.00	22.91	22.09	22.07
			24	23.00	22.74	21.82	21.87
		12	0	22.00	21.81	20.68	20.83
			6	22.00	21.53	20.82	20.86
			13	21.50	21.30	21.16	20.99
		25	0	21.50	21.37	21.21	20.86

LTE-FDD Band 2				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		18650	18900	19150
					1855.0MHz	1880.0MHz	1905.0MHz
10MHz	QPSK	1	0	24.00	23.53	23.59	22.95
			25	24.50	24.16	23.24	23.32
			49	24.00	23.98	23.01	22.86
		25	0	23.50	23.00	22.71	21.84
			13	23.00	22.99	22.60	21.81
			25	23.00	22.80	22.70	22.02
		50	0	23.00	22.82	22.60	21.90
	16QAM	1	0	23.00	22.69	21.84	21.62
			25	23.00	22.73	22.20	22.05
			49	23.00	22.80	21.85	21.57
		25	0	22.00	21.95	21.67	20.88
			13	22.00	22.00	21.64	20.79
			25	22.00	21.73	21.80	21.10
		50	0	22.00	21.61	21.24	20.99
		Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18675
1857.5MHz	1880.0MHz						1902.5MHz
15MHz	QPSK	1	0	24.00	23.91	23.05	22.89
			38	24.50	24.07	23.14	22.88
			74	23.50	23.27	22.93	22.64
		36	0	22.50	22.34	22.07	21.90
			18	22.50	22.45	22.25	22.00
			39	22.50	22.11	22.00	21.73
		75	0	23.00	22.59	22.26	22.06
	16QAM	1	0	23.00	22.87	22.04	21.88
			38	22.50	22.45	22.20	21.99
			74	22.50	22.22	22.00	21.79
		36	0	22.50	22.34	22.07	21.88
			18	22.50	22.40	22.22	22.01
			39	22.50	22.15	21.99	21.77
		75	0	21.50	21.43	21.14	21.08
		Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18700
1860.0MHz	1880.0MHz						1900.0MHz
20MHz	QPSK	1	0	24.00	23.32	23.59	22.90
			50	24.50	24.27	23.28	23.19
			99	24.00	23.53	23.29	22.66
		50	0	23.00	22.98	22.59	22.67
			25	23.00	22.93	22.48	22.20
			50	23.00	22.69	22.17	22.33
		100	0	23.00	22.82	22.14	22.43
	16QAM	1	0	22.50	21.98	22.24	21.77
			50	23.00	22.80	22.69	21.94
			99	22.50	22.30	22.08	21.42
		50	0	22.00	21.93	21.59	21.27
			25	22.00	21.89	21.10	21.26
			50	22.00	21.67	21.23	21.75
		100	0	22.00	21.81	21.05	21.83

Band 4

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		19957	20175	20393
					1710.7MHz	1732.5MHz	1754.3MHz
1.4MHz	QPSK	1	0	23.50	22.13	22.73	23.08
			2	23.50	22.23	22.85	23.24
			5	23.50	22.12	22.72	23.09
		3	0	23.50	22.13	22.76	23.08
			2	23.50	22.15	22.77	23.11
			3	23.50	22.14	22.79	23.15
		6	0	22.50	21.25	21.75	22.24
	16QAM	1	0	22.00	20.99	21.54	21.91
			2	22.50	21.11	21.62	22.23
			5	22.00	21.04	21.48	21.94
		3	0	22.00	20.95	21.61	21.91
			2	22.00	20.94	21.59	21.93
			3	22.00	20.92	21.62	21.90
		6	0	21.50	20.13	20.56	21.18
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19965	20175	20385
					1711.5MHz	1732.5MHz	1753.5MHz
3MHz	QPSK	1	0	23.50	22.14	22.76	23.03
			7	23.50	22.15	22.68	23.10
			14	23.50	22.20	22.71	23.17
		8	0	22.50	21.14	21.81	22.16
			4	22.50	21.16	21.82	22.08
			7	22.50	21.28	21.80	22.21
		15	0	22.50	21.22	21.80	22.08
	16QAM	1	0	22.50	21.16	21.84	22.02
			7	22.50	21.19	21.78	22.09
			14	22.50	21.24	21.76	22.12
		8	0	21.50	20.14	20.82	21.10
			4	21.50	20.11	20.76	21.11
			7	21.50	20.23	20.80	21.18
		15	0	21.50	20.17	20.76	21.06
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19976	20175	20375
					1712.5MHz	1732.5MHz	1752.5MHz
5MHz	QPSK	1	0	23.00	22.13	22.66	22.91
			13	23.50	22.31	22.76	23.18
			24	23.50	22.27	22.61	23.15
		12	0	22.50	21.14	21.76	22.03
			6	22.50	21.14	21.76	22.02
			13	22.50	21.37	21.77	22.13
		25	0	22.50	21.21	21.74	22.12
	16QAM	1	0	22.00	21.06	21.74	21.87
			13	22.50	21.28	21.86	22.12
			24	22.50	21.17	21.73	22.10
		12	0	21.00	20.09	20.79	20.96
			6	21.00	20.08	20.75	20.92
			13	21.50	20.25	20.78	21.11
		25	0	21.50	20.18	20.65	21.06

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)					
Bandwidth	Modulation	RB allocation	RB offset		20000	20175	20350			
					1715.0MHz	1732.5MHz	1750.0MHz			
10MHz	QPSK	1	0	23.00	22.47	22.72	22.60			
			25	23.00	22.31	22.93	22.97			
			49	23.50	22.41	22.58	23.04			
		25	0	22.00	21.12	21.82	21.84			
			13	22.00	21.14	21.84	21.86			
			25	22.50	21.39	21.75	22.15			
		50	0	22.00	21.22	21.74	21.94			
			16QAM	1	0	22.00	21.14	21.54	21.63	
					25	22.50	21.41	21.64	22.16	
	49	22.50			21.40	21.41	22.13			
	25	0		21.00	20.04	20.83	20.79			
		13		21.00	20.08	20.78	20.77			
		25		21.50	20.41	20.79	21.09			
	50	0		21.00	20.19	20.76	20.94			
		Bandwidth		Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20025	20175	20325
								1717.5MHz	1732.5MHz	1747.5MHz
	15MHz	QPSK	1	0	22.50	22.39	22.42	22.38		
				38	23.00	22.34	22.62	22.81		
74				23.00	22.44	22.33	22.93			
36			0	22.00	20.88	21.56	21.43			
			18	22.00	21.38	21.80	21.82			
			39	22.00	21.48	21.52	21.93			
75			0	22.00	21.39	21.71	21.88			
			16QAM	1	0	22.00	21.17	21.58	21.45	
					38	22.00	21.40	21.80	21.87	
74		22.00			21.51	21.50	21.93			
36		0		22.00	20.89	21.56	21.44			
		18		22.00	21.40	21.84	21.81			
		39		22.00	21.51	21.52	22.00			
75		0		21.00	20.27	20.67	20.78			
		Bandwidth		Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20050	20175	20300
								1720.0MHz	1732.5MHz	1745.0MHz
20MHz		QPSK	1	0	22.50	22.34	22.27	22.31		
				50	23.00	22.69	22.81	22.84		
	99			23.00	22.55	22.39	22.87			
	50		0	22.00	21.14	21.71	21.59			
			25	22.00	21.13	21.70	21.66			
			50	22.00	21.57	21.56	21.94			
	100		0	22.00	21.32	21.65	21.76			
			16QAM	1	0	21.50	20.93	21.39	21.24	
					50	22.50	21.58	22.00	21.76	
	99	22.00			21.41	21.53	21.72			
	50	0		21.00	20.12	20.71	20.63			
		25		21.00	20.10	20.70	20.59			
		50		21.00	20.55	20.62	20.93			
	100	0		21.00	20.28	20.62	20.75			

Band 5

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20407	20525	20643
					824.7MHz	836.5MHz	848.3MHz
1.4MHz	QPSK	1	0	25.00	23.99	24.07	24.69
			2	24.50	24.13	24.09	24.30
			5	24.50	24.01	24.09	24.16
		3	0	24.50	24.03	24.08	24.17
			2	24.50	24.07	24.13	24.16
			3	24.50	24.02	24.20	24.18
		6	0	23.50	23.10	23.14	23.20
	16QAM	1	0	23.00	22.83	22.87	22.99
			2	23.50	23.01	23.02	23.18
			5	23.00	22.94	22.89	22.97
		3	0	23.00	22.84	22.92	22.95
			2	23.00	22.79	22.94	22.92
			3	23.00	22.83	22.98	22.93
		6	0	22.50	22.09	22.02	22.17
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20415	20525	20635
					825.5MHz	836.5MHz	847.5MHz
3MHz	QPSK	1	0	25.00	24.67	24.73	24.81
			7	25.00	24.64	24.76	24.77
			14	25.00	24.71	24.84	24.47
		8	0	24.00	23.61	23.69	23.51
			4	24.00	23.64	23.71	23.57
			7	24.00	23.66	23.66	23.57
		15	0	24.00	23.59	23.63	23.58
	16QAM	1	0	24.00	23.61	23.59	23.79
			7	24.00	23.67	23.54	23.43
			14	24.00	23.64	23.53	23.40
		8	0	23.00	22.59	22.66	22.71
			4	23.00	22.61	22.63	22.48
			7	23.00	22.60	22.64	22.41
		15	0	23.00	22.61	22.55	22.65

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20425	20525	20625
					826.5MHz	836.5MHz	846.5MHz
5MHz	QPSK	1	0	25.00	24.75	24.63	24.51
			13	25.00	24.67	24.60	24.17
			24	24.00	23.65	23.61	23.18
		12	0	24.00	23.57	23.62	23.07
			6	24.00	23.64	23.53	23.10
			13	24.00	23.56	23.63	23.20
		25	0	24.00	23.45	23.59	23.34
	16QAM	1	0	24.00	23.64	23.70	23.19
			13	24.00	23.56	23.56	23.14
			24	23.00	22.53	22.62	22.10
		12	0	23.00	22.54	22.58	22.10
			6	23.00	22.55	22.53	22.10
			13	23.00	22.59	22.56	22.28
		25	0	25.00	24.75	24.63	24.51

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20450	20525	20600
					829.0MHz	836.5MHz	844.0MHz
10MHz	QPSK	1	0	25.00	24.58	24.72	24.68
			25	25.00	24.97	24.90	24.79
			49	25.00	24.67	24.72	24.22
		25	0	24.00	23.74	23.68	23.38
			13	24.00	23.76	23.70	23.33
			25	24.00	23.83	23.63	23.39
		50	0	24.00	23.79	23.68	23.34
	16QAM	1	0	24.00	23.57	23.52	23.63
			25	24.00	23.89	23.64	23.35
			49	24.00	23.65	23.49	23.17
		25	0	23.00	22.76	22.64	22.39
			13	23.00	22.73	22.66	22.38
			25	23.00	22.77	22.67	22.37
		50	0	23.00	22.77	22.66	22.38

Band 7

LTE-FDD Band 7					Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20775	21100	21425
					2502.5MHz	2535.0MHz	2567.5MHz
5MHz	QPSK	1	0	24.00	23.16	23.26	23.70
			12	24.00	23.29	23.54	23.93
			24	24.00	23.19	23.47	23.91
		12	0	23.00	22.18	22.40	22.80
			6	23.00	22.14	22.42	22.81
			13	23.00	22.11	22.46	22.82
		25	0	23.00	22.16	22.47	22.78
	16QAM	1	0	23.00	22.01	22.31	22.53
			12	23.00	22.18	22.50	22.72
			24	23.00	22.11	22.51	22.72
		12	0	22.00	21.12	21.42	21.73
			6	22.00	21.15	21.40	21.75
			13	22.00	21.12	21.49	21.76
		25	0	22.00	21.18	21.35	21.73
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20800	21100	21400
10MHz	QPSK	1	0	24.00	23.59	23.26	23.48
			24	24.00	23.24	23.68	23.78
			49	24.00	23.14	23.64	23.77
		25	0	23.00	22.29	22.42	22.72
			12	23.00	22.31	22.43	22.72
			25	23.00	22.32	22.53	22.74
		50	0	23.00	22.27	22.48	22.70
	16QAM	1	0	22.50	22.11	22.01	22.19
			24	22.50	22.49	22.37	22.46
			49	23.00	22.11	22.39	22.57
		25	0	22.00	21.27	21.42	21.69
			12	22.00	21.28	21.43	21.71
			25	22.00	21.25	21.55	21.68
		50	0	22.00	21.25	21.48	21.66

LTE-FDD Band 7				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20825	21100	21375
					2507.5MHz	2535.0MHz	2562.5MHz
15MHz	QPSK	1	0	23.50	22.88	22.85	23.23
			38	24.00	23.22	23.37	23.54
			74	24.00	22.87	23.33	23.60
		38	0	22.00	21.98	21.94	21.95
			18	22.50	22.14	22.42	22.25
			37	22.50	21.78	22.45	22.39
		75	0	23.00	22.17	22.51	22.62
	16QAM	1	0	22.00	21.88	21.94	21.95
			38	22.50	22.19	22.40	22.29
			74	22.50	21.80	22.43	22.33
		38	0	22.00	21.91	21.98	21.97
			18	22.50	22.18	22.44	22.31
			37	22.50	21.81	22.47	22.38
		75	0	22.00	21.08	21.46	21.53
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20850	21100	21350
					2510.0MHz	2535.0MHz	2560.0MHz
20MHz	QPSK	1	0	23.50	22.93	22.80	23.20
			49	24.00	23.31	23.63	23.61
			99	24.00	22.74	23.35	23.55
		50	0	22.50	22.21	22.27	22.38
			25	22.50	22.20	22.24	22.40
			50	22.50	22.09	22.42	22.39
		100	0	22.50	22.16	22.36	22.42
	16QAM	1	0	22.00	21.73	21.83	22.00
			49	23.00	22.25	22.64	22.34
			99	22.50	21.56	22.38	22.30
		50	0	21.50	21.18	21.20	21.43
			25	21.50	21.12	21.20	21.43
			50	21.50	21.07	21.45	21.40
		100	0	21.50	21.08	21.33	21.36

Band 12

LTE-FDD Band 12				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23017	23095	23173
					699.7MHz	707.5MHz	715.3MHz
1.4MHz	QPSK	1	0	24.00	23.87	23.84	23.82
			2	24.00	23.99	23.94	23.98
			5	24.00	23.81	23.85	23.85
		3	0	24.00	23.94	23.84	23.89
			2	24.00	23.94	23.80	23.88
			3	24.00	23.92	23.88	23.93
		6	0	23.00	22.80	22.74	22.83
	16QAM	1	0	23.00	22.70	22.68	22.57
			2	23.00	22.88	22.79	22.73
			5	23.00	22.71	22.65	22.60
		3	0	23.00	22.73	22.68	22.64
			2	23.00	22.71	22.64	22.62
			3	23.00	22.70	22.66	22.60
		6	0	22.00	21.83	21.61	21.80

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23025	23095	23165
					700.5MHz	707.5MHz	714.5MHz
3MHz	QPSK	1	0	24.50	24.02	23.94	23.95
			7	24.50	24.01	23.86	24.00
			14	24.50	23.93	23.95	24.04
		8	0	23.00	22.92	22.86	22.99
			4	23.00	22.92	22.87	22.96
			7	23.00	22.94	22.85	22.96
		15	0	23.00	22.90	22.89	22.89
	16QAM	1	0	23.50	23.02	22.79	22.71
			7	23.00	22.86	22.71	22.76
			14	23.00	22.92	22.73	22.87
		8	0	22.00	21.96	21.83	21.93
			4	22.00	21.92	21.85	21.89
			7	22.00	21.88	21.85	21.91
		15	0	22.00	21.86	21.78	21.80
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23035	23095	23155
					701.5MHz	707.5MHz	713.5MHz
5MHz	QPSK	1	0	17.00	16.89	16.93	16.83
			13	17.50	17.06	17.08	16.69
			24	17.00	16.96	17.00	16.59
		12	0	16.00	15.89	15.94	15.60
			6	16.00	15.84	15.96	15.63
			13	16.50	15.86	16.05	15.91
		25	0	16.50	15.84	16.00	16.01
	16QAM	1	0	16.00	15.78	15.95	15.42
			13	16.50	15.91	16.10	15.58
			24	16.50	15.85	16.02	15.50
		12	0	15.50	14.76	15.01	14.57
			6	15.00	14.81	14.99	14.58
			13	15.50	14.83	15.07	14.91
		25	0	15.00	14.86	14.98	14.99
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23060	23095	23130
					704.0MHz	707.5MHz	711.0MHz
10MHz	QPSK	1	0	24.00	23.63	23.66	23.64
			25	24.00	23.89	23.86	23.86
			49	24.50	24.35	23.77	23.81
		25	0	23.50	23.40	22.87	22.62
			13	23.50	23.38	22.79	22.60
			25	23.50	23.29	22.91	22.67
		50	0	23.50	23.06	22.85	22.68
	16QAM	1	0	23.00	22.79	22.69	22.49
			25	23.00	22.77	22.92	22.73
			49	23.50	23.31	22.73	22.63
		25	0	22.50	22.33	21.78	21.61
			13	22.50	22.35	21.83	21.60
			25	22.50	22.24	21.83	21.73
		50	0	22.00	21.82	21.86	21.69

Band 14

LTE-FDD Band 14				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23305	23330	23355
					790.5MHz	793.0MHz	795.5MHz
5MHz	QPSK	1	0	24.00	23.78	23.72	23.72
			12	24.00	23.91	23.90	23.91
			24	24.00	23.84	23.72	23.76
		12	0	23.00	22.87	22.76	22.74
			6	23.00	22.85	22.79	22.75
			13	23.00	22.79	22.86	22.73
		25	0	23.00	22.85	22.80	22.77
	16QAM	1	0	23.00	22.74	22.85	22.70
			12	23.00	22.90	22.95	22.81
			24	23.00	22.76	22.84	22.72
		12	0	22.00	21.78	21.76	21.70
			6	22.00	21.80	21.74	21.71
			13	22.00	21.75	21.90	21.74
		25	0	22.00	21.90	21.79	21.79
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23330		
					793.0MHz		
10MHz	QPSK	1	0	24.00	23.82		
			25	24.00	23.88		
			49	24.00	23.81		
		25	0	23.00	22.82		
			13	23.00	22.83		
			25	23.00	22.83		
		50	0	23.00	22.84		
	16QAM	1	0	23.00	22.86		
			25	23.00	22.93		
			49	23.00	22.85		
		25	0	22.00	21.77		
			13	22.00	21.78		
			25	22.00	21.82		
		50	0	22.00	21.82		

Band 17

LTE-FDD Band 17				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23755	23790	23825
					706.5MHz	710MHz	713.5MHz
5MHz	QPSK	1	0	24.00	23.68	23.61	23.69
			13	24.00	23.81	23.67	23.82
			24	24.00	23.78	23.63	23.75
		12	0	23.00	22.67	22.52	22.71
			6	23.00	22.66	22.57	22.70
			13	23.00	22.77	22.70	22.67
		25	0	23.00	22.76	22.69	22.71
	16QAM	1	0	23.00	22.57	22.66	22.48
			13	23.00	22.75	22.80	22.67
			24	23.00	22.60	22.65	22.67
		12	0	22.00	21.62	21.58	21.70
			6	22.00	21.65	21.54	21.64
			13	22.00	21.72	21.72	21.69
		25	0	22.00	21.72	21.63	21.71

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23780	23790	23800
					709MHz	710MHz	711MHz
10MHz	QPSK	1	0	24.00	23.65	23.69	23.73
			25	24.00	23.88	23.88	23.95
			49	24.00	23.76	23.81	23.88
		25	0	23.00	22.74	22.64	22.64
			13	23.00	22.67	22.63	22.62
			25	23.00	22.81	22.75	22.77
		50	0	23.00	22.75	22.63	22.67
			0	23.00	22.61	22.49	22.41
			25	23.00	22.92	22.71	22.65
	16QAM	1	49	23.00	22.77	22.57	22.57
			0	22.00	21.69	21.69	21.62
			13	22.00	21.70	21.66	21.66
		25	25	22.00	21.80	21.79	21.78
			0	22.00	21.74	21.70	21.66
			0	22.00	21.74	21.70	21.66
		50	0	22.00	21.74	21.70	21.66

Band 25

LTE-FDD Band 25				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26047	26365	26683
1.4MHz	QPSK	1	0	24.00	23.60	23.31	22.99
			2	24.00	23.74	23.42	23.13
			5	24.00	23.57	23.27	22.99
		3	0	23.50	23.49	23.30	22.99
			2	23.50	23.49	23.30	23.00
			3	24.00	23.50	23.31	23.02
		6	0	23.00	22.64	22.35	22.07
		16QAM	1	0	22.50	22.27	22.05
				2	22.50	22.39	22.19
				5	22.50	22.21	22.06
		3	0	22.50	22.16	22.11	21.70
			2	22.50	22.16	22.13	21.70
			3	22.50	22.24	22.11	21.68
		6	0	22.00	21.52	21.17	20.98
			0	24.00	23.66	23.34	23.04
			7	24.00	23.69	23.38	23.06
			14	24.00	23.66	23.34	23.07
	QPSK	8	0	23.00	22.70	22.37	22.07
			4	23.00	22.66	22.37	22.12
			7	23.00	22.71	22.34	22.09
		15	0	23.00	22.56	22.31	22.00
			0	23.00	22.56	22.20	21.70
			7	23.00	22.54	22.12	21.71
			14	22.50	22.48	22.08	21.76
	16QAM	8	0	22.00	21.65	21.27	21.04
			4	22.00	21.64	21.31	21.03
			7	22.00	21.59	21.31	21.01
		15	0	22.00	21.53	21.20	20.89
			0	24.00	23.66	23.34	23.04
			7	24.00	23.69	23.38	23.06

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26065	26365	26665
					1852.5MHz	1882.5MHz	1912.5MHz
5MHz	QPSK	1	0	24.00	23.54	23.13	22.84
			13	24.00	23.62	23.25	23.07
			24	24.00	23.55	23.14	22.95
		12	0	22.50	22.49	22.22	22.07
			6	23.00	22.55	22.19	22.04
			13	22.50	22.41	22.21	21.78
	16QAM	25	0	22.50	22.48	22.24	21.93
			0	22.50	22.33	22.20	21.71
			13	22.50	22.42	22.28	21.78
		1	24	22.50	22.28	22.19	21.71
			0	21.50	21.45	21.22	21.05
			6	21.50	21.45	21.24	21.01
		12	13	21.50	21.34	21.24	20.76
			25	21.50	21.42	21.21	20.92
			0	21.50	21.42	21.21	20.92

LTE-FDD Band 25				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26090	26365	26640
					1855.0MHz	1882.5MHz	1910.0MHz
10MHz	QPSK	1	0	24.00	23.61	23.19	22.88
			25	24.00	23.85	23.25	23.20
			49	24.00	23.59	23.15	22.94
		25	0	23.00	22.53	22.23	21.86
			13	23.00	22.59	22.25	21.87
			25	22.50	22.43	22.31	21.60
		50	0	22.50	22.42	22.25	21.79
			0	22.50	22.21	21.94	21.92
			25	22.50	22.35	22.18	22.00
	16QAM	1	49	22.50	22.13	21.92	21.86
			0	22.00	21.55	21.24	20.90
			13	22.00	21.58	21.23	20.88
		25	25	21.50	21.40	21.31	20.63
			0	21.50	21.49	21.27	20.73
			0	21.50	21.49	21.27	20.73
		50	0	21.50	21.49	21.27	20.73
			0	21.50	21.49	21.27	20.73
			0	21.50	21.49	21.27	20.73
15MHz	QPSK	1	0	23.50	23.38	23.06	22.79
			38	24.00	23.58	23.22	22.88
			74	23.50	23.27	22.98	22.80
		36	0	22.50	22.31	22.04	21.85
			18	23.00	22.52	22.23	22.00
			39	22.50	22.24	22.01	21.77
		75	0	23.00	22.63	22.24	21.80
			0	22.50	22.37	22.09	21.85
			38	23.00	22.50	22.25	22.03
	16QAM	1	74	22.50	22.23	21.99	21.74
			0	22.50	22.32	22.02	21.84
			18	22.50	22.48	22.24	22.01
		36	39	22.50	22.24	21.99	21.75
			0	22.00	21.51	21.17	20.79
			0	22.00	21.51	21.17	20.79
		75	0	22.00	21.51	21.17	20.79
			0	22.00	21.51	21.17	20.79
			0	22.00	21.51	21.17	20.79

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26140	26365	26590
					1860.0MHz	1882.5MHz	1905.0MHz
20MHz	QPSK	1	0	24.00	23.93	22.97	22.70
			50	24.50	24.39	23.44	22.99
			99	24.00	23.76	22.96	22.67
		50	0	23.00	22.82	22.10	21.94
			25	23.00	22.82	22.11	21.93
			50	22.50	22.28	22.10	21.69
		100	0	22.50	22.39	22.08	21.84
	16QAM	1	0	23.00	22.62	22.09	21.51
			50	23.00	22.94	22.46	21.84
			99	22.50	22.39	21.98	21.42
		50	0	22.00	21.89	21.12	20.96
			25	22.00	21.61	21.08	21.00
			50	21.50	21.23	21.15	20.77
		100	0	21.50	21.34	21.05	20.82

Band 26 Part90

LTE-FDD Band 26 Part90				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26697	26740	26783
					814.7MHz	819.0MHz	823.3MHz
1.4MHz	QPSK	1	0	25.00	24.63	24.66	24.14
			2	25.00	24.85	24.81	24.22
			5	25.00	24.60	24.62	24.15
		3	0	25.00	24.64	24.50	24.23
			2	25.00	24.57	24.11	24.18
			3	25.00	24.62	24.15	24.18
		6	0	24.00	23.66	23.09	23.18
	16QAM	1	0	23.50	23.40	23.45	22.87
			2	24.00	23.65	23.57	23.02
			5	24.00	23.51	23.47	22.89
		3	0	23.50	23.37	23.00	22.87
			2	23.50	23.38	22.98	22.92
			3	23.50	23.35	22.95	22.95
		6	0	23.00	22.61	21.97	22.14
					26705	26740	26775
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	815.5MHz	819.0MHz	822.5MHz
3MHz	QPSK	1	0	24.50	24.08	24.00	23.98
			7	24.50	24.09	24.03	24.02
			14	24.50	24.10	24.02	24.07
		8	0	23.50	23.05	22.94	23.03
			4	23.50	23.03	22.99	23.00
			7	23.50	23.03	22.97	22.96
		15	0	23.00	22.97	22.88	22.91
	16QAM	1	0	23.00	22.89	22.73	22.96
			7	23.00	22.90	22.73	22.99
			14	23.00	22.89	22.82	22.99
		8	0	22.50	22.04	21.97	22.05
			4	22.50	22.03	21.99	22.03
			7	22.50	22.05	22.00	22.02
		15	0	22.00	21.94	21.86	21.97

LTE-FDD Band 26 Part90				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26715	26740	26765
					816.5MHz	819.0MHz	821.5MHz
5MHz	QPSK	1	0	24.50	23.91	24.45	23.88
			13	24.50	23.98	24.07	24.02
			24	24.50	23.85	24.05	23.96
		12	0	23.00	22.93	22.87	22.83
			6	23.00	22.91	22.77	22.86
			13	23.50	23.02	23.03	22.90
		25	0	23.00	22.93	22.94	22.90
	16QAM	1	0	23.50	22.88	23.03	22.92
			13	23.50	23.03	22.95	23.06
			24	23.00	22.94	22.94	22.95
		12	0	22.00	21.94	21.85	21.89
			6	22.00	21.95	21.85	21.91
			13	22.50	22.01	22.01	21.98
		25	0	22.00	21.90	21.95	21.87
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26740		
					819.0MHz		
10MHz	QPSK	1	0	24.00	23.83		
			25	24.00	23.97		
			49	24.00	24.00		
		25	0	23.00	22.82		
			13	23.00	22.80		
			25	23.00	22.96		
		50	0	23.00	22.89		
	16QAM	1	0	23.00	22.62		
			25	23.00	22.97		
			49	23.00	22.78		
		25	0	22.00	21.85		
			13	22.00	21.90		
			25	22.50	22.01		
		50	0	22.00	21.95		

Band 26 Part22

LTE-FDD Band 26 Part22				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26797	26915	27033
					824.7MHz	836.5MHz	848.3MHz
1.4MHz	QPSK	1	0	25.00	24.77	24.15	24.28
			2	24.50	24.39	24.26	24.43
			5	24.50	24.27	24.12	24.21
		3	0	24.50	24.27	24.24	24.29
			2	24.50	24.28	24.24	24.28
			3	24.50	24.33	24.27	24.24
		6	0	23.50	23.18	23.19	23.30
	16QAM	1	0	23.50	23.24	22.91	23.10
			2	23.50	23.16	23.07	23.40
			5	23.50	23.02	22.90	23.10
		3	0	23.50	23.09	23.00	23.06
			2	23.50	23.05	22.99	23.03
			3	23.50	23.04	23.00	23.03
		6	0	22.50	22.07	22.22	22.29

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26805	26915	27025
					825.5MHz	836.5MHz	847.5MHz
3MHz	QPSK	1	0	24.50	24.23	24.32	24.35
			7	24.50	24.28	24.30	24.36
			14	24.50	24.27	24.39	24.36
		8	0	23.50	23.25	23.29	23.36
			4	23.50	23.21	23.27	23.33
			7	23.50	23.25	23.25	23.36
		15	0	23.50	23.18	23.25	23.32
			0	23.50	23.22	23.14	23.33
			7	23.50	23.24	23.08	23.34
	16QAM	1	14	23.50	23.23	23.10	23.29
			0	22.50	22.28	22.33	22.42
			4	22.50	22.27	22.30	22.40
		8	7	22.50	22.28	22.28	22.36
			0	22.50	22.24	22.21	22.34
			0	22.50	22.24	22.21	22.34

LTE-FDD Band 26 Part22				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26815	26915	27015
					826.5MHz	836.5MHz	846.5MHz
5MHz	QPSK	1	0	24.50	24.06	24.12	24.17
			13	24.50	24.25	24.19	24.30
			24	24.50	24.22	24.05	24.21
		12	0	23.50	23.13	23.21	23.12
			6	23.50	23.15	23.17	23.14
			13	23.50	23.11	23.08	23.14
		25	0	23.50	23.11	23.17	23.13
			0	23.50	22.95	23.13	23.04
			13	23.50	23.09	23.23	23.24
	16QAM	1	24	23.50	23.08	23.10	23.12
			0	22.50	22.10	22.22	22.08
			6	22.50	22.13	22.19	22.08
		12	13	22.50	22.15	22.18	22.18
			0	22.50	22.14	22.18	22.19
			0	22.50	22.14	22.18	22.19
		25	0	22.50	22.14	22.18	22.19
			0	22.50	22.14	22.18	22.19
			0	22.50	22.14	22.18	22.19
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26840	26915	26990
					829.0MHz	836.5MHz	844.0MHz
10MHz	QPSK	1	0	25.00	24.57	24.23	24.10
			25	24.50	24.36	24.39	24.34
			49	24.50	24.19	24.18	24.27
		25	0	23.50	23.27	23.24	23.34
			13	23.50	23.23	23.24	23.34
			25	23.50	23.26	23.07	23.38
		50	0	23.50	23.27	23.10	23.34
			0	23.50	23.02	23.05	23.07
			25	23.50	23.33	23.23	23.38
	16QAM	1	49	23.50	23.15	22.99	23.25
			0	22.50	22.22	22.28	22.41
			13	22.50	22.27	22.26	22.38
		25	25	22.50	22.30	22.12	22.37
			0	22.50	22.25	22.14	22.37
			0	22.50	22.25	22.14	22.37
		50	0	22.50	22.25	22.14	22.37
			0	22.50	22.25	22.14	22.37
			0	22.50	22.25	22.14	22.37

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26865	26915	26965
					831.5MHz	836.5MHz	841.5MHz
15MHz	QPSK	1	0	24.50	24.25	23.95	23.95
			38	24.50	24.22	24.17	24.15
			74	24.50	24.04	23.91	24.06
		36	0	23.50	22.99	23.05	23.02
			18	23.50	23.22	23.22	23.17
			39	23.50	23.03	23.10	23.07
		75	0	23.50	23.21	22.99	23.26
	16QAM	1	0	23.50	22.96	23.09	22.92
			38	23.50	23.22	23.23	23.15
			74	23.50	23.01	23.14	23.02
		36	0	23.50	22.94	23.04	22.99
			18	23.50	23.22	23.18	23.17
			39	23.50	22.95	23.08	23.04
		75	0	22.50	22.22	22.04	22.23

Band 41

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		39675	40620	41565
5MHz	QPSK	1	0	24.50	23.55	23.84	24.05
			13	24.50	23.72	24.02	24.29
			24	24.50	23.61	23.93	24.14
		12	0	23.00	22.55	22.92	22.88
			6	23.00	22.58	22.87	22.91
			13	23.00	22.59	22.90	22.92
		25	0	23.00	22.50	22.87	22.83
	16QAM	1	0	23.00	22.43	22.86	22.76
			13	23.50	22.58	23.04	22.93
			24	23.00	22.48	22.92	22.78
		12	0	22.00	21.45	21.91	21.75
			6	22.00	21.49	21.89	21.82
			13	22.00	21.50	21.92	21.85
		25	0	22.00	21.52	21.87	21.80
10MHz	QPSK	1	0	24.00	23.57	23.83	23.96
			25	24.50	24.00	24.20	24.42
			49	24.50	23.77	23.97	24.09
		25	0	23.00	22.63	22.95	22.97
			13	23.00	22.60	22.96	22.96
			25	23.00	22.69	22.95	22.94
		50	0	23.00	22.60	22.96	22.88
	16QAM	1	0	23.00	22.29	22.58	22.86
			25	23.50	22.68	22.93	23.15
			49	23.00	22.49	22.76	22.81
		25	0	22.00	21.63	21.97	21.87
			13	22.00	21.60	21.96	21.89
			25	22.50	21.69	22.00	21.86
		50	0	22.00	21.60	21.94	21.85

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)			
Bandwidth	Modulation	RB allocation	RB offset		39725	40620	41515	
					2503.5MHz	2593.0MHz	2682.5MHz	
15MHz	QPSK	1	0	24.00	23.31	23.69	23.82	
			38	24.50	23.62	23.93	24.12	
			74	24.50	23.68	23.92	24.02	
		36	0	23.00	22.39	22.48	22.79	
			18	23.50	22.72	22.70	23.01	
			39	23.00	22.78	22.67	22.78	
		75	0	23.50	22.79	23.00	23.18	
		16QAM	1	0	23.00	22.39	22.47	22.80
				38	23.00	22.68	22.70	22.98
	74			23.00	22.78	22.69	22.75	
	36		0	23.00	22.40	22.46	22.79	
			18	23.50	22.76	22.70	23.00	
			39	23.00	22.79	22.69	22.74	
	75		0	22.00	21.68	21.93	21.99	
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39750	40620	41490
						2506.0MHz	2593.0MHz	2680.0MHz
20MHz	QPSK	1	0	16.50	16.25	16.17	16.28	
			50	17.50	17.12	16.63	16.93	
			99	17.00	16.66	16.23	16.52	
		50	0	16.00	15.53	15.42	15.47	
			25	16.00	15.51	15.42	15.50	
			50	16.00	15.74	15.37	15.43	
		100	0	16.00	15.65	15.37	15.44	
		16QAM	1	0	15.50	15.33	14.95	15.16
				50	16.50	16.10	15.46	15.60
	99			16.00	15.69	15.10	15.14	
	50		0	15.00	14.50	14.43	14.46	
			25	15.00	14.50	14.48	14.49	
			50	15.00	14.78	14.42	14.36	
	100		0	15.00	14.59	14.40	14.41	

Band 66

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		131979	132322	132665
					1710.7MHz	1745.0MHz	1779.3MHz
1.4MHz	QPSK	1	0	24.00	22.93	23.36	23.67
			2	24.00	23.12	23.04	23.82
			5	24.00	22.91	22.83	23.66
		3	0	24.00	22.97	22.95	23.51
			2	24.00	22.96	22.92	23.51
			3	23.50	22.86	22.97	23.47
		6	0	23.00	21.62	22.01	22.68
	16QAM	1	0	22.50	21.81	21.84	22.34
			2	23.00	21.97	22.01	22.51
			5	22.50	21.77	21.79	22.37
		3	0	22.50	21.76	21.75	22.31
			2	22.50	21.66	21.73	22.30
			3	22.50	21.35	21.78	22.27
		6	0	22.00	20.52	20.93	21.52

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131987	132322	132657
					1711.5MHz	1745.0MHz	1778.5MHz
3MHz	QPSK	1	0	24.00	22.74	23.00	23.75
			7	24.00	22.51	23.04	23.82
			14	24.00	22.56	23.10	23.78
		8	0	23.00	21.61	22.06	22.83
			4	23.00	21.57	22.07	22.84
			7	23.00	21.63	22.17	22.79
		15	0	23.00	21.58	22.06	22.67
	16QAM	1	0	23.00	21.55	22.08	22.65
			7	23.00	21.56	22.12	22.69
			14	23.00	21.58	22.17	22.68
		8	0	22.00	20.56	21.07	21.72
			4	22.00	20.54	21.09	21.71
			7	22.00	20.59	21.14	21.70
		15	0	22.00	20.52	21.06	21.62
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131997	132322	132647
					1712.5MHz	1745.0MHz	1777.5MHz
5MHz	QPSK	1	0	24.00	22.87	22.87	23.59
			13	24.00	22.55	23.03	23.71
			24	24.00	22.52	22.98	23.68
		12	0	23.00	21.38	21.91	22.60
			6	23.00	21.35	21.89	22.64
			13	23.00	21.54	22.07	22.55
		25	0	22.50	21.47	21.99	22.46
	16QAM	1	0	22.50	21.32	21.86	22.39
			13	23.00	21.48	21.99	22.52
			24	22.50	21.43	21.92	22.43
		12	0	22.00	20.31	20.83	21.51
			6	22.00	20.30	20.90	21.54
			13	21.50	20.42	20.92	21.43
		25	0	21.50	20.44	20.96	21.47
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	132022	132322	132622
					1715.0MHz	1745.0MHz	1775.0MHz
10MHz	QPSK	1	0	24.00	22.59	22.78	23.53
			25	24.00	22.86	22.94	23.70
			49	23.50	22.93	22.86	23.47
		25	0	23.00	21.96	21.84	22.56
			13	23.00	21.81	21.82	22.59
			25	22.50	21.72	21.99	22.32
		50	0	22.50	21.64	21.88	22.38
	16QAM	1	0	22.50	21.57	21.77	22.39
			25	23.00	21.97	21.96	22.53
			49	22.50	22.21	21.92	22.39
		25	0	21.50	20.94	20.79	21.40
			13	21.50	20.45	20.79	21.38
			25	21.50	20.72	20.98	21.24
		50	0	21.50	20.58	20.86	21.25

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)			
Bandwidth	Modulation	RB allocation	RB offset		132047	132322	132597	
					1717.5MHz	1745.0MHz	1772.5MHz	
15MHz	QPSK	1	0	23.50	22.00	22.46	23.25	
			38	23.50	22.49	22.73	23.47	
			74	23.50	22.53	22.85	23.00	
		36	0	22.50	21.05	21.51	22.16	
			18	22.50	21.49	21.81	22.41	
			39	22.50	21.54	21.83	22.23	
		75	0	23.00	21.46	21.84	22.59	
		16QAM	1	0	22.50	21.04	21.53	22.19
				38	22.50	21.54	21.84	22.36
	74			22.50	21.58	21.84	22.19	
	36		0	22.50	21.04	21.54	22.19	
			18	22.50	21.51	21.83	22.39	
			39	22.50	21.59	21.85	22.23	
	75		0	21.50	20.38	20.74	21.43	
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	132072	132322	132572
1720.0MHz						1745.0MHz	1770.0MHz	
20MHz	QPSK	1	0	23.50	21.94	22.40	23.11	
			50	24.00	22.71	22.87	23.81	
			99	23.50	22.59	22.88	23.33	
		50	0	22.50	21.28	21.68	22.46	
			25	22.50	21.22	21.65	22.45	
			50	22.50	21.63	21.95	22.20	
		100	0	22.50	21.50	21.85	22.38	
		16QAM	1	0	22.00	20.80	21.39	21.90
				50	22.50	21.62	21.81	22.41
	99			22.50	21.53	21.77	22.05	
	50		0	21.50	20.25	20.66	21.44	
			25	21.50	20.27	20.66	21.45	
			50	21.50	20.63	20.93	21.13	
	100		0	21.50	20.41	20.81	21.30	

8.4 Wi-Fi

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
2.4g Wifi (2.4~2.4835)	802.11b	1	2412	15.25	15.50	Yes
		6	2437	14.69	15.00	No
		11	2462	14.72	15.00	No
	802.11g	1	2412	14.63	15.00	No
		6	2437	14.99	15.00	No
		11	2462	14.78	15.00	No
	802.11n(HT20)	1	2412	14.21	14.50	No
		6	2437	13.77	14.00	No
		11	2462	14.15	14.50	No
	802.11n(HT40)	3	2422	13.56	14.00	No
		6	2437	14.78	15.00	No
		9	2452	14.28	14.50	No

Note: SAR is not required for the following 2.4 GHz OFDM conditions as the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2\text{W/kg}$.

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-1 (5.150~5.250)	802.11a	36	5180	8.33	8.50	No
		40	5200	8.58	9.00	No
		48	5240	7.91	8.00	No
	802.11n(HT20)	36	5180	10.01	10.50	No
		40	5200	10.07	10.50	No
		48	5240	9.52	10.00	No
	802.11ac(VHT20)	36	5180	10.25	10.50	No
		40	5200	10.38	10.50	Yes
		48	5240	9.68	10.00	No
	802.11n(HT40)	38	5190	10.12	10.50	No
		46	5230	9.76	10.00	No
	802.11ac(VHT40)	38	5190	10.22	10.50	No
		46	5230	9.75	10.00	No
	802.11ac(VHT80)	42	5210	10.10	10.50	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2a (5.250~5.350)	802.11a	52	5260	11.37	11.50	Yes
		56	5280	7.34	7.50	No
		64	5320	6.81	7.00	No
	802.11n(HT20)	52	5260	9.45	9.50	No
		56	5280	9.00	9.50	No
		64	5320	8.51	9.00	No
	802.11ac(VHT20)	52	5260	9.58	10.00	No
		56	5280	8.91	9.00	No
		64	5320	8.44	8.50	No
	802.11n(HT40)	54	5270	9.11	9.50	No
		62	5310	8.37	8.50	No
	802.11ac(VHT40)	54	5270	9.00	9.50	No
		62	5310	8.36	8.50	No
	802.11ac(VHT80)	58	5290	8.92	9.00	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2c (5.470~5.725)	802.11a	100	5500	9.87	10.00	No
		120	5600	9.37	9.50	No
		140	5700	6.95	7.00	No
	802.11n(HT20)	100	5500	11.80	12.00	No
		120	5600	10.86	11.00	No
		140	5700	8.52	9.00	No
	802.11ac(VHT20)	100	5500	11.91	12.00	No
		120	5600	10.92	11.00	No
		140	5700	8.69	9.00	No
	802.11n(HT40)	102	5510	11.78	12.00	No
		118	5590	10.79	11.00	No
		134	5670	9.38	9.50	No
	802.11ac(VHT40)	102	5510	12.03	12.50	Yes
		118	5590	11.15	11.50	No
		134	5670	9.56	10.00	No
	802.11ac(VHT80)	106	5530	11.48	11.50	No
		122	5610	9.90	10.00	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-3 (5.725~5.850)	802.11a	149	5745	9.18	9.50	No
		157	5785	10.10	10.50	No
		165	5825	10.27	10.50	Yes
	802.11n(HT20)	149	5745	8.74	9.00	No
		157	5785	9.74	10.00	No

	802.11ac(VHT20)	165	5825	10.16	10.50	No
		149	5745	9.15	9.50	No
		157	5785	10.01	10.50	No
		165	5825	10.25	10.50	No
	802.11n(HT40)	151	5755	9.02	9.50	No
		159	5795	10.11	10.50	No
	802.11ac(VHT40)	151	5755	9.31	9.50	No
		159	5795	7.46	7.50	No
	802.11ac(VHT80)	155	5775	9.45	9.50	No

8.5 Bluetooth

EDR	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	39	78
			2402MHz	2441MHz	2480MHz
	GFSK	9.00	8.56	8.11	8.23
	π/4QPSK	8.50	8.45	8.05	8.22
	8DPSK	9.00	8.63	8.15	8.06
BLE	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	20	39
			2402MHz	2440MHz	2480MHz
	1Mbps	4.50	4.28	3.99	3.01

8.6 NFC

Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)	
	13.56MHz	
12.50	12.31	

Channel	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Exclusion thresholds for 1-g SAR(mW)	RF exposure evaluation required
78	2.480	9.00	7.94	0	10	No
/	0.01356	12.00	15.85	0	39	No
This device has NFC operations, the NFC antenna is integrated into the device for this model, therefore, all SAR test were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the antenna can be found in the operational description. According to FCC KDB publication 447498 D01v06transmitters are consider to be operating simultaneously when there is overlapping transmission, with the exception of transmission during network hand-offs with maximum hand-off duration less than 30 seconds.						

Note

- Per KDB 447498 D01 General RF Exposure Guidance v06, the 1-g SAR test exclusion thresholds for 300 MHz to 6 GHz at *test separation distances* ≤ 40 cm are determined by:

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

*When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine estimated SAR. .
The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

9. Test Exclusion Consideration

Antenna information:



WWAN Main Antenna	GSM/WCDMA/LTE TX/RX
WLAN/BT Antenna	WLAN/BT TX/RX
Note: 1. KDB 447498 D01v06, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm. 2. Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR<1.2W/Kg. 3. EUT is a POS device, the scanning head and the prototype are detachable, so the scanning head is disassembled during the test, so that the prototype is closer to the human model.	

Distance of The Antenna to the EUT surface and edge (mm)						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	<25	<25	<25	50	158	<25
BT/Wifi	<25	<25	66	<25	<25	150
Positions for SAR tests: Hotspot mode						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	Yes	Yes	Yes	No	No	Yes
BT/Wifi	Yes	Yes	No	Yes	Yes	No

9.1 SAR Test Exclusion Consideration Table

Per KDB 447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following format to determine simultaneous transmission SAR test exclusion:

$$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

0.4 W/Kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

Mode	Channel	Frequency (GHz)	Max tune-up power (dBm)	Max. Power (mW)	Exposure Position	Body-worn
					Test Dist.(mm)	10
BT	0	2.402	9.00	7.94	Estimated SAR(W/kg)	0.328
NFC	/	0.01356	12.00	15.85		0.000

10. Test Result

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
GPRS 850+4slots	Front	190	836.6	3.290	0.525	100.00	1.000	31.20	31.50	1.072	0.563	/
	Back	190	836.6	-2.410	0.604	100.00	1.000	31.20	31.50	1.072	0.647	1#
	Left	190	836.6	-1.450	0.421	100.00	1.000	31.20	31.50	1.072	0.451	/
	Bottom	190	836.6	1.800	0.474	100.00	1.000	31.20	31.50	1.072	0.508	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
GPRS 1900+4slots	Front	661	1880.0	1.200	0.338	100.00	1.000	29.53	30.00	1.114	0.377	/
	Back	661	1880.0	2.470	0.379	100.00	1.000	29.53	30.00	1.114	0.422	2#
	Left	661	1880.0	-2.790	0.237	100.00	1.000	29.53	30.00	1.114	0.264	/
	Bottom	661	1880.0	0.810	0.292	100.00	1.000	29.53	30.00	1.114	0.325	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
WCDMA Band 2 (RMC*)	Front	9400	1880.0	-0.410	0.472	100.00	1.000	23.11	23.50	1.094	0.516	/
	Back	9400	1880.0	-2.080	0.526	100.00	1.000	23.11	23.50	1.094	0.575	3#
	Left	9400	1880.0	1.170	0.395	100.00	1.000	23.11	23.50	1.094	0.432	/
	Bottom	9400	1880.0	-3.520	0.433	100.00	1.000	23.11	23.50	1.094	0.474	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
WCDMA Band 5 (RMC*)	Front	4132	826.4	-3.590	0.635	100.00	1.000	22.98	23.00	1.005	0.638	/
	Back	4132	826.4	4.770	0.697	100.00	1.000	22.98	23.00	1.005	0.700	4#
	Left	4132	826.4	-0.730	0.531	100.00	1.000	22.98	23.00	1.005	0.534	/
	Bottom	4132	826.4	-3.400	0.594	100.00	1.000	22.98	23.00	1.005	0.597	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 2 (BW: 20MHz)	1RB	Front	18700	1860.0	-0.020	0.721	100.00	1.000	24.27	24.50	1.054	0.760	/
		Back	18700	1860.0	3.570	0.756	100.00	1.000	24.27	24.50	1.054	0.797	5#
		Left	18700	1860.0	0.310	0.627	100.00	1.000	24.27	24.50	1.054	0.661	/
		Bottom	18700	1860.0	-0.120	0.685	100.00	1.000	24.27	24.50	1.054	0.722	/
	50%RB	Front	18700	1860.0	-3.710	0.684	100.00	1.000	22.98	23.00	1.005	0.687	/
		Back	18700	1860.0	-3.240	0.736	100.00	1.000	22.98	23.00	1.005	0.740	/
		Left	18700	1860.0	-0.200	0.588	100.00	1.000	22.98	23.00	1.005	0.591	/
		Bottom	18700	1860.0	-3.590	0.649	100.00	1.000	22.98	23.00	1.005	0.652	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 4 (BW: 20MHz)	1RB	Front	20300	1745.0	2.280	0.595	100.00	1.000	22.87	23.00	1.030	0.613	/
		Back	20300	1745.0	0.230	0.636	100.00	1.000	22.87	23.00	1.030	0.655	6#
		Left	20300	1745.0	-1.780	0.512	100.00	1.000	22.87	23.00	1.030	0.527	/
		Bottom	20300	1745.0	-1.750	0.554	100.00	1.000	22.87	23.00	1.030	0.571	/
	50%RB	Front	20300	1745.0	-0.440	0.561	100.00	1.000	21.94	22.00	1.014	0.569	/
		Back	20300	1745.0	-4.120	0.603	100.00	1.000	21.94	22.00	1.014	0.611	/
		Left	20300	1745.0	4.120	0.467	100.00	1.000	21.94	22.00	1.014	0.474	/
		Bottom	20300	1745.0	0.710	0.518	100.00	1.000	21.94	22.00	1.014	0.525	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 5 (BW: 10MHz)	1RB	Front	20450	829.0	3.400	0.663	100.00	1.000	24.97	25.00	1.007	0.668	/
		Back	20450	829.0	-3.030	0.701	100.00	1.000	24.97	25.00	1.007	0.706	7#
		Left	20450	829.0	2.140	0.583	100.00	1.000	24.97	25.00	1.007	0.587	/
		Bottom	20450	829.0	-2.330	0.628	100.00	1.000	24.97	25.00	1.007	0.632	/

	50%RB	Front	20450	829.0	-1.280	0.632	100.00	1.000	23.83	24.00	1.040	0.657	/
		Back	20450	829.0	-1.230	0.670	100.00	1.000	23.83	24.00	1.040	0.697	/
		Left	20450	829.0	3.740	0.544	100.00	1.000	23.83	24.00	1.040	0.566	/
		Bottom	20450	829.0	0.230	0.591	100.00	1.000	23.83	24.00	1.040	0.615	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 7 (BW: 20MHz)	1RB	Front	21100	2535.0	4.520	0.645	100.00	1.000	23.63	24.00	1.089	0.702	/
		Back	21100	2535.0	1.340	0.686	100.00	1.000	23.63	24.00	1.089	0.747	8#
		Left	21100	2535.0	-2.500	0.557	100.00	1.000	23.63	24.00	1.089	0.607	/
		Bottom	21100	2535.0	-2.910	0.609	100.00	1.000	23.63	24.00	1.089	0.663	/
	50%RB	Front	21100	2535.0	-2.120	0.616	100.00	1.000	22.42	22.50	1.019	0.628	/
		Back	21100	2535.0	-1.340	0.652	100.00	1.000	22.42	22.50	1.019	0.664	/
		Left	21100	2535.0	3.360	0.521	100.00	1.000	22.42	22.50	1.019	0.531	/
		Bottom	21100	2535.0	-0.250	0.578	100.00	1.000	22.42	22.50	1.019	0.589	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 12 (BW: 10MHz)	1RB	Front	23060	704.0	0.900	0.164	100.00	1.000	24.35	24.50	1.035	0.170	/
		Back	23060	704.0	-4.220	0.193	100.00	1.000	24.35	24.50	1.035	0.200	9#
		Left	23060	704.0	1.970	0.092	100.00	1.000	24.35	24.50	1.035	0.095	/
		Bottom	23060	704.0	-4.050	0.121	100.00	1.000	24.35	24.50	1.035	0.125	/
	50%RB	Front	23060	704.0	-0.660	0.147	100.00	1.000	23.40	23.50	1.023	0.150	/
		Back	23060	704.0	-0.480	0.171	100.00	1.000	23.40	23.50	1.023	0.175	/
		Left	23060	704.0	-3.170	0.078	100.00	1.000	23.40	23.50	1.023	0.080	/
		Bottom	23060	704.0	2.560	0.103	100.00	1.000	23.40	23.50	1.023	0.105	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 14 (BW: 10MHz)	1RB	Front	23330	793.0	3.900	0.962	100.00	1.000	23.88	24.00	1.028	0.989	/
		Back	23330	793.0	2.800	0.991	100.00	1.000	23.88	24.00	1.028	1.019	10#
		Back-repeat	23330	793.0	1.480	0.986	100.00	1.000	23.88	24.00	1.028	1.014	/
		Left	23330	793.0	-3.400	0.894	100.00	1.000	23.88	24.00	1.028	0.919	/
	50%RB	Bottom	23330	793.0	-4.430	0.924	100.00	1.000	23.88	24.00	1.028	0.950	/
		Front	23330	793.0	-3.910	0.935	100.00	1.000	22.83	23.00	1.040	0.972	/
		Back	23330	793.0	-0.800	0.967	100.00	1.000	22.83	23.00	1.040	1.006	/
		Left	23330	793.0	0.040	0.864	100.00	1.000	22.83	23.00	1.040	0.899	/
		Bottom	23330	793.0	3.200	0.901	100.00	1.000	22.83	23.00	1.040	0.937	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 17 (BW: 10MHz)	1RB	Front	23800	711.0	3.760	0.116	100.00	1.000	23.95	24.00	1.012	0.117	/
		Back	23800	711.0	-2.340	0.139	100.00	1.000	23.95	24.00	1.012	0.141	11#
		Left	23800	711.0	-1.590	0.083	100.00	1.000	23.95	24.00	1.012	0.084	/
		Bottom	23800	711.0	-4.200	0.097	100.00	1.000	23.95	24.00	1.012	0.098	/
	50%RB	Front	23800	711.0	1.130	0.092	100.00	1.000	22.77	23.00	1.054	0.097	/
		Back	23800	711.0	2.000	0.113	100.00	1.000	22.77	23.00	1.054	0.119	/
		Left	23800	711.0	-2.050	0.075	100.00	1.000	22.77	23.00	1.054	0.079	/
		Bottom	23800	711.0	-0.800	0.084	100.00	1.000	22.77	23.00	1.054	0.089	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 25 (BW: 20MHz)	1RB	Front	26590	1905.0	3.760	0.418	100.00	1.000	24.39	24.50	1.026	0.429	/
		Back	26140	1860.0	2.010	0.447	100.00	1.000	24.39	24.50	1.026	0.459	12#
		Left	26590	1905.0	1.910	0.364	100.00	1.000	24.39	24.50	1.026	0.373	/
		Bottom	26590	1905.0	0.330	0.393	100.00	1.000	24.39	24.50	1.026	0.403	/

	50%RB	Front	26590	1905.0	-0.410	0.395	100.00	1.000	22.82	23.00	1.042	0.412	/
		Back	26590	1905.0	1.330	0.421	100.00	1.000	22.82	23.00	1.042	0.439	/
		Left	26590	1905.0	1.720	0.339	100.00	1.000	22.82	23.00	1.042	0.353	/
		Bottom	26590	1905.0	1.900	0.372	100.00	1.000	22.82	23.00	1.042	0.388	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 26 Part 90 (BW: 10MHz)	1RB	Front	26740	819.0	2.040	0.965	100.00	1.000	24.00	24.00	1.000	0.965	/
		Back	26740	819.0	-2.900	0.988	100.00	1.000	24.00	24.00	1.000	0.988	13#
		Back-repeat	26740	819.0	3.260	0.982	100.00	1.000	24.00	24.00	1.000	0.982	/
		Left	26740	819.0	-1.490	0.883	100.00	1.000	24.00	24.00	1.000	0.883	/
		Bottom	26740	819.0	-2.630	0.917	100.00	1.000	24.00	24.00	1.000	0.917	/
	50%RB	Front	26740	819.0	-1.100	0.937	100.00	1.000	22.96	23.00	1.009	0.945	/
		Back	26740	819.0	1.480	0.959	100.00	1.000	22.96	23.00	1.009	0.968	/
		Left	26740	819.0	2.120	0.866	100.00	1.000	22.96	23.00	1.009	0.864	/
		Bottom	26740	819.0	2.110	0.884	100.00	1.000	22.96	23.00	1.009	0.892	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 26 Part 22 (BW: 15MHz)	1RB	Front	26865	831.5	2.040	0.634	100.00	1.000	24.25	24.50	1.059	0.671	/
		Back	26865	831.5	-3.700	0.660	100.00	1.000	24.25	24.50	1.059	0.699	14#
		Left	26865	831.5	1.490	0.562	100.00	1.000	24.25	24.50	1.059	0.595	/
		Bottom	26865	831.5	-2.630	0.601	100.00	1.000	24.25	24.50	1.059	0.636	/
	50%RB	Front	26865	831.5	-1.100	0.603	100.00	1.000	23.22	23.50	1.067	0.643	/
		Back	26865	831.5	1.480	0.640	100.00	1.000	23.22	23.50	1.067	0.683	/
		Left	26865	831.5	2.120	0.531	100.00	1.000	23.22	23.50	1.067	0.567	/
		Bottom	26865	831.5	2.110	0.577	100.00	1.000	23.22	23.50	1.067	0.616	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 41 (BW: 20MHz)	1RB	Front	39750	2506.0	3.250	0.957	100.00	1.000	17.12	17.50	1.091	1.044	/
		Back	39750	2506.0	-3.020	0.996	100.00	1.000	17.12	17.50	1.091	1.087	15#
		Back-repeat	39750	2506.0	2.470	0.990	100.00	1.000	17.12	17.50	1.091	1.080	/
		Back	40620	2593.0	-1.590	0.966	100.00	1.000	16.63	17.00	1.089	1.052	/
		Back	41490	2680.0	-4.680	0.975	100.00	1.000	16.69	17.00	1.074	1.047	/
		Left	39750	2506.0	0.820	0.895	100.00	1.000	17.12	17.50	1.091	0.976	/
	50%RB	Bottom	39750	2506.0	-0.310	0.921	100.00	1.000	17.12	17.50	1.091	1.005	/
		Front	39750	2506.0	-0.190	0.922	100.00	1.000	15.74	16.00	1.062	0.979	/
		Back	39750	2506.0	-1.670	0.967	100.00	1.000	15.74	16.00	1.062	1.027	/
		Left	39750	2506.0	3.210	0.864	100.00	1.000	15.74	16.00	1.062	0.918	/
		Bottom	39750	2506.0	1.750	0.894	100.00	1.000	15.74	16.00	1.062	0.949	/

Body(hotspot open, 0mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 66 (BW: 20MHz)	1RB	Front	132572	1770.0	1.950	0.573	100.00	1.000	23.81	24.00	1.045	0.599	/
		Back	132572	1770.0	-2.690	0.618	100.00	1.000	23.81	24.00	1.045	0.646	16#
		Left	132572	1770.0	1.830	0.504	100.00	1.000	23.81	24.00	1.045	0.527	/
		Bottom	132572	1770.0	-0.790	0.535	100.00	1.000	23.81	24.00	1.045	0.559	/
	50%RB	Front	132572	1770.0	0.680	0.544	100.00	1.000	22.46	22.50	1.009	0.549	/
		Back	132572	1770.0	-0.680	0.586	100.00	1.000	22.46	22.50	1.009	0.591	/
		Left	132572	1770.0	-0.272	0.483	100.00	1.000	22.46	22.50	1.009	0.487	/
		Bottom	132572	1770.0	-3.050	0.517	100.00	1.000	22.46	22.50	1.009	0.522	/

Body(hotspot open, 0mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
2.4g (2.4~2.4835) 802.11b	Front	1	2412	1.340	0.445	100.00	1.000	15.25	15.50	1.059	0.471	/
	Back	1	2412	-0.350	0.470	100.00	1.000	15.25	15.50	1.059	0.498	17#
	Right	1	2412	0.870	0.364	100.00	1.000	15.25	15.50	1.059	0.385	/
	Top	1	2412	-2.810	0.416	100.00	1.000	15.25	15.50	1.059	0.441	/
Body(hotspot open, 0mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-1 (5.150~5.250) 802.11ac(VHT20)	Front	40	5200	0.970	0.217	100.00	1.000	10.38	10.50	1.028	0.223	/
	Back	40	5200	-0.490	0.240	100.00	1.000	10.38	10.50	1.028	0.247	18#
	Right	40	5200	0.290	0.164	100.00	1.000	10.38	10.50	1.028	0.169	/
	Top	40	5200	-3.220	0.189	100.00	1.000	10.38	10.50	1.028	0.194	/
Body(hotspot open, 0mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2a (5.250~5.350) 802.11a	Front	52	5260	0.420	0.252	100.00	1.000	11.37	11.50	1.030	0.260	/
	Back	52	5260	2.790	0.284	100.00	1.000	11.37	11.50	1.030	0.293	19#
	Right	52	5260	0.120	0.194	100.00	1.000	11.37	11.50	1.030	0.200	/
	Top	52	5260	-3.650	0.220	100.00	1.000	11.37	11.50	1.030	0.227	/
Body(hotspot open, 0mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2c (5.470~5.725) 802.11ac(VHT40)	Front	102	5510	0.770	0.206	100.00	1.000	12.03	12.50	1.114	0.229	/
	Back	102	5510	-1.920	0.235	100.00	1.000	12.03	12.50	1.114	0.262	20#
	Right	102	5510	3.650	0.149	100.00	1.000	12.03	12.50	1.114	0.166	/
	Top	102	5510	-1.195	0.178	100.00	1.000	12.03	12.50	1.114	0.198	/
Body(hotspot open, 0mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-3 (5.725~5.850) 802.11a	Front	165	5825	0.400	0.198	100.00	1.000	10.27	10.50	1.054	0.209	/
	Back	165	5825	-2.130	0.222	100.00	1.000	10.27	10.50	1.054	0.234	21#
	Right	165	5825	3.070	0.127	100.00	1.000	10.27	10.50	1.054	0.134	/
	Top	165	5825	-1.605	0.164	100.00	1.000	10.27	10.50	1.054	0.173	/

Note:

- The maximum SAR Value of each test band is marked bold.
- SAR plot is provided only for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.
- Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR $\leq 0.8W/kg$, other channels SAR testing is not necessary.
- Per KDB 447498 D01 v06, head/body-worn use is evaluated with the device positioned at 0mm/10 mm from a head/flat phantom respectively filled with head tissue-equivalent medium.
- Per KDB Publication 941225 D06 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.
- Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor= $10^{[(\text{tune-up limit power(dBm)} - \text{Ave.power power (dBm)})/10]}$, where tune-up limit is the maximum rated power among all production units.
Reported SAR(W/kg)=Measured SAR (W/kg)*Scaling Factor.

11. SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is $0.996 > 0.80$ W/kg, repeated measurement is as below.

Mode	Position	Ch.	Freq. (MHz)	1g Meas SAR (W/kg)	the ratio of largest to smallest SAR for the original and first repeated measurements
LTE Band 14 (BW: 10MHz)	Back	23330	793.0	0.991	1.005
	Back-repeat	23330	793.0	0.986	
LTE Band 26 Part 90 (BW: 10MHz)	Back	26740	819.0	0.988	1.006
	Back-repeat	26740	819.0	0.982	
LTE Band 41 (BW: 20MHz)	Back	39750	2506.0	0.996	1.005
	Back-repeat	39750	2506.0	0.990	

According to the above ratio result, we don't need to perform a second repeated measurement for these bands.

12. Simultaneous Transmission

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. The device has 2 Tx antennas, WWAN main antenna, Wifi/BT antenna supports 2.4G/5G Wi-Fi and BT. The 2 antennas can always transmit simultaneously. The work mode combination is showed as below table.

Application Simultaneous Transmission information:

NO.	Configuration	Head	Body-worn
1	WWAN+WIFI(2.4g)	Yes	Yes
2	WWAN+WIFI(5g)	Yes	Yes
3	WWAN+BT	Yes	Yes
4	WWAN+NFC	Yes	Yes

12.2 Sum SAR of Simultaneous Transmission

Hotspot(body-worn)

Band	Test Position	RB allocation	Scaled					Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	Σ SAR (W/kg) WWAN + NFC	SPLSR	Remark
			WWAN	WIFI 2.4G	WIFI 5G	Bluetooth	NFC						
LTE Band 41 QPSK (20MHz)	Front	1RB	1.044	0.471	0.260	0.328	0.000	1.515	1.304	1.372	1.044	N/A	N/A
	Back		1.087	0.498	0.293	0.328	0.000	1.585	1.380	1.415	1.087	N/A	N/A
	Left		0.976	/	/	/	/	0.976	0.976	0.976	0.976	N/A	N/A
	Right		/	0.385	0.200	0.328	0.000	0.385	0.200	0.328	0.000	N/A	N/A
	Top		/	0.441	0.227	0.328	0.000	0.441	0.227	0.328	0.000	N/A	N/A
	Bottom		1.005	/	/	/	/	1.005	1.005	1.005	1.005	N/A	N/A
	Front	50%RB	0.979	0.471	0.260	0.328	0.000	1.450	1.239	1.307	0.979	N/A	N/A
	Back		1.027	0.498	0.293	0.328	0.000	1.525	1.320	1.355	1.027	N/A	N/A
	Left		0.918	/	/	/	/	0.918	0.918	0.918	0.918	N/A	N/A
	Right		/	0.385	0.200	0.328	0.000	0.385	0.200	0.328	0.000	N/A	N/A
	Top		/	0.441	0.227	0.328	0.000	0.441	0.227	0.328	0.000	N/A	N/A
	Bottom		0.949	/	/	/	/	0.949	0.949	0.949	0.949	N/A	N/A

13. Test Equipment List

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
E-Field Probe	MVG	SSE2	04/22 EPG0365	2024/02/06	2025/02/05
6 1/2 Digital Multimeter	Keithley	DMM6500	4527164	2023/11/16	2024/11/15
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	161997	2023/11/16	2024/11/15
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2023/11/16	2024/11/15
E-Series Avg. Power Sensor	KEYSIGHT	E9300A	MY55050017	2024/03/20	2025/03/19
EPM Series Power Meter	KEYSIGHT	E4418B	MY41293435	2024/03/20	2025/03/19
10dB Attenuator	MIDWEST MICROWAVE	263-10dB	/	2024/03/20	2025/03/19
Coupler	MERRIMAC	CWM-10R-10.8G	LOT-83391	2024/03/20	2025/03/19
750MHz Validation Dipole	MVG	SID750	07/22 DIP 0G750-655	2023/02/06	2025/02/05
835MHz Validation Dipole	MVG	SID835	07/22 DIP 0G835-656	2023/02/06	2025/02/05
1800MHz Validation Dipole	MVG	SID1800	07/22 DIP 1G800-657	2023/02/06	2025/02/05
1900MHz Validation Dipole	MVG	SID1900	07/22 DIP 1G900-658	2023/02/06	2025/02/05
2450MHz Validation Dipole	MVG	SID2450	07/22 DIP 2G450-662	2023/02/06	2025/02/05
2600MHz Validation Dipole	MVG	SID2600	07/22 DIP 2G600-663	2023/02/06	2025/02/05
5200MHz-5800MHz Validation Dipole	MVG	SID5000	07/22 DIP5G000-670	2023/02/06	2025/02/05
LIMESAR Dielectric Probe	MVG	SCLMP	06/22 OCPG88	2024/02/02	2025/02/01
ENA Series Network Analyzer	Agilent	E5071B	MY42301221	2023/11/16	2024/11/15
Thermometer	Riters	DT-232	21A11	2024/03/20	2025/03/19
Antenna network emulator	MVG	ANTA 74	07/22 ANTA 74	/	/
SAM Phantom	MVG	SAM	07/22 SAM149	/	/
Mobile Phone Positioning System	MVG	MSH 118	07/22 MSH 118	/	/
Mechanical Calibration Kit	PNA	50Ω 35mm 9G	BTF-EM-068	2023/11/16	2024/11/15
Open SAR test software	MVG	/	V5.3.5	/	/
Note: For dipole antennas, BTF has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria: 1. There is no physical damage on the dipole; 2. System validation with specific dipole is within 10% of calibrated value; 3. Return-loss in within 20% of calibrated measurement. 4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.					

ANNEX A Simulating Liquid Verification Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Dielectric performance of tissue simulating liquid									
Frequency (MHz)	ϵ_r		σ (s/m)		Delta (ϵ_r)	Delta (σ)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
750	41.90	41.80	0.89	0.86	0.24%	3.37%	±5%	20.5	6/8/2024
835	41.50	41.41	0.90	0.87	0.22%	3.33%	±5%	20.5	8/8/2024
1800	40.00	39.91	1.40	1.37	0.23%	2.14%	±5%	20.5	10/8/2024
1900	40.00	39.88	1.40	1.41	0.30%	-0.71%	±5%	20.5	12/8/2024
2450	39.20	39.08	1.80	1.81	0.31%	-0.56%	±5%	20.5	13/8/2024
2600	39.00	38.88	1.96	1.97	0.31%	-0.51%	±5%	20.5	14/8/2024
5200	36.00	35.88	4.66	4.70	0.33%	-0.86%	±5%	20.5	15/8/2024
5400	35.80	35.68	4.86	4.90	0.34%	-0.82%	±5%	20.5	15/8/2024
5600	35.50	35.38	5.07	5.11	0.34%	-0.79%	±5%	20.5	15/8/2024
5800	35.30	35.18	5.27	5.31	0.34%	-0.76%	±5%	20.5	15/8/2024

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

ANNEX B System Check Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %(for 10 g).

Frequency (MHz)	Input Power (mW)	10g SAR (W/Kg)	1g SAR (W/Kg)	10g SAR 1W input power normalized (W/Kg)	1g SAR 1W input power normalized (W/Kg)	10g SAR Standard target (1W) (W/Kg)	1g SAR Standard target (1W) (W/Kg)	10g SAR Deviation	1g SAR Deviation
750	16	0.092	0.138	5.80	8.70	5.55	8.49	-4.50%	-2.47%
835	16	0.106	0.163	6.68	10.28	6.22	9.56	-7.40%	-7.53%
1800	16	0.312	0.588	19.68	37.10	20.10	38.40	2.09%	3.39%
1900	16	0.322	0.63	20.32	39.75	20.50	39.70	0.88%	-0.13%
2450	16	0.352	0.793	22.21	50.03	24.00	52.40	7.46%	4.52%
2600	16	0.421	0.866	26.56	54.64	24.60	55.30	-7.97%	1.19%
5200	13	0.288	1.019	22.15	78.38	21.29	73.88	4.05%	6.09%
5400	13	0.299	1.051	23.00	80.84	23.23	81.47	-0.99%	-0.77%
5600	13	0.304	1.084	23.38	83.38	22.64	78.71	3.28%	5.93%
5800	13	0.277	0.981	21.31	75.46	21.50	74.21	-0.90%	1.68%

ANNEX C SAR Dipole Calibrations

Justification for Extended SAR Dipole Calibrations


Referring to KDB 865664D01V01r04, if dipoles are verified in return loss ($\leq -20\text{dB}$, within 20% of prior calibration) and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended. While calibration intervals not exceed 3 years.

Frequency (MHz)	Return loss(dB)		Impedance(Ω)				error range (%)		Results	Date of Measure ment
	measurement	target	measurement		target		Return loss(±20%)	Impedance(±5 Ω)	(P/F)	
			real part	imaginary part	real part	imaginary part				
CW750	-20.92	-25.44	55.89	1.5	55.2	-1.2	-17.77%	3.4	P	2/5/2024
CW835	-29.88	-26.27	52.8	-1.7	52.5	-4.2	13.74%	2.8	P	2/5/2024
CW1800	-24.55	-26.54	52.4	-0.2	52.8	+3.8	-7.50%	4.4	P	2/5/2024
CW1900	-25.67	-23.01	51.9	-5.3	51.0	-7.0	11.56%	2.6	P	2/5/2024
CW2450	-24.37	-21.23	48.3	5.7	49.4	+8.6	14.79%	4.0	P	2/5/2024
CW2600	-20.56	-23.05	57.3	5.7	54.3	+5.5	-10.80%	3.2	P	2/5/2024
CW5200	-21.14	-20.29	58.4	-4.5	58.76	-4.43	4.19%	0.43	P	2/5/2024
CW5400	-27.63	-29.09	57.5	1.2	53.46	+0.61	-5.02%	4.63	P	2/5/2024
CW5600	-33.45	-31.06	51.7	0.7	52.76	-0.45	7.69%	2.21	P	2/5/2024
CW5800	-28.88	-28.48	50.8	0.1	50.12	-3.76	1.40%	4.34	P	2/5/2024


Dipole calibration report data

Self-examination data


750MHz Dipole




Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-25.44	-20	55.2 Ω - 1.2 j Ω




835MHz Dipole




Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
835	-26.27	-20	52.5 Ω - 4.2 j Ω




1800MHz Dipole




Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
1800	-26.54	-20	$52.8 \Omega + 3.8 j\Omega$




1900MHz Dipole




Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
1900	-23.01	-20	$51.0 \Omega - 7.0 j\Omega$




2450MHz Dipole



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
2450	-21.23	-20	$49.4 \Omega + 8.6 j\Omega$



2600MHz Dipole



System Performance Check Data (750 MHz)

System check at 750 MHz

Date of measurement: 6/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	750.000
Relative permittivity (real part)	41.800
Relative permittivity (imaginary part)	21.460
Conductivity (S/m)	0.860

C. SAR Surface and Volume




Maximum location: X=0.00, Y=9.00 ; SAR Peak: 0.20 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.092
SAR 1g (W/Kg)	0.138
Variation (%)	-2.190
Horizontal validation criteria: minimum distance (mm)	9.285
Vertical validation criteria: SAR ratio M2/M1 (%)	64.79%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.287	0.142	0.092	0.073	0.042



F. 3D Image



System Performance Check Data (835 MHz)

System check at 835 MHz

Date of measurement: 8/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	835.000
Relative permittivity (real part)	41.410
Relative permittivity (imaginary part)	19.490
Conductivity (S/m)	0.870

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-3.00 ; SAR Peak: 0.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.106
SAR 1g (W/Kg)	0.163
Variation (%)	-3.390
Horizontal validation criteria: minimum distance (mm)	8.487
Vertical validation criteria: SAR ratio M2/M1 (%)	66.47%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.059	0.173	0.115	0.061	0.072



F. 3D Image



System Performance Check Data (1800 MHz)

System check at 1800 MHz

Date of measurement: 10/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	1800.000
Relative permittivity (real part)	39.910
Relative permittivity (imaginary part)	14.090
Conductivity (S/m)	1.370

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.00 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.312
SAR 1g (W/Kg)	0.588
Variation (%)	-0.250
Horizontal validation criteria: minimum distance (mm)	8.698
Vertical validation criteria: SAR ratio M2/M1 (%)	55.80%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.003	0.638	0.356	0.204	0.127



F. 3D Image



System Performance Check Data (1900 MHz)

System check at 1900 MHz

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	1900.000
Relative permittivity (real part)	39.880
Relative permittivity (imaginary part)	13.380
Conductivity (S/m)	1.410

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.18 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.322
SAR 1g (W/Kg)	0.630
Variation (%)	-2.080
Horizontal validation criteria: minimum distance (mm)	8.699
Vertical validation criteria: SAR ratio M2/M1 (%)	52.96%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.201	0.759	0.402	0.239	0.156



F. 3D Image



System Performance Check Data (2450 MHz)

System check at 2450 MHz

Date of measurement: 13/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=5mm dy=5mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2450.000
Relative permittivity (real part)	39.080
Relative permittivity (imaginary part)	13.340
Conductivity (S/m)	1.810

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.47 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.352
SAR 1g (W/Kg)	0.793
Variation (%)	-2.570
Horizontal validation criteria: minimum distance (mm)	9.787
Vertical validation criteria: SAR ratio M2/M1 (%)	53.00%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.466	0.900	0.477	0.261	0.158



F. 3D Image



System Performance Check Data (2600 MHz)

System check at 2600 MHz

Date of measurement: 14/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.40
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=5mm dy=5mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2600.000
Relative permittivity (real part)	38.880
Relative permittivity (imaginary part)	12.690
Conductivity (S/m)	1.970

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-1.00 ; SAR Peak: 1.02 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.421
SAR 1g (W/Kg)	0.866
Variation (%)	2.980
Horizontal validation criteria: minimum distance (mm)	9.362
Vertical validation criteria: SAR ratio M2/M1 (%)	54.81%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.020	0.655	0.359	0.187	0.091



F. 3D Image



System Performance Check Data (5200 MHz)

System check at 5200 MHz

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5200.000
Relative permittivity (real part)	35.880
Relative permittivity (imaginary part)	16.250
Conductivity (S/m)	4.700

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.288
SAR 1g (W/Kg)	1.019
Variation (%)	-3.400
Horizontal validation criteria: minimum distance (mm)	6.287
Vertical validation criteria: SAR ratio M2/M1 (%)	54.05%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.268	1.889	1.021	0.523	0.266	0.142	0.085	0.060	0.052



F. 3D Image



System Performance Check Data (5400 MHz)

System check at 5400 MHz

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.12
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5400.000
Relative permittivity (real part)	35.680
Relative permittivity (imaginary part)	16.320
Conductivity (S/m)	4.900

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.78 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.299
SAR 1g (W/Kg)	1.051
Variation (%)	-4.610
Horizontal validation criteria: minimum distance (mm)	6.274
Vertical validation criteria: SAR ratio M2/M1 (%)	54.97%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.660	2.141	1.177	0.614	0.317	0.169	0.098	0.065	0.050



F. 3D Image



System Performance Check Data (5600 MHz)

System check at 5600 MHz

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.18
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5600.000
Relative permittivity (real part)	35.380
Relative permittivity (imaginary part)	16.420
Conductivity (S/m)	5.110

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.90 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.304
SAR 1g (W/Kg)	1.084
Variation (%)	-0.190
Horizontal validation criteria: minimum distance (mm)	7.214
Vertical validation criteria: SAR ratio M2/M1 (%)	51.31%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.748	2.093	1.074	0.514	0.243	0.122	0.072	0.056	0.056



F. 3D Image



System Performance Check Data (5800 MHz)

System check at 5800 MHz

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5800.000
Relative permittivity (real part)	35.180
Relative permittivity (imaginary part)	16.480
Conductivity (S/m)	5.310

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 4.17 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.277
SAR 1g (W/Kg)	0.981
Variation (%)	0.490
Horizontal validation criteria: minimum distance (mm)	7.145
Vertical validation criteria: SAR ratio M2/M1 (%)	44.92%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.948	2.037	0.915	0.361	0.135	0.055	0.033	0.037	0.059



F. 3D Image



ANNEX D Test Data

1-Body with back position in dist. 0mm on Channel 190 in GPRS 850+4slots

SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 8/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Channels	Middle (190)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Frequency (MHz)	836.600
Relative permittivity (real part)	41.408
Relative permittivity (imaginary part)	19.481
Conductivity (S/m)	0.871

C. SAR Surface and Volume



Maximum location: X=-7.00, Y=-32.00 ; SAR Peak: 1.04 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.327
SAR 1g (W/Kg)	0.604
Variation (%)	-2.410
Horizontal validation criteria: minimum distance (mm)	9.558
Vertical validation criteria: SAR ratio M2/M1 (%)	53.68%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
--------	------	------	------	-------	-------


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 81 of 124


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

SAR (W/Kg)	1.032	0.639	0.343	0.191	0.117
------------	-------	-------	-------	-------	-------



F. 3D Image



2-Body with back position in dist. 0mm on Channel 661 in GPRS 1900+4slots

SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 10/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.07
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Channels	Middle (661)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Frequency (MHz)	1880.000
Relative permittivity (real part)	39.886
Relative permittivity (imaginary part)	13.522
Conductivity (S/m)	1.402

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.237
SAR 1g (W/Kg)	0.379
Variation (%)	2.470
Horizontal validation criteria: minimum distance (mm)	9.521
Vertical validation criteria: SAR ratio M2/M1 (%)	48.06%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.083	0.387	0.186	0.164	0.081



F. 3D Image



3-Body with back position in dist. 0mm on Channel 9400 in WCDMA Band 2

SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 10/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.07
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 2 (1900)
Channels	Middle (9400)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	1880.000
Relative permittivity (real part)	39.886
Relative permittivity (imaginary part)	13.522
Conductivity (S/m)	1.402

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.318
SAR 1g (W/Kg)	0.526
Variation (%)	-2.080
Horizontal validation criteria: minimum distance (mm)	8.785
Vertical validation criteria: SAR ratio M2/M1 (%)	60.87%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.818	0.552	0.336	0.210	0.140



F. 3D Image



4-Body with back position in dist. 0mm on Channel 4132 in WCDMA Band 5

SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 5 (850)
Channels	Lower (4132)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	826.400
Relative permittivity (real part)	41.449
Relative permittivity (imaginary part)	19.689
Conductivity (S/m)	0.869

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.371
SAR 1g (W/Kg)	0.697
Variation (%)	4.770
Horizontal validation criteria: minimum distance (mm)	8.635
Vertical validation criteria: SAR ratio M2/M1 (%)	43.79%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.554	0.660	0.289	0.195	0.104



F. 3D Image



5-Body with back position in dist. 0mm on Channel 18700 in LTE band 2

SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 10/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.07
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Channels	Lower (18700)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	1860.090
Relative permittivity (real part)	39.892
Relative permittivity (imaginary part)	13.663
Conductivity (S/m)	1.394

C. SAR Surface and Volume




Maximum location: X=-3.00, Y=0.00 ; SAR Peak: 1.64 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.362
SAR 1g (W/Kg)	0.756
Variation (%)	3.570
Horizontal validation criteria: minimum distance (mm)	9.624
Vertical validation criteria: SAR ratio M2/M1 (%)	48.32%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.627	0.774	0.374	0.111	0.082



F. 3D Image



6-Body with back position in dist. 0mm on Channel 20300 in LTE band 4

SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 10/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.79
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 4
Channels	Higher (20300)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	99
RB size	1

B. Permittivity

Frequency (MHz)	1753.910
Relative permittivity (real part)	39.982
Relative permittivity (imaginary part)	14.348
Conductivity (S/m)	1.346

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.267
SAR 1g (W/Kg)	0.636
Variation (%)	0.230
Horizontal validation criteria: minimum distance (mm)	9.514
Vertical validation criteria: SAR ratio M2/M1 (%)	47.46%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.396	0.630	0.299	0.170	0.050



F. 3D Image



7-Body with back position in dist. 0mm on Channel 20450 in LTE band 5

SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 8/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Channels	Lower (20450)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Frequency (MHz)	829.090
Relative permittivity (real part)	41.437
Relative permittivity (imaginary part)	19.627
Conductivity (S/m)	0.869

C. SAR Surface and Volume




Maximum location: X=24.00, Y=1.00 ; SAR Peak: 1.14 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.392
SAR 1g (W/Kg)	0.701
Variation (%)	-3.030
Horizontal validation criteria: minimum distance (mm)	8.957
Vertical validation criteria: SAR ratio M2/M1 (%)	49.38%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.120	0.648	0.320	0.172	0.116



F. 3D Image



8-Body with back position in dist. 0mm on Channel 21100 in LTE band 7

SAR Measurement at LTE band 7 (Body, Validation Plane)

Date of measurement: 14/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.08
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 7
Channels	Middle (21100)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	49
RB size	1

B. Permittivity

Frequency (MHz)	2534.910
Relative permittivity (real part)	38.967
Relative permittivity (imaginary part)	12.972
Conductivity (S/m)	1.901

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.309
SAR 1g (W/Kg)	0.686
Variation (%)	1.340
Horizontal validation criteria: minimum distance (mm)	8.954
Vertical validation criteria: SAR ratio M2/M1 (%)	53.00%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.152	0.717	0.380	0.196	0.100



F. 3D Image



9-Body with back position in dist. 0mm on Channel 23060 in LTE band 12

SAR Measurement at LTE band 12 (Body, Validation Plane)

Date of measurement: 6/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.63
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Channels	Lower (23060)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Frequency (MHz)	704.090
Relative permittivity (real part)	42.011
Relative permittivity (imaginary part)	22.524
Conductivity (S/m)	0.855

C. SAR Surface and Volume




Maximum location: X=-8.00, Y=-9.00 ; SAR Peak: 0.32 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.119
SAR 1g (W/Kg)	0.193
Variation (%)	-4.220
Horizontal validation criteria: minimum distance (mm)	8.625
Vertical validation criteria: SAR ratio M2/M1 (%)	45.66%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.321	0.173	0.079	0.046	0.042



F. 3D Image



10-Body with back position in dist. 0mm on Channel 23330 in LTE band 14

SAR Measurement at LTE band 14 (Body, Validation Plane)

Date of measurement: 7/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.63
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 14
Channels	Middle (23330)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Frequency (MHz)	793.090
Relative permittivity (real part)	41.602
Relative permittivity (imaginary part)	20.461
Conductivity (S/m)	0.865

C. SAR Surface and Volume




Maximum location: X=26.00, Y=-1.00 ; SAR Peak: 1.49 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.577
SAR 1g (W/Kg)	0.991
Variation (%)	2.800
Horizontal validation criteria: minimum distance (mm)	8.925
Vertical validation criteria: SAR ratio M2/M1 (%)	56.87%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.453	0.932	0.530	0.316	0.209



F. 3D Image



11-Body with back position in dist. 0mm on Channel 23800 in LTE band 17

SAR Measurement at LTE band 17 (Body, Validation Plane)

Date of measurement: 6/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.63
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 17
Channels	Higher (23800)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Frequency (MHz)	711.090
Relative permittivity (real part)	41.979
Relative permittivity (imaginary part)	22.362
Conductivity (S/m)	0.855

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-16.00 ; SAR Peak: 0.56 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.067
SAR 1g (W/Kg)	0.139
Variation (%)	-2.340
Horizontal validation criteria: minimum distance (mm)	10.352
Vertical validation criteria: SAR ratio M2/M1 (%)	67.66%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.486	0.201	0.136	0.076	0.031



F. 3D Image



12-Body with back position in dist. 0mm on Channel 26140 in LTE band 25

SAR Measurement at LTE band 25 (Body, Validation Plane)

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.07
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 25
Channels	Lower (26140)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	48
RB size	1

B. Permittivity

Frequency (MHz)	1859.730
Relative permittivity (real part)	39.892
Relative permittivity (imaginary part)	13.666
Conductivity (S/m)	1.394

C. SAR Surface and Volume




Maximum location: X=10.00, Y=-1.00 ; SAR Peak: 0.70 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.261
SAR 1g (W/Kg)	0.447
Variation (%)	2.010
Horizontal validation criteria: minimum distance (mm)	9.625
Vertical validation criteria: SAR ratio M2/M1 (%)	61.78%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.695	0.471	0.291	0.188	0.132



F. 3D Image



13-Body with back position in dist. 0mm on Channel 26740 in LTE band 26 part 90

SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 26
Channels	Lower (26740)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	5
RB size	20

B. Permittivity

Frequency (MHz)	817.200
Relative permittivity (real part)	41.492
Relative permittivity (imaginary part)	19.903
Conductivity (S/m)	0.868

C. SAR Surface and Volume




Maximum location: X=15.00, Y=6.00 ; SAR Peak: 1.57 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.531
SAR 1g (W/Kg)	0.988
Variation (%)	-2.900
Horizontal validation criteria: minimum distance (mm)	11.247
Vertical validation criteria: SAR ratio M2/M1 (%)	52.10%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.534	0.929	0.484	0.262	0.160



F. 3D Image



14-Body with back position in dist. 0mm on Channel 26865 in LTE band 26 part 22

SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 26
Channels	Lower (26865)
Signal	LTE FDD
Cell Bandwidth	15 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Frequency (MHz)	824.840
Relative permittivity (real part)	41.457
Relative permittivity (imaginary part)	19.725
Conductivity (S/m)	0.869

C. SAR Surface and Volume




Maximum location: X=9.00, Y=8.00 ; SAR Peak: 0.97 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.410
SAR 1g (W/Kg)	0.660
Variation (%)	-3.700
Horizontal validation criteria: minimum distance (mm)	9.511
Vertical validation criteria: SAR ratio M2/M1 (%)	57.58%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.064	0.660	0.380	0.249	0.172



F. 3D Image



15-Body with back position in dist. 0mm on Channel 39750 in LTE band 41

SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 14/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.12
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Channels	Lower (39750)
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Frequency (MHz)	2506.090
Relative permittivity (real part)	39.005
Relative permittivity (imaginary part)	13.097
Conductivity (S/m)	1.870

C. SAR Surface and Volume



Maximum location: X=-21.00, Y=8.00 ; SAR Peak: 2.00 W/kg


D. SAR 1g & 10g

SAR 10g (W/Kg)	0.526
SAR 1g (W/Kg)	0.996
Variation (%)	-3.020
Horizontal validation criteria: minimum distance (mm)	8.622


Vertical validation criteria: SAR ratio M2/M1 (%)	47.86%
---	--------

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.937	1.124	0.538	0.255	0.129



F. 3D Image



16-Body with back position in dist. 0mm on Channel 132572 in LTE band 66

SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 10/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.79
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels	Higher (132572)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	1770.090
Relative permittivity (real part)	39.956
Relative permittivity (imaginary part)	14.257
Conductivity (S/m)	1.355

C. SAR Surface and Volume




Maximum location: X=6.00, Y=32.00 ; SAR Peak: 1.00 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.355
SAR 1g (W/Kg)	0.618
Variation (%)	-2.690
Horizontal validation criteria: minimum distance (mm)	8.952
Vertical validation criteria: SAR ratio M2/M1 (%)	55.83%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	3.867	0.618	0.345	0.169	0.085



F. 3D Image



17-Body with back position in dist. 0mm on Channel 1 in IEEE 802.11b ISM

SAR Measurement at IEEE 802.11b ISM (Body, Validation Plane)

Date of measurement: 13/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.12
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11b ISM
Channels	Lower (1)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	2412.000
Relative permittivity (real part)	39.135
Relative permittivity (imaginary part)	13.343
Conductivity (S/m)	1.782

C. SAR Surface and Volume




Maximum location: X=6.00, Y=1.00 ; SAR Peak: 0.96 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.235
SAR 1g (W/Kg)	0.470
Variation (%)	-0.350
Horizontal validation criteria: minimum distance (mm)	9.144
Vertical validation criteria: SAR ratio M2/M1 (%)	49.09%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.945	0.495	0.243	0.108	0.086



F. 3D Image



18-Body with back position in dist. 0mm on Channel 40 in IEEE 802.11ac U-NII

SAR Measurement at IEEE 802.11ac U-NII (Body, Validation Plane)

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.79
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11ac U-NII
Channels	Middle (40)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5200.000
Relative permittivity (real part)	35.880
Relative permittivity (imaginary part)	16.250
Conductivity (S/m)	4.700

C. SAR Surface and Volume




Maximum location: X=-17.00, Y=-24.00 ; SAR Peak: 0.30 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.188
SAR 1g (W/Kg)	0.240
Variation (%)	-0.490
Horizontal validation criteria: minimum distance (mm)	6.599
Vertical validation criteria: SAR ratio M2/M1 (%)	68.98%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.364	0.245	0.169	0.140	0.104



F. 3D Image



19-Body with back position in dist. 0mm on Channel 52 in IEEE 802.11a U-NII

SAR Measurement at IEEE 802.11a U-NII (Body, Validation Plane)

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.79
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a U-NII
Channels	Lower (52)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5260.000
Relative permittivity (real part)	35.820
Relative permittivity (imaginary part)	16.271
Conductivity (S/m)	4.760

C. SAR Surface and Volume




Maximum location: X=8.00, Y=-32.00 ; SAR Peak: 0.20 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.124
SAR 1g (W/Kg)	0.284
Variation (%)	2.790
Horizontal validation criteria: minimum distance (mm)	5.957
Vertical validation criteria: SAR ratio M2/M1 (%)	57.04%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	0.537	0.284	0.162	0.084	0.216	0.073	0.228	0.103	0.142



F. 3D Image



20-Body with back position in dist. 0mm on Channel 102 in IEEE 802.11ac U-NII

SAR Measurement at IEEE 802.11ac U-NII (Body, Validation Plane)

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11ac U-NII
Channels	Lower (102)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5510.000
Relative permittivity (real part)	35.515
Relative permittivity (imaginary part)	16.375
Conductivity (S/m)	5.016

C. SAR Surface and Volume




Maximum location: X=7.00, Y=-9.00 ; SAR Peak: 0.61 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.096
SAR 1g (W/Kg)	0.235
Variation (%)	-1.920
Horizontal validation criteria: minimum distance (mm)	7.145
Vertical validation criteria: SAR ratio M2/M1 (%)	52.05%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	0.651	0.317	0.165	0.081	0.029	0.070	0.023	0.127	0.025



F. 3D Image



21-Body with back position in dist. 0mm on Channel 165 in IEEE 802.11a U-NII

SAR Measurement at IEEE 802.11a U-NII (Body, Validation Plane)

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.60
Area Scan	dx=8mm dy=8mm, Adaptative 1 max
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a U-NII
Channels	Higher (165)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5825.000
Relative permittivity (real part)	35.155
Relative permittivity (imaginary part)	16.488
Conductivity (S/m)	5.335

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.081
SAR 1g (W/Kg)	0.222
Variation (%)	-2.130
Horizontal validation criteria: minimum distance (mm)	6.544
Vertical validation criteria: SAR ratio M2/M1 (%)	58.94%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	0.813	0.358	0.211	0.021	0.003	0.001	0.012	0.024	0.040




F. 3D Image



ANNEX E SAR Test Setup Photos

Reference Photo: simulation liquid depth 15cm



Test positions



Front (dist. 0mm)



Back (dist. 0mm)



Left (dist. 0mm)



Right (dist. 0mm)



ANNEX F EUT External and Internal Photos

Please refer to RF Report.

ANNEX G Calibration Information

Please refer to the document "Calibration.pdf".



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

--END OF REPORT--