HUMAN EXPOSURE STATEMENT

Calculations can be made to predict RF field strength and power density levels around typical RF sources using the general equations (3) and (4) on page 19 of the following FCC document:

"OET Bulletin 65, Edition 97-01 - Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields".

These equations are generally accurate in the far field of an antenna but will over predict power density in the near field, where they could be used for making a "worst case" prediction.

$$S = PG/4\pi R^2$$
 (3)

Where S = power density (in appropriate units, e.g. mW/cm^2)

P = power input to the antenna (in appropriate units e.g. mW)

G = power gain of the antenna in the direction of interest relative to the isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units

e.g. cm)

or,

$$S = EIRP/4\pi R^2$$
 (4)

Where EIRP = Equivalent Isotropically radiated power

MPE GSM 1900

EIRP: 28.79dBm (756.84mW)

Calculated at distance of 20cm

Power density = $756.84 / (4 \text{ x pi x } 20^2)$ = 0.15 mW/cm^2

Calculation for distance at which power density will be 1mW/cm²

Distance = $\sqrt{\{756.84 / (4 \text{ x pi x 1})\}}$ = 7.76cm

Limit:

1mW/cm² is the reference level for general public exposure according to the OET Bulletin 65, Edition 97-01 Table 1.

MPE BT

EIRP: 0.67dBm (1.16mW)

Calculated at distance of 20cm

Power density = $1.16 / (4 \text{ x pi x } 20^2)$ = 0.0002 mW/cm^2

Calculation for distance at which power density will be 1mW/cm²

Distance = $\sqrt{\{1.16 / (4 \text{ x pi x 1})\}}$ = 0.3cm

Limit:

1mW/cm² is the reference level for general public exposure according to the OET Bulletin 65, Edition 97-01 Table 1.