ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY **CFS8DL3250**
SYOSSET, NY 11791 **FCC ID#_____**

DATE: AUG., 23, 2002 TESTED BY: GREG BARBATO APPROVED BY: KEN ADDY

TEST SAMPLE (model): ADEMCO 3250 (RECEIVER)

TEST METHOD: ANSI C63.4-1992
TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fo= 334.3 MHZ
2) DETECTOR = PEAK.
3) FREQUENCY RANGE SCANNED TO 4 GHz.

4) CONVERTED READING = $10^{\left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20}\right]}$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
334.3	V	11.17	1.5	16.0	27.13	-----	27.13	200
668.5	V	4.83	2.1	21.1	25.2	-----	25.2	200
1002.9	H	2.33	2.85	25.2	33.0	-----	33.0	500
1337.2	H	2.67	3.0	28.8	52.9	-----	52.9	500
1671.5	V	3.53	3.7	31.2	83.3.4	-----	83.4	500