



REPORT No. : SZ19030027S01

Annex C Plots of RF System Check

System Check_835MHz_HAC_RF_E

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C;

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface), Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2018.10.29
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Hearing Aid Compatibility Test (81x401x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Maximum value of Total (interpolated) = 122.1 V/m

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 58.52 V/m; Power Drift = -0.00 dB


Applied MIF = 0.00 dB

RF audio interference level = 41.73 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 41.18 dBV/m	Grid 2 M3 41.73 dBV/m	Grid 3 M3 40.65 dBV/m
Grid 4 M4 36.91 dBV/m	Grid 5 M4 37.32 dBV/m	Grid 6 M4 36.48 dBV/m
Grid 7 M3 41.32 dBV/m	Grid 8 M3 41.71 dBV/m	Grid 9 M3 40.64 dBV/m



0 dB = 122.1 V/m = 41.73 dBV/m

System Check_1880MHz_HAC_RF_E

Communication System: UID 0, CW (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.2 °C;

DASY5 Configuration:

- Probe: ER3DV6 - SN2434; ConvF(1, 1, 1); Calibrated: 2018.10.18;
- Sensor-Surface: (Fix Surface), Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn480; Calibrated: 2018.10.29
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Hearing Aid Compatibility Test (81x321x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Maximum value of Total (interpolated) = 97.46 V/m

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 73.51 V/m; Power Drift = -0.01 dB



Applied MIF = 0.00 dB

RF audio interference level = 39.64 dBV/m

Emission category: M2

MIF scaled E-field

Grid 1 M2 39.23 dBV/m	Grid 2 M2 39.64 dBV/m	Grid 3 M2 38.54 dBV/m
Grid 4 M2 39.05 dBV/m	Grid 5 M2 39.56 dBV/m	Grid 6 M2 38.72 dBV/m
Grid 7 M2 39.31 dBV/m	Grid 8 M2 39.78 dBV/m	Grid 9 M2 38.84 dBV/m



0 dB = 97.46 V/m = 39.78 dBV/m