











Lable Location Information

<p> FCC ID: 2A1MC-DMI IC: 21529-DMI HVIN: DMI CMIIT ID: _____ IFT/223/UCS/DG-AUSE/2302/2021 ANATEL: 04366-21-07311 CNCID: C-22455 </p> <p>  HD18000085  TA-2017/2633   204-810003 </p> <p> Endress+Hauser Flowtec (India) Pvt. Ltd. 431136 Aurangabad, India </p>	<p> Picomag Insertion Order code: DMI-AABEA1 Ser-no: 3B01EA91000 Made in India pressure max.: 16 bar / 230 psi temp. medium: -10...+85°C/+14...+185°F temp. environm.: -10...+60°C/+14...+140°F measuring range: 0...10 m/s </p> <p> IP65/67 </p> <p>     </p> <p>  Bluetooth®  IO-Link </p>
--	---










Printing on both sides of the device



RAL 7035

RAL 5012

Label Location Information

<p> FCC ID: 2A1MC-DMI IC: 21529-DMI HVIN: DMI CMIIT ID: _____ IFT/223/UCS/DG-AUSE/2302/2021 ANATEL: 04366-21-07311 CNCID: C-22455 </p> <div>    </div> <p> Endress+Hauser Flowtec AG 4153 Reinach, Switzerland </p>	<p> Insertion Flowmeter Order code: QDMI-AABEA1 Ser-no: 3801EA91000 Made in India pressure max.: 16 bar / 230 psi temp. medium: -10...+85°C/+14...+185°F temp. environm.: -10...+60°C/+14...+140°F measuring range: 0...10 m/s </p> <p>     </p> <p>  Bluetooth®  IO-Link </p>
---	---

Printing on both sides of the device



RAL 7035

RAL 7040