

# 1. RF Exposure Requirements

---

## 1.1 General Information

### Client Information

|                          |                                                                                             |
|--------------------------|---------------------------------------------------------------------------------------------|
| Applicant:               | CE LINK LIMITED                                                                             |
| Address of applicant:    | 22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong Province, China.                |
| Manufacturer:            | Dongguan CE LINK LIMITED                                                                    |
| Address of manufacturer: | 22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong Province, China.                |
| Factory 1#:              | ANFU CE LINK LIMITED                                                                        |
| Address of factory:      | Anfu County Industrial Zone, Ji'an city, Jiangxi Province, P.R. China.                      |
| Factory 2#:              | CE LINK VIET NAM COMPANY LIMITED                                                            |
| Address of factory:      | Lot CNSG04&CNSG06 Van Trung Industrial Zone, Viet Yen district, Bac Giang Province, Vietnam |

### General Description of EUT:

|                   |                                                                                                                                                                       |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:     | Battery Camera                                                                                                                                                        |
| Trade Name:       | CE-LINK                                                                                                                                                               |
| Model No.:        | IPC-14NH-ZT                                                                                                                                                           |
| Adding Model(s):  | /                                                                                                                                                                     |
| Rated Voltage:    | Rechargeable Lithium-ion Battery: 3.6V<br>External power supply/Solar power supply: 5V                                                                                |
| Rated Current:    | External power supply/Solar power supply: 1.0A                                                                                                                        |
| Battery Capacity: | 5200mAh<br>Model:ADS-6RS-06 05050EPCU                                                                                                                                 |
| Power Adapter:    | Input:AC100-240V~50/60Hz<br>Output:5.0V 1.0A 5W<br>T31ZX T31ZX-BURN-TUYA-IPC-14NH-ZT-V1.0.13-20240615.bin                                                             |
| Software Version: | MCU T31ZX_BURN_TUYA_IPC_14NH_ZT_MCU_CS32L010_20240315_V1.0.31.rar<br>WIFI CELINK_BURN_TUYA_IPC_14NH_WIFI_INP1015_20240530_V1.0.33<br>Main IPC-14NS-MAIN R1V0 20240419 |
| Hardware Version: | LED IPC-14NH_LED R1V0 20240228<br>PIR IPC-14NS PIR R1V0 20230506                                                                                                      |
| FCC ID:           | A4X-IPC-14NH                                                                                                                                                          |
| Equipment Type:   | Mobile device                                                                                                                                                         |

**Technical Characteristics of EUT:**

|                       |                                     |
|-----------------------|-------------------------------------|
| Support Standards:    | 802.11b, 802.11g, 802.11n           |
| Frequency Range:      | 2412-2462MHz for 802.11b/g/n(HT20)  |
| RF Output Power:      | 17.76dBm (Conducted)                |
| Type of Modulation:   | CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM |
| Quantity of Channels: | 11 for 802.11b/g/n(HT20)            |
| Channel Separation:   | 5MHz                                |
| Type of Antenna:      | FPC Antenna                         |
| Antenna Gain:         | 2dBi                                |

**1.2 RF Exposure Exemption**

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

**Option A:** FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

**Option B:** FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula.  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

**Option C:** FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters.

| Single RF Sources Subject to Routine Environmental Evaluation |                                      |
|---------------------------------------------------------------|--------------------------------------|
| RF Source frequency (MHz)                                     | Threshold ERP (watts)                |
| 0.3-1.34                                                      | 1,920 R <sup>2</sup>                 |
| 1.34-30                                                       | 3,450 R <sup>2</sup> /f <sup>2</sup> |
| 30-300                                                        | 3.83 R <sup>2</sup>                  |
| 300-1,500                                                     | 0.0128 R <sup>2</sup> f              |
| 1,500-100,000                                                 | 19.2R <sup>2</sup>                   |

**For Multiple RF sources:** FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

### 1.3 Calculated Result

| Radio Access Technology | Prediction Frequency (MHz) | Output Power (dBm) | Antenna Gain (dBi) | Duty Cycle (%) | Tune-Up Time-Averaged Power (dBm) | ERP (dBm) |
|-------------------------|----------------------------|--------------------|--------------------|----------------|-----------------------------------|-----------|
| Wi-Fi                   | 2412                       | 17.76              | 2.0                | 100            | 18.00                             | 17.85     |

| Frequency (MHz) | Option | Min. Distance (cm) | Max. Power (dBm) (mW) |       | Exposure Limit (mW) | Ratio | Result (Pass/Fail) |
|-----------------|--------|--------------------|-----------------------|-------|---------------------|-------|--------------------|
| 2412            | C      | 20.00              | 17.85                 | 60.95 | 768.00              | 0.08  | Pass               |

Note: 1. Time-Averaged Power=Output Power \* Duty Cycle; ERP= Time-Averaged Power+ Antenna gain-2.15dB

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P<sub>th</sub> (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

**Mode for Simultaneous Multi-band Transmission:**

| Radio Access<br>Technology | Ratio 1 | Ratio 2 | Simultaneous<br>Ratio | Limit | Result    |
|----------------------------|---------|---------|-----------------------|-------|-----------|
|                            |         |         |                       |       | Pass/Fail |
| --                         | --      | --      | --                    | --    | --        |

Result: Pass