



RF EXPOSURE EVALUATION REPORT

TEST REPORT

For

MPOW TECHNOLOGY CO., LIMITED

FLAT/RM 605 6/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET MONGKOK KL HONG KONG

FCC ID: 2AMH2-CA166A

Report Type:		Product Type:
Original Report		AUTO-LOCK WIRELESS CAR
		CHARGER MOUNT
Report Number:	RDG210203012	2B
Report Date:	2021-02-09	
	Jacob Kong	Jacob Gong
Reviewed By:	RF Engineer	
Prepared By:	Bay Area Comp 6/F., West Win Building, Shihu Shenzhen, Guai Tel: +86-755-3 Fax: +86-755-3 www.baclcorp.	oliance Laboratories Corp. (Shenzhen) g, Third Phase of Wanli Industrial la Road, Futian Free Trade Zone, ngdong, China 3320018 3320008 com.cn

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "**★**".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Bay Area Compliance Laboratories Corp. (Shenzhen)

TABLE OF CONTENTS

GENERAL INFORMATION	
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) Objective Test Methodology Test Facility	
SYSTEM TEST CONFIGURATION	4
DESCRIPTION OF TEST CONFIGURATION EUT EXERCISE SOFTWARE EQUIPMENT MODIFICATIONS SUPPORT EQUIPMENT LIST AND DETAILS EXTERNAL VO CARLE	
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	6
FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	7
Applicable Standard Block Diagram of Test Setup Test Data	7

GENERAL INFORMATION

Product	AUTO-LOCK WIRELESS CAR CHARGER MOUNT
Tested Model	CA166A
Voltage Range	DC 5V or 9V
Highest operating frequency	110.5-205KHz
Date of Test	2021-02-08
Sample serial number	RDG210203012-SA-S1 (Assigned by BACL, Shenzhen)
Received date	2021-02-03
Sample/EUT Status	Good Condition

Product Description for Equipment under Test (EUT)

Objective

This report is in accordance with FCC part2.1091 Radiofrequency radiation exposure evaluation: mobile devices and KDB 680106 D01 RF Exposure Wireless Charging Apps v03.

Test Methodology

All tests and measurements indicated in this document were performed in accordance SPR-002 Issue 1.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 342867, the FCC Designation No. : CN1221.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0023.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in normal mode.

EUT Exercise Software

No Software was used to test.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Unknown	Wireless load	Unknown	164661
Dongguan Aohai Power Technology Co.,Ltd.	Adapter	A8-501000	A1906034835

External I/O Cable

Cable Description	Length (m)	From Port	То
Unshielded Un-Detachable DC Cable	1.5	Adapter	Charger

SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
FCC§1.1310 & §2.1091	Maximum Permissible Exposure(MPE)	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date	
Nerve Stimulation Exposure						
Narda	Exposure Level Tester	ELT-400	N-0229	2019-11-19	2021-11-18	
Narda	B Field Probe	ELT Probe 100cm ²	M-0666	2019-11-19	2021-11-18	
ETS-Lindgreen	Field Probe	HI-6005	6564158	2019-12-10	2022-12-09	

FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

(B) Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)			
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f ²)	30			
30–300	27.5	0.073	0.2	30			
300-1500	/	/	f/1500	30			
1500-100,000	/	/	1.0	30			

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

f = frequency in MHz; * = Plane-wave equivalent power density;

According with KDB 680106 D01 RF Exposure Wireless Charging Apps v03 clause 3 c)

c) For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

According to KDB 680106 D01 RF Exposure Wireless Charging App v03 clause 5 b)

- b) Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC or a PAG for equipment approved using certification to address RF exposure compliance. However, the responsible party is required to keep a copy of the test report in accordance with KDB 865664 D02. A copy of the test report is to be submitted with the application if the device is approved using certification.
 - (1) Power transfer frequency is less than 1 MHz.
 - (2) Output power from each primary coil is less than or equal to 15 watts.
 - (3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
 - (4) Client device is placed directly in contact with the transmitter.
 - (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
 - (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

RF Exposure Evaluation Report

Block Diagram of Test Setup



Note: 20 cm for Top test.

Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Blaker Zhang on 2021-02-08.

Test mode: Wireless Charging (Full Load)

H-Filed Strength

Frequency	Position	Position	Position	Position	Position	50%	Limit
Range	A	B	C	D	E	Limit	Test
(kHz)	(A/m)	(A/m)	(A/m)	(A/m)	(A/m)	(A/m)	(A/m)
110.5-205	0.211	0.274	0.252	0.250	0.253	0.815	1.63

E-Filed Strength

Frequency	Position	Position	Position	Position	Position	50%	Limit
Range	A	B	C	D	E	Limit	Test
(kHz)	(V/m)	(V/m)	(V/m)	(V/m)	(V/m)	(V/m)	(V/m)
110.5-205	0.191	0.329	0.285	0.273	0.334	307	614

Note: Test with 15cm distance from the center of the probe(s) to the edge of the device, 20 cm for top test.

Result: Pass

Considerations of compliance 680106 D01 RF Exposure Wireless Charging App v03 clause 5 b:

(1) Power transfer frequency is less than 1 MHz.

Yes, the operation frequency is 110.5-205 kHz.

(2) Output power from each primary coil is less than or equal to 15 watts.

Yes, the maximum output power of primary coil is 10 Watts.

(3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

The transfer system includes one coil to detect and allow coupling only between individual pairs of coils.

(4) Client device is placed directly in contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, mobile exposure conditions only

(6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yes, the test result for H and E-filed strength less than 50% of the MPE limit.

***** END OF REPORT *****

RF Exposure Evaluation Report