



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

中国认可
国际互认
检测
TESTING
CNAS L5785

RF Exposure Evaluation Report

Report No.: CQASZ20250300434E-02
Applicant: Shenzhen Inkbird Technology Co., Ltd.
Address of Applicant: Room 1803, Guowei Building, NO.68 Guowei Road, Xianhu Community, Liantang, Luohu District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: WIRELESS BBQ THERMOMETER
Test Model No.: INT-11P, ISVT-11, INT-11X, INT-11PI, INT-11I, INT-11S, INT-12, INT-12E, INT-12I, INT-13, INT-13E, INT-14S, INT-14, INT-21, INT-22, INT-31, INT-31E, INT-32, INT-32E, INT-33, INT-33E
Model No.: INT-11P
Brand Name: INKBIRD
FCC ID: 2AYZD-INT-11P
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2025-03-04
Date of Test: 2025-03-04 to 2025-03-11
Date of Issue: 2025-4-17
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20230701348E-02	Rev.01	Initial report	2023-08-18
CQASZ20250300434E-02	Rev.02	Update report	2025-4-17

Note:

This test report (Ref. No.: CQASZ20250300434E-02)

This report is for Class II Permissive Change only. Updated test data include Restricted frequency band, Conductive emission, Radiation emission. Other test data refer to the original report CQASZ20230701348E-01, The original FCC ID issue date: 08/21/2023.

Only on the basis of the original report Add the series model No., Add White ceramic probe Photographs of EUT. The installation positions of components on the PCB board are different, but it does not affect the RF.

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE	4
4 SAR EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Standard Requirement</i>	6
4.1.2 <i>Limits</i>	6
4.1.3 <i>EUT RF Exposure</i>	8

3 General Information

3.1 Client Information

Applicant:	Shenzhen Inkbird Technology Co., Ltd.
Address of Applicant:	Room 1803, Guowei Building, NO.68 Guowei Road, Xianhu Community, Liantang, Luohu District, Shenzhen, China
Manufacturer:	Shenzhen Inkbird Technology Co., Ltd.
Address of Manufacturer:	Room 1803, Guowei Building, NO.68 Guowei Road, Xianhu Community, Liantang, Luohu District, Shenzhen, China
Factory:	INKBIRD TECH.C.L.
Address of Factory:	6th Floor, Building 713, Pengji Liantang Industrial Area, NO.2 Pengxing Road, Luohu District, Shenzhen, China

3.2 General Description of EUT

Product Name:	WIRELESS BBQ THERMOMETER
Model No.:	INT-11P, ISVT-11, INT-11X, INT-11PI, INT-11I, INT-11S, INT-12, INT-12E, INT-12I, INT-13, INT-13E, INT-14S, INT-14, INT-21, INT-22, INT-31, INT-31E, INT-32, INT-32E, INT-33, INT-33E
Test Model No	INT-11P
Trade Mark:	INKBIRD
EUT Supports Radios application:	Bluetooth mode 2402-2480MHz
Software Version:	REV1.0.3
Hardware Version:	REV1.1.0
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
EUT Power Supply:	Li-ion battery DC 3.8V 1.8mAh

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.1
Modulation Technique:	Non Frequency Hopping Spread Spectrum(NFHSS)
Modulation Type:	GFSK
Number of Channel:	BLE:40
Transfer Rate:	BLE:1Mbps
Test Software of EUT:	SmartSnippets_Toolbox_v5.0.16.3720
Antenna Type:	PCB antenna
Antenna Gain:	4.91dBi


Note:

Model No.: INT-11P, ISVT-11, INT-11X, INT-11PI, INT-11I, INT-11S, INT-12, INT-12E, INT-12I, INT-13, INT-13E, INT-14S, INT-14, INT-21, INT-22, INT-31, INT-31E, INT-32, INT-32E, INT-33, INT-33E.


Their electrical circuit design, layout, components used and internal wiring are identical.

Only the model names, product shapes and product colors are different. The positions of components on the PCBA board are different.

White probe



Black probe



4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

447498 D04 Interim General RF Exposure Guidance v01

3.2. SAR Test Reduction Guidance

SAR test reduction procedures [Glossary] allow using a particular set of test data as representative of other, similar, test conditions. This may be applied for data within different test positions (e.g. body, head, extremity), wireless modes (e.g. Wi-Fi, cellular), and frequency bands. This test reduction process provides for the use of test data for one specific channel, while referencing to those data for demonstrating compliance in other required channels for each test position of an exposure condition, within the operating mode of a frequency band. This is limited specifically to when the reported 1-g or 10-g SAR for the mid-band or highest output power channel meets any of the following conditions.

4.1.2 Limits

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

4.1.3 EUT RF Exposure

Measurement Data

Channel	Conducted Peak Output Power (dBm)	EIRP (dBm)	ERP (dBm)	Maximum tune-up Power (mW)	Exclusion threshold (mW)
Lowest (2402MHz)	-2.85	2.06	-0.09	0.98	3.0
Middle (2440MHz)	-2.19	2.72	0.57	1.14	
Highest (2480MHz)	-3.27	1.64	-0.51	0.89	

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20250300434E-01

*** END OF REPORT ***