849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: sid@timcoengr.com



Test Report

Product Name: 49 MHz WIRELESS R/C TOY - TX

FCC ID: QG33270T49

Applicant:

PLANET TOYS WORLDWIDE LTD.
1107 CHINACHEM GOLDEN PLAZA
77 MODY ROAD, TST EAST
KOWLOON
HONG KONG

Date Receipt: SEPTEMBER 23, 2003

Date Tested: SEPTEMBER 26, 2003

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: sid@timcoengr.com

TABLE OF CONTENTS LIST

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

TEST REPORT CONTAINING:

PAGE	1 TEST EQUIPMENT LIST
PAGE	2TEST PROCEDURE
PAGE	3RADIATION INTERFERENCE TEST DATA
PAGE	4OCCUPIED BANDWIDTH
PAGE	5OCCUPIED BANDWIDTH PLOT

EXHIBITS CONTAINING:

EXHIBIT	1BLOCK DIAGRAM
EXHIBIT	2SCHEMATIC
EXHIBIT	3 INSTRUCTION MANUAL
EXHIBIT	4LABEL SAMPLE
EXHIBIT	5LABEL LOCATION
EXHIBIT	6EXTERNAL PHOTOGRAPHS
EXHIBIT	7INTERNAL PHOTOGRAPHS
EXHIBIT	8CIRCUIT DESCRIPTION
EXHIBIT	9TEST SET UP PHOTOGRAPH

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: sid@timcoengr.com

Equipment List

Device 3/10-Meter	Manufacturer TEI	Model N/A	Serial Number N/A	Cal/Char Date Listed	Due Date 3/26/04
OATS 3-Meter OATS	TEI	N/A	N/A	3/26/01 Listed 1/13/03	1/13/06
Biconnical Antenna	Eaton	94455-1	1057	CAL 3/18/03	3/18/05
Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
Biconnical Antenna	Electro- Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
Blue Tower Quasi-Peak Adapter	НР	85650A	2811A01279	CAL 4/15/03	4/15/05
Blue Tower RF Preselector	HP	85685A	2926A00983	CAL 4/15/03	4/15/05
Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/15/03	4/15/05
LISN	Electro- Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03
LISN	Electro- Metrics	EM-7820	2682	CAL 3/12/03	3/12/05
Log-Periodic Antenna	Eaton	96005	1243	CAL 5/8/03	5/8/05
Log-Periodic	Electro-	EM-6950	632	CHAR 10/15/01	10/15/03
Antenna	Metrics				
Log-Periodic	Electro-	LPA-25	1122	CAL 10/2/01	10/2/03
Antenna	Metrics				
Log-Periodic	Electro- Metrics	LPA-30	409	CAL 3/4/03	3/4/05
Antenna	Metrics HP	8449B	3008A01075	GIIND 1/20/02	1/20/04
Silver Tower Preamplifier	nr	04436	3000A01075	CHAR 1/28/02	1/28/04
Silver Tower	HP	85650A	3303A01844	CAL 10/14/02	10/14/04
Quasi-Peak					
Adapter					
Silver Tower	HP	85685A	2620A00294	CAL 10/14/02	10/14/04
RF					
Preselector		0566D 0-+ 460	2550300064	GRT 10/14/00	10/14/04
Silver Tower Spectrum Analyzer	HP	8566B Opt 462	3552A22064 3638A08608	CAL 10/14/02	10/14/04
Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CHAR 3/4/01	3/4/03
Tan Tower Quasi-Peak Adapter	НР	85650A	3303A01690	CAL 8/31/01	8/31/03
Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 8/31/01	8/31/03
Tan Tower Spectrum Analyzer	НР	8566B Opt 462	3138A07786 3144A20661	CAL 8/31/01	8/31/03

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: sid@timcoengr.com

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a pre-selector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 80°C with a humidity of 76%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: sid@timcoengr.com

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEEDS 80 dBuV/m AT 3M.

OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz 40.0 dBuV/M MEASURED AT 3 METERS

88 - 216 MHz 43.5 dBuV/M 216 - 960 MHz 46.0 dBuV/M ABOVE 960 MHz 54.0 dBuV/M

TEST DATA:

Emission	Meter	Ant.	Coax	Correction	Field	Margin
Frequency	Reading	Polarity	Loss	Factor	Strength	đВ
\mathtt{MHz}	dBuV		đВ	dВ	dBuV/m	
49.86	48.0	H	0.79	11.63	60.42	19.58
49.86	67.3	V	0.79	10.82	78.91	1.09
99.83	21.5	H	0.80	10.50	32.80	10.70
99.83	23.1	V	0.80	11.31	35.21	8.29
149.73	9.9	V	0.90	16.97	27.77	15.73
149.73	10.5	H	0.90	15.78	27.18	16.32
199.63	13.0	V	1.20	17.48	31.68	11.82
199.63	13.1	H	1.20	16.68	30.98	12.52
249.35	9.2	H	1.40	12.54	23.14	22.86
249.35	11.3	V	1.40	12.06	24.76	21.24
299.18	5.0	H	1.40	14.67	21.07	24.93
299.18	12.0	V	1.40	14.00	27.40	18.60
349.02	5.5	H	1.40	14.78	21.68	24.32
349.02	8.2	V	1.40	14.20	23.80	22.20
398.90	5.2	H	1.60	15.96	22.76	23.24
398.90	7.1	V	1.60	15.76	24.46	21.54
449.10	4.3	H	1.60	16.81	22.71	23.29
449.10	9.1	V	1.60	16.23	26.93	19.07
498.60	4.8	H	1.60	18.20	24.60	21.40
498.60	4.9	v	1.60	17.46	23.96	22.04

SAMPLE CALCULATION: FSdBuV/m = MR (dBuV) + ACFdB.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: NAM NGUYEN DATE: 9/26/2003

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: sid@timcoengr.com

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.235

REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the un-modulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPH ON THE NEXT PAGE REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to 10 dB per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: NAM NGUYEN DATE: 9/26/2003

APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com


888.472.2424 F 352.472.2030 email: sid@timcoengr.com

OCCUPIED BANDWIDTH PLOT

NOTES:

PLANET TOYS WORLDWIDE LTD. 49 MHz WIRELESS R/C TOY - TX - FCC ID: QG33270T49

FCC 15.235 Mask



APPLICANT: PLANET TOYS WORLDWIDE LTD.

FCC ID: QG33270T49