



## RF EXPOSURE REPORT

|                                |   |   |
|--------------------------------|---|---|
| <b>Applicant</b>               | : | Guangdong Jsoul Technology Co., LTD   |
| <b>Address of Applicant</b>    | : | Room 2410, No. 13, Dongguan Avenue, Dongcheng Street, Dongguan City, Guangdong Province   |
| <b>Manufacturer</b>            | : | DONGGUAN CITY SENMAI ELECTRON LIMITED   |
| <b>Address of Manufacturer</b> | : | No.5 building ShuiLing Road ZhouwuIndustrial Zone Dongcheng Sub-district Dongguan City  |
| <b>Equipment under Test</b>    | : | Wireless Headset  |
| <b>Model No.</b>               | : | JS06  |
| <b>FCC ID</b>                  | : | 2BKCV-JS06  |
| <b>Test Standard(s)</b>        | : | KDB447498 D01 General RF Exposure Guidance v06  |
| <b>Report No.</b>              | : | DDT-RE24080801-1E03   |
| <b>Issue Date</b>              | : | 2024/09/20  |
| <b>Issue By</b>                | : | Guangdong Dongdian Testing Service Co., Ltd.<br>Unit 2, Building 1, No. 17, Zongbu 2nd Road,<br>Songshan Lake Park, Dongguan, Guangdong, China,<br>523808 |

# REPORT

Table of Contents

1. General Test Information.....5

1.1. Description of EUT .....5

1.2. Accessories of EUT .....5

1.3. Test laboratory .....5

2. RF Exposure evaluation for FCC.....6

2.1. Assessment procedure.....6

2.2. Assess result.....6

## Test Report Declare

|                                |   |  |
|--------------------------------|---|--|
| <b>Applicant</b>               | : | Guangdong Jsoul Technology Co., LTD  |
| <b>Address of Applicant</b>    | : | Room 2410, No. 13, Dongguan Avenue, Dongcheng Street,<br>Dongguan City, Guangdong Province |
| <b>Equipment under Test</b>    | : | Wireless Headset   |
| <b>Model No.</b>               | : | JS06   |
| <b>Manufacturer</b>            | : | DONGGUAN CITY SENMAI ELECTRON LIMITED  |
| <b>Address of Manufacturer</b> | : | No.5 building ShuiLing Road ZhouwuIndustrial Zone Dongcheng<br>Sub-district Dongguan City  |

**Test Standard Used:**

KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

|                         |                     |                      |                       |
|-------------------------|---------------------|----------------------|-----------------------|
| <b>Report No.:</b>      | DDT-RE24080801-1E03 |                      |                       |
| <b>Date of Receipt:</b> | 2024/08/14          | <b>Date of Test:</b> | 2024/08/14~2024/09/20 |

**Prepared By:**

*Ziqin Chen*  
Ziqin Chen/Engineer

**Approved By:**

*Damon Hu*  
Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

| Rev. | Revisions     | Issue Date | Revised By |
|------|---------------|------------|------------|
| ---  | Initial issue | 2024/09/20 |            |
|      |               |            |            |

## 1. General Test Information

### 1.1. Description of EUT

|                            |  |
|----------------------------|--|
| EUT Name                   | : Wireless Headset   |
| Model Number               | : JS06   |
| Difference of model number | : /  |
| EUT Function Description   | : Please reference user manual of this device                      |
| Power Supply               | : DC 5V by an external adapter or DC 3.7V built-in lithium battery |

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

### 1.2. Accessories of EUT

| Accessories | Manufacturer | Model number | Description |
|-------------|--------------|--------------|-------------|
| /           | /            | /            | /           |

### 1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2. RF Exposure evaluation for FCC

### 2.1. Assessment procedure

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### 2.2. Assess result

**Manufacturing Tolerance:**

**BT:**

| Mode                 | Antenna | Frequency [MHz] | Target Power | Tolerance $\pm$ (dBm) |
|----------------------|---------|-----------------|--------------|-----------------------|
| GFSK (Peak)          | Ant1    | 2402            | 2            | 1                     |
|                      |         | 2441            | 2            | 1                     |
|                      |         | 2480            | 1.5          | 1                     |
| $\pi$ /4DQPSK (Peak) | Ant1    | 2402            | 2.5          | 1                     |
|                      |         | 2441            | 2.5          | 1                     |
|                      |         | 2480            | 2.5          | 1                     |
| 8DPSK (Peak)         | Ant1    | 2402            | 3            | 1                     |
|                      |         | 2441            | 3            | 1                     |
|                      |         | 2480            | 2.5          | 1                     |

**BLE:**

| Mode          | Antenna | Frequency [MHz] | Target Power | Tolerance $\pm$ (dBm) |
|---------------|---------|-----------------|--------------|-----------------------|
| GFSK 1M(Peak) | Ant1    | 2402            | 2            | 1                     |
|               |         | 2440            | 2            | 1                     |
|               |         | 2480            | 1.5          | 1                     |

**Estimtion Result:**

Worse case is as below: [2441 MHz, 3.5 dBm, (2.24 mW) output power]

$(2.24/5) \cdot [\sqrt{2.441(\text{GHz})}] = 0.695 < 3.0$  for 1-g SAR

Then SAR evaluation is not required.

-----End Report-----