

FCC PART 15B

TEST REPORT

For

HONG KONG IPRO TECHNOLOGY CO.,LIMITED

12/F 3 LOCKHART ROAD WANCHAI HK

FCC ID: PQ4IPROA29

Report Type: Original Report	Product Type: Mobile Phone
Report Number:	RDG200910003-00B
Report Date:	2020-10-28
Reviewed By:	Ivan Cao Assistant Manager 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

General Information.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
DECLARATIONS.....	4
System Test Configuration.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	6
TEST EQUIPMENT LIST	7
ENVIRONMENTAL CONDITIONS	7
Summary of Test Results.....	8
FCC Part 15B §15.107 – Conducted emissions	9
EUT SETUP	9
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST DATA	10
FCC Part 15B §15.109 – Radiated emissions	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST DATA	14

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Mobile Phone
EUT Model:		A29
Highest Operation Frequency:		2480 MHz
Rated Input Voltage:		DC 3.7V from battery or DC 5V from adapter
Adapter Information	Input:	100Vac-240Vac 50/60Hz 0.2A
	Output:	5.0Vdc 1A
Serial Number:		RDG200910003-RF-S1
EUT Received Date:		2020.09.11
EUT Received Status:		Good

Objective

This report is prepared on behalf of **HONG KONG IPRO TECHNOLOGY CO.,LIMITED** in accordance with FCC Part 15B Part 2, Part J, and Part 15, Subpart A and B of the Federal Communications Commission's rules.

The objective is to determine the compliance of EUT with: FCC Part 15B.

Related Submittal(s)/Grant(s)

FCC Part 22H, 24E PCE submissions with FCC ID: PQ4IPROA29

FCC Part 15C DSS submissions with FCC ID: PQ4IPROA29

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

Measurement Uncertainty

Parameter	Measurement Uncertainty
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~13GHz: 5.23 dB
Temperature	±1℃
Humidity	±5%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Downloading mode.

EUT Exercise Software

No software was used during test.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HP	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	293
DELL	Laptop	PP11L	QDS-BRCM1017

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Serial Cable	Yes	No	1.2	Serial Port of Laptop	Modem
Keyboard Cable	Yes	No	1.5	USB Port of Laptop	Keyboard
Parallel Cable	Yes	No	1.2	Parallel Port of Laptop	Printer
USB Cable	Yes	No	1.2	Laptop	EUT
Earphone Cable	No	No	1.5	EUT	Earphone

Block Diagram of Test Setup



Test Equipment List

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted Emissions					
R&S	LISN	ENV 216	101614	2020-09-12	2021-09-12
R&S	EMI Test Receiver	ESCI	101121	2020-07-07	2021-07-07
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2020-09-05	2021-09-05
R&S	Test Software	EMC32	Version 9.10.00	N/A	N/A
Spurious Emissions					
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2020-05-06	2021-05-06
HP	Amplifier	8447D	2727A05902	2020-09-05	2021-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Agilent	Spectrum Analyzer	E4440A	SG43360054	2020-07-07	2021-07-07
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2020-09-05	2021-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2020-09-05	2021-09-05

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Environmental Conditions

Test Item:	Conducted emissions	Radiated emissions (Below 1GHz)	Radiated emissions (Above 1GHz)
Temperature:	23.7 °C	27.4°C	26 °C
Relative Humidity:	58 %	41%	37%
ATM Pressure:	100.6kPa	100.9kPa	101.1kPa
Tester:	Barry Yang	Jalon Liu	Felix Wang
Test Date:	2020-10-27	2020-10-28	2020-10-26

SUMARY OF TEST RESULTS

FCC Part 15B

Clause	Description of Test	Test Result
§15.107	Conducted emissions	Compliance
§15.109	Radiated emissions	Compliance

FCC PART 15B §15.107 – CONDUCTED EMISSIONS**EUT Setup**

- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter or EUT was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT. The report shall list the six emissions with the smallest margin relative to the limit, unless the margin is greater than 20 dB.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result (QuasiPeak or Average) = Meter Reading + Corr.

Note:

Corr. = Cable loss + Factor of coupling device


The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Result


Test Data

Test Result: Compliance, *Please refer to following table and plots:*

Test mode: Downloading

AC120V, 60 Hz, Line:**Final Result**


Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.263546	29.94	---	61.32	31.38	9.000	L1	9.6
0.470023	---	20.50	46.51	26.01	9.000	L1	9.6
0.470023	24.17	---	56.51	32.34	9.000	L1	9.6
0.494060	---	21.71	46.10	24.39	9.000	L1	9.6
0.516743	24.89	---	56.00	31.11	9.000	L1	9.6
0.543169	---	19.13	46.00	26.87	9.000	L1	9.6
0.683241	19.76	---	56.00	36.24	9.000	L1	9.6
0.805479	---	19.88	46.00	26.12	9.000	L1	9.7
0.805479	23.44	---	56.00	32.56	9.000	L1	9.7
0.829947	---	19.58	46.00	26.42	9.000	L1	9.7
0.829947	23.65	---	56.00	32.35	9.000	L1	9.7
1.023352	---	20.29	46.00	25.71	9.000	L1	9.7

AC120V, 60 Hz, Neutral:**Final Result**


Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.470023	---	18.23	46.51	28.28	9.000	N	9.6
0.494060	---	19.67	46.10	26.43	9.000	N	9.6
0.516743	23.89	---	56.00	32.11	9.000	N	9.6
0.540467	23.90	---	56.00	32.10	9.000	N	9.6
0.540467	---	18.99	46.00	27.01	9.000	N	9.6
0.805479	23.03	---	56.00	32.97	9.000	N	9.6
0.998148	23.59	---	56.00	32.41	9.000	N	9.6
0.998148	---	18.35	46.00	27.65	9.000	N	9.6
1.049193	---	19.25	46.00	26.75	9.000	N	9.6
1.070335	22.50	---	56.00	33.50	9.000	N	9.6
1.159249	19.14	---	56.00	36.86	9.000	N	9.6
2.461795	---	17.56	46.00	28.44	9.000	N	9.6

FCC PART 15B §15.109 – RADIATED EMISSIONS**EUT Setup**

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed at the 3 meters distance, above 1GHz were performed at the 3 meters, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	Reduced video bandwidth	/	AVG

Test Procedure

During the radiated emissions, the adapter was connected to the first AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Meter Reading+ Corrected

Corrected = Antenna Factor + Cable Loss - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Result}$$


Test Data

Please refer to following table and plots:

Test Mode: Downloading


1) 30MHz-1GHz:

Horizontal:

80.0 dB μ V/m

No.	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1	50.3700	50.27	QP	-16.27	34.00	40.00	6.00
2	119.2400	50.90	QP	-12.70	38.20	43.50	5.30
3	179.3800	50.20	QP	-9.80	40.40	43.50	3.10
4	323.9100	42.14	peak	-7.04	35.10	46.00	10.90
5	624.6100	37.85	peak	-0.83	37.02	46.00	8.98
6	879.7200	34.99	peak	2.88	37.87	46.00	8.13


Vertical:




No.	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1	47.4600	46.95	QP	-14.45	32.50	40.00	7.50
2	179.3800	50.30	QP	-9.80	40.50	43.50	3.00
3	323.9100	46.73	peak	-7.04	39.69	46.00	6.31
4	468.4400	43.61	peak	-3.97	39.64	46.00	6.36
5	624.6100	40.60	peak	-0.83	39.77	46.00	6.23
6	879.7200	33.42	peak	2.88	36.30	46.00	9.70

2) 1GHz-13GHz:

Horizontal:

100.0 dB μ V/m

No.	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1	1270.000	41.23	peak	-0.14	41.09	74.00	32.91
2	1270.000	29.16	AVG	-0.14	29.02	54.00	24.98
3	1714.000	43.10	peak	1.92	45.02	74.00	28.98
4	1714.000	31.06	AVG	1.92	32.98	54.00	21.02
5	2158.000	45.82	peak	3.83	49.65	74.00	24.35
6	2158.000	33.67	AVG	3.83	37.50	54.00	16.50
7	2950.000	41.82	peak	6.02	47.84	74.00	26.16
8	2950.000	29.68	AVG	6.02	35.70	54.00	18.30
9	12340.000	36.09	peak	20.43	56.52	74.00	17.48
10	12340.000	24.06	AVG	20.43	44.49	54.00	9.51

Vertical:100.0 dB μ V/m

No.	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1	1594.000	45.12	peak	1.43	46.55	74.00	27.45
2	1594.000	33.05	AVG	1.43	34.48	54.00	19.52
3	1720.000	47.25	peak	1.94	49.19	74.00	24.81
4	1720.000	35.16	AVG	1.94	37.10	54.00	16.90
5	2200.000	39.55	peak	3.84	43.39	74.00	30.61
6	2200.000	27.38	AVG	3.84	31.22	54.00	22.78
7	2482.000	40.21	peak	3.83	44.04	74.00	29.96
8	2482.000	28.13	AVG	3.83	31.96	54.00	22.04
9	9034.000	36.37	peak	17.43	53.80	74.00	20.20
10	9034.000	24.21	AVG	17.43	41.64	54.00	12.36

*****END OF REPORT*****