

FIELD STRENGTH OF SPURIOUS RADIATION
SECTION 2.1053

MEASUREMENT: 5

SECTION 2.1053

FIELD STRENGTH OF SPURIOUS RADIATION

Field strength measurements of radiated spurious emissions were made at a ten meter Open Area Test Site (OATS) maintained by Lucent Technologies Bell Laboratories Global Product Compliance Laboratory in Holmdel, New Jersey. A complete description and full measurement data for the site is on file with the Commission (FCC File 31040/SIT).

The 6 SRFU19s were assembled in a BTS2000 Cabinet. Each SRFU19's were operating on different frequency blocks. The SRFU19's were operating at a RF output level of 27 watts. The combined RF output level for 2 SRFU 19 was 34W. The output terminals (J4) were terminated with 50 ohm load. The spectrum from 10 MHz to the 10th harmonic of the carrier was searched for spurious radiation. Measurements were made according to ANSI C63.4. The test was repeated different combinations of 2 single SRFUs and 2 two SRFUs combined. All emissions more than 20 dB below the specification limit were considered not reportable (Section 2.1057(c)).

The calculated emission levels were found by:

$$\text{Measured level (dB}\mu\text{V)} + \text{Cable Loss(dB)} + \text{Antenna Factor(dB)} = \text{Field Strength (dB}\mu\text{V/m)}$$

Section 24.238 and 2.1053 contains the requirements for the levels of spurious radiation as a function of the level of the unmodulated carrier. The reference level for the unmodulated carrier is calculated as the field produced by an ideal isotropic antenna excited by the transmitter output power according to the following relation taken from Reference Data for Radio Engineers, page 676, 4th edition, IT&T Corp.

$$E = [(30 \cdot P)^{1/2}] / R$$
$$20 \log (E \cdot 10^6) - (43 + 10 \log P) = 71.8 \text{ dB}\mu\text{V/meter}$$

E = Field Intensity in Volts/meter

P = Transmitted Power in Watts

R = Distance in meters = 10 m

RESULTS:

For this particular test, the field strength of any spurious radiation is required to be less than 71.8 dB μ V/meter. Reportable measurements are equal to or greater than 51.8 dB μ V/meter. Over the spectrum investigated, 10 MHz to 10th of the carrier, no reportable spurious emissions were detected. This demonstrates that the "GSM 1900 Transceiver", Single Radio Frequency Unit (SRFU19), with combiner the subject of this application, complies with Sections 2.1053, 24.238 and 2.1057 of the Rules.

