

The University of Michigan
Radiation Laboratory
3228 EECS Building
Ann Arbor, MI 48109-2122
Tel: (734) 764-0500

Measured Radio Frequency Emissions
From

Martec Transmitter
Model: DM-3003

Report No. 415031-124
July 29, 2002


For:
Martec Access Products Inc
240 Sheffield Street
Mountainside, NJ 07092

Contact:
Cathie A Moran
Tel: 908-233-5766
Fax: 908-233-0691
PO: Verbal

Measurements made by:

Valdis V. Liepa
Joseph D. Brunett

Tests supervised by:
Report approved by:


Valdis V. Liepa
Research Scientist

Summary

Tests for compliance with FCC Regulations Part 15, Subpart C, and Industry Canada RSS-210, were performed on Martec model DM-3003. This device is subject to the Rules and Regulations as a Transmitter.

In testing completed on 17-Jul-02, the device tested in the worst case met the allowed FCC specifications for radiated emissions by 1.0 dB (see p. 6). Besides harmonics, there were no other significant spurious emissions found; emissions from digital circuitry were negligible. The conducted emission tests do not apply, since the device is powered from three 1.5 VDC batteries.

1. Introduction

Martec model DM-3003 was tested for compliance with FCC Regulations, Part 15, adopted under Docket 87-389, April 18, 1989, and with Industry Canada RSS-210, Issue 5, November, 2001. The tests were performed at the University of Michigan Radiation Laboratory Willow Run Test Range following the procedures described in ANSI C63.4-1992 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The Site description and attenuation characteristics of the Open Site facility are on file with FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057).

2. Test Procedure and Equipment Used

The pertinent test equipment commonly used in our facility for measurements is listed in Table 2.1 below. The middle column identifies the specific equipment used in these tests.

Table 2.1 Test Equipment.

Test Instrument	Eqpt. Used	Manufacturer/Model
Spectrum Analyzer (0.1-1500 MHz)		Hewlett-Packard, 182T/8558B
Spectrum Analyzer (9kHz-22GHz)	X	Hewlett-Packard 8593A SN: 3107A01358
Spectrum Analyzer (9kHz-26GHz)	X	Hewlett-Packard 8593E, SN: 3412A01131
Spectrum Analyzer (9kHz-26GHz)		Hewlett-Packard 8563E, SN: 3310A01174
Spectrum Analyzer (9kHz-40GHz)		Hewlett-Packard 8564E, SN: 3745A01031
Power Meter		Hewlett-Packard, 432A
Power Meter		Anritsu, ML4803A/MP
Harmonic Mixer (26-40 GHz)		Hewlett-Packard 11970A, SN: 3003A08327
Harmonic Mixer (40-60 GHz)		Hewlett-Packard 11970U, SN: 2332A00500
Harmonic Mixer (75-110 GHz)		Hewlett-Packard 11970W, SN: 2521A00179
Harmonic Mixer (140-220 GHz)		Pacific Millimeter Prod., GMA, SN: 26
S-Band Std. Gain Horn		S/A, Model SGH-2.6
C-Band Std. Gain Horn		University of Michigan, NRL design
XN-Band Std. Gain Horn		University of Michigan, NRL design
X-Band Std. Gain Horn		S/A, Model 12-8.2
X-band horn (8.2- 12.4 GHz)		Narda 640
X-band horn (8.2- 12.4 GHz)		Scientific Atlanta , 12-8.2, SN: 730
K-band horn (18-26.5 GHz)		FXR, Inc., K638KF
Ka-band horn (26.5-40 GHz)		FXR, Inc., U638A
U-band horn (40-60 GHz)		Custom Microwave, HO19
W-band horn(75-110 GHz)		Custom Microwave, HO10
G-band horn (140-220 GHz)		Custom Microwave, HO5R
Bicone Antenna (30-250 MHz)	X	University of Michigan, RLBC-1
Bicone Antenna (200-1000 MHz)	X	University of Michigan, RLBC-2
Dipole Antenna Set (30-1000 MHz)	X	University of Michigan, RLDP-1,-2,-3
Dipole Antenna Set (30-1000 MHz)		EMCO 2131C, SN: 992
Active Rod Antenna (30 Hz-50 MHz)		EMCO 3301B, SN: 3223
Active Loop Antenna (30 Hz-50 MHz)		EMCO 6502, SN:2855
Ridge-horn Antenna (300-5000 MHz)	X	University of Michigan
Amplifier (5-1000 MHz)	X	Avantak, A11-1, A25-1S
Amplifier (5-4500 MHz)	X	Avantak
Amplifier (4.5-13 GHz)		Avantek, AFT-12665
Amplifier (6-16 GHz)		Trek
Amplifier (16-26 GHz)		Avantek
LISN Box		University of Michigan
Signal Generator		Hewlett-Packard 8657B

3. Configuration and Identification of Device Under Test

The DUT is a 303 MHz transmitter, 3 x 2 x 9 inches in size. The carrier is AM modulated and LC stabilized; the modulating circuit is stabilized within the IC. The antenna is integrated into the PCB.

The DUT was designed and manufactured by Martec Access Products Inc., 240 Sheffield Street, Mountainside, NJ 07092. It is identified as:

Martec Access Products Transmitter
Model: DM-3003
S/N or P/N: Proto
FCC ID: JCQ993
IC: 1907A-993

Since the transmitter transmits continuously as long as it detects a vibration, only one transmitter was used in all of the measurements. Note: The DUT mechanically activated and ceases to transmit within 5 seconds of deactivation, see Figure 6.4. See Attachments file in this submittal for specific details about the Safety/Emergency Equipment designation for this device.

3.1 Modifications Made

The R44 resistor on the DUT was changed to 604 ohms from 330 ohms after the device failed to pass the radiated emissions limits.

4. Emission Limits

The DUT tested falls under the category of an Intentional Radiators and the Digital Devices. For FCC, it is subject to Part 15, Subpart C, (Section 15.231), Subpart B, (Section 15.109), and Subpart A, (Section 15.33). For Industry Canada it is subject to RSS-210, (Sections 6.1 and 6.3). The applicable testing frequencies with corresponding emission limits are given in Tables 4.1 and 4.2 below. As a digital device, the DUT is considered as a Class B device.

4.1 Radiated Emission Limits

Table 4.1. Radiated Emission Limits (FCC: 15.33, 15.35, 15.109; IC: RSS-210, 6.2.2(r)).
(Digital Class B)

Freq. (MHz)	E_{lim} (3m) μ V/m	E_{lim} dB(μ V/m)
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
960-2000	500	54.0

Note: Average readings apply above 1000 MHz (1 MHz BW)
Quasi-Peak readings apply to 1000 MHz (120 kHz BW)

Table 4.2. Radiated Emission Limits (FCC: 15.231(b), 15.205(a); IC: RSS-210; 6.1, 6.3).
(Transmitter)

Frequency (MHz)	Fundamental Ave. E_{lim} (3m)		Spurious** Ave. E_{lim} (3m)	
	(μ V/m)	dB (μ V/m)	(μ V/m)	dB (μ V/m)
260.0-470.0	3750-12500*		375-1250	
322-335.4 399.9-410 608-614	Restricted Bands		200	46.0
960-1240 1300-1427 1435-1626.5 1660-1710 1718.9-1722.2 2200-2300	Restricted Bands		500	54.0

* Linear interpolation, formula: $E = -7083 + 41.67 * f$ (MHz)

** Measure up to tenth harmonic; 120 kHz BW up to 1 GHz, 1 MHz BW above 1 GHz

4.3 Conducted Emissions Limits

The conductive emission limits and tests do not apply here, since the DUT is powered by three 1.5 VDC batteries.

5. Radiated Emission Tests and Results

5.1 Anechoic Chamber Measurements

To familiarize with the radiated emission behavior of the DUT, the DUT was first studied and measured in a shielded anechoic chamber. In the chamber there is a set-up similar to that of an outdoor 3-meter site, with a turntable, an antenna mast, and a ground plane. Instrumentation includes spectrum analyzers and other equipment as needed.

In testing for radiated emissions, the transmitter was activated by subtle shaking for repeated pulse emissions. It was placed on the test table flat, on its side, or on its end.

In the chamber we studied and recorded all the emissions using a Bicone antenna up to 300 MHz and a ridged horn antenna above 200 MHz. The measurements made in the chamber below 1 GHz are used for pre-test evaluation only. The measurements made above 1 GHz are used in pre-test evaluation and in the final compliance assessment. We note that for the horn antenna, the antenna pattern is more directive and hence the measurement is essentially that of free space (no ground reflection). Consequently it is not essential to measure the DUT for both antenna polarizations, as long as the DUT is measured on all three of its major axis. In the chamber we also recorded the spectrum and modulation characteristics of the carrier. These data are presented in subsequent sections. We also note that in scanning from 30 MHz to 3.03 GHz using Bicone and the ridge horn antennas, there were no other significant spurious emissions observed.

5.2 Open Site Radiated Emission Tests

After the chamber measurements, the emissions were re-measured on the outdoor 3-meter site at fundamental and harmonics up to 1 GHz using tuned dipoles and/or the high frequency Bicone. Photographs included in this filing show the DUT on the Open Area Test Site (OATS).

5.3 Computations and Results for Radiated Emissions

To convert the dBm's measured on the spectrum analyzer to dB(μ V/m), we use expression

$$E_3(\text{dB}\mu\text{V/m}) = 107 + P_R + K_A - K_G$$

where P_R = power recorded on spectrum analyzer, dB, measured at 3m
 K_A = antenna factor, dB/m
 K_G = pre-amplifier gain, including cable loss, dB

When presenting the data, at each frequency the highest measured emission under all of the possible orientations is given. Computations and results are given in Table 5.1. There we see that the DUT meets the limit by 1.0 dB.

5.4 Conducted Emission Tests

These tests do not apply, since the DUT is powered from three 1.5 VDC batteries.

6. Other Measurements

6.1 Correction for Pulse Operation

When the transmitter is activated by its vibration sensing circuit, it transmits ASK encoded words, with a period of 285ms so long as the vibration is detected. The code in the worst case consists of two wake-up pulses, 1.55 ms in length, followed by 52 Manchester encoded bits. Each bit has a maximum length of 0.5 ms. See Figure 6.1. Thus, the duty factor is

$$K_E = (2 \times 1.55 \text{ ms} + 52 \times 0.5 \text{ ms}) / 100 \text{ ms} = 0.291 \text{ or } -10.7 \text{ dB.}$$

6.2 Emission Spectrum

Using the ridge-horn antenna and DUT placed in its aperture, emission spectrum was recorded and is shown in Figure 6.2.

6.3 Bandwidth of the Emission Spectrum

The measured spectrum of the signal is shown in Figure 6.3. The allowed (-20 dB) bandwidth is 0.25% of 303MHz, or 757.5 KHz. From the plot we see that the -20 dB bandwidth is 81.8 kHz, and the center frequency is 303.0 MHz.

6.4 Effect of Supply Voltage Variation

The DUT has been designed to be powered by three 1.5 VDC battery. For this test, the battery was replaced by a laboratory variable power supply. Relative power radiated was measured at the fundamental as the voltage was varied from 3.5 to 6 volts. The emission variation is shown in Figure 6.5.

6.5 Input Voltage at Battery Terminals

Batteries:	before testing	$V_{oc} = 4.91 \text{ V}$
	after testing	$V_{oc} = 4.52 \text{ V}$
Ave. current from batteries		$I = 18 \text{ mA (pulsed)}$

Table 5.1 Highest Emissions Measured

Radiated Emission - RF											Martec Doorminder; FCC/IC	
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dBµV/m	E3lim dBµV/m	Pass dB	Comments	
1	303.0	Dip	H	-20.3	Pk	18.6	20.6	73.9	74.9	1.0	flat	
2	303.0	Dip	V	-23.4	Pk	18.6	20.6	70.8	74.9	4.1	end	
3	606.0	Dip	H	-58.7	Pk	24.9	17.3	45.1	54.9	9.8	flat	
4	606.0	Dip	V	-63.6	Pk	24.9	17.3	40.2	54.9	14.7	end	
5	909.0	Dip	H	-56.3	Pk	28.5	15.0	53.4	54.9	1.5	flat	
6	909.0	Dip	V	-59.4	Pk	28.5	15.0	50.3	54.9	4.6	end	
7	1212.0	Horn	H	-42.6	Pk	20.5	28.0	46.1	54.0	7.9	flat	
8	1515.0	Horn	H	-52.2	Pk	21.3	28.0	37.3	54.0	16.7	flat	
9	1818.0	Horn	H	-57.4	Pk	22.1	28.0	32.9	54.9	22.0	flat	
10	2121.0	Horn	H	-62.8	Pk	22.8	28.1	28.1	54.9	26.8	flat	
11	2424.0	Horn	H	-61.7	Pk	23.6	28.3	29.8	54.9	25.1	flat	
12	2727.0	Horn	H	-64.7	Pk	24.5	28.2	27.8	54.0	26.2	flat	
13	3030.0	Horn	H	-64.8	Pk	25.4	27.9	28.9	54.9	26.0	flat, noise	
14												
15												
16												
17												
18	* Includes 10.7 dB duty factor											
19												
20												
21												
22	Digital emissions more than 20 dB below FCC/IC Class B Limit.											
23												
24												
25												
26												
27												

Conducted Emissions							
#	Freq. MHz	Line Side	Det. Used	Vtest dBµV	Vlim dBµV	Pass dB	Comments
							Not applicable

Meas. 5/29/2002; U of Mich.






Figure 6.1. Transmissions modulation characteristics: (top) complete transmission, (center) expanded bit, (bottom) expanded period.




Figure 6.2. Emission spectrum of the DUT (pulsed emission).
The amplitudes are only indicative (not calibrated).




Figure 6.3. Measured bandwidth of the DUT (pulsed emission).
"locked in" mode.




Figure 6.4. Transmitter 5 sec. transmission limit verification




Figure 6.5. Relative emission at 303.0 MHz vs. supply voltage (pulsed emission).