



Full

TEST REPORT

No. I18D00164-SRD01

For

Client : Gemalto M2M GmbH

Production : EHS6

Model Name : EHS6

FCC ID : QIPEHS6

IC ID : 7830A-EHS6

Hardware Version: B2.1

Software Version: 04.003

Issued date: 2019-01-24

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

Note: ANSI/TIA-603-E and KDB 971168 D01 has not been approved by A2LA.

Test Laboratory:

ECIT Shanghai, East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: welcome@ecit.org.cn

Revision Version

Report Number	Revision	Date	Memo
I18D00164-SRD01	00	2019-01-24	Initial creation of test report

CONTENTS

1.	TEST LABORATORY	5
1.1.	TESTING LOCATION	5
1.2.	TESTING ENVIRONMENT	5
1.3.	PROJECT DATA	5
1.4.	SIGNATURE	5
2.	CLIENT INFORMATION	6
2.1.	APPLICANT INFORMATION	6
2.2.	MANUFACTURER INFORMATION	6
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1.	ABOUT EUT	7
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
3.4.	STATEMENTS.....	7
4.	REFERENCE DOCUMENTS.....	8
4.1.	REFERENCE DOCUMENTS FOR TESTING	8
5.	SUMMARY OF TEST RESULTS.....	9
6.	TEST EQUIPMENT UTILIZED	10
7.	TEST ENVIRONMENT	12
8.	MEASUREMENT UNCERTAINTY	13
ANNEX A.	MEASUREMENT RESULTS.....	14
ANNEX A.1.	OUTPUT POWER	14
ANNEX A.2.	PEAK-TO-AVERAGE POWER RATIO	16
ANNEX A.3.	OCCUPIED BANDWIDTH	18
ANNEX A.4.	-26DB EMISSION BANDWIDTH	30
ANNEX A.5.	BAND EDGE AT ANTENNA TERMINALS	42

ANNEX A.6. FREQUENCY STABILITY	49
ANNEX A.7. CONDUCTED SPURIOUS EMISSION.....	54
ANNEX A.8. RADIATED.....	69
ANNEX A.9. RECEIVER RADIATION EMISSION.....	86
ANNEX B. DEVIATIONS FROM PRESCRIBED TEST METHODS.....	88

1. Test Laboratory

1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301
FCC registration No	958356
IC registration No	10766A-1

1.2. Testing Environment

Normal Temperature:	15-35°C
Extreme Temperature:	-30/+85°C
Relative Humidity:	20-75%


1.3. Project data

Project Leader:	Zhou Yan
Testing Start Date:	2018-08-10
Testing End Date:	2019-01-24

1.4. Signature



Yang Dejun
(Prepared this test report)



Shi Hongqi
(Reviewed this test report)



Zheng Zhongbin
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Gemalto M2M GmbH
Address: Gemalto M2M GmbH, Werinherstrasse 81 81541 München, Germany
Postcode: /
Telephone: +86 1059373423

2.2. Manufacturer Information

Company Name: Gemalto M2M GmbH
Address: Gemalto M2M GmbH, Werinherstrasse 81 81541 München, Germany
Postcode: /
Telephone: +86 1059373423

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description	EHS6
Model name	EHS6
FCC ID	QIPEHS6
IC ID	7830A-EHS6
Frequency	GSM850/900/1800/1900; WCDMA Band I/II/V/VIII
Extreme Temperature	-30/+85°C
Nominal Voltage	3.8V
Extreme High Voltage	4.5V
Extreme Low Voltage	3.3V

Note: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT used during the test

EUT ID*	Model Name	SN or IMEI	HW Version	SW Version	Date of receipt
N02	EHS6	NA	B2.1	04.003	2018-08-09
N01	EHS6	NA	B2.1	04.003	2018-08-09

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	RF cable	---
AE2	Dummy Battery	---

*AE ID: is used to identify the test sample in the lab internally.

3.4. Statements

The EHS6 , supporting GPRS/EDGE/WCDMA , manufactured by Gemalto M2M GmbH , which is a new product for testing.

ECIT has verified that the compliance of the tested device specified in section 5 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 5 of this test report.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	2018/10/01
FCC Part 22	PUBLIC MOBILE SERVICES	2018/10/01
FCC Part 2	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS	2018/10/01
ANSI-TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
ANSI C63.26	American National Standard of Procedures for Compliance Testing of Licensed Transmitters Used in Licensed Radio	2015
KDB 971168 D01	Measurement Guidance for Certification of Licensed Digital Transmitters	v03r01
RSS-Gen	RSS-Gen —General Requirements for Compliance of Radio Apparatus	2018/4
RSS-132	Cellular Telephone Systems Operating in the Bands 824-849 MHz and 869-894 MHz	2013/1
RSS-133	2 GHz Personal Communications Services	2018/1

5. SUMMARY OF TEST RESULTS

Item	Test items	FCC rules	IC rules	result
1	Output Power	2.1046/22.913(a)/24.23	RSS-132 5.4/ RSS-133 6.4	Pass
2	Peak-to-Average	24.232(d)	RSS-132 5.4/ RSS-133 6.4	Pass
3	99%Occupied	2.1049(h)(i)/ 22.917(b)	RSS-Gen 4.6	Pass
4	-26dB Emission	22.917(b)/§24.238(b)	RSS-Gen 4.6	Pass
5	Band Edge at antenna terminals	22.917(a)/24.238(a)	RSS-132 5.5/ RSS-133 6.5	Pass
6	Frequency stability	2.1055/24.235	RSS-132 5.3/ RSS-133 6.3	Pass
7	Conducted Spurious mission	2.1053/22.917(a)/24.23	RSS-132 5.5/ RSS-133 6.5	Pass
8	Emission Limit	2.1051/22.917/24.238/	RSS-132 5.5/ RSS-133 6.5	Pass
9	Receiver Radiated Emissions	/	RSS-132 5.6/ RSS-133 6.6	Pass

6. Test Equipment Utilized

Climate chamber

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Climate chamber	SH-641	92012011	ESPEC	2017-12-25	2 Year

Radiated emission test system

The test equipment and ancillaries used are as follows.

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Universal Radio Communication Tester	CMU200	123123	R&S	2018-05-11	1 Year
2	EMI Test Receiver	ESU40	100307	R&S	2018-05-11	1 Year
3	TRILOG Broadband Antenna	VULB9163	VULB9163-515	Schwarzbeck	2017-02-25	3 Year
4	Double-ridged Waveguide Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year
5	2-Line V-Network	ENV216	101380	R&S	2018-05-11	1 Year
6	Substitution Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year
7	RF Signal Generator	SMF100A	102314	R&S	2018-05-11	1 Year
8	Substitution Antenna	VUBA9117	9117-266	Schwarzbeck	2017-11-18	3 Year
9	Amplifier	SCU08	10146	R&S	2018-05-11	1 Year

Conducted test system

No.	Name	Type	SN	Manufacture	Calibration date	Cal.interval
1	Spectrum Analyzer	FSQ26	101096	R&S	2018-05-11	1 Year
2	Universal Radio Communicat	CMU200	123124	R&S	2018-05-11	1 Year
3	DC Power Supply	ZUP60-1 4	LOC-220Z006 -0007	TDL-Lambda	2018-05-11	1 Year

7. Test Environment

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Ground system resistance	< 0.5 Ω

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.9 meters×10.9 meters×5.4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
VSWR	Between 0 and 6 dB, from 1GHz to 18GHz
Site Attenuation Deviation	Between -4 and 4 dB, 30MHz to 1GHz
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

8. Measurement Uncertainty

Measurement uncertainty for all the testing in this report are within the limit specified in ECIT documents .

The detailed measurement uncertainty is defined in ECIT documents.

Measurement Items	Range	Confidence Level	Calculated Uncertainty
Maximum Peak Output Power	30MHz-3600MHz	95%	$\pm 0.544\text{dB}$
EBW and VBW	30MHz-3600MHz	95%	$\pm 62.04\text{Hz}$
Transmitter Spurious Emission-Conducted	30MHz-2GHz	95%	$\pm 0.90\text{dB}$
Transmitter Spurious Emission-Conducted	2GHz-3.6GHz	95%	$\pm 0.88\text{dB}$
Transmitter Spurious Emission-Conducted	3.6GHz-8GHz	95%	$\pm 0.96\text{dB}$
Transmitter Spurious Emission-Conducted	8GHz-20GHz	95%	$\pm 0.94\text{dB}$
Transmitter Spurious Emission-Radiated	9KHz-30MHz	95%	$\pm 5.66\text{dB}$
Transmitter Spurious Emission-Radiated	30MHz-1000MHz	95%	$\pm 4.98\text{dB}$
Transmitter Spurious Emission-Radiated	1000MHz -18000MHz	95%	$\pm 5.06\text{dB}$
Transmitter Spurious Emission-Radiated	18000MHz -40000MHz	95%	$\pm 5.20\text{dB}$
Frequency stability	1MHz-16GHz	95%	$\pm 62.04\text{Hz}$

ANNEX A. MEASUREMENT RESULTS

ANNEX A.1. OUTPUT POWER

A.1.1. Summary

During the process of testing, the EUT was controlled Rhode & Schwarz Digital Radio. Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2. Conducted

A.1.2.1. Method of Measurements

Method of measurements please refer to KDB971168 D01 v03 clause 5.

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSQ(peak).

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.2MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V. (bottom, middle and top of operational frequency range).

A.1.2.2 Test procedures:

1. The transmitter output port was connected to base station.
2. Set the EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

A.1.2.3 Limit:

22.913(a) Mobile stations are limited to 7watts.

24.232(c) Mobile and portable stations are limited to 2 watts.

A.1.2.4 Test Procedure:

The transmitter output power was connected to calibrated attenuator, the other end of which was connected to signal analyzer. Transmitter output power was read off the power in dBm. The power outputs at the transmitter antenna port was determined by adding the value of attenuator to the signal analyzer reading.

A.1.2.5 GSM Test Condition:

RBW	VBW	Sweep time	Span
-----	-----	------------	------

3MHz	10MHz	Auto	50MHz
------	-------	------	-------

A.1.2.6 WCDMA Test Condition:

RBW	VBW	Sweep time	Span
10MHz	30MHz	Auto	50MHz

A.1.2.7 Measurement results:

GPRS 850 (GMSK 1 Slot)	
Channel/fc(MHz)	AV power (dBm)
Mid 189/836.4	33.92
Low 128/824.2	33.44
High 251/848.8	32.91
EDGE 850 (8PSK 1 Slot)	
Channel/fc(MHz)	AV power (dBm)
Mid 189/836.4	27.29
Low 128/824.2	27.78
High 251/848.8	27.42

GPRS 1900 (GMSK 1 Slot)	
Channel/fc(MHz)	AV power (dBm)
Mid 661/1880	29.8
Low 512/1850.2	30.05
High 810/1909.8	29.19
EDGE 1900 (8PSK 1 Slot)	
Channel/fc(MHz)	AV power (dBm)
Mid 661/1880	25.47
Low 512/1850.2	25.68
High 810/1909.8	25.17

WCDMA II	
Channel/fc(MHz)	AV power (dBm)
Mid 9400 /1880	23.99
Low 9262/1852.4	24.03
High 9538/1907.6	23.82
WCDMA BAND V	
Channel/fc(MHz)	AV power (dBm)
Mid 4183/836.6	24.17
Low 4132/826.4	24.2
High 4233/846.6	24.15

Conclusion: PASS

ANNEX A.2. Peak-to-Average Power Ratio

Method of test measurements please refer to KDB971168 D01 v03 clause 5.7.

A.2.1 PAPR Limit

The peak-to-average power ratio (PAPR) of the transmission may not exceed 13dB

A.2.2 Test procedures

- The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- Select the spectrum analyzer CCDF function.
 - Set $RBW \geq$ signal's occupied bandwidth.
 - Set the number of counts to a value that stabilizes the measured CCDF curve;
 - Sweep time \geq 1s.
- Record the maximum PAPR level associated with a probability of 0.1%.

A.2.3 Test results:

GPRS850			
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
PAPR(dB)	6.17	6.45	6.56
EDGE850			

Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
PAPR(dB)	6.47	6.43	6.54

GPRS1900			
Channel	512	661	810
Frequency (MHz)	1850.2	1880	1909.8
PAPR(dB)	8.48	8.41	8.41
EDGE1900			
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
PAPR(dB)	8.65	8.65	8.65

WCDMA Band II			
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880	1907.6
PAPR(dB)	3.43	3.25	3.17
WCDMA Band V			
Channel	4132	4183	4233
Frequency (MHz)	826.4	836.4	846.6
PAPR(dB)	3.43	3.26	3.21

Conclusion: PASS

ANNEX A.3. Occupied Bandwidth

Method of test please refer to KDB971168 D01 v03 clause 4.0.

A.3.1. Occupied Bandwidth

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of GSM850, PCS1900, WCDMA BANDII and WCDMA BANDV.

A.3.2 Test Procedure:


1. The EUT output RF connector was connected with a short cable to the signal analyzer.
2. RBW was set to about 1% of emission BW, VBW \geq 3 times RBW,.
3. 99% bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

A.3.3 Test result:

GPRS850		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)
Mid 189	836.4	238.782
Low 128	824.2	240.385
High 251	848.8	243.59
EDGE850		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)
Mid 189	836.4	243.59
Low 128	824.2	250
High 251	848.8	245.192


Conclusion: PASS

GPRS 850




Date: 14.AUG.2018 04:44:12

Channel 189-Occupied Bandwidth (99%)



Date: 14.AUG.2018 04:44:59


Channel 128-Occupied Bandwidth (99%)



Date: 14.AUG.2018 04:45:46


Channel 251-Occupied Bandwidth (99%)

EDGE 850




Date: 14.AUG.2018 04:49:47

Channel 189-Occupied Bandwidth (99%)



Date: 14.AUG.2018 04:50:34

Channel 128-Occupied Bandwidth (99%)



Date: 14.AUG.2018 04:51:21


Channel 251-Occupied Bandwidth (99%)

GPRS1900		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)
Mid 661	1880	245.192
Low 512	1850.2	243.59

High 810	1909.8	246.795
EDGE1900		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)
Mid 661	1880	248.397
Low 512	1850.2	248.397
High 810	1909.8	248.397


Conclusion: PASS

GPRS 1900




Date: 14.AUG.2018 08:42:09

Channel 661-Occupied Bandwidth



Date: 14.AUG.2018 08:43:10


Channel 512-Occupied Bandwidth



Date: 14.AUG.2018 08:43:58


Channel 810-Occupied Bandwidth

EDGE 1900




Date: 14.AUG.2018 08:46:02

Channel 661-Occupied Bandwidth



Date: 14.AUG.2018 08:46:54

Channel 512-Occupied Bandwidth




Date: 14.AUG.2018 08:47:48

Channel 810-Occupied Bandwidth


WCDMA BAND II		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(MHz)
Mid 9400	1880	4.071
Low 9262	1852.4	4.071
High 9538	1907.6	4.071

Conclusion: PASS
WCDMA BAND II




Date: 14.AUG.2018 07:28:36

Channel 9400-Occupied Bandwidth



Date: 14.AUG.2018 07:29:38

Channel 9262-Occupied Bandwidth




Date: 14.AUG.2018 07:30:40

Channel 9538-Occupied Bandwidth


WCDMA BAND V		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(MHz)
Mid 4183	836.6	4.071
Low 4132	826.4	4.054
High 4233	846.6	4.071

Conclusion: PASS

WCDMA BAND V




Channel 4183-Occupied Bandwidth



Date: 14.AUG.2018 07:32:56

Channel 4132-Occupied Bandwidth



Date: 14.AUG.2018 07:34:00

Channel 4233-Occupied Bandwidth

ANNEX A.4. -26dB Emission Bandwidth

Method of test please refer to KDB971168 D01 v03 clause 4.0.

A.4.1. -26dB Emission Bandwidth

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of GSM850, PCS1900, WCDMA BANDII and WCDMA BANDV.

A.4.2 Test Procedure:

1. The EUT output RF connector was connected with a short cable to the signal analyzer.
2. RBW was set to about 1% of emission BW, VBW \geq 3 times RBW,.
3. 26dB bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

A.4.3 Measurement methods:

For GSM: signal analyzer setting as: RBW=3KHz;VBW=10KHz;Span=1MHz.


For WCDMA: signal analyzer setting as: RBW=50KHz;VBW=200KHz;Span=10MHz.

A.4.4 Test results:

GPRS 850		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 189	836.4	315.705
Low 128	824.2	312.5
High 251	848.8	320.513
EDGE 850		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 189	836.4	306.09
Low 128	824.2	315.705
High 251	848.8	304.487


Conclusion: PASS

GPRS 850




Date: 14.AUG.2018 05:01:54

Channel 189- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 05:02:24


Channel 128- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 05:02:53


Channel 251- Emission Bandwidth (-26dBc BW)

EDGE 850




Date: 14.AUG.2018 05:05:16

Channel 189- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 05:05:45

Channel 128- Emission Bandwidth (-26dBc BW)




Date: 14.AUG.2018 05:06:14

Channel 251- Emission Bandwidth (-26dBc BW)


GPRS1900		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 661	1880	312.5
Low 512	1850.2	307.692
High 810	1909.8	307.692
EDGE1900		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 661	1880	309.295
Low 512	1850.2	304.487
High 810	1909.8	302.885

Conclusion: PASS

GPRS 1900




Channel 661- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 05:09:44


Channel 512- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 05:10:12


Channel 810- Emission Bandwidth (-26dBc BW)

EDGE 1900




Date: 14.AUG.2018 05:12:34

Channel 661- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 05:13:02

Channel512- Emission Bandwidth (-26dBc BW)




Date: 14.AUG.2018 05:13:30

Channel 810- Emission Bandwidth (-26dBc BW)

WCDMA BAND II		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 9400	1880	4.583
Low 9262	1852.4	4.615
High 9538	1907.6	4.599


Conclusion: PASS

WCDMA BAND II




Date: 14.AUG.2018 07:36:44

Channel 9400- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 07:37:15

Channel 9262- Emission Bandwidth (-26dBc BW)




Channel 9538- Emission Bandwidth (-26dBc BW)

WCDMA BAND V		
Test channel	Frequency (MHz)	-26dBc Emission Bandwidth(MHz)
Mid 4183	836.6	4.631
Low 4132	826.4	4.599
High 4233	846.6	4.615


Conclusion: PASS

WCDMA BAND V




Date: 14.AUG.2018 07:38:26

Channel 4183- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 07:38:58

Channel4132- Emission Bandwidth (-26dBc BW)



Date: 14.AUG.2018 07:39:30

Channel 4233- Emission Bandwidth (-26dBc BW)

ANNEX A.5. Band Edge at antenna terminals

Method of test measurements please refer to KDB971168 D01 v03 clause 6


A.5.1 Limit:

The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specification in the instruction manual and/or alignment procedure, shall not be less than $43+10\log(\text{Mean power in watts})$ dBc below the mean power output outside a license's frequency block(-13dBm).

A.5.2 Test procedure:


1. The RF output of the transceiver was connected to a signal analyzer through appropriate attenuation.
2. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.
3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band
4. The limit line is derived from $43+10\log(P)$ Db below the transmitter power P(Watts)
 $=P(W)-[43+10\log(P)](Db)$
 $=[30+10\log(P)](dBm)-[43+10\log(P)](Db)$
 $=-13dBm$

GPRS 850



Date: 24.JAN.2019 08:28:40


Channel 128- LOW BAND EDGE BLOCK



Date: 24.JAN.2019 08:29:28


Channel 251- HIGH BAND EDGE BLOCK

EDGE 850



Date: 24.JAN.2019 08:32:41


Channel 128- LOW BAND EDGE BLOCK



Date: 24.JAN.2019 08:33:29


Channel 251- HIGH BAND EDGE BLOCK

GPRS 1900



Date: 24.JAN.2019 08:37:14


Channel 512- LOW BAND EDGE BLOCK



Date: 24.JAN.2019 08:38:02


Channel 810- HIGH BAND EDGE BLOCK

EDGE 1900



Date: 24.JAN.2019 08:40:57

Channel 512- LOW BAND EDGE BLOCK




Date: 24.JAN.2019 08:41:46

Channel 810- HIGH BAND EDGE BLOCK

WCDMA BAND II


East China Institute of Telecommunications
TEL: +86 21 63843300 FAX: +86 21 63843301

Page Number : 46 of 88
Report Issued Date : Jan.24.2019



Date: 24.JAN.2019 08:20:28

Channel 9262- LOW BAND EDGE BLOCK



Date: 24.JAN.2019 08:21:23


Channel 9538- HIGH BAND EDGE BLOCK

Conclusion: PASS

WCDMA BAND V


East China Institute of Telecommunications
TEL: +86 21 63843300 FAX: +86 21 63843301

Page Number : 47 of 88
Report Issued Date : Jan.24.2019



Date: 24.JAN.2019 08:22:25

Channel 4132- LOW BAND EDGE BLOCK



Date: 24.JAN.2019 08:23:19

Channel 4233- HIGH BAND EDGE BLOCK

Conclusion: PASS

ANNEX A.6. FREQUENCY STABILITY

Method of test measurements please refer to KDB971168 D01 v03 clause 9

A.5.1. Method of Measurement and test procedures

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of GSM850, PCS1900, WCDMA BANDII and WCDMA BANDV, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +90°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +90°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +90°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.5.2. Measurement Limit**A.5.2.1. For Hand carried battery powered equipment**

According to the JTC standard the GSM frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. And the WCDMA is 2.5ppm. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.3VDC and 4.5VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages was varied from 85% to 115%.

A.5.2.2. For equipment powered by primary supply voltage

According to the JTC standard the GSM frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. And the WCDMA is 2.5ppm. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.5.3 Test results**GSM850Mid Channel/fc(MHz) 189/836.4****Frequency Error VS Temperature**

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.8	-30	-3.24	2091
3.8	-20	-4.21	2091
3.8	-10	-1.09	2091
3.8	0	-5.54	2091
3.8	10	-2.09	2091
3.8	20	-2.54	2091
3.8	30	-1.03	2091
3.8	40	-2.45	2091
3.8	50	-2.78	2091
3.8	60	-3.23	2091
3.8	70	-1.78	2091
3.8	80	-1.04	2091
3.8	90	-2.33	2091

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.3	25	-2.67	2091
3.8	25	0.54	2091
4.5	25	-1.98	2091

PCS1900 Mid Channel/fc(MHz) 661/1880**Frequency Error VS Temperature**

Power Supply (VDC)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.8	-30	-2.67	4700
3.8	-20	-2.45	4700
3.8	-10	-1.55	4700
3.8	0	-2.89	4700
3.8	10	-3.3	4700
3.8	20	-0.56	4700
3.8	30	-0.47	4700
3.8	40	-0.33	4700
3.8	50	-3.9	4700
3.8	60	-2.09	4700
3.8	70	-1.76	4700
3.8	80	-0.45	4700
3.8	90	-0.96	4700

Frequency Error VS Voltage

Power Supply (VDC)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.3	25	-1.55	4700
3.8	25	-2.09	4700
4.5	25	-1.98	4700

WCDMA BAND II Mid Channel/fc(MHz) 9400 /1880**Frequency Error VS Temperature**

Power Supply (VDC)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.8	-30	-3.37	4700
3.8	-20	-5.4	4700
3.8	-10	-4	4700
3.8	0	2.3	4700
3.8	10	-0.6	4700
3.8	20	0.35	4700
3.8	30	-3.49	4700
3.8	40	-1.95	4700
3.8	50	-3.34	4700
3.8	60	-5.89	4700
3.8	70	0.43	4700
3.8	80	-1.34	4700
3.8	90	-3.68	4700

Frequency Error VS Voltage

Power Supply (VDC)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.3	25	0.63	4700
3.8	25	-5.33	4700
4.5	25	-4.52	4700

WCDMA BAND V Mid Channel/fc(MHz) 4183/836.6**Frequency Error VS Temperature**

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.8	-30	-2.41	2091.5
3.8	-20	-2.44	2091.5
3.8	-10	-2.53	2091.5
3.8	0	-1.94	2091.5
3.8	10	-0.76	2091.5
3.8	20	0.14	2091.5
3.8	30	-1.08	2091.5
3.8	40	-0.55	2091.5
3.8	50	-0.4	2091.5
3.8	60	-3.57	2091.5
3.8	70	-2.17	2091.5
3.8	80	-0.53	2091.5
3.8	90	-0.28	2091.5

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(°C)	Frequency error(Hz)	Limit (Hz)
3.3	25	-4.9	2091.5
3.8	25	-2.03	2091.5
4.5	25	-2.01	2091.5

Conclusion: PASS

ANNEX A.7. CONDUCTED SPURIOUS EMISSION**A.7.1. GSM Measurement Method and test procedures**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.

2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.

3. The procedure to get the conducted spurious emission is as follows:

The trace mode is set to MaxHold to get the highest signal at each frequency;

Wait 25 seconds;Get the result.

4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM 850 Transmitter

Channel	Frequency(MHz)
128	824.2
189	836.4
251	848.8

PCS 1900 Transmitter

Channel	Frequency(MHz)
512	1850.2
661	1880.0
810	1909.8

A.7.1.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A7.1.2. Measurement result


Spurious emission limit -13dBm.

Note: peak above the limit line is the carrier frequency.

A7.1.2.1. GSM 850




Channel 128: 30MHz~1GHz




Date: 14.AUG.2018 08:03:52

Channel 128: 1GHz~10GHz




Date: 14.AUG.2018 08:02:30

Channel 189: 30MHz~1GHz




Date: 14.AUG.2018 08:02:52

Channel 189: 1GHz~10GHz



Date: 14.AUG.2018 08:04:29


Channel 251: 30MHz~1GHz



Date: 14.AUG.2018 08:04:51


Channel 251: 1GHz~10GHz

A7.1.2.2. PCS 1900




Date: 14.AUG.2018 08:15:17

Channel 512: 30MHz~1GHz



Date: 14.AUG.2018 08:15:39

Channel 512: 1GHz~20GHz




Date: 14.AUG.2018 08:14:18

Channel 661: 30MHz~1GHz



Date: 14.AUG.2018 08:16:16

Page Number : 60 of 88
Report Issued Date : Jan.24.2019



Channel 810: 1GHz~20GHz

Conclusion: PASS

A7.2. WCDMA Measurement Method and test procedures

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band V, data taken from 30 MHz to 10GHz.

2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.

3. The procedure to get the conducted spurious emission is as follows:

The trace mode is set to MaxHold to get the highest signal at each frequency;

Wait 25 seconds;

Get the result.

4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

WCDMA Band II Transmitter

Channel	Frequency (MHz)
9262	1852.40

9400	1880.00
9538	1907.60

WCDMA Band V Transmitter

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

A 7.2.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A 7.2.2. Measurement result

Spurious emission limit -13dBm.


Note: peak above the limit line is the carrier frequency.

A 7.2.2.1. WCDMA Band II



Date: 14.AUG.2018 07:53:05

Channel 9262: 30MHz~1GHz



Date: 14.AUG.2018 07:53:28

Channel 9262: 1GHz~20GHz



1 PR
MASH

Ref 30 dBm * Att 40 dB RBW 1 MHz VBW 3 MHz SWT 110 ms

Marker 2 [T1] -31.06 dBm 17.17850000 GHz

30 Offset 5 dB

1 20

10

0

-10

-20

-30

-40

-50

-60

-70


D1 -13 dBm

Marker 1 [T1] 19.60 dBm 1.881125000 GHz

Start 1 GHz 1.9 GHz/ Stop 20 GHz


Date: 14.AUG.2018 07:52:21

Page Number : 64 of 88
Report Issued Date : Jan.24.2019



Date: 14.AUG.2018 07:54:12

Channel 9538: 30MHz~1GHz




Date: 14.AUG.2018 07:54:34

Channel 9538:1GHz~20GHz


Conclusion: PASS

A 7.2.2.2. WCDMA Band V




Date: 14.AUG.2018 07:56:33

Channel 4132: 30MHz~1GHz




Date: 14.AUG.2018 07:56:56

Channel 4132:1GHz~20GHz




Date: 14.AUG.2018 07:55:27

Channel 4183: 30MHz~1GHz




Date: 14.AUG.2018 07:55:49

Channel 4183: 1GHz~20GHz



Date: 14.AUG.2018 07:57:40

Channel 4233: 30MHz~1GHz



Date: 14.AUG.2018 07:58:02

Channel 4233:1GHz~20GHz

Conclusion: PASS

ANNEX A.8. RADIATED

A.8.1. ERP

A.8.1.1. GSM ERP

A.8.1.1.1. Description


This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

A.8.1.1.2. Method of Measurement


The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receiving antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).

3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at thereference point of the chamber. An RF Signal source for the frequency band of interest is disconnected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} - P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.8.1.1.3 GSM 850-ERP 22.913(a)

A.8.1.1.3.1 Limits

	Power Step	Burst Peak ERP (dBm)
GPRS	3	$\leq 38.45\text{dBm}$ (7W)
EDGE	6	$\leq 38.45\text{dBm}$ (7W)

A.8.1.1.3.2 Measurement result

GPRS(GMSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a Antenna Gain(dBd)	PeakERP(dBm)	Polarization
824.2	-5.55	3.1	37	3.11	31.46	H
836.6	-4.79	3.1	37	3.11	32.22	H
848.8	-4.73	3.1	37	3.11	32.28	H

EDGE(8PSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a Antenna Gain(dBd)	PeakERP(dBm)	Polarization
824.2	-11.41	3.1	37	3.11	25.60	H
836.6	-10.74	3.1	37	3.11	26.27	H
848.8	-10.58	3.1	37	3.11	26.43	H

Frequency: 824.2MHz

$$\text{Peak ERP(dBm)} = P_{\text{Mea}}(-10.58\text{dBm}) - P_{\text{cl}}(3.1\text{dB}) + P_{\text{Ag}}(37\text{dB}) + G_{\text{a}}(3.11\text{dBd}) \\ = 26.43\text{dBm}$$

Note: ANALYZER SETTINGS: RBW = VBW = 3MHz

A.8.1.1.4 PCS 1900-EIRP 24.232(c)

A.8.1.1.4.1 Limits

	Power Step	Burst Peak EIRP (dBm)
GPRS	3	≤33dBm (2W)
EDGE	6	≤33dBm (2W)

A.8.1.1.4.2 Measurement result

GPRS(GMSK)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dBi)	PeakEIRP(dBm)	Polarization
1850.2	-9.53	4.6	36	4.7	26.57	V
1880.0	-8.62	4.6	35.6	4.7	27.08	H
1909.8	-9.91	4.7	36	4.7	26.09	V

EDGE(8PSK)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dBi)	PeakEIRP(dBm)	Polarization
1850.2	-13.86	4.6	36	4.7	22.24	V
1880.0	-13.17	4.6	35.6	4.7	22.53	H
1909.8	-14.26	4.7	36	4.7	21.74	V

Frequency: 1850.2MHz

$$\text{Peak EIRP(dBm)} = P_{\text{Mea}}(-14.26\text{dBm}) - P_{\text{cl}}(4.7\text{dB}) + P_{\text{Ag}}(36\text{dB}) + G_{\text{a}}(4.7\text{dB}) = 21.74\text{dBm}$$

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.8.1.2. WCDMA ERP

A.8.1.2.1. Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval

of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. "Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.8.1.2.2. Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be

recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{\text{Mea}} + P_{\text{Ag}} - P_{\text{cl}} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.

A.8.1.2.3 WCDMA Band II-ERP

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

A.8.1.2.3 Measurement result

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dBi)	PeakEIRP(dBm)	Polarization
1852.4	-22.19	3.54	43.8	2.9	20.97	V
1880.0	-22.05	3.54	43.8	2.9	21.11	H
1907.6	-22.9	3.54	43.8	2.9	20.26	V

Frequency: 1852.40MHz

$$\text{Peak EIRP(dBm)} = P_{\text{Mea}}(-22.9\text{dBm}) - P_{\text{cl}}(3.54\text{dB}) + P_{\text{Ag}}(43.8\text{dB}) + G_a(2.9\text{dBi}) = 20.26\text{dBm}$$

ANALYZER SETTINGS: RBW = VBW = 5MHz

A.8.1.2.4 Limits

	Burst Peak EIRP (dBm)
WCDMA Band V	≤38.45dBm (7W)

A.8.1.2.4 Measurement result

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dBd)	PeakERP(dBm)	Polarization
826.4	-12.52	3.1	37	2.9	24.28	H
836.6	-12.71	3.1	37	2.9	24.09	H
846.6	-13.23	3.1	37	2.9	23.57	H

Frequency: 826.4 MHz

$$\text{Peak ERP(dBm)} = P_{\text{Mea}}(-13.23\text{dBm}) - P_{\text{cl}}(3.1\text{dB}) + P_{\text{Ag}}(37\text{dB}) + G_a(2.9\text{dBd}) = 23.57\text{dBm}$$

ANALYZER SETTINGS: RBW = VBW = 5MHz

Note: the EUT was displayed in several different direction, the worst cases were shown.

A.8.2 EMISSION LIMIT (§2.1051/§22.917§24.238)


A.8.2.1 GSM Measurement Method

The measurement procedures in TIA-603E-2016 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

A.8.2.2 The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss .

The measurement results are obtained as described below:

Power(EIRP)= P_{Mea} - P_{pl} + G_a

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi

A.8.2.3 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.8.2.4 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.8.2.5 Measurement Results

Measurements results:

Frequency	Channel	Frequency Range	Result
GSM850	Low	30MHz~10GHz	P
	Middle	30MHz~10GHz	P
	High	30MHz~10GHz	P

GSM1900	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

GSM850

GPRS Mode Channel 128

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1483.1	-42.22	4.1	3.4	-42.92	-13	V
2572.5	-36.82	5.4	3.7	-38.52	-13	H
3465.0	-48.38	6.4	4.7	-50.08	-13	H
4249.6	-50.98	7.1	7.7	-50.38	-13	V
5086.2	-50	7.9	9.0	-48.9	-13	H
5837.3	-51.04	8.4	10.5	-48.94	-13	V

Note:

GPRS 850, CH128

Power(ERP)= Pmea-Pcl+Ga=-51.04-8.4+10.5=-48.94dbm

This method Applicable to the following table.

GPRS Mode Channel 189

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1718.6	-44.5	4.4	2.9	-46	-13	V
2584.3	-36.14	5.5	3.7	-37.94	-13	H
3411.9	-49.06	6.3	4.7	-50.66	-13	H
4238.1	-50.27	7.1	7.7	-49.67	-13	H

5008.8	-50.43	7.8	9.0	-49.23	-13	H
5869.6	-51.33	8.4	10.5	-49.23	-13	H

GPRS Mode Channel 251**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1727.1	-43.79	4.5	2.9	-45.39	-13	V
2625.0	-36.08	5.5	3.7	-37.88	-13	V
3589.6	-47.2	6.5	4.7	-49	-13	V
4356.9	-50.92	7.2	7.7	-50.42	-13	V
5243.1	-48.66	8.0	8.7	-47.96	-13	V
6015.4	-49.5	8.6	10.4	-47.7	-13	V

EGPRS Mode Channel 128**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1735.7	-43.96	4.4	2.9	-45.46	-13	H
2601.4	-36.35	5.5	3.7	-38.15	-13	V
3423.5	-48.74	6.3	4.7	-50.34	-13	V
4209.2	-51.28	7.0	7.7	-50.58	-13	H
5081.5	-50.69	7.9	9.0	-49.59	-13	V
5994.2	-49.61	8.6	10.4	-47.81	-13	V

Note:

EGPRS 850, CH128**Power(ERP)= P_{mea}-P_{cl}+G_a=-49.61-8.6+10.4=-47.81dbm****This method Applicable to the following table.****EGPRS Mode Channel 189****Final result:**

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dBm)	G _a (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1722.9	-44.16	4.4	2.9	-45.66	-13	H
2565.0	-36.79	5.4	3.7	-38.49	-13	V
3410.8	-48.61	6.3	4.7	-50.21	-13	V
4221.9	-51.2	7.0	7.7	-50.5	-13	H
5142.7	-50.36	7.9	8.7	-49.56	-13	H
6021.5	-49.69	8.6	10.4	-47.89	-13	V

EGPRS Mode Channel 251**Final result:**

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dBm)	G _a (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1733.6	-43.94	4.4	2.9	-45.44	-13	V
2540.4	-36.93	5.4	3.7	-38.63	-13	V
3450.0	-47.86	6.4	4.7	-49.56	-13	V
4221.9	-51.15	7.0	7.7	-50.45	-13	V
5020.4	-50.66	7.8	9.0	-49.46	-13	H
5882.3	-51.01	8.5	10.4	-49.11	-13	V

PCS1900**GPRS Mode Channel 512****Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3879.0	-54.72	6.8	7.7	-53.82	-13	V
5819.4	-54.02	8.4	10.5	-51.92	-13	V
7617.6	-54.43	9.7	14.6	-49.53	-13	V
9505.2	-54.81	10.7	18.6	-46.91	-13	V
11648.4	-48.5	12.2	17.6	-43.1	-13	V
13320.0	-48.47	13.6	21.8	-40.27	-13	V

GPRS Mode Channel 661**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3869.4	-54.36	6.7	7.7	-53.36	-13	V
5733.0	-54.7	8.5	10.5	-52.7	-13	V
7626.0	-55.06	9.7	15.3	-49.46	-13	H
9544.8	-54.51	10.7	18.6	-46.61	-13	H
11298.0	-49.52	12.1	18.5	-43.12	-13	V
13304.4	-48.86	13.6	21.8	-40.66	-13	V

GPRS Mode Channel 810**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3868.2	-54.81	6.7	7.7	-53.81	-13	V
5724.6	-54.63	8.5	10.5	-52.63	-13	H
7591.2	-53.9	9.7	14.6	-49	-13	V
9532.8	-54.18	10.7	18.6	-46.28	-13	V
11593.2	-49.48	12.2	18.1	-43.58	-13	H
13336.8	-49.21	13.6	21.8	-41.01	-13	H

Conclusion: PASS**Note: the EUT was displayed in several different direction, the worst cases were shown.****EGPRS Mode Channel 512****Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3885.6	-54.36	6.8	7.7	-53.46	-13	H
5779.2	-54.5	8.4	10.5	-52.4	-13	V
7647.6	-55.05	9.7	15.3	-49.45	-13	H
9513.6	-54.6	10.7	18.6	-46.7	-13	V
11528.4	-49.63	12.3	18.1	-43.83	-13	V
13300.8	-48.31	13.6	21.8	-40.11	-13	V

EGPRS Mode Channel 661**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3828.0	-53.87	6.7	7.7	-52.87	-13	H
5733.0	-54.93	8.5	10.5	-52.93	-13	H
7596.0	-54.1	9.7	14.6	-49.2	-13	V
9542.4	-55.01	10.7	18.6	-47.11	-13	H
11431.2	-49.99	12.1	18.1	-43.99	-13	H
13531.2	-49.35	13.7	23.4	-39.65	-13	V

EGPRS Mode Channel 810**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3841.8	-53.33	6.7	7.7	-52.33	-13	H
5728.2	-54.61	8.5	10.5	-52.61	-13	V
7650.0	-54.51	9.7	15.3	-48.91	-13	V
9511.2	-54.47	10.7	18.6	-46.57	-13	H
11625.6	-48.22	12.2	17.6	-42.82	-13	H
13347.6	-48.3	13.6	21.8	-40.1	-13	V

Conclusion: PASS**Note: the EUT was displayed in several different direction, the worst cases were shown.**

A.7.2.2. WCDMA Measurement Method

The measurements procedures in TIA-603E-2016 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238 and Part 24.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band V.

The procedure of radiated spurious emissions is the same like GSM.

A.7.2.2.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.7.2.2.2. Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the WCDMA Band V (826.4MHz, 836.6MHz and 846.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.7.2.2.3. Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band II	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P
WCDMA Band V	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

WCDMA BAND II Mode Channel 9262**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3702.8	-47.65	6.6	7.7	-46.55	-13	V
5558.8	-60.63	8.2	9.5	-59.33	-13	V
7375.2	-62.63	9.7	14.6	-57.73	-13	V
9223.2	-61.49	10.5	18.5	-53.49	-13	H
10792.4	-56.06	11.7	17.3	-50.46	-13	H
12886.5	-56.12	13.0	20.2	-48.92	-13	V

WCDMA BAND II Mode Channel 9400**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3761.6	-47.58	6.6	7.7	-46.48	-13	V
5439.6	-59.72	8.1	9.5	-58.32	-13	V
7174.4	-61.61	9.4	13.7	-57.31	-13	H
9006.0	-62.39	10.4	18.3	-54.49	-13	H
10771.2	-56.48	11.7	17.3	-50.88	-13	V
12532.6	-54.58	12.7	18.7	-48.58	-13	V

WCDMA BAND II Mode Channel 9538
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3813.2	-50.52	6.7	7.7	-49.52	-13	V
5719.2	-61.28	8.5	10.5	-59.28	-13	V
7611.6	-62.02	9.7	14.6	-57.12	-13	V
9577.2	-61.14	10.8	18.6	-53.34	-13	H
11602.7	-56.38	12.2	18.1	-50.48	-13	H
13304.4	-57.22	13.6	21.8	-49.02	-13	H

WCDMA BAND V Mode Channel 4132
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1654.6	-40.37	4.3	2.9	-41.77	-13	V
2562.3	-50.29	5.4	3.7	-51.99	-13	V
3448.0	-62.63	6.4	4.7	-64.33	-13	H
4270.8	-60.91	7.1	7.7	-60.31	-13	V
5129.6	-60.21	7.9	8.7	-59.41	-13	V
6050.8	-61.19	8.6	10.4	-59.39	-13	V

WCDMA BAND V Mode Channel 4183
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1675.0	-40.43	4.3	2.9	-41.83	-13	V
2547.7	-50.44	5.4	3.7	-52.14	-13	V
3374.0	-63.12	6.2	4.7	-64.62	-13	H
4219.2	-61.62	7.0	7.7	-60.92	-13	V
5018.0	-60.66	7.8	9.0	-59.46	-13	V
5840.8	-61.5	8.4	10.5	-59.4	-13	V

WCDMA BAND V Mode Channel 4233**Final result:**

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1694.6	-43.1	4.4	2.9	-44.6	-13	V
2563.8	-50.58	5.4	3.7	-52.28	-13	V
3390.8	-61.9	6.3	4.7	-63.5	-13	V
4232.8	-62.8	7.1	7.7	-62.2	-13	H
5066.4	-59.31	7.8	9.0	-58.11	-13	V
5942.4	-61.34	8.5	10.4	-59.44	-13	V


Conclusion: PASS


Note: the EUT was displayed in several different direction, the worst cases were shown.

ANNEX A.9. RECEIVER RADIATION EMISSION**A.9.1 Method of Measurement**

The EUT is placed on a 80cm height non-conductive table locating on the center of turntable. From 30MHz-1GHz, the measurement distance is 10m. For frequency range above 1GHz, the measurement distance is 3m.

The EUT is measured with travel charger and the operating mode is idle without CMW500's signaling.

A. 9.2 Measurement results**Idle Mode: 30MHz-1GHz**



Idle Mode: 1GHz-18GHz

ANNEX B. Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

*****End Of Report*****