

International Compliance Testing Laboratory 3356 N. San Marcos Place, Suite 107 Chandler, AZ 85225

fax: (480) 926-3598

Flom Associates,

http://www.mflom.com info@mflom.com

Date of Report: Date of Submission:

December 14, 2004 January 21, 2005

Federal Communications Commission Via: Electronic Filing

Attention:

Authorization & Evaluation Division

Applicant: Equipment: FCC ID: FCC Rules:

Vertu I td. Ascent, Type RHV-5 P7QRHV-5 22, 24, Confidentiality

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours

David E. Lee, **Compliance Test Manager**

enclosure(s) cc: Applicant DEL/cva

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598





Transmitter Certification

of

FCC ID: P7QRHV-5 Model: Ascent, Type RHV-5

to

Federal Communications Commission

Rule Part(s) 22H, 24E and Confidentiality

Date Of Report: December 14, 2004

On the Behalf of the Applicant:

Vertu Ltd.

At the Request of:

P.O. J93-4971588

Vertu Ltd. Beacon Hill Road Church Crookham, Hampshire GU52 8DY UK

Attention of:

Mark Pope, Certification and Compliance Manager +44 1252 611135; FAX: -611302 Mobile: +44 7774 8158594 mark.pope@vertu.com

David E. Lee, Compliance Test Manager

Supervised By:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598



List of Exhibitsa (FCC Certification (Cellular Transmitters) - Revised 9/28/98)

Applicant:

Vertu Ltd.

FCC ID:

P7QRHV-5

By Applicant:

- 1. Letter of Authorization
- 2. Identification Drawings, 2.1033(c)(11) Label Location of Label Compliance Statement Location of Compliance Statement
- 3. Photographs, 2.1033(c)(12)
- 4. Confidentiality Request: 0.457 And 0.459
- 5. Documentation: 2.1033(c)
 - (3) User Manual
 - (9) Tune Up Info
 - (10) Schematic Diagram
 - (10) Circuit Description Block Diagram Parts List Active Devices

6. SAR Report

By M.F.A. Inc.

A. Testimonial & Statement of Certification



The Applicant has been cautioned as to the following:

15.21 Information to User.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.



Table of Contents

Rule	Description	Page
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Radiated)	7
	GSM: Emission Masks (Occupied Bandwidth)	9
	Bluetooth: Emission Masks (Occupied Bandwidth)	19
2.1053(a)	Field Strength of Spurious Radiation	25
2.1055(a)(1)	Frequency Stability (Temperature Variation)	32
2.1055(b)(1)	Frequency Stability (Voltage Variation)	34
2.202(g)	Necessary Bandwidth and Emission Bandwidth	36



Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)	Test Report
b) Laboratory: (FCC: 31040/SIT) (Canada: IC 2044)	M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, AZ 85225
c) Report Number:	d04c0040
d) Client:	Vertu Ltd. Beacon Hill Road Church Crookham, Hampshire GU52 8DY UK
e) Identification:	Ascent, Type RHV-5 FCC ID: P7QRHV-5 S/N: 004400/12/179245/9
Description:	Cellular/PCS
f) EUT Condition:	Not required unless specified in individual tests.
g) Report Date: EUT Received:	December 14, 2004 November 8, 2004
h, j, k):	As indicated in individual tests.
i) Sampling method:	No sampling procedure used.
I) Uncertainty:	In accordance with MFA internal quality manual.
m) Supervised by:	1 da
	David E. Lee, Compliance Test Manager

n) Results:

o) Reproduction:

The results presented in this report relate only to the item tested.

This report must not be reproduced, except in full, without written permission from this laboratory.



List of General Information Required for Certification

In Accordance with FCC Rules and Regulations, Volume II, Part 2 and to

22H, 24E and Confidentiality

Sub-Part 2.1033 (c)(1): Name and Address of Applicant:

Vertu Ltd. Beacon Hill Road Church Crookham, Hampshire GU52 8DY UK

Manufacturer:

Applicant

(c)(2): FCC ID:

Model Number:

P7QRHV-5 Ascent, Type RHV-5

The P7QRHV-5 Mobile phone combines PCS technology and performance with design and craftsmanship to produce a product available in a number of cosmetic finishes. As this is restricted to cosmetics all will have the same Model, Type and FCCID.

The Electrical design is particularly robust and incorporates a self-contained, multiplayer, double-sided screened board with screening of the digital, base band and RF circuitry.

Cosmetic finishing of the phone allows some variation of the Ceramic and Leather components, as well as levels of polishing and finishing and color, using these materials. Test results demonstrate the equivalence of products tested and the independence of these finishing components from electrical performance in any mix/match combination.

(c)(3): Instruction Manual(s):

Please See Attached Exhibits

(c)(4):	Type of Emission:		256KGXW
(c)(5):	Frequency Range, MHz:		824 - 849 1850 - 1910
(c)(6):	Power Rating, Watts:		1.82 for GSM 850
	Switchable	X Variable	1.23 101 GSM 1900 N/A
(c)(7):	Maximum Power Rating, Watts:		7.0 for Part 22H 2.0 for Part 24E



Subpart 2.1033 (continued)

(c)(8): Voltages & Currents in All Elements in Final RF Stage, Including Final Transistor or Solid State Device:

Collector Current, A	=	per manual
Collector Voltage, Vdc	=	per manual
Supply Voltage, Vdc	=	4.0

(c)(9): Tune-Up Procedure:

Please See Attached Exhibits

(c)(10): Circuit Diagram/Circuit Description:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please See Attached Exhibits

(c)(11): Label Information:

Please See Attached Exhibits

(c)(12): Photographs:

Please See Attached Exhibits

(c)(13): Digital Modulation Description:

____ Attached Exhibits _X_ N/A

(c)(14): Test and Measurement Data:

Follows







A2LA

"A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 - 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Certificate Number: 2152-01

NIST

I am pleased to inform you that your laboratory has been validated by the Chinese Taipei Bureau of Standards, Metrology and Inspection (BSMI) under the Asia Pacific Economic Cooperation Mutual Recognition Agreement (APEC MRA). Your laboratory is now formally designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC MRA between the American Institute in Taiwan (AIT) and the Taipei Economic and Cultural Representative Office (TECRO) in the United States, covering equipment subject to Electro-Magnetic Compatibility (EMC) requirements. The names of all validated and nominated laboratories will be posted on the NIST website at http://ts.nist.gov/mra under the 'Asia' category."

BSMI Number: SL2-IN-E-041R

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 4 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Sub-part 2.1033(c)(14):

Test and Measurement Data

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- 21 Domestic Public Fixed Radio Services
- 22 Public Mobile Services
- X 22 Subpart H Cellular Radiotelephone Service
- 22.901(d) Alternative technologies and auxiliary services
 - 23 International Fixed Public Radiocommunication services
- X 24 Personal Communications Services
- 74 Subpart H Low Power Auxiliary Stations
- 80 Stations in the Maritime Services
- 80 Subpart E General Technical Standards
- 80 Subpart F Equipment Authorization for Compulsory Ships
- 80 Subpart K Private Coast Stations and Marine Utility Stations
- 80 Subpart S Compulsory Radiotelephone Installations for Small Passenger Boats
- 80 Subpart T Radiotelephone Installation Required for Vessels on the Great Lakes
- 80 Subpart U Radiotelephone Installations Required by the Bridge-to-Bridge Act
- 80 Subpart V Emergency Position Indicating Radiobeacons (EPIRB'S)
- 80 Subpart W Global Maritime Distress and Safety System (GMDSS)
- 80 Subpart X Voluntary Radio Installations
- 87 Aviation Services
- 90 Private Land Mobile Radio Services
- 94 Private Operational-Fixed Microwave Service
- 95 Subpart A General Mobile Radio Service (GMRS)
- 95 Subpart C Radio Control (R/C) Radio Service
- 95 Subpart D Citizens Band (CB) Radio Service
- 95 Subpart E Family Radio Service
- 95 Subpart F Interactive Video and Data Service (IVDS)
- 97 Amateur Radio Service
- 101 Fixed Microwave Services



Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2001, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.



Name of Test: R. F. Power Output (Radiated)

Specification: 47 CFR 2.1046(a)

Measurement Procedure (Radiated)

- 1. The EUT was placed on an open-field site and its radiated field strength at a known distance was measured by means of a spectrum analyzer. Equivalent loading was calculated from the equation $P_t=((E \times R)^2/49.2)$ watts, where R = 3m.
- 2. Measurement accuracy is ±1.5 dB.

Test Equipment

	Asset	Description	s/n	Cycle	Last Cal
Tra	nsducer				
	i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-03
Х	i00089	Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-03
Х	i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Jan-04
Amj	plifier				
Х	i00028	HP 8449A	2749A00121	12 mo.	May-04
Spe	ctrum Ana	lyzer			
Х	i00029	HP 8563E	3213A00104	12 mo.	May-04
Х	i00033	HP 85462A	3625A00357	12 mo.	Sep-04



0.407

Name of Test:

R. F. Power Output (Radiated)

Measurement Results

GSM / GPRS 850

g04b0007: 2004-Nov-08 Mon 15:38:00

Frequency Tuned,	Frequency Emission,	Meter,	CF, dB	ERP, dBm	ERP, Watts
MHz	MHz	dBuV/m			
824.200000	824.138000	95.94	32.73	31.3	1.349
836.600000	836.550000	96.08	33.92	32.6	1.820
848.800000	848.838000	95.11	33.12	30.9	1.230
EGPRS 850					
g04b0006: 2004-Nov	-08 Mon 14:48:00				
Frequency Tuned,	Frequency Emission,	Meter,	CF, dB	ERP, dBm	ERP, Watts
MHz	MHz	dBuV/m			
824.200000	824.163000	91.92	32.73	27.3	0.537
836.600000	836.500000	90.54	32.92	26.1	0.407

GSM / GPRS 1900

848.800000

g04b0002: 2004-Nov-08 Mon 11:39:00

848.700000

Frequency Tuned,	Frequency Emission,	Meter,	CF, dB	EIRP, dBm	EIRP, Watts	
MHz	MHz	dBuV/m				
1850.200000	1850.225000	81.13	44.15	30.1	1.023	
1880.00000	1880.025000	81.20	44.31	30.3	1.072	
1909.800000	1909.825000	81.63	44.47	30.9	1.230	

90.32

33.12

26.1

EGPRS 1900

g04b0003: 2004-Nov-08 Mon 16:48:00

Frequency Tuned, MHz	Frequency Emission, MHz	Meter, dBuV/m	CF, dB	EIRP, dBm	EIRP, Watts	
1850.200000	1850.100000	77.73	44.15	26.7	0.468	
1880.00000	1879.900000	77.55	44.31	26.6	0.457	
1909.800000	1909.738000	78.23	44.47	27.5	0.562	

Bluetooth

g04b0008: 2004-Nov-08 Mon 11:39:00

Frequency Tuned, MHz	Frequency Emission, MHz	Meter, dBuV/m	CF, dB	EIRP, dBm	EIRP, Watts
2.402000	2401.950000 2440.950000	48.42 49.40	48.01 48.33	1.2 2.5	0.00132
2.480000	2479.950000	47.73	48.64	1.1	0.00129

Supervised By:

David E. Lee, Compliance Test Manager

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598



Name of Test:	Emission Masks (Occupied Bandwidth)
Specification:	47 CFR 2.1049(c)(1), 22

Measurement Procedure

- A) The EUT and test equipment were set up as shown below
- B) For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
- C) The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.

Transmitter Equipment

The relevant equipment used during the test is listed below.

Directional Coupler Serial no. C-1530-10-U (0204) RLC Electronics Calibration N/A

Directional Coupler Serial no. C-0510-10-U (0204) RLC Electronics Calibration N/A

Base Station EmulatorSerial no. 1100.0008.02Rohde & Schwarz CMU200Calibrated 9 Dec, 2003Due 09 Dec, 2004

Spectrum AnalyserSerial no. 3943A11206Agilent 8563ECalibrated 29 Jun, 2003Due 29 Jun, 2006



Test Set-Up

The measurement equipment is set up as shown below.



Measurement Procedure

- 1) The EUT is connected via a conducted connection and placed in a call with random (worst case) modulation against the base station emulator.
 - a) For PCS mid channel 661, Tx Power Control level 0 (max power).
 - b) For GSM850 mid channel 192, Tx Power Control level 5 (max power).
- 2) The spectrum analyser is connected via the coupled RF port on the base station emulator.
- 3) The maximum power in 1 MHz RBW is measured.
- 4) The Occupied Bandwidth is measured via the 99% Power BW function on the spectrum analyser.
- 5) The channel is changed to low channel PCS CH512 and GSM850 CH128.
- 6) The band edge emissions limit is checked in 1% RBW for compliance.
- 7) The channel is changed to the next band edge channel.
- 8) The band edge emissions limit is checked in 1% RBW for compliance.
- 9) Repeat 7) & 8) up to the last band edge channel 810. For GSM850 emission limit is checked up to the band edge CH251.
- 10) The results are attached in the following pages.



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



Power: Modulation: HIGH POWER, REFERENCE IN 1MHZ GSM 850 MID CHANNEL

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 11 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



Power: Modulation: HIGH POWER GSM 850 MID CHANNEL, 99% POWER BANDWIDTH

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 12 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



1 Trace A ▼ 824.000000 MHz -11.0000 dBm

Power: Modulation: HIGH POWER GSM 850 LOW CHANNEL, LOWER BAND EDGE

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 13 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



Power: Modulation: HIGH POWER GSM 850 HIGH CHANNEL, UPPER BAND EDGE

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 14 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



Power: Modulation: HIGH POWER, REFERENCE IN 1MHz GSM 1900 MID CHANNEL

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 15 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



Power: Modulation: HIGH POWER GSM 1900 MID CHANNEL, 99% POWER BANDWIDTH

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 16 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



1 Trace A ▼ 1.850000 GHz -17.8300 dBm

Power: Modulation: HIGH POWER GSM 1900 LOW CHANNEL, LOWER BAND EDGE

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 17 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

Applicant Supplied Data



Power: Modulation: HIGH POWER GSM 1900 HIGH CHANNEL, UPPER BAND EDGE

Verified by:

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

David E. Lee, Compliance Test Manager

> Page 18 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Name of Test: Emission Masks (Occupied Bandwidth)

Specification: 47 CFR 2.1049(c)(1), 22

Test Equipment: As per previous page

Measurement Procedure

- A) The EUT and test equipment were set up as shown below
- B) For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ±2.5/±1.25 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
- C) For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
- D) The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.

	(1) Test Sample	(2)	(3)	
	Power		(4)	
Asset	Description	s/n	Cycle	Last Cal
(1) Audio Os a i00017	cillator/Generator HP 8903A Modulation Meter	2216A01753	12 mo.	Apr-04
(2) Coaxial At X i00231/2 i00123	t enuator PASTERNACK PE7021-30 (30 dB) NARDA 766 (10 dB)	231 or 232 7802A	NCR NCR	
(3) Interface X i00021	HP 8954A Transceiver Interface	2146A00159	NCR	
(4) Spectrum X i00048 i00029	Analyzer HP 8566B Spectrum Analyzer HP 8563E Spectrum Analyzer	2511A01467 3213A00104	12 mo. 12 mo.	Oct-04 May-04
M. Flom Associa	tes, Inc.			Page 19 c

Transmitter Test Set-Up: Occupied Bandwidth

3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598



Emission Masks (Occupied Bandwidth)

Measurement Results

g04b0019: 2004-Nov-10 Wed 09:26:00 State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: Modulation: HIGH BLUETOOTH LOW CHANNEL

Samir Mahmoud, Test Technician

Performed by:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 20 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

g04b0020: 2004-Nov-10 Wed 09:31:00 State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: Modulation: HIGH BLUETOOTH MID CHANNEL

Samir Mahmoud, Test Technician

Performed by:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 21 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

g04b0021: 2004-Nov-10 Wed 09:47:00 State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: Modulation: HIGH BLUETOOTH HIGH CHANNEL

Samir Mahmoud, Test Technician

Performed by:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 22 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

g04b0018: 2004-Nov-10 Wed 09:25:00 State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: Modulation: HIGH BLUETOOTH LOW BAND EDGE

Samir Mahmoud, Test Technician

Performed by:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 23 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Emission Masks (Occupied Bandwidth)

Measurement Results

g04b0022: 2004-Nov-10 Wed 09:54:00 State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: Modulation: HIGH BLUETOOTH UPPER BAND EDGE

Samir Mahmoud, Test Technician

Performed by:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 24 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Management Descendance		
Guide:	ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917	
Specification:	47 CFR 2.1053(a)	
Name of Test:	Field Strength of Spurious Radiation	

Measurement Procedure

Definition:

Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

Method of Measurement:

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHZ), 1 MHZ (> 1GHz).
 - 2) Video Bandwidth = 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
 - C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load that is placed on the turntable. The RF cable to this load should be of minimum length.





Name of Test: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.



Name of Test: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
 L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =

10log₁₀(TX power in watts/0.001) - the levels in step I)

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment

	Asset	Description	s/n	Cycle	Last Cal
Tra	nsducer				
	i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-03
Х	i00089	Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-03
Х	i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Jan-04
Am	plifier				
Х	i00028	HP 8449A	2749A00121	12 mo.	May-04
Spe	ectrum Ana	lyzer			
Х	i00029	HP 8563E	3213A00104	12 mo.	May-04
Х	i00033	HP 85462A	3625A00357	12 mo.	Sep-04
Sub	stitution G	Generator			
Х	i00067	HP 8920A Communication TS	3345U01242	12 mo.	Jun-04
	i00207	HP 8753D Network Analyzer	3410A08514	12 mo.	Jul-04



Field Strength of Spurious Radiation

GSM / GPRS 850

g04b0008: 2004-Nov-08 Mon 16:04:00 State: 2:High Power

Frequency Tuned,	Frequency Emission,	Meter,	CF, dB	ERP, dBm	Margin, dB
MHz	MHz	dBuV			
824.200000	1648.516667	44.00	2.93	-50.4	-37.5
836.600000	1673.323333	43.17	3.20	-51.0	-38.0
848.800000	1697.640000	46.30	3.47	-47.6	-34.6
824.200000	2472.800001	41.33	5.20	-50.8	-37.9
836.600000	2509.986667	40.33	5.24	-51.8	-38.8
848.800000	2546.608333	42.47	5.22	-49.7	-36.7
824.200000	3297.006668	34.00	6.94	-56.4	-43.5
836.600000	3346.586667	35.17	7.25	-55.0	-42.0
848.800000	3395.273333	29.30	7.54	-60.5	-47.6
824.200000	4121.213335	29.00	12.47	-55.9	-42.9
836.600000	4183.186667	35.67	12.42	-49.3	-36.3
848.800000	4244.013333	28.47	12.37	-56.5	-43.6
824.200000	4945.420002	32.83	12.14	-52.4	-39.4
836.600000	5019.786667	32.17	12.14	-53.1	-40.1
848.800000	5092.816667	28.80	12.16	-56.4	-43.4
824.200000	5769.626669	26.50	13.36	-57.5	-44.5
836.600000	5856.386667	30.67	13.71	-53.0	-40.0
848.800000	5941.616667	28.63	14.04	-54.7	-41.7
824.200000	6593.833336	29.50	13.40	-54.5	-41.5
836.600000	6692.950000	28.33	13.38	-55.7	-42.7
848.800000	6790.413333	27.13	13.36	-56.9	-43.9
824.200000	7418.040003	31.17	15.25	-51.0	-38.0
836.600000	7529.550000	30.17	15.74	-51.5	-38.5
848.800000	7639.211667	31.47	16.20	-49.7	-36.7
824.200000	8242.246670	32.00	17.65	-47.7	-34.8
836.600000	8366.150000	31.33	17.63	-48.4	-35.4
848.800000	8488.005000	26.63	17.63	-53.1	-40.1

Samir Mahmoud, Test Technician

Performed By:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598



Field Strength of Spurious Radiation

EGPRS 850

g04b0009: 2004-Nov-09 Tue 09:30:00 State: 2:High Power

Frequency Tuned,	Frequency Emission,	Meter,	CF, dB	ERP, dBm	Margin, dB
MHz	MHz	dBuV			
824.200000	1648.080000	36.00	2.93	-58.4	-45.5
836.600000	1673.063333	37.00	3.20	-57.2	-44.2
848.800000	1697.536667	35.67	3.47	-58.2	-45.3
824.200000	2472.423334	40.50	5.20	-51.7	-38.7
836.600000	2509.646667	41.83	5.24	-50.3	-37.3
848.800000	2546.336667	32.33	5.22	-59.8	-46.9
824.200000	3296.630001	35.17	6.94	-55.3	-42.3
836.600000	3346.246667	31.33	7.24	-58.8	-45.8
848.800000	3395.136667	30.83	7.54	-59 0	-46.0
824.200000	4120.280001	36.33	12.47	-48.6	-35.6
836.600000	4182.846667	29.33	12.42	-55.6	-42.7
848.800000	4243.936667	30.50	12.37	-54.5	-41.5
824.200000	4944.486668	30.67	12.14	-54.6	-41.6
836.600000	5019.446667	31.83	12.14	-53.4	-40.4
848.800000	5092.736667	29.67	12.16	-55.5	-42.6
824.200000	5769.413335	27.83	13.36	-56.2	-43.2
836.600000	5856.046667	29.67	13.71	-54.0	-41.0
848.800000	5941.536667	26.50	14.04	-56.8	-43.9
824.200000	6593.620002	30.00	13.40	-54.0	-41.0
836.600000	6692.646667	28.00	13.38	-56.0	-43.0
848.800000	6790.336667	30.00	13.36	-54.0	-41.0
824.200000	7417.826669	31.50	15.24	-50.6	-37.7
836.600000	7529.246667	33.67	15.74	-48.0	-35.0
848.800000	7639.136667	30.50	16.20	-50.7	-37.7
824.200000	8242.033336	29.67	17.65	-50.1	-37.1
836.600000	8365.846667	29.67	17.63	-50.1	-37.1
848.800000	8487.936667	36.17	17.63	-43.6	-30.6

Samir Mahmoud, Test Technician

Performed By:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 29 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Field Strength of Spurious Radiation

GSM / GPRS 1900

g04b0010: 2004-Nov-09 Tue 10:21:00 STATE: 2:High Power

Frequency Tuned,	Frequency Emission,	Meter, dBuV	CF, dB	EIRP, dBm	Margin, dB
MHz	MHz				
1850.200000	3700.400000	32.33	10.00	-52.9	-42.1
1880.000000	3759.640000	29.67	10.53	-55.0	-44.2
1909.800000	3819.296667	35.83	11.04	-48.4	-37.5
1850.200000	5550.600000	34.17	12.48	-48.6	-37.8
1880.000000	5640.110000	34.17	12.84	-48.2	-37.4
1909.800000	5729.150000	35.67	13.20	-46.4	-35.5
1850.200000	7401.626667	35.33	15.17	-44.7	-33.9
1880.000000	7520.110000	33.00	15.69	-46.5	-35.7
1909.800000	7639.933333	35.33	16.21	-43.7	-32.9
1850.200000	9250.693333	36.00	16.74	-42.5	-31.7
1880.000000	9400.110000	33.50	18.75	-43.0	-32.2
1909.800000	9548.550000	36.83	20.05	-38.3	-27.5
1850.200000	11102.036667	36.33	25.59	-33.3	-22.5
1880.000000	11280.896667	36.33	27.76	-31.1	-20.3
1909.800000	11458.916667	36.00	29.88	-29.3	-18.5
1850.200000	12952.236667	30.83	12.77	-51.6	-40.8
1880.000000	13160.073333	35.83	13.63	-45.8	-34.9
1909.800000	13367.666667	37.67	14.66	-42.9	-32.1
1850.200000	14801.046667	37.33	14.82	-43.1	-32.3
1880.000000	15039.946667	37.50	16.77	-41.0	-30.1
1909.800000	15279.236667	38.50	14.66	-42.1	-31.2
1850.200000	16651.693333	37.83	10.76	-46.6	-35.8
1880.000000	16919.626667	37.83	7.50	-49.9	-39.1
1909.800000	17189.036667	36.00	8.48	-50.7	-39.9

Samir Mahmoud, Test Technician

Performed By:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598

Page 30 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Field Strength of Spurious Radiation

EGPRS 1900

g04b0011: 2004-Nov-09 Tue 11:27:00 STATE: 2:High Power

Frequency Tuned,	Frequency Emission,	Meter, dBuV	CF, dB	EIRP, dBm	Margin, dB
MHz	MHz				
1880.000000	3701.306667	37.17	10.00	-48.1	-37.2
1880.000000	3760.026667	37.00	10.53	-47.7	-36.9
1909.800000	3820.436667	30.17	11.05	-54.0	-43.2
1880.000000	5611.097000	36.17	12.73	-46.3	-35.5
1880.000000	5639.813333	35.00	12.84	-47.4	-36.6
1909.800000	5729.570000	35.17	13.20	-46.9	-36.0
1880.000000	7460.603667	35.67	15.44	-44.1	-33.3
1880.000000	7519.586667	35.50	15.69	-44.0	-33.2
1909.800000	7639.370000	33.50	16.20	-45.5	-34.7
1880.000000	9310.057000	36.83	17.54	-40.9	-30.0
1880.000000	9400.836667	36.50	18.76	-40.0	-29.1
1909.800000	9549.170000	35.33	20.05	-39.8	-29.0
1880.000000	11160.457000	36.33	26.30	-32.6	-21.8
1880.000000	11280.723333	36.83	27.76	-30.6	-19.8
1909.800000	11458.970000	34.83	29.88	-30.5	-19.7
1880.000000	13012.003667	37.33	12.89	-45.0	-34.2
1880.000000	13159.423333	37.00	13.63	-44.6	-33.8
1909.800000	13368.770000	35.67	14.66	-44.9	-34.1
1880.000000	14860.487000	38.17	15.52	-41.5	-30.7
1880.000000	15040.346667	37.67	16.77	-40.8	-30.0
1909.800000	15278.570000	35.83	14.66	-44.7	-33.9
1880.000000	16710.453667	37.67	10.04	-47.5	-36.7
1880.000000	16919.456667	37.33	7.50	-50.4	-39.6
1909.800000	17188.370000	34.83	8.47	-51.9	-41.1

Samir Mahmoud, Test Technician

Performed By:



 Name of Test:
 Frequency Stability (Temperature Variation)

Specification: 47 CFR 2.1055(a)(1)

Measurement Procedure

- A) The EUT and test equipment were set up as shown on the following page.
- B) With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
- C) With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.

FCC Requirements: +/- 1ppm

GSM Requirements: +/- 0.1 ppm

Transmitter Test Set-Up



Test Equipment

The relevant equipment used during the test is listed below.

Environmental Chamber Thermotron \$1.2	Serial no. 30913NMP As: Calibrated 7 Aug 04	Due 7 Aug 05	
Base Station Emulator	Serial no. 100715	NMP Asset reg.	7937
Rohde & Schwarz CMU200	Calibrated 9 April 04		Due 9 April 05
Power Supply	Serial no. 2924A-02342	NMP Asset reg.	458
Agilent 6632A	Calibrated 20 Aug 04		Due 20 Aug 05

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598



Frequency Stability (Temperature Variation)

Measurement Results

Applicant Supplied Data

Temperature (°C)		GSM850 Frequency Error (Limit = +/- 89 H	Hz) Iz	F	GSM1900 Frequency Error Limit = +/- 185	(Hz) Hz
	ch 128 ch 192 ch 251		ch 512	ch 661	ch 810	
-30	-22.04	-24.43	-22.55	-24.54	-35.93	-47.92
-20	-17.26	-22.04	-30.62	-25.08	32.00	-31.73
-10	-22.62	11.67	5.86	-26.17	32.81	29.36
0	6.76	20.00	10.77	-33.90	-31.59	26.17
10	7.86	25.68	4.37	30.17	-34.44	28.75
20	-10.67	-7.89	11.28	31.32	31.46	-27.33
30	-17.00	-14.67	2.63	33.02	-35.05	23.39
40	-16.93	-11.96	-19.91	34.10	-31.79	-37.56
50	-20.62	-23.59	-10.28	-33.97	31.53	-35.26

Verified by:

David E. Lee, Compliance Test Manager



Name of Test:	Frequency Stability (Voltage Variation)
Specification:	47 CFR 2.1055(d)(1)
Guide:	ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Measurement Procedure

- A) The EUT was placed in a temperature chamber (if required) at 25±5°C and connected as shown below.
- B) The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- C) The variation in frequency was measured for the worst case.

Transmitter Test Set-Up: Voltage Variation



	Asset	Description	s/n	Cycle	Last Cal
(1)	Temperatur	e, Humidity, Vibration			
	i00027	Tenney Temp. Chamber	9083-765-234	NCR	
(2)	Coaxial Atte	nuator			
χ́	i00231/2	PASTERNACK PE7021-30 (30 dB)	231 or 232	NCR	
	i00122/3	NARDA 766 (10 dB)	7802 or 7802A	NCR	
(3)	RF Power				
Х	i00020	HP 8901A Power Mode	2105A01087	12 mo.	Apr-04
(4)	Frequency (Counter			
X	i00020	HP 8901A Frequency Mode	2105A01087	12 mo.	Apr-04

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598



Results:

Frequency Stability (Voltage Variation)

Applicant Supplied Data

FCC Requirements: +/- 1ppm

GSM Requirements: +/- 0.1 ppm

Voltage (%)	Voltage (V)	GSM850 Frequency Error (Hz) Limit = +/- 89 Hz			GSM1900 Frequency Error (Hz) Limit = +/- 185 Hz		
		ch 128	ch 192	ch 251	ch 512	ch 661	ch 810
End Point	<3.4	Tx off	Tx off	Tx off	Tx off	Tx off	Tx off
Nominal	4.0	-2.66	11.99	-11.77	27.81	23.80	22.58
115% Nominal	4.6	-9.44	13.09	-11.70	25.66	22.51	21.86
85% Nominal	3.4	-6.73	-5.44	-15.39	-47.02	21.72	23.65

The transmit power amplifier supply is disabled below 3.3 V and phone powers off at 3.2 V.

Verified by:

David E. Lee, Compliance Test Manager

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(480) 926-3100 phone, fax (480) 926-3598

Page 35 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Necessary Bandwidth and Emission Bandwidth

Specification:

47 CFR 2.202(g)

Modulation =

Necessary Bandwidth:		
Necessary Bandwidth (B_N) ,	=	256kHz
(measured at the 99% power bandwidth)		240kHz

Supervised By:

David E. Lee, Compliance Test Manager

END OF TEST REPORT

Page 36 of 36 FCC ID: P7QRHV-5 MFA p04b0003, d04c00400



Testimonial and Statement of Certification

This is to certify that:

- 1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
- 2. **That** the technical data supplied with the application was taken under my direction and supervision.
- 3. **That** the data was obtained on representative units, randomly selected.
- 4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

David E. Lee, Compliance Test Manager

Certifying Engineer:

M. Flom Associates, Inc. 3356 N. San Marcos Place, Suite 107 Chandler, Arizona 85225-7176 (480) 926-3100 phone, fax (480) 926-3598