

APPENDIX D: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table D-1
SAR System Validation Summary – 1g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
L	3500	08/10/2021	7539	3500	Head	2.783	38.261	PASS	PASS	PASS	TDD	PASS	N/A
L	3700	08/10/2021	7539	3700	Head	2.966	37.937	PASS	PASS	PASS	TDD	PASS	N/A
I	3500	08/03/2021	7551	3500	Body	3.325	49.471	PASS	PASS	PASS	TDD	PASS	N/A
L	3500	10/13/2021	7670	3500	Body	3.416	50.337	PASS	PASS	PASS	TDD	PASS	N/A
I	3700	08/03/2021	7551	3700	Body	3.515	49.242	PASS	PASS	PASS	TDD	PASS	N/A
L	3700	10/13/2021	7670	3700	Body	3.637	50.037	PASS	PASS	PASS	TDD	PASS	N/A

Table D-2
SAR System Validation Summary – 10g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
I	3500	08/03/2021	7551	3500	Body	3.325	49.471	PASS	PASS	PASS	TDD	PASS	N/A
I	3700	08/03/2021	7551	3700	Body	3.515	49.242	PASS	PASS	PASS	TDD	PASS	N/A

NOTE: Probes have been calibrated for both CW and modulated signals. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: A3LSMF926U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 05/23/21 - 01/03/22	DUT Type: Portable Handset			APPENDIX D: Page 1 of 1