





LTE band 71 (15 MHz)




LTE band 71 (15 MHz)




LTE band 71 (20 MHz)



QPSK Low Channel - 1 RB




QPSK High Channel - 1 RB



QPSK Low Channel - Full RB

QPSK High Channel - Full RB

LTE band 71 (20 MHz)



8. Frequency Stability

8.1. Limit

- § 2.1055 (a), § 2.1055 (d) & following:

- §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table of this section.

For Mobile devices operating in the 824 to 849 MHz band at a power level less than or equal to 3 Watts, the limit specified in Table C-1 is +/- 2.5 ppm.

- §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.


- §27.54, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

- §90.213, transmitters used in the services governed by this part must have a minimum frequency stability as specified in the following table.

For Mobile devices operating in the 809 to 824 MHz band at a power level 2 Watts or less, the limit specified in Table is +/- 2.5 ppm.

8.2. Test Procedure

1. Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Mobile Test Unit via feed-through attenuators.
2. The EUT was placed inside the temperature chamber.
3. After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from Mobile Test Unit.



8.3. Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

LTE band 7 at middle channel

Reference Frequency: 2 535.0 MHz			
Frequency Stability versus Temperature			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
50	4.00	9.31	0.000 23
40		13.16	0.001 75
30		8.30	-0.000 17
20(Ref.)		8.72	-
10		7.01	-0.000 67
0		8.01	-0.000 28
-10		11.92	0.001 26
-20		14.08	0.002 11
-30		3.77	-0.001 95
Frequency Stability versus Power Supply			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
20	3.40 (85%)	10.93	0.000 87
	4.60 (115%)	9.62	0.000 36

LTE band 12/17 at middle channel

Reference Frequency: 707.5 MHz			
Frequency Stability versus Temperature			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
50	4.00	8.12	0.000 10
40		11.83	0.005 34
30		6.15	-0.002 69
20(Ref.)		8.05	-
10		4.38	-0.005 19
0		6.88	-0.001 65
-10		9.02	0.001 37
-20		14.20	0.008 69
-30		4.97	-0.004 35
Frequency Stability versus Power Supply			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
20	3.40 (85%)	11.07	0.004 27
	4.60 (115%)	9.66	0.002 28

LTE band 26/5 Part 22 at middle channel

Reference Frequency: 836.5 MHz			
Frequency Stability versus Temperature			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
50	4.00	8.53	0.001 78
40		7.88	0.001 00
30		12.48	0.006 50
20(Ref.)		7.04	-
10		3.11	-0.004 70
0		7.19	0.000 18
-10		13.16	0.007 32
-20		8.14	0.001 32
-30		4.02	-0.003 61
Frequency Stability versus Power Supply			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
20	3.40 (85%)	11.05	0.004 79
	4.60 (115%)	9.67	0.003 14

LTE band 41 at middle channel

Reference Frequency: 2 593.0 MHz			
Frequency Stability versus Temperature			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
50	4.00	8.27	0.000 72
40		11.31	0.001 89
30		13.79	0.002 85
20(Ref.)		6.41	-
10		9.29	0.001 11
0		11.03	0.001 78
-10		9.92	0.001 35
-20		9.78	0.001 30
-30		8.27	0.000 72
Frequency Stability versus Power Supply			
Environment Temperature (°C)	Power Supplied (V)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
20	3.40 (85%)	10.92	0.001 74
	4.60 (115%)	9.53	0.001 20

