

RF EXPOSURE EVALUATION REPORT

FCC ID : 2AEUPBHARG081
Equipment : Battery Doorbell Plus
Brand Name : Ring
Model Name : 5F77E9
Applicant : Ring LLC
12515 Cerise Ave, Hawthorne, CA 90250, USA
Manufacturer : Ring LLC
12515 Cerise Ave, Hawthorne, CA 90250, USA
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full



Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. DETERMINATION OF EXEMPTION	5
4. RF EXPOSURE EVALUATION	6
4.1. Standalone assessment	6



History of this test report

Report No.	Version	Description	Issued Date
FA290506	Rev. 01	Initial issue of report	Dec. 14, 2022

**1. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	Battery Doorbell Plus
Brand Name	Ring
Model Name	5F77E9
FCC ID	2AEUPBHARG081
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2400 MHz ~ 2483.5 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	WLAN: 802.11b/g/n HT20 Bluetooth LE
EUT Stage	Identical Prototype

Reviewed by: **Jason Wang**Report Producer: **Daisy Peng****2. Maximum RF average output power among production units**

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Ant 1 Tune-up Limit
	802.11b 1Mbps	1	2412	19.50
		6	2437	19.00
		11	2462	18.00
		12	2467	14.00
		13	2472	12.00
	802.11g 6Mbps	1	2412	16.00
		6	2437	19.00
		11	2462	18.00
		12	2467	14.00
		13	2472	9.00
	802.11n-HT20 MCS0	1	2412	15.00
		6	2437	17.50
		11	2462	17.00
		12	2467	13.50
		13	2472	9.00

Mode	Channel	Frequency (MHz)	Tune-up Limit
			1Mbps
LE	CH 00	2402	8.50
	CH 19	2440	8.50
	CH 39	2480	8.50

3. Determination of exemption

Per 1.1307(b)(3), (i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

- (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);
- (B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold Pth (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by:

$$P_{th} \text{ (mW)} = ERP_{20cm} (d / 20)^x \text{ for distance } d \leq 20cm$$

$$P_{th} \text{ (mW)} = ERP_{20cm} \text{ for distance } 20cm < d \leq 40cm$$

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right)$$

$$ERP_{20cm} \text{ (mW)} \begin{array}{ll} 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz:} & 2040 f \\ 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz:} & 3060 \end{array}$$

- (C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

4. RF Exposure Evaluation

4.1. Standalone assessment

General Note:

1. P_i is mean the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm
2. P_{th} is mean the exemption threshold power (P_{th}) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i .
3. The distance of 20cm is used in the calculation formula of part1.1307(b)(3)(i)(B)

Band	Antenna Gain (dBi)	Maximum Conducted Power (dBm)	Maximum EIRP (dBm)	Maximum ERP (dBm)	Maximum EIRP (mW)	Maximum ERP (mW)	P_i (dBm)	P_i (mW)	Part1.1307 option(b) Threshold (mW)
WLAN2.4GHz Band	2.86	19.50	22.4	20.21	172.19	104.95	20.21	104.95	3060.000
Bluetooth	1.07	8.50	9.6	7.42	9.06	5.52	8.50	7.08	3060.000

Conclusion:

According to 47 CFR §1.1307, the RF exposure analysis concludes that the RF Exposure is FCC compliant.