




# **RADIO TEST REPORT**

**Test Report No. : 13830995H-A**

**Applicant** : ALPS ALPINE CO., LTD.  
**Type of EUT** : KEYLESS ENTRY SYSTEM  
**Model Number of EUT** : TB1G496  
**FCC ID** : CWTB1G496  
**Test regulation** : FCC Part 15 Subpart C: 2021  
**Test Result** : Complied (Refer to SECTION 3)

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
7. The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
8. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
9. The information provided from the customer for this report is identified in SECTION 1.

**Date of test:** July 4, 2021

**Representative test engineer:**   
Takafumi Noguchi  
Engineer

**Approved by:**   
Shinichi Miyazono  
Engineer



CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.  
☒ There is no testing item of "Non-accreditation".

**UL Japan, Inc.**  
**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone : +81 596 24 8999  
Facsimile : +81 596 24 8124

## **REVISION HISTORY**

**Original Test Report No.: 13830995H-A**

Revision	Test report No.	Date	Page revised	Contents
- (Original)	13830995H-A	July 19, 2021	-	-

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	MCS	Modulation and Coding Scheme
AC	Alternating Current	MRA	Mutual Recognition Arrangement
AFH	Adaptive Frequency Hopping	N/A	Not Applicable
AM	Amplitude Modulation	NIST	National Institute of Standards and Technology
Amp, AMP	Amplifier	NS	No signal detect.
ANSI	American National Standards Institute	NSA	Normalized Site Attenuation
Ant, ANT	Antenna	NVLAP	National Voluntary Laboratory Accreditation Program
AP	Access Point	OBW	Occupied Band Width
ASK	Amplitude Shift Keying	OFDM	Orthogonal Frequency Division Multiplexing
Atten., ATT	Attenuator	P/M	Power meter
AV	Average	PCB	Printed Circuit Board
BPSK	Binary Phase-Shift Keying	PER	Packet Error Rate
BR	Bluetooth Basic Rate	PHY	Physical Layer
BT	Bluetooth	PK	Peak
BT LE	Bluetooth Low Energy	PK/w	Peak with duty factor
BW	BandWidth	PN	Pseudo random Noise
Cal Int	Calibration Interval	PRBS	Pseudo-Random Bit Sequence
CCK	Complementary Code Keying	PSD	Power Spectral Density
Ch., CH	Channel	QAM	Quadrature Amplitude Modulation
CISPR	Comite International Special des Perturbations Radioelectriques	QP	Quasi-Peak
CW	Continuous Wave	QPSK	Quadri-Phase Shift Keying
DBPSK	Differential BPSK	RBW	Resolution Band Width
DC	Direct Current	RDS	Radio Data System
D-factor	Distance factor	RE	Radio Equipment
DFS	Dynamic Frequency Selection	RF	Radio Frequency
DQPSK	Differential QPSK	RMS	Root Mean Square
DSSS	Direct Sequence Spread Spectrum	RSS	Radio Standards Specifications
EDR	Enhanced Data Rate	Rx	Receiving
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	SA, S/A	Spectrum Analyzer
EMC	ElectroMagnetic Compatibility	SG	Signal Generator
EMI	ElectroMagnetic Interference	SVSWR	Site-Voltage Standing Wave Ratio
EN	European Norm	TR	Test Receiver
ERP, e.r.p.	Effective Radiated Power	Tx	Transmitting
EU	European Union	VBW	Video BandWidth
EUT	Equipment Under Test	Vert.	Vertical
Fac.	Factor	WLAN	Wireless LAN
FCC	Federal Communications Commission		
FHSS	Frequency Hopping Spread Spectrum		
FM	Frequency Modulation		
Freq.	Frequency		
FSK	Frequency Shift Keying		
GFSK	Gaussian Frequency-Shift Keying		
GNSS	Global Navigation Satellite System		
GPS	Global Positioning System		
Hori.	Horizontal		
ICES	Interference-Causing Equipment Standard		
IEC	International Electrotechnical Commission		
IEEE	Institute of Electrical and Electronics Engineers		
IF	Intermediate Frequency		
ILAC	International Laboratory Accreditation Conference		
ISED	Innovation, Science and Economic Development Canada		
ISO	International Organization for Standardization		
JAB	Japan Accreditation Board		
LAN	Local Area Network		
LIMS	Laboratory Information Management System		

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer information.....</b>	<b>5</b>
<b>SECTION 2: Equipment under test (EUT).....</b>	<b>5</b>
<b>SECTION 3: Test specification, procedures &amp; results.....</b>	<b>6</b>
<b>SECTION 4: Operation of EUT during testing .....</b>	<b>9</b>
<b>SECTION 5: Radiated emission (Fundamental and Spurious Emission) .....</b>	<b>10</b>
<b>SECTION 6: Automatically deactivate .....</b>	<b>12</b>
<b>SECTION 7: -20 dB and 99% Occupied Bandwidth .....</b>	<b>12</b>
<b>APPENDIX 1: Test data .....</b>	<b>13</b>
Automatically deactivate .....	13
Radiated Emission (Fundamental and Spurious Emission) .....	14
-20 dB Bandwidth / 99 % Occupied Bandwidth.....	16
<b>APPENDIX 2: Test instruments .....</b>	<b>17</b>
<b>APPENDIX 3: Photographs of test setup .....</b>	<b>18</b>
Radiated Spurious Emission .....	18
Worst Case Position .....	20

## **SECTION 1: Customer information**

Company Name	:	ALPS ALPINE CO., LTD.
Address	:	6-3-36, Nakazato, Furukawa, Osaki-city, Miyagi-pref, 989-6181, Japan
Telephone Number	:	+81-229-23-5111
Facsimile Number	:	+81-229-24-6334
Contact Person	:	Yuji Ouchi

The information provided from the customer is as follows;

- Applicant, Type of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer information
- SECTION 2: Equipment under test (EUT)
- SECTION 4: Operation of EUT during testing

\* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

## **SECTION 2: Equipment under test (EUT)**

### **2.1. Identification of EUT**

Type	:	KEYLESS ENTRY SYSTEM
Model Number	:	TB1G496
Serial Number	:	Refer to SECTION 4.2
Rating	:	DC 3.0 V
Receipt Date	:	July 1, 2021
Country of Mass-production	:	Japan
Condition of EUT	:	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	:	No Modification by the test lab.

### **2.2. Product Description**

Model: TB1G496 (referred to as the EUT in this report) is a KEYLESS ENTRY SYSTEM.

### **Radio Specification**

Radio Type	:	Transmitter
Frequency of Operation	:	433.92 MHz
Modulation	:	FSK
Antenna Type	:	Pattern Loop Antenna
Operating temperature range	:	-20 to +70 deg. C
Clock frequency (Maximum)	:	27.6 MHz

## **SECTION 3: Test specification, procedures & results**

### **3.1 Test Specification**

Test Specification : FCC Part 15 Subpart C  
FCC Part 15 final revised on May 3, 2021 and effective July 2, 2021

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
Section 15.231 Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

### **3.2 Procedures and results**

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted emission	ANSI C63.10:2013 6 Standard test methods	Section 15.207	N/A	N/A	*1)
Automatically Deactivate	ANSI C63.10:2013 6 Standard test methods	Section 15.231(a)(1)	N/A	Complied a)	Radiated
Electric Field Strength of Fundamental Emission	ANSI C63.10:2013 6 Standard test methods	Section 15.231(b)	3.8 dB 433.92 MHz Vertical PK with Duty factor	Complied# b)	Radiated
Electric Field Strength of Spurious Emission	ANSI C63.10:2013 6 Standard test methods	Section 15.205 Section 15.209 Section 15.231(b)	22.9 dB 867.840 MHz Horizontal PK with Duty factor	Complied b)	Radiated
-20dB Bandwidth	ANSI C63.10:2013 6 Standard test methods	Section 15.231(c)	N/A	Complied c)	Radiated
Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422. *1) The test is not applicable since the EUT does not have AC Mains.  a) Refer to APPENDIX 1 (data of Automatically deactivate) b) Refer to APPENDIX 1 (data of Radiated Emission (Electric Field Strength of Fundamental and Spurious Emission)) c) Refer to APPENDIX 1 (data of -20dB and 99% Occupied Bandwidth) Symbols: Complied                The data of this test item has enough margin, more than the measurement uncertainty. Complied#              The data of this test item meets the limits unless the measurement uncertainty is taken into consideration.					

#### **FCC Part 15.31 (e)**

The test was performed with the New Battery during the tests.  
Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.  
Therefore, the equipment complies with the antenna requirement of Section 15.203.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99 % Occupied Bandwidth	ANSI C63.10:2013 6 Standard test methods	Reference data	N/A	-	Radiated

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

There is no applicable rule of uncertainty in this applied standard. Therefore, the results are derived depending on whether or not laboratory uncertainty is applied.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k=2$ .

#### Radiated emission

Measurement distance	Frequency range	Uncertainty (+/-)
3 m	9 kHz to 30 MHz	3.3 dB
10 m		3.2 dB
3 m	30 MHz to 200 MHz	(Horizontal) 4.8 dB
		(Vertical) 5.0 dB
	200 MHz to 1000 MHz	(Horizontal) 5.2 dB
		(Vertical) 6.3 dB
10 m	30 MHz to 200 MHz	(Horizontal) 4.8 dB
		(Vertical) 4.8 dB
	200 MHz to 1000 MHz	(Horizontal) 5.0 dB
		(Vertical) 5.0 dB
3 m	1 GHz to 6 GHz	4.9 dB
	6 GHz to 18 GHz	5.2 dB
1 m	10 GHz to 26.5 GHz	5.5 dB
	26.5 GHz to 40 GHz	5.5 dB
10 m	1 GHz to 18 GHz	5.2 dB

#### Antenna Terminal test

Test Item	Uncertainty (+/-)
Automatically Deactivate	0.10 %
-20 dB Bandwidth / 99 % Occupied Bandwidth	0.96 %

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

\*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 199967

ISED Lab Company Number: 2973C / CAB identifier: JP0002

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8999, Facsimile: +81 596 24 8124

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-

### 3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.




## **SECTION 4: Operation of EUT during testing**

### **4.1. Operating Mode(s)**

Test Item*	Mode
Automatically Deactivate	Normal use mode
Electric Field Strength of Fundamental Emission Electric Field Strength of Spurious Emission -20 dB & 99 % Occupied Bandwidth	Transmitting mode (Tx 433.92 MHz) *1)
<p>* The system was configured in typical fashion (as a user would normally use it) for testing.</p> <p>*1) The software of this mode is the same as one of normal product, except that EUT continues to transmit when transmitter button is being pressed (For Normal use mode, EUT stops to transmit in a given time, even if transceiver button is being pressed.)</p> <p>* EUT was set by the software as follows; Software: 5AB-01134 Version A06 (for Normal use mode) 5AB-01134 Version Z15 (for Transmitting mode) (Date: 2021,01,22 (for Normal use mode), 2021,04,15 (for Transmitting mode) Storage location: EUT memory)</p> <p>*This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.</p>	

Justification: The system was configured in typical fashion (as a user would normally use it) for testing.

### **4.2. Configuration and peripherals**



\* Setup were taken into consideration and test data was taken under worse case conditions.

#### **Description of EUT**

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	KEYLESS ENTRY SYSTEM	TB1G496	21062901 *1) 21062902 *2)	ALPS ALPINE CO., LTD.	EUT

\*1) Used for Normal use mode

\*2) Used for Transmitting mode

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 5: Radiated emission (Fundamental and Spurious Emission)**

### **Test Procedure**

[For below 30 MHz]

The noise level was checked by moving a search-coil (Loop Antenna) close to the EUT.

[For 30 MHz to 1 GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The measuring antenna height was varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detector function of the test receiver / spectrum analyzer.

### **Test Antennas are used as below;**

Frequency	Below 30 MHz	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn

	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz	Above 1 GHz
Detector Type	Peak	Peak	Peak	Peak	Peak and Peak with Duty factor	Peak and Peak with Duty factor
IF Bandwidth	200 Hz	200 Hz	9.1 kHz	9.1 kHz	120 kHz	PK: S/A: RBW 1 MHz, VBW: 3 MHz

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

**Measurement range** : 9 kHz - 4.4 GHz

**Test data** : APPENDIX

**Test result** : Pass

**UL Japan, Inc.**


**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999


Facsimile : +81 596 24 8124

[Test Setup]  
Below 1 GHz



Test Distance: 3 m

Above 1 GHz



Distance Factor:  $20 \times \log (4.0 \text{ m} / 3.0 \text{ m}) = 2.5 \text{ dB}$

\* Test Distance:  $(3 + \text{SVSWR Volume} / 2) - r = 4.0 \text{ m}$

SVSWR Volume : 2.0 m

(SVSWR Volume has been calibrated based on CISPR 16-1-4.)

$r = 0.0 \text{ m}$

\* The test was performed with  $r = 0.0 \text{ m}$  since EUT is small and it was the rather conservative condition.

## **SECTION 6: Automatically deactivate**

### **Test Procedure**

The measurement was performed with Electric field strength using a spectrum analyzer.

Test data : APPENDIX  
Test result : Pass

## **SECTION 7: -20 dB and 99% Occupied Bandwidth**

### **Test Procedure**

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
20 dB Bandwidth	500 kHz	9.1 kHz	27 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99 % Occupied Bandwidth *)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
*) Peak hold was applied as Worst-case measurement.							


Test data : APPENDIX  
Test result : Pass

## APPENDIX 1: Test data

### Automatically deactivate

Report No.	13830995H
Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	July 4, 2021
Temperature / Humidity	24 deg. C / 62 % RH
Engineer	Takafumi Noguchi
Mode	Normal use mode

Time of Transmitting [sec]	Limit [sec]	Result
0.185	5.00	Pass



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Radiated Emission (Fundamental and Spurious Emission)

Report No. 13830995H  
Test place Ise EMC Lab.  
Semi Anechoic Chamber No.3  
Date July 4, 2021  
Temperature / Humidity 24 deg. C / 62 % RH  
Engineer Takafumi Noguchi  
Mode Transmitting mode (Tx 433.92 MHz)

Polarity [Hori/Vert]	Frequency [MHz]	Reading (PK) [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (PK) [dBuV/m]	Result (PK / W) [dBuV/m]	Limit (PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (PK) [dB]	Margin (AV) [dB]	Inside or Outside of Restricted Bands	Remarks
Hori.	433.920	81.2	16.2	11.0	32.1	0.0	76.3	76.3	100.8	80.8	24.5	4.5	Carrier	
Hori.	867.840	34.1	21.6	13.4	31.2	0.0	37.9	37.9	80.8	60.8	42.9	22.9	Outside	
Hori.	1301.760	44.8	25.8	6.1	34.4	0.0	42.3	42.3	73.9	53.9	31.6	11.6	Inside	Floor noise
Hori.	1735.680	44.2	25.0	5.7	33.4	0.0	41.5	41.5	80.8	60.8	39.3	19.3	Outside	Floor noise
Hori.	2169.600	43.3	28.3	5.7	32.7	0.0	44.6	44.6	80.8	60.8	36.2	16.2	Outside	Floor noise
Hori.	2603.520	43.1	27.8	5.9	32.5	0.0	44.3	44.3	80.8	60.8	36.5	16.5	Outside	Floor noise
Hori.	3037.440	43.1	28.6	6.0	32.3	0.0	45.4	45.4	80.8	60.8	35.4	15.4	Outside	Floor noise
Hori.	3471.360	42.9	28.7	6.2	32.1	0.0	45.7	45.7	80.8	60.8	35.1	15.1	Outside	Floor noise
Hori.	3905.280	42.6	29.7	6.4	31.9	0.0	46.8	46.8	73.9	53.9	27.1	7.1	Inside	Floor noise
Hori.	4339.200	42.2	30.4	6.7	31.8	0.0	47.5	47.5	73.9	53.9	26.4	6.4	Inside	Floor noise
Vert.	433.920	81.9	16.2	11.0	32.1	0.0	77.0	77.0	100.8	80.8	23.8	3.8	Carrier	
Vert.	867.840	32.2	21.6	13.4	31.2	0.0	36.0	36.0	80.8	60.8	44.8	24.8	Outside	
Vert.	1301.760	44.7	25.8	6.1	34.4	0.0	42.2	42.2	73.9	53.9	31.7	11.7	Inside	Floor noise
Vert.	1735.680	44.2	25.0	5.7	33.4	0.0	41.5	41.5	80.8	60.8	39.3	19.3	Outside	Floor noise
Vert.	2169.600	43.2	28.3	5.7	32.7	0.0	44.5	44.5	80.8	60.8	36.3	16.3	Outside	Floor noise
Vert.	2603.520	43.0	27.8	5.9	32.5	0.0	44.2	44.2	80.8	60.8	36.6	16.6	Outside	Floor noise
Vert.	3037.440	43.1	28.6	6.0	32.3	0.0	45.4	45.4	80.8	60.8	35.4	15.4	Outside	Floor noise
Vert.	3471.360	43.0	28.7	6.2	32.1	0.0	45.8	45.8	80.8	60.8	35.0	15.0	Outside	Floor noise
Vert.	3905.280	42.5	29.7	6.4	31.9	0.0	46.7	46.7	73.9	53.9	27.2	7.2	Inside	Floor noise
Vert.	4339.200	41.9	30.4	6.7	31.8	0.0	47.2	47.2	73.9	53.9	26.7	6.7	Inside	Floor noise

Sample calculation:

Result of PK = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1GHz) +Distance factor (above 1 GHz)} - Gain (Amplifier)

Result of PK with Duty factor (PK / W) = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz) +Distance factor (above 1 GHz)} - Gain (Amplifier) + Duty factor

For above 1GHz : Distance Factor:  $20 \times \log(4.0 \text{ m}/3.0 \text{ m}) = 2.50 \text{ dB}$

Since the peak emission result satisfied the average limit, duty factor was omitted.

Although Duty of this product was 100% or less, the result of AV (PK with Duty factor) was calculated by applying Duty 100% as worst.

Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

**UL Japan, Inc.**

**Ise EMC Lab.**


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Radiated Spurious Emission (Plot data, Worst case)

Report No. 13830995H  
Test place Ise EMC Lab.  
Semi Anechoic Chamber No.3  
Date July 4, 2021  
Temperature / Humidity 24 deg. C / 62 % RH  
Engineer Takafumi Noguchi  
Mode Transmitting mode (Tx 433.92 MHz)




## -20 dB Bandwidth / 99 % Occupied Bandwidth

Report No.	13830995H
Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	July 4, 2021
Temperature / Humidity	24 deg. C / 62 % RH
Engineer	Takafumi Noguchi
Mode	Transmitting mode (Tx 433.92 MHz)

Bandwidth Limit : Fundamental Frequency      433.92 MHz x 0.25% = 1084.800 kHz

-20dB Bandwidth [kHz]	Bandwidth Limit [kHz]	Result
191.9460	1084.800	Pass

99% Occupied Bandwidth Bandwidth [kHz]	Bandwidth Limit [kHz]	Result
207.2208	1084.800	Pass





## APPENDIX 2: Test instruments

### Test equipment

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	MAEC-03	142008	AC3_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	05/22/2020	24
RE	MOS-13	141554	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	1301	01/15/2021	12
RE	MMM-08	141532	DIGITAL HiTESTER	HIOKI E.E. CORPORATION	3805	51201197	01/07/2021	12
RE	MJM-16	142183	Measure	KOMELON	KMC-36	-	-	-
RE	COTS-ME MI-02	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	MAT-95	142314	Attenuator	Pasternack Enterprises	PE7390-6	D/C 1504	06/09/2021	12
RE	MBA-03	141424	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103+BBA9106	1915	08/13/2020	12
RE	MCC-51	141323	Coaxial cable	UL Japan	-	-	07/06/2020	12
RE	MLA-22	141266	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-191	08/13/2020	12
RE	MPA-13	141582	Pre Amplifier	SONOMA INSTRUMENT	310	260834	02/18/2021	12
RE	MTR-09	141950	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	06/03/2021	12
RE	MHA-20	141507	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	258	10/01/2020	12
RE	MPA-11	141580	MicroWave System Amplifier	Keysight Technologies Inc	83017A	MY39500779	03/03/2021	12
RE	MCC-231	177964	Microwave Cable	Junkosha INC.	MMX221	1901S329(1m)/ 1902S579(5m)	03/04/2021	12
RE	MHF-27	141297	High Pass Filter(1.1-10GHz)	TOKYO KEIKI	TF219CD1	1001	01/14/2021	12
RE	MAEC-03-SVSWR	142013	AC3_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/01/2021	24
RE	MLPA-07	142645	Loop Antenna	UL Japan	-	-	-	-

\*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item: RE: Radiated Emission test

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124