

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BAHT-W3

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
2.4G WIFI	802.11g&2 437	25±1	26	398.107 2	1.4488 (1.61dBi)	0.1148	1	Pass
BLE	GFSK& MCH	4±1	5	3.1623	1.4488 (1.61dBi)	0.0009	1	Pass
EDR	GFSK&M CH	7±1	8	6.3096	1.4488 (1.61dBi)	0.0018	1	Pass
5.2GWIFI	802.11a20 &5240	20±1	21	125.892 5	1.3062 (1.16dBi)	0.0327	1	Pass
5.8GWIFI	802.11n(H T20)& 5785	17±1	18	63.0957	1.2589 (1.14dBi)	0.0164	1	Pass

BT+WIFI supported simultaneous transmission:

EDR+2.4GWIFI: Σ MPE Ratio=0.0018+0.1148=0.1166

EDR+5.2GWIFI: Σ MPE Ratio=0.0018+0.0327=0.0345

EDR+2.4GWIFI+5.2GWIFI: Σ MPE Ratio=0.0018+0.1148+0.0327=0.1493
≤1, So passed.