

## FCC Part 15, Subpart B, Class B

ARTIKA FOR LIVING INC.

Essence 4 pendant

Test Model: OME59B

Additional Model No.: OME59B-XXXXXX

("X" can be A to Z and/or 0 to 9 and/or blank (commercial code))

Prepared for	:	ARTIKA FOR LIVING INC.
Address	:	1756 50th avenue, Lachine, Qc, CanadaH8T 2V5 Lachine Canada
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	December 03, 2021
Number of tested samples	:	1
Sample number	:	211206145A
Serial number	:	Prototype
Date of Test	:	December 03, 2021 ~ December 14, 2021
Date of Report	:	December 14, 2021

**FCC Part 15, Subpart B, Class B**  
**FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014**

**Report Reference No. .... : LCS211206145AE**

**Date Of Issue ..... : December 14, 2021**

**Testing Laboratory Name .... : Shenzhen LCS Compliance Testing Laboratory Ltd.**

**Address ..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park**  
Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,  
518000, China

**Testing Location/ Procedure... : Full application of Harmonised standards ■**  
Partial application of Harmonised standards □  
Other standard testing method □

**Applicant's Name..... : ARTIKA FOR LIVING INC.**

**Address ..... : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5 Lachine**  
Canada

**Test Specification**

**Standard..... : FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014**

**Test Report Form No..... : LCSEMC-1.0**

**TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.**

**Master TRF..... : Dated 2011-03**

**SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. is acknowledged as copyright owner and source of the material. SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description..... : Essence 4 pendant**

**Test Model ..... : OME59B**

**Trade Mark ..... : ARTIKA**

**Ratings ..... : AC 120V, 60Hz, 26W**

**Result ..... : Positive**

**Compiled by:**



Cherry Chen/ Administrators

**Supervised by:**



Jin Wang/ Technique principal

**Approved by:**



Gavin Liang/ Manager

**FCC -- TEST REPORT****Test Report No. : LCS211206145AE**December 14, 2021

Date of issue

Test Model ..... : OME59B

EUT..... : Essence 4 pendant

**Applicant..... : ARTIKA FOR LIVING INC.**Address..... : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5  
Lachine Canada

Telephone..... : /

Fax..... : /

**Manufacturer..... : ZHONGSHAN C5 LIGHTING CO. LTD**Address..... : 1# Henglong Road, Tongyi Industrial Area, Cao San,  
Guzhen, Zhongshan, Guangdong, China.

Telephone..... : /

Fax..... : /

**Factory..... : ZHONGSHAN C5 LIGHTING CO. LTD**Address..... : 1# Henglong Road, Tongyi Industrial Area, Cao San,  
Guzhen, Zhongshan, Guangdong, China.

Telephone..... : /

Fax..... : /

**Test Result** according to the standards on page 6: **Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

Revision	Issue Date	Revisions	Revised By
000	December 14, 2021	Initial Issue	Gavin Liang

## TABLE OF CONTENTS

Test Report Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. GENERAL INFORMATION .....</b>	<b>7</b>
2.1. Description of Device (EUT) .....	7
2.2. Support Equipment List.....	7
2.3. Description of Test Facility .....	7
2.4. Statement of the Measurement Uncertainty .....	8
2.5. Measurement Uncertainty.....	8
<b>3. TEST RESULTS .....</b>	<b>9</b>
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT .....	9
3.2. Radiated emission Measurement .....	13
<b>4. TEST SETUP PHOTOGRAPHS OF EUT .....</b>	<b>17</b>
<b>5. EXTERIOR PHOTOGRAPHS OF THE EUT .....</b>	<b>17</b>
<b>6. INTERIOR PHOTOGRAPHS OF THE EUT.....</b>	<b>17</b>

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
Radiated disturbance	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
N/A is an abbreviation for Not Applicable.			

**Test mode:**

Mode

Lighting

Record

\*\*\*Note: All test modes were tested, but we only recorded the worst case in this report.

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

EUT : Essence 4 pendant

Trade Mark : ARTIKA

Test Model : OME59B

Additional Model : OME59B-XXXXXX  
("X" can be A to Z and/or 0 to 9 and/or blank  
(commercial code))

Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested

Power Supply : AC 120V, 60Hz, 26W

Highest internal frequency (Fx)	Highest measured frequency
$F_x \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} < F_x \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} < F_x \leq 1 \text{ GHz}$	5 GHz
$F_x > 1 \text{ GHz}$	5 × Fx up to a maximum of 6 GHz

NOTE 1 For FM and TV broadcast receivers, Fx is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.  
Where Fx is unknown, the radiated emission measurements shall be performed up to 6 GHz.

### 2.2. Support Equipment List

Name	Manufacturers	M/N	S/N
--	--	--	--

### 2.3. Description of Test Facility

Site Description  
EMC Lab.

: NVLAP Accreditation Code is 600167-0.  
FCC Designation Number is CN5024.  
FCC Test Firm Registration Number: 254912  
CAB identifier is CN0071.  
CNAS Registration Number is L4595.

## 2.4. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 2.5. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucisp)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	$\pm 2.63$ dB $\pm 2.35$ dB	$\pm 3.8$ dB $\pm 3.4$ dB
Radiated Emission	Level accuracy (30MHz to 1000MHz)	$\pm 3.48$ dB	$\pm 5.3$ dB
Radiated Emission	Level accuracy (above 1000MHz)	$\pm 3.90$ dB	$\pm 5.2$ dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.



### 3. TEST RESULTS


#### 3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

##### 3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	EZ	EZ-EMC	/	N/A	N/A
2	EMI Test Receiver	R&S	ESPI	101840	2021-06-22	2022-06-21
3	Artificial Mains	SCHWARZBECK	NSLK8127	8127716	2021-06-22	2022-06-21
4	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2021-06-22	2022-06-21
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2021-10-19	2022-10-18

##### 3.1.2. Block Diagram of Test Setup



##### 3.1.3. Test Standard

###### Power Line Conducted Emission Limits (Class B)

Frequency (MHz)			Limit (dB $\mu$ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

##### 3.1.4. EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

### 3.1.5. Operating Condition of EUT

3.1.5.1. Setup the EUT as shown on Section 3.1.2

3.1.5.2. Turn on the power of all equipments.

3.1.5.3. Let the EUT work in measuring Lighting and measure it.

### 3.1.6. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.


The frequency range from 150kHz to 30MHz is investigated

### 3.1.7. Test Results

**PASS.**


The test result please refer to the next page.

<b>Test Model</b>	OME59B	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	23.9°C, 53% RH	<b>Test Engineer</b>	Jay Li
<b>Pol</b>	Line	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	45.06	10.24	55.30	65.79	-10.49	QP	
2		0.1539	25.06	10.24	35.30	55.79	-20.49	AVG	
3		0.2378	40.44	10.22	50.66	62.17	-11.51	QP	
4		0.2378	19.80	10.22	30.02	52.17	-22.15	AVG	
5	*	0.2880	40.14	10.20	50.34	60.58	-10.24	QP	
6		0.2880	22.71	10.20	32.91	50.58	-17.67	AVG	
7		10.0129	34.90	10.20	45.10	60.00	-14.90	QP	
8		10.0129	24.28	10.20	34.48	50.00	-15.52	AVG	
9		13.5304	37.02	10.20	47.22	60.00	-12.78	QP	
10		13.5304	25.14	10.20	35.34	50.00	-14.66	AVG	
11		20.0806	36.68	10.20	46.88	60.00	-13.12	QP	
12		20.0806	26.26	10.20	36.46	50.00	-13.54	AVG	

<b>Test Model</b>	OME59B	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	23.9°C, 53% RH	<b>Test Engineer</b>	Jay Li
<b>Pol</b>	Neutral	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	45.66	10.24	55.90	66.00	-10.10	QP	
2		0.1500	25.76	10.24	36.00	56.00	-20.00	AVG	
3		0.1882	43.38	10.23	53.61	64.12	-10.51	QP	
4		0.1882	25.39	10.23	35.62	54.12	-18.50	AVG	
5		0.3232	37.10	10.20	47.30	59.62	-12.32	QP	
6		0.3232	17.93	10.20	28.13	49.62	-21.49	AVG	
7		0.7630	32.89	10.20	43.09	56.00	-12.91	QP	
8		0.7630	21.75	10.20	31.95	46.00	-14.05	AVG	
9		0.9499	33.55	10.20	43.75	56.00	-12.25	QP	
10		0.9499	20.85	10.20	31.05	46.00	-14.95	AVG	
11		20.5442	34.83	10.20	45.03	60.00	-14.97	QP	
12		20.5442	25.00	10.20	35.20	50.00	-14.80	AVG	

Note: Pre-Scan all mode, Thus record worse case mode result in this report.  
Margin=Reading level + Correct - Limit

## 3.2. Radiated emission Measurement

### 3.2.1. Test Equipment


The following test equipments are used during the radiated emission measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	EZ	EZ-EMC	/	N/A	N/A
2	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2020-08-05	2022-08-04
3	Positioning Controller	MF	MF7082	MF78020803	2021-06-22	2022-06-21
4	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2020-07-26	2022-07-25
5	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-07-02	2022-07-01
6	EMI Test Receiver	R&S	ESR 7	101181	2021-06-22	2022-06-21
7	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2021-11-21	2022-11-20
8	Broadband Preamplifier	/	BP-01M18G	P190501	2021-06-22	2022-06-21
9	RF Cable-R03m	Jye Bao	RG142	CB021	2021-06-22	2022-06-21
10	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2021-06-22	2022-06-21
11	EMI Test Software	AUDIX	E3	/	N/A	N/A

### 3.2.2. Block Diagram of Test Setup



Below 1GHz



Above 1GHz

### 3.2.3. Radiated Emission Limit (Class B)

Limits for Radiated Disturbance Below 1GHz

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46
960 ~ 1000	3	500	54

Remark: (1) Emission level  $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$   
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Limits for Radiated Emission Above 1GHz

Frequency (MHz)	Distance (Meters)	Peak Limit ( $\text{dB}\mu\text{V/m}$ )	Average Limit ( $\text{dB}\mu\text{V/m}$ )
Above 1000	3	74	54

\*\*\*Note: The lower limit applies at the transition frequency.

### 3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Lighting and measure it.

### 3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.

The bandwidth of the EMI test receiver is set at 120kHz, 300kHz.  
 The frequency range from 30MHz to 1000MHz is checked.


### 3.2.7. Radiated Emission Noise Measurement Result

**PASS.**

The scanning waveforms please refer to the next page.

<b>Test Model</b>	OME59B	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	23.8°C, 55% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Jay Li	<b>Test Voltage</b>	AC 120V/60Hz

80.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1		32.1231	26.46	8.20	34.66	40.00	-5.34	QP			
2	*	40.3641	25.42	11.44	36.86	40.00	-3.14	QP			
3		51.3230	19.43	13.13	32.56	40.00	-7.44	QP			
4		72.9425	21.51	10.65	32.16	40.00	-7.84	QP			
5		108.8377	19.72	11.67	31.39	43.50	-12.11	QP			
6		165.4142	12.56	12.31	24.87	43.50	-18.63	QP			

<b>Test Model</b>	OME59B	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	23.8°C, 55% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Jay Li	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree	Comment
1	*	32.1090	19.90	12.37	32.27	40.00	-7.73	QP		
2		40.5414	14.47	13.42	27.89	40.00	-12.11	QP		
3		75.5125	16.62	9.93	26.55	40.00	-13.45	QP		
4		109.2679	21.22	12.84	34.06	43.50	-9.44	QP		
5		177.5092	16.29	10.64	26.93	43.50	-16.57	QP		
6		260.8294	12.28	13.03	25.31	46.00	-20.69	QP		

Note: Pre-Scan all mode, Thus record worse case mode result in this report.  
Margin=Reading level + Factor - Limit



#### **4. TEST SETUP PHOTOGRAPHS OF EUT**

Please refer to separated files for Test Setup Photos of the EUT.

#### **5. EXTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separated files for External Photos of the EUT.

#### **6. INTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF TEST REPORT-----