

User Manual

Narwal Wet Dry Vacuum S10 Pro

MAGNETIC TUBES

CONTENTS

Dead-end

There is no further review activity. A survey instrument reports the results, plus comments on responses. The results of the survey are then used by the agency planning the review activity.

© 2006 The Authors
Journal compilation © 2006 Blackwell Publishing Ltd

1. The first step is to identify the problem. This involves understanding the current situation and what needs to be changed.

The data in this paper were collected from 1998 to 2001. The data were collected from the following sources:

© 2001 Blackwell Science Ltd *Journal of Internal Medicine* 250: 111–117



1. **အခြေခံအားဖြည့်ဆည်းပေးခြင်း**
 2. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 3. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 4. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 5. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 6. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 7. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 8. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 9. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**
 10. **အားလုံးအတွက်အကျိုးရှိစေခြင်း**

[illegible]


10

Product At A Glance

Check List
Wet Dry Macroms



Self-cleaning mode



How to Use

First-time Use

[View our most all time popular](#)

Insert the tip of the handle with the sharp end up and push it into the plastic. When the handle is firm without twisting.



Language Rights Institute

On the initial startup, a language web browser page will appear. Press the **OK** button on the left screen or the **enter** key on the keyboard to merge the content on the right.

How to change the growth of

After the well cleaning tool is connected to a power supply, just that well dry-run at the same. When it begins drying out, the power stops the charging situation, and charging starts.



Wet Dry Micromix



Downloaded from <http://ajphaphysocpharm.sagepub.com> at
UNIVERSITY OF CALIFORNIA LIBRARY on June 11, 2015

© 2005 Blackwell Publishing Ltd, *Journal of Internal Medicine* 258: 103–110

Building the class will take time to open it up.



© 2006 Blackwell Publishing Ltd

Expenditure on advertising is not a fixed cost. It can be varied according to the needs of the business.



How to print and start the machine

Remove the top cover from the left side of the base. Hold your  Power On/Off button with your index finger and gently press and hold it in for 10 seconds (about when it beeps). You can also disconnect the remote and manual controls.  Power On/Off button is on the remote. When the remote is held in front of you, it is right, you can not hold the wheel under the door when you are in the house. Then you can hold it 10 seconds (about when it beeps) and hold it.



Instructions for Use

*Note: when the amount is not defined and the answer is only, you only press the button to come up the answer.


Buttons	Status	Remarks
Press the Off button	When leaving the room	Start power, power on delay
	When entering the room	Power on timer for 10 power off
	During self-cleaning activity	Start power, and the power on

	When cleaning the floor	Short press: select the mode (Smart/Turbo/Quick/Normal) Press and hold: start the hand movement release to end the movement
	During self-cleaning (except self-cleaning)	Short press: start drying only
	During charging with the station on	Press and hold for 15s start self-cleaning only
	During charging with the station on	Short press: start self-cleaning and drying in sequence Press and hold for 15s start self-cleaning only
	Changing the mode while	Press the mode button and self-cleaning button simultaneously to change the screen language

About the screen



Screen Mode



Cleaning and Maintenance

Suggested Maintenance Cycle

Main part	Part	Suggested maintenance cycle
Main Unit	Dry water tank	Clean after every use
	Floor	Clean after every use and replace every 3 months
	Roller brush cover	Cleaning daily or demand
	Roller brush	Cleaning daily or demand and replace every 3-6 months
	Roller	Cleaning daily or demand

Self-cleaning time

Cleaning time	Cleaning daily or demand
---------------	--------------------------

Maintenance Methods

Dry water tank

How to replace the water tank

Remove the dry water tank. Press and hold the water tank button.




Self-cleaning and drying

Start self-cleaning and drying

Press the mode button to start self-cleaning and drying. Press the Self-Cleaning button to start self-cleaning and drying. Press the Self-Cleaning button to start self-cleaning and drying. Press the Self-Cleaning button to start self-cleaning and drying.

Note: If the machine prompts that the floor water tank is short of water, please check the floor water tank to ensure the self-cleaning and drying.



Tip

Check regularly on the level

If the base is slightly tilted, it will even when the floor is not horizontal. It is possible several hundred self-cleaning cycles later the floor is not properly cleaned. Check the leveling feet under the plate for the above-mentioned.



Cleaning tray of the self-cleaning base

Check regularly on the level

Remove the cleaning tray from the self-cleaning base.

Clean the tray with a piece of cloth.



Not dry vacuum and self-cleaning base

To avoid an unpleasant vacuum, always disconnect the vacuum cleaner before use.

Before using the self-cleaning base, please turn off the machine and plug the power cord.

Use a clean and dry cloth to wipe clean the machine and the base and prevent water damage to electrical components.

Make sure that the vacuum cleaner is not used at the self-cleaning position for the first step.



1. Check the vacuum cleaner.



2. Check the self-cleaning base.

3. Check the self-cleaning base.

4. Check the self-cleaning base.

5. Check the self-cleaning base.

6. Check the self-cleaning base.

7. Check the self-cleaning base.

8. Check the self-cleaning base.

Problem Analysis and Troubleshooting

FAQ

In case of any fault when the product is working, the service or fault group in the column on the right, please refer to the following table.

Problem	Description	Possible causes	Solution
Unable to turn on or charge the machine	The product cannot start charging. It may be not properly connected to the power supply.	The self-cleaning base is not connected to the power supply.	Make sure the self-cleaning base is properly connected to the power supply. Check the power cord and the self-cleaning base for any damage.
		The power supply is not working.	Check the power supply and the power cord. Make sure the power supply is working properly.
		The self-cleaning base is not working properly.	Check the self-cleaning base for any damage. Make sure the self-cleaning base is working properly.
Unable to start cleaning	The self-cleaning base is not working properly. It may be not properly connected to the power supply.	The power supply is not working.	Check the power supply and the power cord. Make sure the power supply is working properly.
Part not installed or not in place	The self-cleaning base is not working properly. It may be not properly connected to the power supply.	The self-cleaning base is not working properly.	Check the self-cleaning base for any damage. Make sure the self-cleaning base is working properly.
		The self-cleaning base is not working properly.	Check the self-cleaning base for any damage. Make sure the self-cleaning base is working properly.
Full dirty water tank	The self-cleaning base is not working properly. It may be not properly connected to the power supply.	The self-cleaning base is not working properly.	Check the self-cleaning base for any damage. Make sure the self-cleaning base is working properly.
		The self-cleaning base is not working properly.	Check the self-cleaning base for any damage. Make sure the self-cleaning base is working properly.
Clean water tank short of water	The self-cleaning base is not working properly. It may be not properly connected to the power supply.	The self-cleaning base is not working properly.	Check the self-cleaning base for any damage. Make sure the self-cleaning base is working properly.
		The self-cleaning base is not working properly.	Check the self-cleaning base for any damage. Make sure the self-cleaning base is working properly.

Stuck roller brush	The product pauses and broadcasts "Roller brush stuck. Please clean it." The outer ring of the screen keeps flashing red.	The roller brush fails to work properly because it is stuck by hair or other foreign objects.	Please remove the roller brush to check if there is any foreign matter blocking it. If yes, clean the roller brush and put it back in place.
High dirt level	The product broadcasts "Dirty roller brush detected. You are recommended to put it back to the base for self-cleaning." The outer ring of the screen flashes red for 5s.	The product's dirt sensor detects a consistently high dirt level.	Place the product back onto the base for self-cleaning. If the problem persists after self-cleaning, you can try to clean the dirty water pipe with the cleaning brush.
Pipe clogging	The product pauses and broadcasts "Pipe clogged. Please manually clean the pipe and the roller brush." The outer ring of the screen keeps flashing red.	The product's pipe is clogged.	Use the cleaning brush to clean the pipe and the dirt suction port.
Base overflowing	Self-cleaning pauses and the product broadcasts "Base overflowing. Please clean and air dry the base." The outer ring of the screen keeps flashing red.	Lots of water builds around the base and runs across it.	To avoid electric shock, the product and the base will turn themselves off and report the problem. Please clean and air dry the base timely and contact customer service.

Fault Warning

When the product reports the error on the screen or by voice, it indicates that there is a fault. Please use your phone to scan the QR code and contact customer service for help.

Voice prompt	Remedies
Operation fault. Please contact customer service.	Please contact customer service or technical support for more help.

1. If the troubleshooting steps provided in the table above are not effective, you can contact Customer Service via email or reach out to your local purchase channel for contact information. Alternatively, you can scan the QR code on the official website to access more information and assistance.

2. Please use the product as instructed in the manual, and any loss caused by improper use shall be borne by the user.