

	SAR TEST REPORT				
Report Reference No:	CTL1605271944F-SAR				
FCC ID	2AIJ4T-M1				
Compiled by		T. WALLOW			
(position+printed name+signature).:	File administrators Jacky Chen	Jack Oren			
Supervised by		Allan Maria			
(position+printed name+signature).:	Project Engineer Allen Wang	Mien Vang			
Approved by		1,12.			
(position+printed name+signature).:	Manager Tracy Qi	hunder			
Date of issue:	June 18, 2016				
Authorized Lab.	Shenzhen CTL Testing Technol	ogy Co., Ltd.			
Address	Floor 1-A, Baisha Technology Nanshan District, Shenzhen, Chin	Park, No.3011, Shahexi Road, a 518055			
Applicant's name	Quanzhou HengLiDa Tel-Equip	nent Co.,Ltd.			
Address	659 Xingpu, Xiamei Town, Nan'an City, Fujian Province,China				
Test specification:					
	IEEE 1528:2013				
Standard	47CFR §2.1093				
TRF Originator	Shenzhen CTL Testing Technology Co., Ltd.				
Master TRF:	Dated 2014-01				
Shenzhen CTL Testing Technology (This publication may be reproduced in Shenzhen CTL Testing Technology Co material. Shenzhen CTL Testing Techn liability for damages resulting from the placement and context.	Co., Ltd. All rights reserved. whole or in part for non-commercia ., Ltd. is acknowledged as copyrigh ology Co., Ltd. takes no responsib reader's interpretation of the reproc	I purposes as long as the at owner and source of the ility for and will not assume duced material due to its			
Test item description:	Two way radio				
Trade Mark:	<i><i>BELIDA</i></i>				
Manufacturer:	Quanzhou HengLiDa Tel-Equip	ment Co.,Ltd.			
Model/Type reference:	T-M1				
Listed Models:	/				
Ratings	DC 3.70V				
EUT Type:	Production Unit				
Exposure category:	General /Uncontrolled environment				
Result:	PASS				

TEST REPORT

Test Report No. :	CTL16052	June 18, 2016 Date of issue
Equipment under Test	: Two	way radio
Model /Type	: T-M1	
Listed Models	: /	
Applicant	: Quar	nzhou HengLiDa Tel-Equipment Co.,Ltd.
Address	: 659) China	Kingpu, Xiamei Town, Nan'an City, Fujian Province, a
Manufacturer	: Quar	nzhou HengLiDa Tel-Equipment Co.,Ltd.
Address	: 659) China	Kingpu, Xiamei Town, Nan'an City, Fujian Province, a
She	SE L	E CAR
Test Result:		PASS
(D)	(JAC)	

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. 7 Testing Techno

** Modifited History **

Revison	Description	Issued Data	Remark
Revsion 1.0	Initial Test Report Release	2016-06-18	Tracy Qi



Page 4 of 56

Contents

<u>1.</u>	TEST STANDARDS	5
2	SUMMARY	6
<u></u>		•
2.1.	General Remarks	6
2.2.	Product Description	6
2.3.	Summary SAR Results	6
2.4.	Equipment under Test	7
2.5.	EUT operation mode	7
2.6.	TEST Configuration	7
2.7.	EUT configuration	7
<u>3.</u>	TEST ENVIRONMENT	8
3.1.	Address of the test laboratory	8
3.2.	Test Facility	8
3.3.	Environmental conditions	8
3.4.	SAR Limits	8
3.5.	Equipments Used during the Test	9
<u>4.</u>	SAR MEASUREMENTS SYSTEM CONFIGURATION	10
4.1.	SAR Measurement Set-up	10
4.2	DASY5 E-field Probe System	11
43	Phantoms	11
4.0.	Device Holder	12
45	Scanning Procedure	12
46	Data Storage and Evaluation	13
47	SAR Measurement System	14
4.8	Dielectric Performance	15
4.0.	System Check	16
4.10.	Measurement Procedures	17
E	TEST CONDITIONS AND RESULTS	2.2
<u>5.</u>	TEST CONDITIONS AND RESULTS	
5.1.	Conducted Power Results	22
5.2.	Transmit Antennas	22
5.3.	Standalone SAR Test Exclusion Considerations	22
5.4.	Standalone SAR Test Exclusion Considerations and Estimated SAR	23
5.5.	Test reduction procedure	23
5.6.	SAR Measurement Results	23
5.7.	Simultaneous TX SAR Considerations	24
5.8.	SAR Measurement Variability	24
5.9.	Measurement Uncertainty (300-3GHz)	25
5.10.	System Check Results	29
5.11.	SAR Test Graph Results	31
<u>6.</u>	CALIBRATION CERTIFICATE	33
6.1.	Probe Calibration Ceriticate	33
6.2.	D450V3 Dipole Calibration Certificate	44
6.3.	DAE4 Calibration Certificate	52
<u>7.</u>	TEST SETUP PHOTOS	55

1. <u>TEST STANDARDS</u>

The tests were performed according to following standards:

<u>IEEE 1528-2013 (2014-06):</u> Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques

<u>IEEE Std. C95-3 (2002)</u>: IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave

<u>IEEE Std. C95-1 (1992)</u>: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

<u>IEC 62209-2 (2010)</u>: Human exposure to radio frequency fields from hand-held and bodymounted wireless communication devices. Human models, instrumentation, and procedures. Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)

<u>KDB 865664D01v01r04 (August 7, 2015)</u>: SAR Measurement Requirements for 100 MHz to 6 GHz <u>KDB 865664D02v01r02 (October 23, 2015)</u>: RF Exposure Compliance Reporting and Documentation Considerations

KDB 447498 D01 General RF Exposure Guidance v06 (October 23, 2015): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2015 October TCB Workshop: SAR may be scaled if radio is tested at lower power without overheating as invalid SAR results cannot be scaled to compensate for power droop



2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	•••	June 12, 2016
Testing commenced on	•••	June 16, 2016
Testing concluded on	:	June 16, 2016

2.2. Product Description

EUT Name	:	Two way radio
Model Number	:	T-M1
Trade Mark	:	<i><i>ELIDA</i></i>
EUT function description	•	Please reference user manual of this device
Power supply	:	DC 3.70V from battery
Operation frequency range	:	462.55 MHz - 462.725 MHz (GMRS)
Modulation type		FM (GMRS)
RF Rated Output power	:	1W (GMRS)
Emission type	-	F3E (GMRS)
Antenna Type	-	External and Integrated
Antenna Gain	:	2dBi (GMRS)
Date of Receipt	:	2016/06/12
Device Type	:	Portable
Sample Type	:	Prototype Unit
Exposure category:	•	General exposure / Uncontrolled environment
Test Frequency:	:	462.6375 MHz
Frequency list	1	

Frequency list

Channel	Frequency(MHz)	Туре
1	462.5500	GMRS
2	462.5625	GMRS
3	462.5750	GMRS
4	462.5875	GMRS
5	462.6000	GMRS
6	462.6125	GMRS
7	462.6250	GMRS
8	462.6375	GMRS
9	462.6500	GMRS
10	462.6625	GMRS
11	462.6750	GMRS
12	462.6875	GMRS
13	462.7000	GMRS
14	462.7125	GMRS
15	462.7250	GMRS

2.3. Summary SAR Results

The maximum of results of SAR found during testing are follows:

Mode	Channel Frequency Position		Maximum Report SAR Results (W/kg)		
woue	Separation	(MHz)	FUSICION	100% duty cycle	50% duty cycle
GMRS	12.5KHz	462.6375	Face-held	1.432	0.716
GMRS	12.5KHz	462.6375	Body-Worn	2.349	1.175

<Highest Reported standalone SAR Summarv>

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

2.4. Equipment under Test

Power supply system utilised

Power supply voltage	:	0	120V / 60 Hz	0	115V / 60Hz
		0	12 V DC	0	24 V DC
			Other (specified in blank bel	ow	

DC 3.70 V

2.5. EUT operation mode

The spatial peak SAR values were assessed for UHF systems. Battery and accessories shell be specified by

the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain

uniform power output.

2.6. TEST Configuration

Face-Held Configuration

Face-held Configuration- per FCC KDB447498 page 22: "A test separation distance of 25 mm must be applied for in-front-of the face SAR test exclusion and SAR measurements."

Body-worn Configuration

Body-worn measurements-per FCC KDB447498 page 22 "When body-worn accessory SAR testing is required, the body-worn accessory requirements in section 4.2.2 should be applied. PTT two-way radios that support held-to-ear operating mode must also be tested according to the exposure configurations required for handsets. This generally does not apply to cellphones with PTT options that have already been tested in more conservative configurations in applicable wireless modes for SAR compliance at 100% duty factor."

2.7. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

Accessory name	Internal Identification	Model	Description	Remark
Sample	S1	T-M1	Sample with Internal Antenna and Internal Belt Clip	performed
Battery	B1	602660P	3.7V, 1100mAh integrated	performed
Audio Accessories	AC1	T-M1	Earphone with PPT	performed

AE ID: is used to identify the test sample in the lab internally.

3. <u>TEST ENVIRONMENT</u>

3.1. Address of the test laboratory

Shenzhen Yidajietong Test Technology Co., Ltd.

3/F., Building 12, Shangsha Innovation & Technology Park, Futian District, Shenzhen, Guangdong, China

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7547

The Testing and Technology Center for SHENZHEN YIDA JIETONG INFORMATION TECHNOLOGY CO., LTD has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: March, 2015. Valid time is until March, 2018.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	18-25 ° C
	1 Vator
Humidity:	40-65 %
	A COMPANY
Atmospheric pressure:	950-1050mbar

3.4. SAR Limits

	SAR (W/kg)			
Exposure Limits	(General Population /	(Occupational /		
Exposure Linits	Uncontrolled Exposure	Controlled Exposure		
	Environment)	Environment)		
Spatial Average	0.08	0.4		
(averaged over the whole body)	0.00	0:4		
Spatial Peak	1.60	8.0		
(averaged over any 1 g of tissue)	1.00	8.0		
Spatial Peak	sting 10	20.0		
(hands/wrists/feet/ankles averaged over 10 g)	SUILING H.U	20.0		

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

3.5. Equipments Used during the Test

				Calib	ration
Test Equipment	Manufacturer Type/Model Serial Number		Last	Calibration	
				Calibration	Interval
Data Acquisition Electronics DAEx	SPEAG	DAE4	1315	2015/07/22	1
E-field Probe	SPEAG	EX3DV4	3842	2015/08/26	1
System Validation Dipole D450V3	SPEAG	D450V3	1072	2015/11/25	3
Network analyzer	Agilent	8753E	US37390562	2016/03/05	1
Dielectric Probe Kit	Agilent	85070E	US44020288	/	/
Power meter	Agilent	E4417A	GB41292254	2015/12/15	1
Power sensor	Agilent	8481H	MY41095360	2015/12/15	1
Power sensor	Agilent	8481H	MY41095361	2015/12/15	1
Signal generator	IFR	2032	203002/100	2015/10/12	1
Amplifier	AR	75A250	302205	2015/10/12	1

Note:

- 1) Per KDB865664D01 requirements for dipole calibration, the test laboratory has adopted three year extended calibration interval. Each measured dipole is expected to evalute with following criteria at least on annual interval.
 - a) There is no physical damage on the dipole;
 - b) System check with specific dipole is within 10% of calibrated values;
 - c) The most recent return-loss results, measued at least annually, deviates by no more than 20% from the previous measurement;
 - d) The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within 50 Ω from the provious measurement.
- 2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

Testing Technolog

4. SAR Measurements System configuration

4.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, ADconversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

A unit to operate the optical surface detector which is connected to the EOC.

The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.

The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.

DASY5 software and SEMCAD data evaluation software.

Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.

The generic twin phantom enabling the testing of left-hand and right-hand usage.

The device holder for handheld Mobile Phones.

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles allowing to validate the proper functioning of the system.



4.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ES3DV3 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

Probe Specification

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	 ± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)
Dynamic Range	5 μW/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of Mobile Phones
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI
Isotropic E-Field Probe	O NUR CILINA -

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:

4.3. Phantoms

Phantom for compliance testing of handheld andbody-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI isfully compatible with the IEC 62209-2 standard and all known tissuesimulating liquids. ELI has been optimized regarding its performance and can beintegrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurementgrids, by teaching three points. The phantom is compatible with all SPEAGdosimetric probes and dipoles.

4.4. Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the DASY system.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

Device holder supplied by SPEAG

4.5. Scanning Procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. \pm 5 %.

Page 13 of 56

The "surface check" measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1 mm). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^{\circ}$.)

Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot.Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

Zoom Scan

Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by 7x7x7 points within a cube whose base is centered around the maxima found in the preceding area scan.

Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as: • maximum search • extrapolation • boundary correction • peak search for averaged SAR During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 7x7x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1g and 10g cubes.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube 7x7x7 scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

4.6. Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters: - Sensitivity

- Conversion factor

- Diode compression point

Normi, ai0, ai1, ai2 ConvFi Dcpi

Device parameters: - Frequency	f
Device parameters Trequency	I
- Crest factor	C
Media parameters: - Conductivity	σ
- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

With Vi = compensated signal of channel i(i = x, y, z)Ui = input signal of channel i(i = x, y, z)cf = crest factor of exciting field(DASY parameter)dcpi = diode compression point(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

		$E - \text{fieldprobes}: \qquad E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$ $H - \text{fieldprobes}: \qquad H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{r}$
With	Vi	= compensated signal of channel i $(i = x, y, z)$
	Normi	= sensor sensitivity of channel i (i = x, y, z) [mV/(V/m)2] for E-field Probes
	ConvF	= sensitivity enhancement in solution
	aij	= sensor sensitivity factors for H-field probes
	f	= carrier frequency [GHz]
	Ei	= electric field strength of channel i in V/m
	Hi	= magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_y^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{c}{1}$$

			PILU
with	SAR	= local specific absorption rate in mW/g	10
	Etot	= total field strength in V/m	
	σ	= conductivity in [mho/m] or [Siemens/m]	
	ρ	= equivalent tissue density in g/cm3	

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

4.7. SAR Measurement System

The SAR measurement system being used is the DASY5 system, the system is controlled remotely from a PC, which contains the software to control the robot and data acquisition equipment. The software also displays the data obtained from test scans.

In operation, the system first does an area (2D) scan at a fixed depth within the liquid from the inside wall of the phantom. When the maximum SAR point has been found, the system will then carry out a 3D scan centred at that point to determine volume averaged SAR level.

4.7.1 Tissue Dielectric Parameters for Head and Body Phantoms

The liquid is consisted of water, salt, Glycol, Sugar, Preventol and Cellulose. The liquid has previously been proven to be suited for worst-case. It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB865664.

Target Frequency	He	ad	Body		
(MHz)	٤r	σ(S/m)	٤r	σ(S/m)	
150	52.3	0.76	61.9	0.80	
300	45.3	0.87	58.2	0.92	
450	43.5	0.87	56.7	0.94	
835	41.5	0.90	55.2	0.97	
900	41.5	0.97	55.0	1.05	
915	41.5	0.98	55.0	1.06	
1450	40.5	1.20	54.0	1.30	
1610	40.3	1.29	53.8	1.40	
1800-2000	40.0	1.40	53.3	1.52	
2450	39.2	1.80	52.7	1.95	
3000	38.5	2.40	52.0	2.73	
5800	35.3	5.27	48.2	6.00	

(ϵ_r = relative permittivity, σ = conductivity and ρ = 1000 kg/m³)

4.8. Dielectric Performance

Dielectric performance of Head and Body tissue simulating liquid.

.VI

Mixture %	Frequency (Brain) 450MHz
Water	38.56
Sugar	56.32
Salt	3.95
Preventol	0.10
Cellulose	1.07
Dielectric Parameters Target Value	f=450MHz ε _r =43.5 σ=0.87

Composition	of the Head	Tissue Equ	ivalent Matte
-------------	-------------	-------------------	---------------

Composition of the Body	Tissue Equivalent Matter
Mixture %	Frequency (Brain) 450MHz
Water	56.16
Sugar	46.78
Salt	1.49
Preventol	0.10
Cellulose	0.47
Dielectric Parameters Target Value	f=450MHz ε _r =56.7 σ=0.94

Ticcuo	Measured	Target	Tissue		Measure	ed Tissue		Liquid	
Туре	Frequency (MHz)	٤r	σ	٤r	Dev. %	σ	Dev. %	Temp.	Test Data
	450	43.5	0.87	45.6	4.83%	0.90	3.45%	22.2	
450H	462	43.5	0.87	45.3	4.14%	0.89	2.30%	dogroo	2016-06-16
	463	43.5	0.87	45.3	4.14%	0.89	2.30%	uegree	
	450	56.7	0.93	58.1	2.47%	0.95	2.15%	22.2	
450B	462	56.7	0.93	57.7	1.76%	0.95	2.15%	ZZ.Z	2016-06-16
	463	56.7	0.93	57.7	1.76%	0.95	2.15%	uegree	

4.9. System Check

The purpose of the system check is to verify that the system operates within its specifications at the decice test frequency. The system check is simple check of repeatability to make sure that the system works correctly at the time of the compliance test;

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system (±10 %).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.

The output power on dipole port must be calibrated to 30 dBm (1000mW) before dipole is connected.

Justification for Extended SAR Dipole Calibrations

Referring to KDB 865664D01V01r04, if dipoles are verified in return loss (<-20dB, within 20% of prior calibration), and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended. While calibration intervals not exceed 3 years.

System Check in Head Tissue Simulating Liquid

Freq	Test Date	Dielectric Parameters		Temp	250mW Measured		1W Nor	malized	1W 1	Farget	Limit Devi	(±10% ation)
		εr	σ(s/m)		SAR _{1g}	SAR _{10g}						
450MHz	2016/06/16	45.6	0.90	22.2	1.180	0.785	4.720	3.140	4.800	3.190	-1.67%	-1.57%

System Check in Body Tissue Simulating Liqu	id
---	----

Freq	Test Date	Dielectric Parameters		Temp	250mW Measured		1W Normalized		1W Target		Limit (±10% Deviation)	
		εr	σ(s/m)		SAR _{1g}	SAR _{10g}	SAR _{1g}	SAR _{10g}	SAR _{1g}	SAR _{10g}	SAR _{1g}	SAR _{10g}
450MHz	2016/06/16	58.1	0.95	22.2	1.130	0.768	4.520	3.072	4.690	3.080	-3.62%	-0.26%

Note:

1. The graph results see system check.

2. Target Values used derive from the calibration certificate

4.10. Measurement Procedures

Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in Picture 11

Step 1: The tests described in 11.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (fc) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in Chapter 8),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.
- d) If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 11.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.

Picture 11 Block diagram of the tests to be performed

Picture 12 Block diagram of the tests to be performed

Measurement procedure

The following procedure shall be performed for each of the test conditions (see Picture 11) described in 11.1:

- a) Measure the local SAR at a test point within 8 mm or less in the normal direction from the inner surface of the phantom.
- b) Measure the two-dimensional SAR distribution within the phantom (area scan procedure). The boundary of the measurement area shall not be closer than 20 mm from the phantom side walls. The distance between the measurement points should enable the detection of the location of local maximum with an

accuracy of better than half the linear dimension of the tissue cube after interpolation. A maximum grip spacing of 20 mm for frequencies below 3 GHz and (60/f [GHz]) mm for frequencies of 3GHz and greater is recommended. The maximum distance between the geometrical centre of the probe detectors and the inner surface of the phantom shall be 5 mm for frequencies below 3 GHz and $\delta ln(2)/2$ mm for frequencies of 3 GHz and greater, where δ is the plane wave skin depth and ln(x) is the natural logarithm. The maximum variation of the sensor-phantom surface shall be ±1 mm for frequencies below 3 GHz and ±0.5 mm for frequencies of 3 GHz and greater. At all measurement points the angle of the probe with respect to the line normal to the surface should be less than 5°. If this cannot be achieved for a measurement distance to the phantom inner surface shorter than the probe diameter, additional measurement distance to the phantom inner surface shorter than the probe diameter, additional

- c) From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that are not within the zoom-scan volume; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR limit. This is consistent with the 2 dB threshold already stated;
- d) Measure the three-dimensional SAR distribution at the local maxima locations identified in step
- The horizontal grid step shall be (24 / f[GHz]) mm or less but not more than 8 mm. The minimum zoom e) size of 30 mm by 30 mm and 30 mm for frequencies below 3 GHz. For higher frequencies, the minimum zoom size of 22 mm by 22 mm and 22 mm. The grip step in the vertical direction shall be (8-f[GHz]) mm or less but not more than 5 mm, if uniform spacing is used. If variable spacing is used in the vertical direction, the maximum spacing between the two closest measured points to the phantom shell shall be (12 / f[GHz]) mm or less but not more than 4 mm, and the spacing between father points shall increase by an incremental factor not exceeding 1.5. When variable spacing is used, extrapolation routines shall be tested with the same spacing as used in measurements. The maximum distance between the geometrical centre of the probe detectors and the inner surface of the phantom shall be 5 mm for frequencies below 3 GHz and $\delta \ln(2)/2$ mm for frequencies of 3 GHz and greater, where δ is the plane wave skin depth and $\ln(x)$ is the natural logarithm. Separate grids shall be centered on each of the local SAR maxima found in step c). Uncertainties due to field distortion between the media boundary and the dielectric enclosure of the probe should also be minimized, which is achieved is the distance between the phantom surface and physical tip of the probe is larger than probe tip diameter. Other methods may utilize correction procedures for these boundary effects that enable high precision measurements closer than half the probe diameter. For all measurement points, the angle of the probe with respect to the flat phantom surface shall be less than 5. If this cannot be achieved an additional uncertainty evaluation is needed.
- f) Use post processing(e.g. interpolation and extrapolation) procedures to determine the local SAR values at the spatial resolution needed for mass averaging.

Measurement procedure

The following procedure shall be performed for each of the test conditions (see Picture 11) described in 11.1:

- g) Measure the local SAR at a test point within 8 mm or less in the normal direction from the inner surface of the phantom.
- h) Measure the two-dimensional SAR distribution within the phantom (area scan procedure). The boundary of the measurement area shall not be closer than 20 mm from the phantom side walls. The distance between the measurement points should enable the detection of the location of local maximum with an accuracy of better than half the linear dimension of the tissue cube after interpolation. A maximum grip spacing of 20 mm for frequencies below 3 GHz and (60/f [GHz]) mm for frequencies of 3GHz and greater is recommended. The maximum distance between the geometrical centre of the probe detectors and the inner surface of the phantom shall be 5 mm for frequencies below 3 GHz and of local maximum. The maximum variation of the sensor-phantom surface shall be ±1 mm for frequencies below 3 GHz and ±0.5 mm for frequencies of 3 GHz and greater. At all measurement points the angle of the probe with respect to the line normal to the surface should be less than 5°. If this cannot be achieved for a measurement distance to the phantom inner surface shorter than the probe diameter, additional measurement distance to the phantom inner surface shorter than the probe diameter, additional measurement distance to the phantom inner surface shorter than the probe diameter, additional measurement distance to the phantom inner surface shorter than the probe diameter, additional measurement distance to the phantom inner surface shorter than the probe diameter, additional measurement distance to the phantom inner surface shorter than the probe diameter, additional measurement distance
- From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that are not within the zoom-scan volume; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR limit. This is consistent with the 2 dB threshold already stated;
- j) Measure the three-dimensional SAR distribution at the local maxima locations identified in step
- k) The horizontal grid step shall be (24 / f[GHz]) mm or less but not more than 8 mm. The minimum zoom size of 30 mm by 30 mm and 30 mm for frequencies below 3 GHz. For higher frequencies, the minimum zoom size of 22 mm by 22 mm and 22 mm. The grip step in the vertical direction shall be (8-f[GHz]) mm or less but not more than 5 mm, if uniform spacing is used. If variable spacing is used in the vertical direction, the maximum spacing between the two closest measured points to the phantom shell shall be (12 / f[GHz]) mm or less but not more than 4 mm, and the spacing between father points shall increase by an incremental factor not exceeding 1.5. When variable spacing is used, extrapolation routines shall be tested with the same spacing as used in measurements. The maximum distance between the geometrical

centre of the probe detectors and the inner surface of the phantom shall be 5 mm for frequencies below 3 GHz and $\delta \ln(2)/2$ mm for frequencies of 3 GHz and greater, where δ is the plane wave skin depth and $\ln(x)$ is the natural logarithm. Separate grids shall be centered on each of the local SAR maxima found in step c). Uncertainties due to field distortion between the media boundary and the dielectric enclosure of the probe should also be minimized, which is achieved is the distance between the phantom surface and physical tip of the probe is larger than probe tip diameter. Other methods may utilize correction procedures for these boundary effects that enable high precision measurements closer than half the probe diameter. For all measurement points, the angle of the probe with respect to the flat phantom surface shall be less than 5. If this cannot be achieved an additional uncertainty evaluation is needed.

I) Use post processing(e.g. interpolation and extrapolation) procedures to determine the local SAR values at the spatial resolution needed for mass averaging.

Power Drift

To control the output power stability during the SAR test, DASY5 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 2 to Table 6 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

5. TEST CONDITIONS AND RESULTS

5.1. Conducted Power Results

<GMRS ERP Power>

According KDB 447498 D01 General RF Exposure Guidance v06ection 4.1 2) states that "Unless it is specified differently in the published RF exposure KDB procedures, these requirements also apply to test reduction and test exclusion considerations. Time-averaged maximum conducted output power applies to SAR and, as required by § 2.1091(c), time-averaged ERP applies to MPE. When an antenna port is not available on the device to support conducted power measurement, such as FRS and certain Part 15 transmitters with built-in integral antennas, the maximum output power allowed for production units should be used to determine RF exposure test exclusion and compliance."

SAR may be scaled if radio is tested at lower power without overheating as invalid SAR results cannot be scaled to compensate for power droop according to October 2015 TCB Workshop.

Modulation	Channel	Test Test		Measured Average ERP Power				
Туре	Separation	Channel	Frequency	(dBm)	(Watts)			
FM	12.5KHz	Ch8	462.6375	30.57	1.1402			

Manufacturing tolerance

GMRS									
GMRS (Average ERP Power)									
Frequency (MHz)	462.6375								
Target (dBm)	31.0								
Tolerance ±(dB)	1.0								

1 .

5.2. Transmit Antennas

. D.

5.3. Standalone SAR Test Exclusion Considerations

Per KDB447498 for standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by::

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] ·[√f(GHz)] ≤ 3.0 for 1-q SAR and \leq 7.5 for 10-q extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Standalone SAR test exclusion considerations												
Communication systemFrequency (MHz)ConfigurationMaximum Average Power (dBm)Separation Distance (mm)Calculation ResultSAR Exclusion ThresholdsStar Exclusion Exclusion Exclusion	andalone SAR xclusion											
CMPS 450 Head Face 32.0 25 24.6 3.0	no											
Body worn 32.0 5 123.1 3.0	no											

Remark:

- 1. When the minimum test separation distance is < 5 mm, a distance of 5 mm applied to determine SAR test exclusion
- 2. PTT devices standalone SAR test exclusion considerations should at 50% duty cycle.
- 3. CW mode states duty cycle is 100%, PTT mode states duty cycle is 50%.

5.4. Standalone SAR Test Exclusion Considerations and Estimated SAR

Per KDB447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion;

 (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√f(GHz)/x] W/kg for test separation distances \leq 50 mm;

where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

Per FCC KD B447498 D01, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the transmitting antenna in a specific a physical test configuration is ≤1.6 W/Kg.When the sum is greater than the SAR limit, SAR test exclusion is determined by the SAR to peak location separation ratio.

Ratio=
$$\frac{(SAR_1 + SAR_2)^{1.5}}{(SAR_1 + SAR_2)^{1.5}} < 0.04$$

Estimated stand alone SAR										
			Maximum Power	Soporation	Estimated SAR _{1-g} (W/kg)					
Communication system	Frequency (MHz)	Configuration	(including tune-up tolerance) (dBm)	Distance (mm)	100% Duty Cyele	50% Duty Cyele				
N/A	N/A	Head Face	N/A	N/A	N/A	N/A				
N/A	N/A	Body Worn	N/A	N/A	N/A	N/A				

Remark:

1. When the minimum test separation distance is < 5 mm, a distance of 5 mm applied to determine SAR test exclusion

5.5. Test reduction procedure

The maximum power level, Pmax,m, that can be transmitted by a device before the SAR averaged over a mass, m, exceeds a given limit, SAR_{lim}, can be defined. Any device transmitting at power levels below P_{max,m} can then be excluded from SAR testing. The lowest possible value for $P_{max,m}$ is: $P_{max,m} = SAR_{lim}^* \square m$.

5.6. SAR Measurement Results

It is determined by user manual for the distance between the EUT and the phantom bottom.

The distance is 10mm and just applied to the condition of body worn accessory.

The calculated SAR is obtained by the following formula:

Reported SAR=Measured SAR × 10^{(PTarget-PMeasured)/10}

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power

		Duty	Cycle
--	--	------	-------

Mode	Duty Cycle
GMRS	1:1

Test Fre	equency	Mada	Maximum Allowed	Measured	Test	Measurement SAR _{1-g} (W/Kg)		Power	Scaling	Repo SAF (W/	rted R _{1-g} kg)	SAR limit	Ref.
Channel	MHz	woae	Power (dBm)	(dBm)	Configuration	100% Duty Cycle	50% Duty Cycle	drift	Factor	100% Duty Cycle	50% Duty Cycle	1g (W/kg)	Plot
				The EUT displa	ay towards ground	d for 12.5 k	(Hz (Analo	og, face he	ld)				
Ch8	462.6375	5 PTT	32.00	30.57	Face Held	1.03	0.515	-0.17	1.39	1.432	0.716	1.60	1
				The EUT display	/ towards ground	for 12.5 K	Hz (Analog	g, Body-W	orn)				
Ch8	462.6375	5 PTT	32.00	30.57	Body Worn	1.69	0.845	-0.15	1.39	2.349	1.175	1.60	2

Note:

- 1. When devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, must be tested for SAR compliance using a conservative minimum test separation distance ≤ 5 mm to support compliance refer to KDB447498.
- 2. Except when area scan based 1-g SAR estimation applies, a zoom scan measurement is required at the highest peak SAR location determined in the area scan to determine the 1-g SAR. When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR refer to KDB865664D01v01r04.
- 3. PTT devices standalone SAR test exclusion considerations should at 50% duty cycle.

5.7. Simultaneous TX SAR Considerations

5.7.1 Introduction

Device with GMRS function only, no simultaneous transmission.

5.7.2 Evaluation of Simultaneous SAR

N/A

5.8. SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is \geq 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds

						Highost	First Repeated		
Frequency (MHz)	Mode	Carry Accessory	Audio Accessory	Test Position	Repeated SAR (yes/no)	Measured SAR _{1-g} (W/kg)	Measured SAR _{1-g} (W/kg)	Largest to Smallest SAR Ratio	
462.6375	PTT	S1	AC1	Body-worn	yes	1.69	1.60	0.95	

Remark:

1. PTT devices standalone SAR test exclusion considerations should at 50% duty cycle.

5.9. Measurement Uncertainty (300-3GHz)

		A	ccording to I	EC62209-1/IE	EE 15	28:201	3			
No.	Error Description	Туре	Uncertainty Value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measuremer	nt System			• 						
1	Probe calibration	В	5.50%	N	1	1	1	5.50%	5.50%	∞
2	Axial isotropy	В	4.70%	R	$\sqrt{3}$	0.7	0.7	1.90%	1.90%	œ
3	Hemispherical isotropy	В	9.60%	R	$\sqrt{3}$	0.7	0.7	3.90%	3.90%	œ
4	Boundary Effects	В	1.00%	R	$\sqrt{3}$	1	1	0.60%	0.60%	∞
5	Probe Linearity	В	4.70%	R	$\sqrt{3}$	1	1	2.70%	2.70%	œ
6	Detection limit	В	1.00%	R	$\sqrt{3}$	1	1	0.60%	0.60%	∞
7	RF ambient conditions- noise	в	0.00%	R	√3	1	1	0.00%	0.00%	œ
8	RF ambient conditions- reflection	HBY .	0.00%	R	√3	-11-	-1	0.00%	0.00%	~
9	Response time	В	0.80%	R	$\sqrt{3}$	1	1.	0.50%	0.50%	œ
10	Integration time	В	5.00%	R	$\sqrt{3}$	1	10	2.90%	2.90%	∞
11	RF ambient	В	3.00%	R	$\sqrt{3}$	1	1	1.70%	1.70%	∞
12	Probe positioned mech. restrictions	в	0.40%	R	√3	1	P	0.20%	0.20%	œ
13	Probe positioning with respect to phantom shell	B	2.90%	R	√3	10	5	1.70%	1.70%	œ
14	Max.SAR evalation	В	3.90%	Ing I	$\sqrt{3}$	1	1	2.30%	2.30%	œ
Test Sample	Related	-								
15	Test sample positioning	Α	1.86%	N	1	1	1	1.86%	1.86%	∞
16	Device holder uncertainty	А	1.70%	N	1	1	1	1.70%	1.70%	œ
17	Drift of output power	В	5.00%	R	$\sqrt{3}$	1	1	2.90%	2.90%	œ
Phantom and	J Set-up									
18	Phantom uncertainty	В	4.00%	R	$\sqrt{3}$	1	1	2.30%	2.30%	∞
19	Liquid conductivity (target)	В	5.00%	R	$\sqrt{3}$	0.64	0.43	1.80%	1.20%	∞
20	Liquid conductivity (meas.)	A	0.50%	N	1	0.64	0.43	0.32%	0.26%	œ
21	Liquid permittivity (target)	В	5.00%	R	√3	0.64	0.43	1.80%	1.20%	œ

22	Liquid cpermittivity (meas.)	A	0.16%	Ν	1	0.64	0.43	0.10%	0.07%	8
Combined standard uncertainty	$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i}$	$\overline{\iota_i^2}$	/	/	/	/	/	10.20%	10.00%	8
Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$		/	R	K=2	/	/	20.40%	20.00%	8

			Accordin	g to IEC6220	9-2/20	10				
No.	Error Description	Туре	Uncertainty Value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measuremer	nt System									
1	Probe calibration	В	6.20%	N	1	1	1	6.20%	6.20%	∞
2	Axial isotropy	В	4.70%	R 🥂	$\sqrt{3}$	0.7	0.7	1.90%	1.90%	œ
3	Hemispherical isotropy	В	9.60%	R	$\sqrt{3}$	0.7	0.7	3.90%	3.90%	∞
4	Boundary Effects	в	2.00%	R	$\sqrt{3}$	E	1	1.20%	1.20%	∞
5	Probe Linearity	В	4.70%	74R	$\sqrt{3}$	1	1	2.70%	2.70%	∞
6	Detection limit	В	1.00%	R	$\sqrt{3}$	1	14	0.60%	0.60%	∞
7	RF ambient conditions- noise	в	0.00%	CT R	√3	1	1	0.00%	0.00%	œ
8	RF ambient conditions- reflection	в	0.00%	R	√3	1	P	0.00%	0.00%	8
9	Response time	В	0.80%	R	$\sqrt{3}$	1	0	0.50%	0.50%	œ
10	Integration time	в	5.00%	R	$\sqrt{3}$	O	1	2.90%	2.90%	∞
11	RF Ambient	В	3.00%	ind Te	$\sqrt{3}$	1	1	1.70%	1.70%	∞
12	Probe positioned mech. restrictions	В	0.80%	R	√3	1	1	0.50%	0.50%	8
13	Probe positioning with respect to phantom shell	В	6.70%	R	$\sqrt{3}$	1	1	3.90%	3.90%	œ
14	Max.SAR Evalation	В	3.90%	R	$\sqrt{3}$	1	1	2.30%	2.30%	8
15	Modulation Response	В	2.40%	R	$\sqrt{3}$	1	1	1.40%	1.40%	8
Test Sample	Related									
16	Test sample positioning	А	1.86%	N	1	1	1	1.86%	1.86%	~
17	Device holder uncertainty	А	1.70%	N	1	1	1	1.70%	1.70%	∞
18	Drift of output power	В	5.00%	R	$\sqrt{3}$	1	1	2.90%	2.90%	∞
Phantom and	d Set-up									

19	Phantom uncertainty	В	6.10%	R	$\sqrt{3}$	1	1	3.50%	3.50%	8
20	SAR correction	В	1.90%	R	$\sqrt{3}$	1	0.84	1.11%	0.90%	8
21	Liquid conductivity (target)	В	5.00%	R	$\sqrt{3}$	0.64	0.43	1.80%	1.20%	8
22	Liquid conductivity (meas.)	А	0.50%	Ν	1	0.64	0.43	0.32%	0.26%	8
23	Liquid permittivity (target)	В	5.00%	R	$\sqrt{3}$	0.64	0.43	1.80%	1.20%	8
24	Liquid cpermittivity (meas.)	А	0.16%	Ν	1	0.64	0.43	0.10%	0.07%	8
25	Temp.Unc Conductivity	В	3.40%	R	$\sqrt{3}$	0.78	0.71	1.50%	1.40%	8
26	Temp.Unc Permittivity	В	0.40%	R	$\sqrt{3}$	0.23	0.26	0.10%	0.10%	8
Combined standard uncertainty	$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i}$	u_i^2	粒	/ 杰	1	1	/	12.90%	12.70%	8
Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$	24	D D D D	R	K=2			25.80%	25.40%	8

	Uncert	tainty o	of a System P	erformance C	Check	with D	ASY5 S	System		
			Accordin	ng to IEC6220	9-2/20	10		-		
No.	Error Description	Туре	Uncertainty Value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement System							0			-
1	Probe calibration	В	6.00%	N	1	1	Y	6.00%	6.00%	8
2	Axial isotropy	В	4.70%	R	$\sqrt{3}$	0.7	0.7	1.90%	1.90%	8
3	Hemispherical isotropy	В	0.00%	R	$\sqrt{3}$	0.7	0.7	0.00%	0.00%	8
4	Boundary Effects	В	1.00%	ind Te	$\sqrt{3}$	1	1	0.60%	0.60%	8
5	Probe Linearity	В	4.70%	R	$\sqrt{3}$	1	1	2.70%	2.70%	8
6	Detection limit	В	1.00%	R	$\sqrt{3}$	1	1	0.60%	0.60%	∞
7	RF ambient conditions- noise	В	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	œ
8	RF ambient conditions- reflection	В	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	8
9	Response time	В	0.80%	R	$\sqrt{3}$	1	1	0.50%	0.50%	8
10	Integration time	В	5.00%	R	$\sqrt{3}$	1	1	2.90%	2.90%	8
11	RF Ambient	В	3.00%	R	$\sqrt{3}$	1	1	1.70%	1.70%	8
12	Probe positioned mech. restrictions	В	0.80%	R	$\sqrt{3}$	1	1	0.50%	0.50%	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~

13	Probe positioning with respect to phantom shell	В	6.70%	R	$\sqrt{3}$	1	1	3.90%	3.90%	8
14	Max.SAR Evalation	В	3.90%	R	$\sqrt{3}$	1	1	2.30%	2.30%	8
15	Modulation Response	В	2.40%	R	$\sqrt{3}$	1	1	1.40%	1.40%	8
Test Sample	Related	•							1	
16	Test sample positioning	А	0.00%	Ν	1	1	1	0.00%	0.00%	8
17	Device holder uncertainty	А	2.00%	Ν	1	1	1	2.00%	2.00%	8
18	Drift of output power	В	3.40%	R	$\sqrt{3}$	1	1	2.00%	2.00%	8
Phantom and	l Set-up				-		-			
19	Phantom uncertainty	В	4.00%	R	$\sqrt{3}$	1	1	2.30%	2.30%	8
20	SAR correction	В	1.90%	R	$\sqrt{3}$	1	0.84	1.11%	0.90%	8
21	Liquid conductivity (meas.)	A	0.50%	N M	21	0.64	0.43	0.32%	0.26%	8
22	Liquid cpermittivity (meas.)	A	0.16%	R	1	0.64	0.43	0.10%	0.07%	8
23	Temp.Unc Conductivity	в	1.70%	R	$\sqrt{3}$	0.78	0.71	0.80%	0.80%	8
24	Temp.Unc Permittivity	в	0.40%	R	$\sqrt{3}$	0.23	0.26	0.10%	0.10%	8
Combined standard uncertainty	$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i}$	ι_i^2			1	1	1	12.90%	12.70%	8
Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$			R	K=2	1	5	18.80%	18.40%	8
Testing Technon										

5.10. System Check Results

System Performance Check at 450 MHz Head TSL

DUT: Dipole450 MHz; Type: D450V2; Serial: 1021

Date/Time: 06/16/2016 09:15:34 AM

Communication System: DuiJiangJi; Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): f = 450 MHz; σ = 0.89 S/m; ϵ_r = 44.1; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Probe: EX3DV4 – SN3842; ConvF(10.24, 10.24, 10.24); Calibrated: 8/26/2015;

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1315; Calibrated: 07/22/2015

Phantom: ELI 4.0; Type: QDOVA001BA;

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

System Performance Check at 450MHz/Area Scan (61x201x1): Interpolated grid: dx=1.500 mm, dy=1.50 mm

Maximum value of SAR (interpolated) = 1.51 mW/g

System Performance Check at 450MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 40.9 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.80 mW/g

SAR(1 g) = 1.18 mW/g; SAR(10 g) = 0.785 mW/g

Maximum value of SAR (measured) = 1.49 mW/g

0 dB = 1.49 mW/g = 1.73 dB mW/g

System Performance Check at 450 MHz Body TSL

DUT: Dipole450 MHz; Type: D450V2; Serial: 1021

Date/Time: 06/16/2016 15:28:11 PM

Medium parameters used (interpolated): f = 450 MHz; σ = 0.95 S/m; ϵ_r = 58.10; ρ = 1000 kg/m³

Communication System: DuiJiangJi; Frequency: 450 MHz;Duty Cycle: 1:1

Phantom section: Flat Section

DASY5 Configuration:

Probe: EX3DV4 - SN3842; ConvF(10.28, 10.28, 10.28); Calibrated: 8/26/2015;

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1315; Calibrated: 07/22/2015

Phantom: ELI 4.0; Type: QDOVA001BA;

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

System Performance Check at 450MHz/Area Scan (61x201x1): Interpolated grid: dx=1.500 mm, dy=1.50 mm

Maximum value of SAR (interpolated) = 1.48 mW/g

System Performance Check at 450MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 40.1 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.75 mW/g

SAR(1 g) = 1.13 mW/g; SAR(10 g) = 0.768 mW/g

Maximum value of SAR (measured) = 1.42 mW/g

0 dB = 1.42 mW/g = 1.52 dB mW/g

System Performance Check 450MHz Body 250mW

5.11. SAR Test Graph Results

SAR plots for **the highest measured SAR** in each exposure configuration, wireless mode and frequency band combination according to FCC KDB 865664 D02

Face Held for FM Modulation at 12.5KHz Channel Separation, Front towards Phantom 462.6375MHz

Communication System: PTT 450; Frequency: 462.6375 MHz;Duty Cycle:1:1

Medium parameters used (interpolated): f = 463.0 MHz; σ = 0.89 S/m; ϵ_r = 45.3; ρ = 1000 kg/m³

Phantom section: Flat Section

Probe: EX3DV4 - SN3842; ConvF(10.24, 10.24, 10.24); Calibrated: 8/26/2015;

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1315; Calibrated: 07/22/2015

Phantom: ELI 4.0; Type: QDOVA001BA;

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

Towards Phantom _25mm/Area Scan (51x141x1): Interpolated grid: dx=1.50 mm, dy=1.50 mm

Maximum value of SAR (interpolated) = 1.14 mW/g

Towards Phantom _25mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=8mm, dz=5mm

Reference Value = 34.79 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.28 mW/g

Maximum value of SAR (measured) = 1.20 mW/g

0 dB = 1.20 mW/g = 0.79 dB mW/g

Date/Time: 06/16/2016 11:24:19 AM

Figure 1: Face held for FM Modulation at 12.5KHz Channel Separation Front towards Phantom 462.6375 MHz

Body- Worn FM Modulation at 12.5KHz Channel Separation, Front towards Ground 462.6375MHz

Communication System: PTT 450; Frequency: 462.6375 MHz;Duty Cycle:1:1

Medium parameters used (interpolated): f = 463.0 MHz; σ = 0.97 S/m; ϵ_r = 58.85; ρ = 1000 kg/m³

Phantom section : Flat Section

Probe: EX3DV4 - SN3842; ConvF(10.28, 10.28, 10.28); Calibrated: 8/26/2015;

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1315; Calibrated: 07/22/2015

Phantom: ELI 4.0; Type: QDOVA001BA;

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

Towards Ground_0mm/Area Scan (51x141x1): Interpolated grid: dx=1.50 mm, dy=1.50 mm

Maximum value of SAR (interpolated) = 1.72 mW/g

Towards Ground_0mm/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 47.7 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 2.12 mW/g

SAR(1 g) = 1.69 mW/g; SAR(10 g) = 1.27 mW/g

Date/Time: 06/16/2016 17:13:07 PM

Plot 2: Body-worn for FM Modulation at 12.5KHz Channel Separation; Front towards Ground 462.6375 MHz

6. Calibration Certificate

6.1. Probe Calibration Ceriticate

Accredited by the Swiss Accredit The Swiss Accreditation Service	ich, Switzerland ation Service (SAS) ce is one of the signatorie	BIC-MRA S to the EA	Schweizerischer Kalibrierdiens Service suisse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service creditation No.: SCS 0108
Multilateral Agreement for the CIQ (Shenzhe	recognition of calibration	certificates Certificate No:	EX3-3842_Aug15
CALIBRATION	CERTIFICATI		
Object	EX3DV4 - SN:38	42	
Calibration procedure(s)	QA CAL-01.v9, C Calibration proce	A CAL-12.v9, QA CAL-23.v5, QA dure for dosimetric E-field probes	CAL-25.v6
Calibration date:	August 26, 2015		
Calibration Equipment used (M8	TE critical for calibration)		
Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Primary Standards Power meter E44198	ID GB41293874	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128)	Scheduled Calibration Mar-16
Primary Standards Power meter E44198 Power sensor E4412A	ID GB41293874 MY41498087	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128)	Scheduled Calibration Mar-16 Mar-16
Primary Standards Power meter E44198 Power sensor E4412A Reference 3 dB Attenuator	ID GB41293874 MY41498087 SN: S5054 (3c)	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129)	Scheduled Calibration Mar-16 Mar-16 Mar-16
Primary Standards Power meter E44198 Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (20x)	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 30 dB Attenuator	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (20x) SN: S5129 (30b)	Gal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Mar-16
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 30 dB Attenuator Reference Probe ES3DV2	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (20x) SN: S5129 (30b) SN: 3013	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 30 dB Attenuator Reference Probe ES3DV2 DAE4	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (20x) SN: S5129 (30b) SN: 3013 SN: 660	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 30 dB Attenuator Reference Probe ES3DV2 DAE4	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (202) SN: S5129 (30b) SN: 3013 SN: 660	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15) Check Date (in house)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16 Scheduled Check
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Reference LB 9649C	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (202) SN: S5129 (30b) SN: 3013 SN: 660 ID ID	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15) Check Date (in house) 4-Aug-99 (in house check Apr-13)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16 Scheduled Check
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards RF generator HP 8648C Notemak Appleme UP 9259	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (20x) SN: S5129 (30b) SN: 3013 SN: 660 ID US3642U01700 LIS37300585	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15) Check Date (in house) 4-Aug-99 (in house check Apr-13) 18-Ocl-01 (in house check Apr-13)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16 Scheduled Check In house check: Apr-16 In house check: Cher 15
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards RF generator HP 8648C Network Analyzer HP 8753E	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (202) SN: S5129 (30b) SN: 3013 SN: 660 ID US3642U01700 US37390585	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15) Check Date (in house) 4-Aug-99 (in house check Apr-13) 18-Oct-01 (in house check Oct-14)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16 Scheduled Check In house check: Apr-16 In house check: Oct-15
Primary Standards Power meter E4419B Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards RE generator HP 8648C Network Analyzer HP 8753E	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (202) SN: S5129 (30b) SN: 3013 SN: 660 ID US3642U01700 US37390585 Name	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15) Check Date (in house) 4-Aug-99 (in house check Apr-13) 18-Oct-01 (in house check Oct-14)	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16 Scheduled Check In house check: Apr-16 In house check: Oct-15 Signature
Primary Standards Power meter E4419B Power sensor E4419A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards RE generator HP 8648C Network Analyzer HP 8753E Calibrated by	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5277 (202) SN: S5129 (30b) SN: 3013 SN: 660 ID US3642U01700 US37390585 Name Claudio Leubler	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15) Check Date (in house) 4-Aug-99 (in house check Apr-13) 18-Oct-01 (in house check Oct-14) Function Laboratory Technician	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16 Scheduled Check In house check: Apr-16 In house check: Oct-15
Primary Standards Power meter E4419B Power sensor E4419A Reference 3 dB Attenuator Reference 30 dB Attenuator Reference 20 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards RE generator HP 8648C Network Analyzer HP 8763E Calibrated by:	ID GB41293874 MY41498087 SN: S5054 (3c) SN: S5129 (30b) SN: 3013 SN: 660 ID US3642U01700 US37390585 Name Claudio Leubler Katja Pokovic	Cal Date (Certificate No.) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02128) 01-Apr-15 (No. 217-02129) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02132) 01-Apr-15 (No. 217-02133) 30-Dec-14 (No. ES3-3013_Dec14) 14-Jan-15 (No. DAE4-660_Jan15) Check Date (in house) 4-Aug-99 (in house check Apr-13) 18-Oct-01 (in house check Oct-14) Function Laboratory Technician Technical Manager	Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jan-16 Scheduled Check In house check: Apr-16 In house check: Oct-15 Signature

Certificate No: EX3-3842_Aug15

Page 1 of 11

Calibration Laboratory of Schmid & Partner

Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland

Schweizerischer Kalibrierdienst S

- Service suisse d'étalonnage С
- Servizio svizzero di taratura S

Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary: TSL tissue simulating liquid NORMx,y,z sensitivity in free space ConvF sensitivity in TSL / NORMx.y.z DCP diode compression point CF crest factor (1/duty_cycle) of the RF signal A, B, C, D modulation dependent linearization parameters Polarization op o rotation around probe axis Polarization 9 9 rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., 9 = 0 is normal to probe axis

Connector Angle information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013. "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1. "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)". February 2005
- IEC 62209-2. "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010 KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORMx, y.z: Assessed for E-field polarization () = 0 (f 900 MHz in TEM-cell; f > 1800 MHz; R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E^2 -field uncertainty inside TSL (see below *ConvF*)
- NORM(f)x,y,z = NORMx,y,z * frequency response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- Ax,y.z; Bx,y.z; Cx,y.z; Dx,y.z; VRx,y.z; A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx.y,z * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).

Certificate No: EX3-3842_Aug15

Page 2 of 11

August 26, 2015

Probe EX3DV4

SN:3842

Manufactured: Calibrated: October 25, 2011 August 26, 2015

Calibrated for DASY/EASY Systems (Note: non-compatible with DASY2 system!)

Certificate No: EX3-3842_Aug15

Page 3 of 11

August 26, 2015

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3842

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm $(uV/(V/m)^2)^{A}$	0.34	0.53	0.42	± 10.1 %
DCP (mV) ^h	101.6	99.9	99.5	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dBõV	С	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	152.0	±3.0 %
		Y	0.0	0.0	1.0		143.5	
		Z	0.0	0.0	1.0		147.4	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

 ^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).
 ^B Numerical linearization parameter, uncertainty not required.
 ^E Uncertainty is determined using the max, deviation from linear response applying rectangular distribution and is expressed for the square of the first-statement of the square of field value.

Certificate No: EX3-3842_Aug15

Page 4 of 11

August 26, 2015

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3842

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
450	43.5	0.94	10.24	10.24	10.24	0.18	1.20	± 13.3 %
750	41.9	0.89	9.45	9.45	9.45	0.34	0.93	± 12.0 %
835	41.5	0.90	9.04	9.04	9.04	0.18	1.60	± 12.0 %
900	41.5	0.97	8.92	8.92	8.92	0.22	1.45	± 12.0 %
1750	40.1	1.37	7.80	7.80	7.80	0.35	0.80	± 12.0 %
1900	40.0	1.40	7.54	7.54	7.54	0.29	0.80	± 12.0 %
2450	39.2	1.80	6.82	6.82	6.82	0.35	0.86	± 12.0 %
2600	39.0	1.96	6.74	6.74	6.74	0.37	0.92	± 12.0 %

Calibration Parameter Determined in Head Tissue Simulating Media

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity is durancies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters. (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters. (ϵ AlphaDpeth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Certificate No: EX3-3842_Aug15

Page 5 of 11

August 26, 2015

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3842

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
450	56.7	0.94	10.28	10.28	10.28	0.10	1.20	± 13.3 %
750	55.5	0.96	9.38	9.38	9.38	0.35	1.02	± 12.0 %
835	55.2	0.97	9.18	9.18	9.18	0.27	1.22	± 12.0 %
900	55.0	1.05	9.11	9.11	9.11	0.26	1.17	± 12.0 %
1750	53.4	1.49	7.46	7.46	7.46	0.35	0.80	± 12.0 %
1900	53.3	1.52	7.29	7.29	7.29	0.40	0.86	± 12.0 %
2450	52.7	1.95	6.87	6.87	6.87	0.34	0.80	± 12.0 %
2600	52.5	2.16	6.76	6.76	6.76	0.32	0.80	± 12.0 %

Calibration Parameter Determined in Body Tissue Simulating Media

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz. ^F At frequencies below 3 GHz, the validity of tissue parameters (*i*: and *a*) can be relaxed to ± 10% if liquid compensation formula is applied to measured 5 AB whose At frequencies 0 APR - 10 MHz.

At irrequencies below 3 GHz, the validity of tissue parameters (i: and σ) can be relaxed to ± 10% it inquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (i: and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters. ^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Certificate No: EX3-3842_Aug15

Page 6 of 11

August 26, 2015

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)

Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

Certificate No: EX3-3842_Aug15

Page 7 of 11

August 28 2015

Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Certificate No: EX3-3842_Aug15

Page 8 of 11

August 26, 2015

Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Certificate No: EX3-3842_Aug15

Page 9 of 11

August 26, 2015

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3842

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	66.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Certificate No: EX3-3842_Aug15

Page 11 of 11

6.2. D450V3 Dipole Calibration Certificate

Engineering AG reglassetrasse 40, 1964 Zarish	y of h, Switzerland	۲	S Schweizerscher Kalibrierdiener G Service suisse d'étalennage Servizie svizzero di terzhare S Ewizs Calibration Service
consisted by the Swiss According the Swiss Accordington Service Autological Agreement for the re	tion Service (SAS) I is one of the signatories ecognition of calibration	s to the EA certificates	Accreditation No.: SCS 0108
lient Auden		Certificate	No: D450V3-1072_Nov15
CALIBRATION C	ERTIFICATE		
kan:	D450V3 - SN: 10	72	
Calibration proceedants)	QA CAL-15.v8 Calibration proces	dure for dipole validation kits b	elow 700 MHz
Calibration statu	Novombor 25, 20	15	
Ni calibrations have been conduc	cise in the peaks apprend	y taolity: anironment temperature (52 a	87°C and humidity < 70%.
vi calibratione have been conduc Satibration Equipment used (MAT	TE official ter osibection)	y taolity: antironment temperature d2 a	SPC and humidity = 70%.
il calibratione have been conduc alibration Equipment used (ML ¹ timory Standards	TE critical tor collection)	y taolity: animovement temperature d2 a Cal Date (Cartificate No.) D1 Ave 52 (No. 9 (Commo	Shedwad Calculor Mar 10
il calibratione have been conduc alibration Equipment used (MAT timory Standards Laws meter E441130 have calent F441130	TE critical for calibration) ID # CD041293074 MY41430057	y taolity: animovement temperature d2 a Cal Date (Cartificate Ne.) D1 Apr 15 (No. 217-82120) D1 Apr 15 (No. 217-82120)	Sheckard fumility = 70%. Scheckard Calibration Mar-16 Mar-16
i calibratione have been conduc alibration Equipment used (M4.1 timory Standards Uwer meter E441130 town sensor E44112A kilengees 2 dB //tem.ater	TE oritikul ter osibestion) 10 e 0041293074 MY41498067 Ski SSS4 /dei	y taolity: animovement temperature (22 a Cal Date (Cartificate Nn.) D1 Apr:15 (No. 217-02120) D1 Apr:15 (No. 217-02120) D1 Apr:15 (No. 217-02120)	Schooland humality = 70%. Schooland Calibration Mar 16 Mar 16 Mar 16 Mar 16
il calibratione have been conduc alibration Equipment used (MA1 timory Blandards Uwer meter E+4180 twer sensor E4412A kiferosec 3 d3 Attenuator afferosec 30 d3 Attenuator	TE oritikul ter osibestist) 10 e 0041299074 Mr41499077 Ski SS054 (2e) SKi SS054 (2e)	y taolity: animovement temperature (22 a Cal Date (Cartificate Nn.) D1 Apr-15 (No. 217-02120) D1 Apr-15 (No. 217-02120) D1 Apr-15 (No. 217-02120) D1 Apr-15 (No. 217-02120) D1 Apr-15 (No. 217-02120)	Schooland humaky = 70%. Schooland Calibration Mar-16 Mar-16 Mar-16 Mar-16
II calibratione have been conduct alibration Equipment used (MAT twoary Glandards Uwer moter E44130 tower select E44130	TE orikkul ter osibestise) 10 e 0241239074 MY41498077 SN S5054 (3c) SN S5056 (20v) SN 5047.27(0537)	y taolity: animovement temperature (22 a Cal Date (Cartificate No.) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02130)	School Juniality = 70%. School Juni Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-10
Hosilinatione have been conduct altituation Equipment used (MAT Versary Standards Versar Index E44100 Itseer seasor K44125 Verlandes 29 dB Attenuator Verlandes 29 dB Attenuator	TE oritikus tur osibestius) 10 e 0041233074 MY41436077 SN 35054 (3e) SN 30356 (20) SN 3047 2/ 0652* SN 1407	y tability: antironment temperature (22 a Cal Date (Cartificate No.) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02130) 01 Apr 15 (No. 217-02130) 00-0ao 14 (No. 613-1507, Dect4)	School and humality = 70%. School and Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-10 Disc-15
Hosilinations have been conduct altituation Equipment used (MAT "Weary Glandards "Swar motor E44100 town select E441000 town se	TE orikkul ter osibesitur) 10 e 0241239074 MY41498077 SN 5554 (3c) SN 55564 (3c) SN 55564 (3c) SN 5564 (3c) SN 5564 (3c) SN 5647 (27) SN 5647 (27) SN 5647 (27) SN 5647 (27) SN 564 (3c) SN 564 (3c) S	y tability: antironment temperature (22 a Cal Date (Certificate Ne.) 91 Apr:15 (No. 217-02120) 01 Apr:15 (No. 217-02120) 00 Apr:15 (No. 217-02120) 00 Apr:15 (No. 217-02120) 00 Apr:15 (No. 217-02120)	Schoolaad Calibration Mar 16 Mar 10 Mar 10 Mar 10 Mar 10 Mar 10 Dec 15 Jai 14
Vi calibratione have been conduct calibration Equipment used (MAT Veryary Standards Veryary Standards Veryary Standards Veryary Standards Veryary Standards Veryary Standards Veryary Standards Veryary Standards	TE oriNeal for oxibeation) 10 e 0241239074 Mm41498077 SM SS054 (Se) SM SS054 (Se) SM S056 (20k) SM S056 (20k) SM 5047,27 (0532) SM 1407 DN 054 10 e	y tability: antironment temperature G2 a Cal Date (Certificate Ne.) 91 Apr:15 (No. 217-02120) 01 Apr:15 (No. 217-02120) 00 Apr:15 (No. 217-02120) Date: 2 (No. 217-02120) Date: 3 (No. 217-02120) Date: 3 (No. 217-02120) Date: 3 (No. 217-02120)	Schedues Calcuton Mar 16 Mar 16 Mar 16 Mar 16 Mar 16 Mar 10 Disc 15 Jai 18 Scheduld Check
Hosilinations have been conduct administrations Equipment used (MAT "Weary Standards "Swar meter E44100 town seesor K44100 town seesor K44100 town seesor K44100 town seesor K44100 town seesor K44100 town seeson K441000 tow	TE orikus ter osibester) 10 ± 004133674 MY41498077 SN SS54 (5c) SN SS564 (5c) SN SS564 (5c) SN SS647 (27) SN S547 (27) SN S557 (27) SN S577 (27)	y tability: antironment temperature (22 a Cal Date (Cartificate Nn.) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02120) 01 Apr 15 (No. 217-02130) 01 Apr 15 (No. 217-02130) 01 Apr 15 (No. 217-02130) 00 Jac 16 (No. 613-1507, Det 4) 00 Jac 17 (No. 613-1507, Det 4) 00 J	SPC and humakly < 70%. Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Dec-15 Jai-18 Scheduled Check Is house sheck Apr-15
Vi calibratione have been conduct Calibration Equipment used (MA) Trensry Standards "Swor meter E44180 "Swor meter E44180 "Swor setsor E4412A Reference 2 dB Attenuator Vipe-N manuator continuion Reference Picto E150VE SAE4 Recondery Standards IF paramatics HP 80508	TE oritikul ter osibexiler) 10 # 0041230074 NY41498057 SN SS054 (2e) 3N 35056 (20) SN 5847 27 05527 SN 1607 0N 054 10 # US0042001700 US57396265 3420	y facility: anticentent temperature (22 a Cal Date (Cartificate Ne.) D1 Apr 15 (No. 217-02120) D1 A	SPC and humality = 70%. Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Disc-15 Jai-14 Scheduled Check Is house sheck: Apr-15 Is house sheck: Apr-15
Vi calibratione have been conduct Calibration Equipment used (MA) Frenary Standards Fower meter E44180 Fower setsor E4412A Reference 3 dB Attenuator Reference 3 dB Attenuator Reference Poolo E150VE DAEA Secondary Standards FF generator 19° 80400 webwark Anaryzer 19° 87538	TE oritikul für osibektivi) 10 # 0041230074 NY41490007 SN SS054 (2e) 3N SS054 (2e) 3N S0058 (20N) SN S054 (2e) 3N S054 (2e) 10 # US0542001700 US0542001700 US57390000 34200 Name	y tability: antironment temperature (22 a Cal Date (Cartificate Ne.) D1 Apr 15 (No. 217-02120) D1 A	SPC and humality = 70%. Scheduled Calibration Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Disc-15 Jai-14 Scheduled Check In house sheck: Apr-15 In house sheck: Apr-15 In house sheck: Cit-15 Sgneture
Ni calibratione have been conduc Calibration Equipment used (MAT Power Index En4190 Power Index En4190 Power sensor H44190 Power 2 49 Attenuator Peteronee 2 49 Attenuator Type-Ni mematch condimation Defensive 20 40 Attenuator Type-Ni mematch condimation Defensive Poloo ETSD/VE DAEA Secondorr Standards PF generator INP 80400 Network Analyzer INP 87538 Calibrated hy:	TE oritikus für ositikesius) 10 e 0041239874 MY+1498057 SN SS054 (Se) 3N SS0	y facility: anticentral temperature (22 a Cal Date (Cartificate Ne.) D1-Apr-15 (No. 217-02102) D1-Apr-15 (No. 217-02102) D1-Apr-15 (No. 217-02109) D1-Apr-15 (No. 217-02109) D1-A	SPC and humidity = 70%. Scheduled Calibration Mar-10 Mar-10 Mar-10 Mar-10 Disc-15 Jul-10 Disc-15 Jul-10 Scheduled Check Is house sheck Apr-15 Is house sheck Apr-15 Is house sheck Apr-15 Is house sheck Car-15 Signature Suff MMM
Vi calibratione have been conduc Calibration Equipment used (M4.1 Prevary Standards Power meter E44100 Power setsor E4412A Reference 3 dB Attenuator Patientice 20 dB Attenuator DAEM Secondory Standards PE personator HP 80400 watwork Anaryzer HP 87538 Calibrated by:	TE orikkul ter osibeskier) 10 e 0041230074 NY41490007 SN SS054 (2e) ON S0058 (20k) SN S0058 (20k) SN S0058 (20k) SN S0057 (270582* SN 1607 ON 054 10 e US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 US0042001700 SN SS054 SN SN SS054 SN SN SN SS054 SN SN SS054 SN SN S	y facility: anticentent temperature (22 a Car Date (Cartificate Ne.) D1-Apr-15 (No. 217-02120) D1-Apr-15 (No. 217-02120) D1-Apr-16 (No. 518-1910) D1-Aug-16 (No. 5	SPC and humidity = 70%. Scheduod Caliboriton Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Mar-16 Disc-15 Jal-18 Schedunid Check Ischose sheek: Apr-15 Ischose sheek: Apr-15 Mar-16 Mar-17 Mar-16 Mar-17 Mar-16 Mar-17 Mar-17 Mar-17 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-18 Mar-19 Mar-18 Mar-19 Mar-

Certilicate No. 0400V0-1072_Nov15

Page 1 of 8

Calibration Laboratory of Schmid & Partner

Engineering AG Zeughausstrosse 43, 8084 Zurich, Switzerland

G s

Schweizerischer Kalibrierdienst Service suisse d'étalonnege Servizio svizzero di taratura

Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificated

Glossary:	
TSL	tissue simulating Iquid
ConvF	sensitivity in TSL / NORM x,y,z

N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Fate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, 'Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)', March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end
 of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed
 point exactly below the center marking of the flat phantom section, with the arms oriented
 parallel to the body axis.
- Feed Pcint Impedance and Return Loss: These parameters are measured with the dipole
 positioned under the liquid filled phantom. The impedance stated is transformed from the
 measurement at the SMA connector to the feed point. The Return Loss ensures low
 reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the covarage factor k=2, which for a normal distribution corresponds to a covarage probability of approximately 95%.

Certilicate No: D450V3-1072_Nov15

Testing Techn

Measurement Conditions

DASY system configuration, as far as not	given on page 1.	
DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	ELI4 Flat Phantom	Shell thickness, 2 ± 0,2 mm
Distance Dipole Center - TSL	16 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	43.5	0.87 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	44.0 ± 6 %	0.89 mho/m ±6 %
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	230 mW input power	1.10 W/kg
SAR for nominal Head TSL parameters	normalized to 1//	4.57 W/kg ± 18.1 % (k=2)
SAR averaged over 10 cm ² (10 g) of Head TSL	condition	
SAR averaged over 10 cm ² (10 g) of Head TSL SAR measured	condition 250 mW input power	0.778 Wikg

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	56.7	0.94 mho/m
Measured Body TSL parameters	3° (S.0 ± 0.55)	56.3 ± 0 %	0.95 mhc/m ± 6 %
Body TSL temperature change during test	<0.5 ℃		

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of BodyTSL	Condition	
SAR measured	250 mW input power	1.13 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	4.48 W/kg ± 18.1 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR averaged over 10 cm ³ (10 g) of Body TSL SAR measured	condition 250 mW input power	0.744 W/kg

Certificate No: D450V3-1072_Nov15

Page 3 of 8

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

impedance, transformed to feed point	67.0 Ω - 4.4 jΩ	
Return Loss	- 22.2 dB	

Antenna Parameters with Body TSL

Impedance, transformed to feed point	53.6 Ω - 9.0 μΩ	
Return Loss	- 20.6 dB	

General Anterna Parameters and Design

Electrical Delay (one direction)	1.356 na	

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxis cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this shange. The overall dipole length is still according to the Sterlard.

according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be domaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	November 25, 2009

MIL
ing TROL
ing to

DASY5 Validation Report for Head TSL

Date: 25.11.2015

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN: 1072

 $\begin{array}{l} Communication \ System: \ UID \ 0 - CW; \ Frequency: 450 \ MHz \\ Medium \ parameters \ used: \ f = 450 \ MHz; \ \sigma = 0.89 \ S/m; \ \epsilon_r = 44; \ \rho = 1000 \ kg/m^3 \\ Phantom \ section \ \ Flat \ Section \\ Measurement \ Standard: \ DASY5 (IEEE/IEC/ANSI \ C63.19-2011) \\ \end{array}$

DASY52 Configuration:

- Probe: E13DV6 SN1507; ConvF,6.58, 6.58, 6.58); Calibrated: 30.12.2014;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 08.07.2015
- · Phantom ELI v4.0; Type: QDOVA001BB; Serial: TP:1003
- DASY5252.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Head Tissue/d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value= 39.53 V/m; Power Dritt = -0.04 dB Peak SAR (extrapolated) = 1.67 W/kg SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.778 W/kg Maximum value of SAR (measured) = 1.25 W/kg

0 dB = 1.25 W/kg = 0.97 dBW/kg

Certificate No: D45CV3-1072_Nov15	Page 5 of 8	
I To		Tachin
10	sting	160
	0	

Impedance Measurement Plot for Head TSL

DASY5 Validation Report for Body TSL

Date: 25.11.2015

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN: 1072

Communication System: UID 0 - CW; Frequency: 450 MHz Medium parameters used: f = 450 MHz; σ = 0.95 S/m; ϵ_r = 56.3; ρ = 1000 kg/m³ Phantom section Flat Section Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ET3DV6 SN1507; ConvF(7.05, 7.05, 7.05); Calibrated: 30.12.2014;
- · Sensor-Surface: 4mm (Mechanical Surface Detection)
- · Electronics: DAE4 Sn654; Calibrated: 08.07.2015
- · Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003
- DASY5252.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Body Tissue/d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 36.53 V/m; Power Drift = -0.03 dB Peak SAR (extrapolated) = 1.81 W/kg SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.744 W/kg Maximum value of SAR (measured) = 1.21 W/kg

Impedance Measurement Plot for Body TSL

6.3. DAE4 Calibration Certificate

Tel: +86-10-623	804633-2218 Fax: +	trict, Beijing, 100191, China 86-10-62304633-2209	CALIBRATION No. L0570
Client : CIG	(Shenzhen)	www.chinattl.cn Certificate	No: Z15-97098
CALIBRATION	CERTIFICAT	E	
Object	DAE4 -	SN: 1315	
Calibration Procedure(s)	FD-Z11 Calibra (DAEx)	-2-002-01 tion Procedure for the Data Acquis	sition Electronics
Calibration date:	July 22	, 2015	
This calibration Certifica measurements(SI). The pages and are part of the All calibrations have be humidity<70%. Calibration Equipment us	te documents the t measurements and e certificate. een conducted in t sed (M&TE critical fo	traceability to national standards, wh the uncertainties with confidence prob the closed laboratory facility: enviro or calibration)	ich realize the physical units ability are given on the followir nment temperature(22±3)°C ar
This calibration Certifica measurements(SI). The pages and are part of the All calibrations have be humidity<70%. Calibration Equipment us Primary Standards	te documents the t measurements and e certificate. een conducted in t sed (M&TE critical fo ID # Cal	traceability to national standards, wh the uncertainties with confidence prob the closed laboratory facility: enviro or calibration) I Date(Calibrated by, Certificate No.)	ich realize the physical units ability are given on the followir nment temperature(22±3)°C ar Scheduled Calibration
This calibration Certifica measurements(SI). The pages and are part of the All calibrations have be humidity<70%. Calibration Equipment us Primary Standards Process Calibrator 753	te documents the t measurements and e certificate. een conducted in t sed (M&TE critical fo ID # Cal 1971018	traceability to national standards, wh the uncertainties with confidence prob the closed laboratory facility: enviro or calibration) I Date(Calibrated by, Certificate No.) 06-July-15 (CTTL, No:J15X04257)	ich realize the physical units ability are given on the followir nment_temperature(22±3)°C ar Scheduled Calibration July-16
This calibration Certifica measurements(SI). The pages and are part of the All calibrations have be humidity<70%. Calibration Equipment us Primary Standards Process Calibrator 753	te documents the t measurements and e certificate. een conducted in t sed (M&TE critical fo ID # Cal 1971018	traceability to national standards, wh the uncertainties with confidence prob the closed laboratory facility: enviro or calibration) I Date(Calibrated by, Certificate No.) 06-July-15 (CTTL, No:J15X04257)	ich realize the physical units hability are given on the followir nment temperature(22±3)°C ar Scheduled Calibration July-16
This calibration Certifica measurements(SI). The pages and are part of the All calibrations have be humidity<70%. Calibration Equipment us Primary Standards Process Calibrator 753 Calibrated by:	te documents the t measurements and e certificate. een conducted in t sed (M&TE critical fo ID # Cal 1971018 Name Yu Zongying	traceability to national standards, wh the uncertainties with confidence prob the closed laboratory facility: enviro or calibration) I Date(Calibrated by, Certificate No.) 06-July-15 (CTTL, No:J15X04257) Function SAR Test Engineer	ich realize the physical units hability are given on the followir nment temperature(22±3)°C ar Scheduled Calibration July-16
This calibration Certifica measurements(SI). The pages and are part of the All calibrations have be humidity<70%. Calibration Equipment us Primary Standards Process Calibrator 753 Calibrated by: Reviewed by:	te documents the t measurements and e certificate. een conducted in f sed (M&TE critical fo ID # Cal 1971018 Name Yu Zongying Qi Dianyuan	traceability to national standards, wh the uncertainties with confidence prob the closed laboratory facility: enviro or calibration) I Date(Calibrated by, Certificate No.) 06-July-15 (CTTL, No:J15X04257) Function SAR Test Engineer SAR Project Leader	ich realize the physical units hability are given on the followin nment temperature(22±3)°C ar Scheduled Calibration July-16

Certificate No: Z15-97098

Page 1 of 3

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209 E-mail: cttl@chinattl.com Http://www.chinattl.cn

Glossary: DAE Connector angle

data acquisition electronics information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters:

- DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.

Certificate No: Z15-97098

Page 2 of 3

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209 E-mail: ettl@chinattl.com Http://www.chinattl.cn

DC Voltage Measurement

A/D - Converter Re	solution nomi	nal		
High Range:	1LSB =	6.1µV,	full range =	-100+300 mV
Low Range:	1LSB =	61nV .	full range =	-1+3mV
DASY measuremen	nt parameters	: Auto Zero T	ime: 3 sec: Meas	uring time: 3 sec

Calibration Factors	x	Y	Z
High Range	$405.192 \pm 0.15\%$ (k=2)	$405.031 \pm 0.15\%$ (k=2)	404.98 ± 0.15% (k=2)
Low Range	3.99083 ± 0.7% (k=2)	3.98595 ± 0.7% (k=2)	3.9887 ± 0.7% (k=2)

Connector Angle

Connector Angle to be used in DASY system	21°±1°

Certificate No: Z15-97098

Page 3 of 3

7. Test Setup Photos

Photograph of the depth in the Head Phantom (450MHz)

Photograph of the depth in the Body Phantom (450MHz)

Face-held, the front of the EUT towards phantom (The distance is 25mm)

Body-worn, the front of the EUT towards ground (The distance is 0mm)

