### 47 CFR PART 15 SUBPART C TEST REPORT

for

## **Articulating TPMS Sensor Trigger Device**

### Model No.: TPMSWAND

### FCC ID: 2ANR7-TPMSWAND

of

Applicant: ATEQ INSTRUMENTS (ASIA)PTE LTD. TAIWAN BRANCH (SINGAPORE) Address: NO.3, LANE 223, SAN JIA DONG STREET, 40642, TAICHUNG, TAIWAN

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



### Report No.: W6M22503-24247-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C. TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: <u>wts@wts-lab.com</u>



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND **TABLE OF CONTENTS** 

1	Gen	eral Information	2
	1.1	Notes	2
	1.2	TESTING LABORATORY	3
	1.2.	1 Location	3
	1.2.	2 Details of accreditation status	3
	1.3	DETAILS OF APPROVAL HOLDER	3
	1.4	APPLICATION DETAILS	3
	1.5	GENERAL INFORMATION OF TEST ITEM	4
	1.6	TEST STANDARDS	4
2	Tec	hnical test	5
	2.1	SUMMARY OF TEST RESULTS	5
	2.2	TEST ENVIRONMENT	5
	2.3	Test Equipment List	6
	2.4	GENERAL TEST PROCEDURE	7
3	Test	t results (enclosure)	8
	3.1	PEAK OUTPUT POWER	8
	3.2	SPURIOUS EMISSIONS RADIATED – TRANSMITTER OPERATING	11
	3.3	OCCUPIED BANDWIDTH	13
	3.4	ANTENNA REQUIREMENT	14
	3.5	RADIATED EMISSIONS FROM RECEIVER SECTION OF RECEIVER PART	15
	3.6	Power Line Conducted Emission	17

### **Appendix: Diagrams**



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND 1 General Information

### 1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that is performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

- 1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
- 2. The test report may only be reproduced or published in full.
- 3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
- 4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

### **Tester:**

April 30, 2025

Date

WTS-Lab. Name

Rick Chen.

Signature

### Technical responsibility for area of testing:

April 30, 2025		Kevin Wang	Kevin Wong
Date	WTS	Name	Signature

Rick Chen



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND **1.2 Testing laboratory** 

### 1.2.1 Location

10m OATS No.5-1, Lishui, Shuang Sing Village, Wanli Dist., New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber/Conducted Emission No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd. 6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.) Tel: 886-2-6606-8877

### **1.2.2** Details of accreditation status

Accredited testing laboratory FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037 Industry Canada filed test laboratory Reg. No.: 20037, 31634

### Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name:	./.
Accredited number:	./.
Street:	./.
Town:	./.
Country:	./.

### 1.3 Details of approval holder

Name:	ATEQ INSTRUMENTS (ASIA)PTE LTD. TAIWAN BRANCH (SINGAPORE)
Street:	NO.3, LANE 223, SAN JIA DONG STREET, 40642,
Town:	TAICHUNG,
Country:	TAIWAN
1.4 Application details	
Date of receipt of test item:	March 26, 2025
Date of test:	from March 27, 2025 to April 23, 2025



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND **1.5 General information of Test item** 

Type of test item:	Articulating TPMS Sensor Trigger Device			
Model number:	TPMSWAND			
Multi-listing model number:	TPMS WAND			
Brand name:	Snap-on			
Transmitting frequency:	125 kHz			
Operation modes:	ASK			
Antenna type:	Coil Antenna			
Antenna gain:	7dBi			
Power supply:	USB 5Vd.c. Battery 3.6Vd.c. 2550mAh 9.18Wh			
Sample no.:	#01			

### Manufacturer: (if different from Approval Holder)

Name:	Might Electronic Co., Ltd.
Street:	No. 41-1, Lin 2, Yuan-Shan Tsuen, Hsin-Feng Hsiang,
Town:	Hsin-Chu Hsien 304,
Country:	Taiwan (R.O.C.)

### 1.6 Test standards

47 CFR PART 15 SUBPART C § 15.209 (2023-10) ANSI C63.10:2013



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND

### 2 Technical test

### 2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course	×
of the tests performed.	
or	

The deviations were ascertained in the course of the tests performed.

### 2.2 Test environment

Relative humidity content:	20 75 %
Air pressure:	86 103 kPa
Details of power supply	USB 5Vd.c. Battery 3.6Vd.c. 2550mAh 9.18Wh
Extreme conditions parameters:	test voltage : extreme min : V max : V

Test item Name	Measurement Uncertainty	
Estimation Result of Uncertainty of Conducted Emission (Power Line Conducted Emission) (CR)	Expanded Uncertainty : AMN : 1.08 dB	
Estimation Result of Uncertainty of Radiated Emission (3M - 966A)(Peak Output Power, Spurious Emissions radiated – Transmitter operating, Radiated Emissions from Receiver Section of Receiver Part)	Expanded Uncertainty : 0.009-30 MHz : 1.85 dB 30-1000 MHz : 3.92 dB 1-18 GHz : 3.19 dB 18-40 GHz : 1.90 dB	
Estimation Result of Uncertainty of Bandwidth Measurement (Occupied Bandwidth)	Expanded Uncertainty : 0.37 kHz	

The decision rule is: Measurement uncertainty is not included in the calculation of test results.



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND

## 2.3 Test Equipment List

### Max Output Power & spurious emission (9k~30M)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2024/9/11	2025/9/10
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2025/4/9	2026/4/8
ETSTW-RE 176	Loop Antenna	FMZB 1513-60	39	SCHWARZBECK	2024/8/21	2025/8/20
ETSTW-Cable 090	N type Cable (15m)	EMCCFD400-NM-NM-15000	230732	EMCI	2024/8/3	2025/8/2

#### Spurious emission (30M~1G)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2024/9/11	2025/9/10
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2025/4/9	2026/4/8
ETSTW-RE 160	Amplifier Module	CHC 3	None	WTS	2024/7/12	2025/7/11
ETSTW-RE 176	Loop Antenna	FMZB 1513-60	39	SCHWARZBECK	2024/8/21	2025/8/20
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT- 06007	SCHWARZBECK&EMC	2025/3/10	2026/3/9
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2024/7/12	2025/7/11
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2024/7/12	2025/7/11
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2024/7/12	2025/7/11
ETSTW-Cable 090	N type Cable (15m)	EMCCFD400-NM-NM- 15000	230732	EMCI	2024/8/3	2025/8/2

### Occupied bandwidth

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2025/3/5	2026/3/4

### AC Conducted Emission (CR)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-CE 032	EMI Test Receiver	ESR3	102830	R&S	2024/4/22	2025/4/21
ETSTW-CE 035	AC Power Source	AFC-150	A2000386	All power	Fu	inction Test
ETSTW-CE 034	Line-Impedance Stabilisation Network	NSLK8127	01087	SCHWARZBECK	2024/7/18	2025/7/17
ETSTW-Cable 092	BNC Cable (3m)	EMCCFD-300-BM-BM-3000	240108	EMCI	2025/1/9	2026/1/8



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND **2.4 General Test Procedure** 

**POWER LINE CONDUCTED INTERFERENCE:** The procedure used was ANSI STANDARD C63.10-2013 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

**RADIATION INTERFERENCE:** The test procedure used was according to ANSI STANDARD C63.10-2013 6.3 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of  $dB\mu V$ ) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:Freq (MHz)METER READING + ACF + CABLE LOSS (to the receiver) = FS33 $20 \text{ dB}\mu\text{V} + 10.36 \text{ dB} + 6 \text{ dB} = 36.36 \text{ dB}\mu\text{V/m} @3m$ 

ANSI STANDARD C63.10-2013 6.2.2 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm height and with dimensions of 1m by 1.5m (non metallic table). The EUT was placed in the centre of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10<sup>th</sup> harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND <u>3 Test results (enclosure)</u>

Test case	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.209	×	×	
Spurious Emissions radiated – Transmitter operating	15.209	×	×	
Spurious Emissions radiated – Receiver operating	15.109			
Occupied bandwidth	2.1049	×	×	
Antenna Requirement	FCC 15.203	×	×	
Power Line Conducted Emission	FCC 15.207	×	X	

The following is intentionally left blank.



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND

#### 3.1 **Peak Output Power**

FCC Rules: 15.209

The power was measured with modulation (declared by the applicant).



M/N:

Test Mode: TX 125KHz Note :

Power: 3.6 Vd.c. Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	0.1253	59.09	peak	18.64	77.73	105.58	100	180	-27.85	



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND Limits: 15.209

Frequency of Emission (MHz)	Field Strength of Fundamental Limit uV/m	Measurement distance
0.009 - 0.490	2400 / f (KHz)	300
0.49 - 1.705	24000 / f (KHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

The test was performed in the anechoic chamber at 3 meter test distance, i.e. the distance between measuring antenna and EUT boundary. The results were extrapolated by using the square of an inverse linear distance factor DF:

DF (distance factor) =  $40 \log (D_1/D_2) = 80 \text{ dB}$ , where

 $D_1$  is the 300 meter specified measurement distance,  $D_2$  is the 3 meter test measurement distance.

For 125 kHz frequency the calculated limit is:  $Limit_{3m} = Limit_{300m} + DF = 25.60 \text{ dBuV/m} + 80 \text{ dB} = 105.60 \text{ dBuV/m}$ 



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND

### 3.2 Spurious Emissions radiated – Transmitter operating

#### FCC Rules: 15.209

The field strength of any emission appearing outside of the specific band shall not exceed the general radiated emission limits in 15.209.

Model:	T	PMSWANI	)	Date:				
Mode:			Te	emperature:	°C	C Engir	neer:	
<b>Polarization</b> :		Horizontal		Humidity:	%			
Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)

Polarization:	Vertical
---------------	----------

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)

Note

- 1. Correction Factor = Antenna factor + Cable loss Preamplifier
- 2. The formula of measured value as: Test Result = Reading + Correction Factor
- 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.
- 5. See attached diagrams in the Appendix.

All other not noted test plots do not contain significant test results in relation to the limits. **TEST RESULT (Transmitter):** The unit DOES meet the FCC requirements.

Limits: 15.209		
Frequency of Emission (MHz)	Field Strength of Fundamental Limit uV/m	Measurement distance
0.009 - 0.490	2400 / f (KHz)	300
0.49 - 1.705	24000 / f (KHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

\* In the emission table above, the tighter limit applies at the band edges.

The test was performed in the anechoic chamber at 3 meter test distance, i.e. the distance between measuring antenna and EUT boundary. The results were extrapolated by using the square of an inverse linear distance factor DF:



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND  $DF = 40 \log (D_1/D_2) = 80 \text{ dB}$ , where

For  $D_1$  is the 300 meter specified measurement distance.  $D_2$  is the 3 meter test measurement distance. The DF = 80 dB was applied for limit calculation at 3 meter test distance measurements.

For  $D_1$  is the 30 meter specified measurement distance.  $D_2$  is the 3 meter test measurement distance. The DF = 40 dB was applied for limit calculation at 3 meter test distance measurements.

If the frequency between 9 - 490 kHz, Limit =  $20\log(2400/f(kHz)) + 80$ 

If the frequency between 490 - 1705 kHz, Limit =  $20\log(2400/f(kHz)) + 40$ 

If the frequency between 1705 - 30000 kHz, Limit =  $20\log 30 + 40$ 

For 125 kHz frequency the calculated limit is: Limit3m = Limit300m + DF = 25.59 dBuV/m + 80 dB = 105.59 dBuV/m



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND **3.3 Occupied Bandwidth** 

FCC Rules: 2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated are each equal to 0.5% of the total mean power radiated by a given emission.

The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth specifications are given, the following guidelines are used:

Fundamental frequency	Minimum resolution bandwidth
9 kHz to 30 MHz	1 kHz
30 MHz to 1000 MHz	10 kHz
1000 MHz to 40 GHz	100 kHz

Test date: April 18, 2025 Temperature: 28.7°C Humidity: 45.0 % Tester: Rick **Test result:** 



Date: 18.APR.2025 17:04:27



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND **3.4** Antenna requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

Explanation: This antenna is Coil antenna which passes antenna requirement.

The equipment meets the	yes	no
requirements	×	



Registration number: W6M22503-24247-C-1

FCC ID: 2ANR7-TPMSWAND

### 3.5 Radiated Emissions from Receiver Section of Receiver Part

### For the frequency from 9 kHz to 30 MHz:

### FCC Rule: 15.209

The field strength of any emission appearing outside of the specific band shall not exceed the general radiated emission limits in 15.209.

Frequency of Emission (MHz)	Field Strength of Fundamental Limit uV/m	Measurement distance
0.009 - 0.490	2400 / f (KHz)	300
0.49 - 1.705	24000 / f (KHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

\* In the emission table above, the tighter limit applies at the band edges.

Note: The above field strength limits are specified at a distance of 3 meters.

The test was performed in the anechoic chamber at 3 meter test distance, i.e. the distance between measuring antenna and EUT boundary. The results were extrapolated by using the square of an inverse linear distance factor DF:

 $DF = 40 \log (D_1/D_2) = 80 \text{ dB}$ , where

For  $D_1$  is the 300 meter specified measurement distance.  $D_2$  is the 3 meter test measurement distance. The DF = 80 dB was applied for limit calculation at 3 meter test distance measurements.

For  $D_1$  is the 30 meter specified measurement distance.

 $D_2$  is the 3 meter test measurement distance.

The DF = 40 dB was applied for limit calculation at 3 meter test distance measurements.

If the frequency between 9 - 490 kHz, limit =  $20\log(2400/f(kHz)) + 80$ 

If the frequency between 490 - 1705 kHz, limit =  $20\log(2400/f(kHz)) + 40$ 

If the frequency between 1705 - 30000 kHz, limit =  $20\log 30 + 40$ 

For 125 kHz frequency the calculated limit is: Limit<sub>3m</sub> = Limit<sub>300m</sub> + DF = 25.59 dBuV/m + 80 dB = 105.59 dBuV/m

Explanation: This test is not required because the EUT is a transmitter only.



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND For the frequency from 30 MHz to 1000 MHz.:

### FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission	Field Strength	Field Strength
(MHz)	(microvolts/meter)	(dBmicrovolts/meter)
30 - 88	100	40.0
88-216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

Model: Mode: Polarization:	T]	PMSWANI  Horizontal	D Te	Date: emperature: Humidity:	°C %	C Engir	neer:	
Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)

Polarization	Vertical							
Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)

Note

- 1. Correction Factor = Antenna factor + Cable loss Preamplifier
- 2. The formula of measured value as: Test Result = Reading + Correction Factor
- 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND **3.6** Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.





Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND



Note

- 1. The formula of measured value as: Test Result = Reading + Correction Factor
- 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
- 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.
- 5. Up Line: QP Limit Line, Down Line: Ave Limit Line.



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND

### Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)			
	Quasi Peak	Average		
0.15-0.5	66 to 56	56 to 46		
0.5-5	56	46		
5-30	60	50		



Registration number: W6M22503-24247-C-1 FCC ID: 2ANR7-TPMSWAND

# **Appendix**

### **Measurement diagrams**

Spurious Emissions Radiated





Site : 966A Chamber Condition : FCC\_15.209 RE (9k-30M) (3M) EUT : W6M22503-24247 M/N: Test Mode : TX 125KHz Note :

Polarization: Power : 3.6 Vd.c. Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	0.0154	41.31	peak	18.41	59.72	123.68	100	180	-63.96	
	0.0310	34.26	peak	19.47	53.73	117.64	100	15	-63.91	
	0.0470	32.54	peak	19.01	51.55	114.04	100	180	-62.49	
	0.0628	24.48	peak	18.82	43.30	111.54	100	222	-68.24	
	0.0783	22.98	peak	18.70	41.68	109.64	100	10	-67.96	
	0.0933	20.96	peak	18.59	39.55	108.12	100	181	-68.57	
*	0.1252	59.09	peak	18.64	77.73	105.58			-27.85	RF Power





Site : 966A Chamber Condition : FCC\_15.209 RE (9k-30M) (3M) EUT : W6M22503-24247 M/N: Test Mode : TX 125KHz Note :

Polarization: Power : 3.6 Vd.c. Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	0.2494	46.21	peak	19.12	65.33	99.63	100	339	-34.30	
	0.3751	38.39	peak	19.32	57.71	96.11	100	105	-38.40	
	0.4993	31.57	peak	19.33	50.90	73.64	100	278	-22.74	
	8.8223	24.91	peak	21.33	46.24	69.54	100	314	-23.30	
	13.9146	28.55	peak	22.26	50.81	69.54	100	11	-18.73	
*	25.0545	27.46	peak	23.77	51.23	69.54	100	258	-18.31	





Site : 966A Chamber Condition : FCC\_part 15 RE-Class C\_30-1000MHz EUT : W6M22503-24247 M/N: Test Mode : TX 125KHz Note :

Polarization: Horizontal Power : 3.6 Vd.c. Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	84.3200	50.15	peak	-18.03	32.12	40.00	100	127	-7.88	
*	170.6500	53.09	peak	-13.15	39.94	43.50	100	110	-3.56	
	266.6800	50.87	peak	-13.18	37.69	46.00	100	272	-8.31	
	274.4400	50.02	peak	-12.91	37.11	46.00	100	255	-8.89	
	680.8700	33.50	peak	-3.59	29.91	46.00	100	195	-16.09	
	920.4600	33.72	peak	-0.69	33.03	46.00	100	206	-12.97	





Site : 966A Chamber Condition : FCC\_part 15 RE-Class C\_30-1000MHz EUT : W6M22503-24247 M/N: Test Mode : TX 125KHz Note :

Polarization: Vertical Power : 3.6 Vd.c. Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	30.9700	49.17	peak	-15.01	34.16	40.00	100	97	-5.84	
	48.4300	47.59	peak	-12.84	34.75	40.00	100	75	-5.25	
	64.9200	49.48	peak	-13.99	35.49	40.00	100	254	-4.51	
*	84.3200	54.30	peak	-18.03	36.27	40.00	100	265	-3.73	
	172.5900	47.22	peak	-13.33	33.89	43.50	100	86	-9.61	
	280.2600	40.38	peak	-12.71	27.67	46.00	100	216	-18.33	