

# Test Report

Report Number:

**F231413E3**

Equipment under Test (EUT):

**Display with Bluetooth communication**

**VU231C**

Applicant:

**Endress+Hauser SE+Co. KG**

Manufacturer:

**Endress+Hauser SE+Co. KG**



Deutsche  
Akkreditierungsstelle  
D-PL-17186-01-00

## References

- [1] **ANSI C63.10-2020**, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
- [2] **FCC CFR 47 Part 15**, Radio Frequency Devices
- [3] **558074 D01 15.247 Meas Guidance v05r02 (April 2019)**, GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
- [4] **RSS-247, Issue 3 (2023-08)** Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
- [5] **RSS-Gen, Issue 5 Amendment 2 (2021-02)** General Requirements for Compliance of Radio Apparatus

## Test Result

The requirements of the tests performed as shown in the overview (clause 4) were fulfilled by the equipment under test. The complete test results are presented in the following.

“Passed” indicates that the equipment under test conforms with the relevant limits of the testing standard without taking any measurement uncertainty into account as stated in clause 1.3 of ANSI C63.10 (2013). However, the measurement uncertainty is calculated and shown in this test report.

Tested and written  
by:

Signature

Reviewed and  
approved by:

Signature

**This test report is only valid in its original form.**

Any reproduction of its contents in extracts without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT NUMBER.

<b>Contents:</b>	<b>Page</b>
1 Identification .....	5
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Test Laboratory .....	5
1.4 EUT (Equipment under Test) .....	6
1.5 Technical Data of Equipment .....	7
1.6 Dates .....	8
2 Operational States .....	9
2.1 Description of function of the EUT .....	9
3 Additional Information .....	9
4 Overview.....	10
5 Results.....	11
5.1 Test setups .....	11
5.2 Duty cycle .....	17
5.3 DTS bandwidth .....	18
5.4 Occupied bandwidth – power bandwidth (99%) .....	20
5.5 DTS fundamental emission output power .....	22
5.6 DTS maximum power spectral density .....	25
5.7 DTS band-edge emission measurements.....	28
5.8 Radiated emissions .....	34
6 Measurement Uncertainties .....	45
7 Test Equipment used for Tests .....	46
8 Test site Verification.....	47
9 Report History.....	47
10 List of Annexes .....	47

# 1 Identification

## 1.1 Applicant

Name:	Endress+Hauser SE+Co. KG
Address:	Hauptstr. 1, 79689 Maulburg
Country:	Germany
Name for contact purposes:	Mr. Florian SEIDLER, Mr. Ralf REIMELT
Phone:	+49-7622-28-1450
eMail address:	florian.seidler@endress.com, ralf.reimelt@endress.com
Applicant represented during the test by the following person:	-

## 1.2 Manufacturer

Name:	Endress+Hauser SE+Co. KG
Address:	Hauptstr. 1, 79689 Maulburg
Country:	Germany
Name for contact purposes:	Mr. Florian SEIDLER, Mr. Ralf REIMELT
Phone:	+49-7622-28-1450
eMail address:	florian.seidler@endress.com, ralf.reimelt@endress.com
Manufacturer represented during the test by the following person:	-

## 1.3 Test Laboratory

The tests were carried out by: **PHOENIX TESTLAB GmbH**  
**Königswinkel 10**  
**32825 Blomberg**  
**Germany**

accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS) according to DIN EN ISO/IEC 17025:2018. The accreditation is only valid for the scope of accreditation listed in the annex of the certificate D-PL-17186-01-00. FCC Test Firm Designation Number DE0004, FCC Test Firm Registration Number 469623, CAB Identifier DE0003 and ISED# 3469A.

## 1.4 EUT (Equipment under Test)

Test object: *	Display with Bluetooth communication
Model name: *	VU231C
Model number: *	VU231C
Order number: *	-
FCC ID: *	LCGVU231C
IC certification number: *	2519A-VU231C
PMN: *	VU231C
HVIN: *	VU231C
FVIN: *	S140 V7.2.0
HMN: *	-

\* Declared by the applicant

	EUT number	
	1 (radiated)	2 (conducted)
Serial number: *	FMR30B_DISP_237	FMR30B_DISP_239
PCB identifier: *	VU231C: 71599593	VU231C: 71599593
Hardware version: *	01.00.00	01.00.00
Software version: *	S140 V7.2.0	Radio Test S140

\* Declared by the applicant

Two EUTs were used for the tests. In the overview in chapter 4 is shown which EUT was used for which test.

Note: PHOENIX TESTLAB GmbH does not take samples. The samples used for tests are provided exclusively by the applicant.

## 1.5 Technical Data of Equipment

General EUT data			
Power supply EUT: *	DC		
Supply voltage EUT: *	$U_{nom} = 3.0 \text{ V}_{DC}$	$U_{min} = 1.7 \text{ V}_{DC}$	$U_{max} = 3.6 \text{ V}_{DC}$
Temperature range: *	-40 °C to +80 °C		
Lowest / highest internal clock frequency:	32 MHz / 2480 MHz		

\* Declared by the applicant

Ports / Connectors				
Identification	Connector		Length during test	Shielding (Yes / No)
	EUT	Ancillary		
DC and data*	Fixed	-	-	-
-	-	-	-	-
-	-	-	-	-

\* Declared by the applicant

Bluetooth® low energy frequencies			
Channel 00	2402 MHz	Channel 01	2404 MHz
Channel 02	2406 MHz	Channel 03	2408 MHz
...	...	...	...
...	...	...	...
Channel 18	2438 MHz	Channel 19	2440 MHz
...	...	...	...
...	...	...	...
Channel 36	2474 MHz	Channel 37	2476 MHz
Channel 38	2478 MHz	Channel 39	2480 MHz

Bluetooth® low energy radio mode	
Fulfills radio specification: *1	Bluetooth® low energy (BLE) 5.1
Radio chip: *1	Nordic nRF52840 (SoC)
Antenna type: *1	PCB Antenna
Antenna name: *1	-
Antenna gain: *2	Peak: 1.1 dBi
Antenna connector: *1	-
Supply voltage radio module: *1	$U_{nom} = 3.0 V_{DC}$ $U_{min} = 1.7 V_{DC}$ $U_{max} = 3.6 V_{DC}$
Type of modulation: *1	BLE (1 Mbps PHY) GFSK
	BLE (2 Mbps PHY) GFSK
	BLE (500 kbps coded PHY) GFSK
	BLE (125 kbps coded PHY) GFSK
Operating frequency range: *1	BLE (1 Mbps PHY) 2402 – 2480 MHz
	BLE (2 Mbps PHY) 2402 – 2480 MHz
	BLE (500 kbps coded PHY) 2402 – 2480 MHz
	BLE (125 kbps coded PHY) 2402 – 2480 MHz
Number of channels: *1	BLE (1 Mbps PHY) 40 (2 MHz channel spacing)
	BLE (2 Mbps PHY) 40 (2 MHz channel spacing)
	BLE (500 kbps coded PHY) 40 (2 MHz channel spacing)
	BLE (125 kbps coded PHY) 40 (2 MHz channel spacing)

\*1 Declared by the applicant

\*2 Based on the antenna test report F231413E5 by PHOENIX TESTLAB GmbH

### 1.5.1 Ancillary Equipment / Equipment used for testing

Equipment used for testing	
-	-

Ancillary equipment	
Laptop*	Fujitsu Lifebook U759
-	-

\* Provided by the laboratory

### 1.6 Dates

Date of receipt of test sample:	22.07.2024
Start of test:	07.08.2024
End of test:	16.10.2024



## 2 Operational States

### 2.1 Description of function of the EUT

The equipment under test (EUT) is the Bluetooth Low Energy-radio part of a radio module for the implementation in measurement equipment.

#### 2.1.1 The following states were defined as the operating conditions:

For the BTLE radio tests the test modes were set via terminal commands at a laptop connected via an USB-to-serial converter.

During all conducted and radiated tests, the EUT was supplied by 3.3 V DC as declared by the applicant.

#### 2.1.2 Operation modes

Operation mode #	Radio technology	Frequency [MHz]	Channel / Band	Modulation / Mode	Data rate	Power setting
1	Bluetooth® LE	2402	0	GFSK	125 kbps	"pos8dBm"
2	Bluetooth® LE	2440	19	GFSK	125 kbps	"pos8dBm"
3	Bluetooth® LE	2480	39	GFSK	125 kbps	"pos8dBm"
4	Bluetooth® LE	2402	0	GFSK	500 kbps	"pos8dBm"
5	Bluetooth® LE	2440	19	GFSK	500 kbps	"pos8dBm"
6	Bluetooth® LE	2480	39	GFSK	500 kbps	"pos8dBm"
7	Bluetooth® LE	2402	0	GFSK	1 Mbps	"pos8dBm"
8	Bluetooth® LE	2440	19	GFSK	1 Mbps	"pos8dBm"
9	Bluetooth® LE	2480	39	GFSK	1 Mbps	"pos8dBm"
10	Bluetooth® LE	2402	0	GFSK	2 Mbps	"pos8dBm"
11	Bluetooth® LE	2440	19	GFSK	2 Mbps	"pos8dBm"
12	Bluetooth® LE	2480	39	GFSK	2 Mbps	"pos8dBm"

## 3 Additional Information

The EUT was not labeled as required by FCC / IC.

## 4 Overview

Application	Frequency range [MHz]	FCC 47 CFR Part 15 section [2]	RSS-247 [4] RSS-Gen [5]	Tested EUT	Status
Maximum peak conducted output power	2400.0 - 2483.5	15.247 (b) (3), (4)	5.4 (d) [4]	2	Passed
Maximum conducted output power	2400.0 - 2483.5	15.247 (b) (3), (4)	5.4 (d) [4]	2	Passed
DTS Bandwidth / 99% Bandwidth	2400.0 - 2483.5	15.247 (a) (2)	5.2 (a) [4]	2	Passed
Peak Power Spectral Density	2400.0 - 2483.5	15.247 (e)	5.2 (b) [4]	2	Passed
Average Power Spectral Density	2400.0 - 2483.5	15.247 (e)	5.2 (b) [4]	2	Passed
Band edge compliance	2400.0 - 2483.5	15.247 (d) 15.205 (a) 15.209 (a)	5.5 [4]	2	Passed
Maximum unwanted emissions	0.009 – 26.5* <sup>1</sup>	15.247 (d) 15.205 (a) 15.209 (a)	8.9 [5]	1* <sup>1</sup>	Passed* <sup>1</sup>
Antenna Requirement	-	15.203 15.247 (b)	6.8 [5] 5.4 (f) (ii) [4]	-	Passed
Conducted emissions on supply line	0.15 – 30	15.207 (a)	8.8 [5]	-* <sup>2</sup>	Not tested* <sup>2</sup>

\*<sup>1</sup> As declared by the applicant the highest radio clock frequency is 2.48 GHz.  
Therefore, the radiated emission measurement must be carried out up to 10<sup>th</sup> of the highest radio clock frequency in this case 26.5 GHz.

\*<sup>2</sup> Not tested, because the tests were not ordered by the applicant.

## 5 Results

### 5.1 Test setups

#### 5.1.1 Radiated: 9 kHz to 30 MHz


##### 5.1.1.1 Preliminary measurement 9 kHz to 30 MHz

In the first stage a preliminary measurement is performed in a semi-anechoic chamber at a measuring distance of 3 meters. Table-top devices are set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices are placed directly on the turntable / ground plane. The setup of the equipment under test is in accordance with [1].

The frequency range 9 kHz to 30 MHz is monitored with an EMI receiver while the system and its cables are manipulated to find out the configuration with the maximum emission levels if applicable. The EMI receiver is set to MAX hold mode. The EUT and the measuring antenna are rotated around their vertical axis to find the maximum emission levels.

The resolution bandwidth of the EMI receiver is set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	9 kHz



Procedure preliminary measurement:

Pre-scans are performed in the frequency range 9 kHz to 150 kHz and 150 kHz to 30 MHz.

The following procedure is used:

- 1) Monitor the frequency range with the measuring antenna facing the EUT and an EUT / turntable azimuth of 0°.
- 2) Manipulate the system cables to produce the maximum levels of emissions.

- 3) Rotate the EUT by 360 ° to maximize the detected signals.
- 4) Measure the frequencies of the highest detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency values.
- 5) If the EUT is portable or ceiling mounted, repeat steps 1 to 4 with other orientations (x,y,z) of the EUT.
- 6) Rotate the measuring antenna and repeat steps 1 to 5.


### 5.1.1.2 Final measurement 9 kHz to 30 MHz

In the second stage a final measurement is performed on an open area test site with no conducting ground plane at a measuring distance of 3 m, 10 m, or 30 m. If the standard requires larger measuring distances for a given frequency, the results are extrapolated according to section 15.31 (f) (2) [2]. The final measurement is performed with an EMI receiver set to Quasi-Peak detector, except for the frequency bands 9 kHz to 90 kHz and 110 kHz to 490 kHz where an Average detector is used according section 15.209 (d) [2].

At the frequencies, which were detected during the preliminary measurements, the final measurement is performed while rotating the EUT and the measuring antenna in the range of 0 ° to 360 ° around their vertical axis until the maximum level value is found.

The resolution bandwidth of the EMI receiver is set to the following values:

Frequency range	Resolution bandwidth	Measuring time
9 kHz to 150 kHz	200 Hz	1 s
150 kHz to 30 MHz	9 kHz	1 s



Procedure final measurement:

The following procedure is used:

- 1) Monitor the selected frequencies from the preliminary measurement with the measuring antenna facing the EUT and an EUT azimuth of 0 °.
- 2) Rotate the EUT by 360 ° to maximize the detected signals.
- 3) Rotate the measuring antenna and repeat steps 1 to 2 until the maximum value is found and note it.
- 4) If the EUT is portable or ceiling mounted, repeat steps 1 to 3 with other orientations (x,y,z) of the EUT.

## 5.1.2 Radiated: 30 MHz to 1 GHz


### 5.1.2.1 Preliminary and final measurement 30 MHz to 1 GHz

The preliminary and final measurements are performed in a semi-anechoic chamber with a metal ground plane at a measuring distance of 3 meters. Table-top devices are set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices are placed directly on the turntable / ground plane. The setup of the equipment under test is in accordance with [1].

During the tests the EUT is rotated in the range of 0 ° to 360 °, the measuring antenna is set to horizontal and vertical polarization and raised and lowered in the range from 1 m to 4 m to find the maximum level of emissions.

The resolution bandwidth of the EMI receiver is set to the following values:

Test	Frequency range	Step-size	Resolution bandwidth	Measuring time	Detector
Preliminary measurement	30 MHz to 1 GHz	30 kHz	120 kHz	-	Peak Average
Frequency peak search	$\pm 120$ kHz	10 kHz	120 kHz	1 s	Peak
Final measurement	30 MHz to 1 GHz	-	120 kHz	1 s	QuasiPeak



Procedure preliminary measurement:

The following procedure is used:

- 1) Set the measuring antenna to 1 m height.
- 2) Monitor the frequency range at horizontal polarization of the measuring antenna and an EUT / turntable azimuth of 0 °.
- 3) Rotate the EUT by 360° to maximize the detected signals.
- 4) Repeat steps 2 to 3 with the vertical polarization of the measuring antenna.
- 5) Increase the height of the measuring antenna for 0.5 m and repeat steps 2 to 4 until the final height of 4 m is reached.
- 6) The highest values for each frequency are saved by the software, including the measuring antenna height and polarization and the turntable azimuth for that value.

Procedure final measurement:

The following procedure is used:

- 1) Select the highest frequency peaks (lowest margin to the limit) for the final measurement.
- 2) The software determines the exact peak frequencies by doing a partial scan with reduced step size of the pre-scan of the selected peaks.
- 3) If the EUT is portable or ceiling mounted, find the worst-case EUT orientation (x,y,z) for the final test.
- 4) The worst-case measuring antenna height is found via varying the height by +/- 0.5 m from the value obtained in the preliminary measurement while monitoring the emission level.
- 5) The worst-case turntable position is found via varying the turntable azimuth by +/- 30° from the value obtained in the preliminary measurement while monitoring the emission level.
- 6) The final measurement is performed at the worst-case measuring antenna height and the worst-case turntable azimuth.
- 7) Steps 2 to 6 are repeated for each frequency peak selected in step 1.

### 5.1.3 Radiated: 1 GHz to 40 GHz


#### 5.1.3.1 Preliminary and final measurement 1 to 40 GHz

The preliminary and final measurements are performed in a fully anechoic chamber at a measuring distance of 3 meters. Table-top devices are set up on a non-conducting turn device at the height of 1.5 m. The setup of the equipment under test is in accordance with [1].

During the tests the EUT is rotated in the range of 0 ° to 360 ° and the measuring antenna is set to horizontal and vertical polarization to find the maximum level of emissions. After these steps, the measurement is repeated after reorientating the EUT in 30 ° steps.

The resolution bandwidth of the EMI receiver is set to the following values:

Test	Frequency range	Step-size	Resolution bandwidth	Measuring time	Detector
Preliminary measurement	1 - 40 GHz	250 kHz	1 MHz	-	Peak Average
Final measurement	1 - 40 GHz	-	1 MHz	100 ms	Peak Average



Procedure preliminary measurement:

The following procedure is used:

- 1) Monitor the frequency range at horizontal polarisation of the measuring antenna and an EUT / turntable azimuth of 0 °.
- 2) Rotate the EUT by 360° to maximize the detected signals.
- 3) Repeat steps 1 to 2 with the vertical polarisation of the measuring antenna.
- 4) Repeat steps 1 to 3 with the EUT reorientated by an angle of 30° (60°, 90°, 120° and 150°), according to 6.6.5.4 in [1].

- 5) The highest values for each frequency are saved by the software, including the measuring antenna polarization, the turntable azimuth and the turn device elevation for that value.


Procedure final measurement:

The following procedure is used:

- 1) Set the turntable and the turn device to the position which leads to the highest emission for the first frequency identified in the preliminary measurements.
- 2) Set the measurement antenna to the polarisation which leads to the highest emission for the first frequency identified in the preliminary measurements.
- 3) Set the spectrum analyser to EMI mode with Peak and Average detector activated.
- 4) The worst-case turntable position is found via varying the turntable azimuth by  $\pm 30^\circ$  from the value obtained in the preliminary measurement while monitoring the emission level.
- 5) The final measurement is performed at the worst-case turntable azimuth.
- 6) Repeat steps 1 to 5 for each frequency detected during the preliminary measurements.

#### 5.1.4 Conducted: Antenna port

Test setup (conducted)		
Used	Antenna connector	Comment
<input checked="" type="checkbox"/>	Temporary antenna connector	As provided by the applicant
<input type="checkbox"/>	Normal antenna connector	-



The 10 dB external attenuation are considered in all relevant plots



## 5.2 Duty cycle

### 5.2.1 Test setup (Duty cycle)

Test setup (Duty cycle)			
Used	Setup	See sub-clause	Comment
<input type="checkbox"/>	Radiated: 1 GHz to 40 GHz	5.1.3	-
<input checked="" type="checkbox"/>	Conducted: Antenna port	5.1.4	-

### 5.2.2 Test method (Duty cycle)

Test method (Duty cycle)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input type="checkbox"/>	11.6. a)	Diode detector	No limitation	-
<input checked="" type="checkbox"/>	11.6. b)	Zero span	No limitation	-

### 5.2.3 Test results (Duty cycle)

Ambient temperature:	23 °C
Relative humidity:	65 %

Date:	16.08.2024
Tested by:	D. BRUSCHINSKI

The duty cycle is 100 %.

No DCCF is applied, duty cycle  $\geq$  98%.

Test equipment (please refer to chapter 7 for details)
1 - 2

### 5.3 DTS bandwidth

#### 5.3.1 Test setup (DTS bandwidth)

Test setup (DTS bandwidth)			
Used	Setup	See sub-clause	Comment
<input type="checkbox"/>	Radiated: 1 GHz to 40 GHz	5.1.3	-
<input checked="" type="checkbox"/>	Conducted: Antenna port	5.1.4	-

#### 5.3.2 Test method (DTS bandwidth)


Test method (DTS bandwidth)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input checked="" type="checkbox"/>	11.8.1	Option 1	No limitations	-
<input type="checkbox"/>	11.8.2	Option 2	No limitations	6 dB down function

#### 5.3.3 Test results (DTS bandwidth)

Ambient temperature:	23 °C
Relative humidity:	65 %

Date:	16.08.2024
Tested by:	D. BRUSCHINSKI

Worst case plot (operation mode 1):



Operation mode #	DTS bandwidth [MHz]	Minimum DTS bandwidth Limit [MHz]
1	<b>0.684</b>	0.5
2	0.705	0.5
3	0.729	0.5
4	0.772	0.5
5	0.743	0.5
6	0.751	0.5
7	0.789	0.5
8	0.804	0.5
9	0.761	0.5
10	1.440	0.5
11	1.366	0.5
12	1.432	0.5

Test result: Passed

Test equipment (please refer to chapter 7 for details)

1 - 2

## 5.4 Occupied bandwidth – power bandwidth (99%)

### 5.4.1 Test Setup (Occupied bandwidth – power bandwidth (99%))

Test setup (Occupied bandwidth – power bandwidth (99%))			
Used	Setup	See sub-clause	Comment
<input type="checkbox"/>	Radiated: 1 GHz to 40 GHz	5.1.3	-
<input checked="" type="checkbox"/>	Conducted: Antenna port	5.1.4	-

### 5.4.2 Test method (Occupied bandwidth – power bandwidth (99%))

Test method (Occupied bandwidth – power bandwidth (99%))				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input type="checkbox"/>	6.9.2	Relative measurement procedure	-	n-dB down
<input checked="" type="checkbox"/>	6.9.3	Power bandwidth (99%)	*	99% power function


\* See RSS-GEN Issue 5 (2018-05) sub-clause 6.7 for details.

### 5.4.3 Test results (Occupied bandwidth – power bandwidth (99%))

Ambient temperature:	23 °C
Relative humidity:	65 %

Date:	16.08.2024
Tested by:	D. BRUSCHINSKI

Worst case plot (operation mode 10):



Operation mode #	99% bandwidth [MHz]
1	1.086
2	1.094
3	1.099
4	1.047
5	1.064
6	1.060
7	1.059
8	1.073
9	1.078
<b>10</b>	<b>2.082</b>
11	2.077
12	2.068

Test result: Passed

Test equipment (please refer to chapter 7 for details)
1 - 2

## 5.5 DTS fundamental emission output power

### 5.5.1 Test setup (DTS fundamental emission output power)

Test setup (DTS fundamental emission output power)			
Used	Setup	See sub-clause	Comment
<input type="checkbox"/>	Radiated: 1 GHz to 40 GHz	5.1.3	-
<input checked="" type="checkbox"/>	Conducted: Antenna port	5.1.4	-

### 5.5.2 Test method (DTS fundamental emission output power)

Test method (Maximum peak conducted output power)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input checked="" type="checkbox"/>	11.9.1.1	RBW $\geq$ DTS bandwidth	-	Zero span mode
<input type="checkbox"/>	11.9.1.2	PKPM1 Peak power meter method*	-	-

\* VBW of the peak power meter has to be  $>$  OBW of the fundamental.

Test method (Maximum conducted (average) output power)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input checked="" type="checkbox"/>	11.9.2.2.2	Method AVGSA-1	$D \geq 98\%$	-
<input type="checkbox"/>	11.9.2.2.3	Method AVGSA-1A (alternative)	$D \geq 98\%$	-
<input type="checkbox"/>	11.9.2.2.4	Method AVGSA-2	Constant D ( $\pm 2\%$ )	-
<input type="checkbox"/>	11.9.2.2.5	Method AVGSA-2A (alternative)	Constant D ( $\pm 2\%$ )	-
<input type="checkbox"/>	11.9.2.2.6	Method AVGSA-3A	-	-
<input type="checkbox"/>	11.9.2.2.7	Method AVGSA-3A (alternative)	-	-
<input type="checkbox"/>	11.9.2.3.1	Method AVGPM	Constant D ( $\pm 2\%$ )	-
<input type="checkbox"/>	11.9.2.3.2	Method AVGPM-G	-	-


### 5.5.3 Test results (DTS fundamental emission output power)

Ambient temperature:	23 °C
Relative humidity:	65 %

Date:	16.08.2024
Tested by:	D. BRUSCHINSKI

#### 5.5.3.1 Maximum peak conducted output power:

Worst case plot (operation mode 1):




Operation mode	Reading [dBm]	Correction factor [dB]	Result [dBm]	Limit [dBm]	Antenna gain * [dBi]	e.i.r.p. [dBm]	Limit e.i.r.p. [dBm]
1	7.4	0.3	7.7	30	0.4	8.1	36
2	7.2	0.3	7.5	30	1.1	8.6	36
3	7.1	0.3	7.4	30	0.5	7.9	36
4	7.1	0.3	7.4	30	0.4	7.8	36
5	7.3	0.3	7.6	30	1.1	8.7	36
6	7.1	0.3	7.4	30	0.5	7.9	36
7	7.3	0.3	7.6	30	0.4	8.0	36
8	7.3	0.3	7.6	30	1.1	8.7	36
9	7.1	0.3	7.4	30	0.5	7.9	36
10	7.2	0.3	7.5	30	0.4	7.9	36
11	7.2	0.3	7.5	30	1.1	8.6	36
12	6.9	0.3	7.2	30	0.5	7.7	36

\* The calculation of the antenna gain is shown in the antenna report F231413E5 by PHOENIX TESTLAB GmbH.

Test result: Passed

### 5.5.3.2 Maximum conducted (average) output power

Worst case plot (operation mode 1):



Operation mode	Reading [dBm]	Corr. Fact. [dB]	DCCF [dB]	Result [dBm]	Limit [dBm]	Antenna gain [dBi]	e.i.r.p. [dBm]	Limit e.i.r.p. [dBm]
1	7.4	0.3	0.0	7.7	30	0.4	8.1	36
2	7.1	0.3	0.0	7.4	30	1.1	8.5	36
3	7.1	0.3	0.0	7.4	30	0.5	7.9	36
4	7.1	0.3	0.0	7.4	30	0.4	7.8	36
5	7.2	0.3	0.0	7.5	30	1.1	8.6	36
6	7.1	0.3	0.0	7.4	30	0.5	7.9	36
7	7.3	0.3	0.0	7.6	30	0.4	8.0	36
8	7.2	0.3	0.0	7.5	30	1.1	8.6	36
9	7.1	0.3	0.0	7.4	30	0.5	7.9	36
10	7.1	0.3	0.0	7.4	30	0.4	7.8	36
11	7.2	0.3	0.0	7.5	30	1.1	8.6	36
12	6.9	0.3	0.0	7.2	30	0.5	7.7	36

\* The calculation of the antenna gain is shown in the antenna report F231413E5 by PHOENIX TESTLAB GmbH.

Test result: Passed

Test equipment (please refer to chapter 7 for details)
1 - 2



## 5.6 DTS maximum power spectral density

### 5.6.1 Test setup (DTS maximum PSD level in the fundamental emission)

Test setup (DTS fundamental emission output power)			
Used	Setup	See sub-clause	Comment
<input type="checkbox"/>	Radiated: 1 GHz to 40 GHz	5.1.3	-
<input checked="" type="checkbox"/>	Conducted: Antenna port	5.1.4	-

### 5.6.2 Test method (DTS maximum PSD level in the fundamental emission)

Test method (Maximum <i>peak</i> power spectral density level in the fundamental emission)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input checked="" type="checkbox"/>	11.10.2	Method PKPSD (peak PSD)	No limitations	-

Test method (Maximum <i>average</i> power spectral density level in the fundamental emission)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input checked="" type="checkbox"/>	11.10.3	Method AVGPSD-1	$D \geq 98\%$	-
<input type="checkbox"/>	11.10.4	Method AVGPSD-1A (alternative)	$D \geq 98\%$	-
<input type="checkbox"/>	11.10.5	Method AVGPSD-2	Constant D ( $\pm 2\%$ )	-
<input type="checkbox"/>	11.10.6	Method AVGPSD-2A (alternative)	Constant D ( $\pm 2\%$ )	-
<input type="checkbox"/>	11.10.7	Method AVGPSD-3	No limitations	-
<input type="checkbox"/>	11.10.8	Method AVGPSD-3A (alternative)	No limitations	-


### 5.6.3 Test results (DTS maximum PSD level in the fundamental emission)

Ambient temperature:	23 °C
Relative humidity:	65 %

Date:	16.08.2024
Tested by:	D. BRUSCHINSKI

#### 5.6.3.1 Maximum peak PSD:

Worst case plot (operation mode 1):




Operation mode	Reading [dBm/3 kHz]	Corr. Fact. [dB]	Result [dBm/3 kHz]	Limit [dBm/3 kHz]
1	1.4	0.3	1.7	8.0
2	1.2	0.3	1.5	8.0
3	1.1	0.3	1.4	8.0
4	-5.1	0.3	-4.8	8.0
5	-4.2	0.3	-3.9	8.0
6	-4.2	0.3	-3.9	8.0
7	-4.6	0.3	-4.3	8.0
8	-5.9	0.3	-5.6	8.0
9	-6.8	0.3	-6.5	8.0
10	-9.0	0.3	-8.7	8.0
11	-8.4	0.3	-8.1	8.0
12	-9.4	0.3	-9.1	8.0

Test result: Passed

### 5.6.3.2 Maximum average PSD

Worst case plot (operation mode 1):



Operation mode	Reading [dBm/3 kHz]	Corr. Fact. [dB]	DCCF [dB]	Result [dBm/3 kHz]	Limit [dBm/3 kHz]
1	0.7	0.3	0.0	<b>1.0</b>	8.0
2	0.3	0.3	0.0	0.6	8.0
3	0.4	0.3	0.0	0.7	8.0
4	-13.9	0.3	0.0	-13.6	8.0
5	-13.6	0.3	0.0	-13.3	8.0
6	-13.9	0.3	0.0	-13.6	8.0
7	-12.6	0.3	0.0	-12.3	8.0
8	-13.5	0.3	0.0	-13.2	8.0
9	-13.1	0.3	0.0	-12.8	8.0
10	-14.7	0.3	0.0	-14.4	8.0
11	-14.6	0.3	0.0	-14.3	8.0
12	-15.2	0.3	0.0	-14.9	8.0

Test result: Passed

Test equipment (please refer to chapter 7 for details)
1 - 2

## 5.7 DTS band-edge emission measurements

### 5.7.1 Test setup (Band edge – unrestricted bands)

Test setup (Band edge – unrestricted bands)			
Used	Setup	See sub-clause	Comment
<input checked="" type="checkbox"/>	Radiated: 1 GHz to 40 GHz (final measurement)	5.1.3	-
<input checked="" type="checkbox"/>	Conducted: Antenna port (preliminary measurement)	5.1.4	-

### 5.7.2 Test method (Band edge – unrestricted bands)

Test method (Band edge – unrestricted bands)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input type="checkbox"/>	11.11.	20 dBc (Peak)	Peak power	*1
<input checked="" type="checkbox"/>	11.11.	30 dBc (Average)	RMS power	*2

\*1 As declared in “47 CFR 15.247(d)” In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits

\*2 If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 5.7.3 Test results (Band edge – unrestricted bands)

Ambient temperature:	23 °C / 22 °C
Relative humidity:	65 % / 33 %

Date:	16.08.2024 / 16.10.2024
Tested by:	D. BRUSCHINSKI

**Worst case plot lower band edge, radiated measurement (operation mode 10):**



## Conducted preliminary measurements:

### Lower band edge (operation mode 1):

Frequency [MHz]	Reference [dB(μV/m)]	Limit [dB(μV/m)]	Unrestricted band emission [dB(μV/m)]	Margin [dB]
2399.992	5.3	-24.7	-42.1	17.4

### Lower band edge (operation mode 4):

Frequency [MHz]	Reference [dB(μV/m)]	Limit [dB(μV/m)]	Unrestricted band emission [dB(μV/m)]	Margin [dB]
2399.992	6.1	-23.9	-41.8	17.9

### Lower band edge (operation mode 7):

Frequency [MHz]	Reference [dB(μV/m)]	Limit [dB(μV/m)]	Unrestricted band emission [dB(μV/m)]	Margin [dB]
2399.980	5.9	-24.1	-41.4	17.3

### Lower band edge (operation mode 10):

Frequency [MHz]	Reference [dB(μV/m)]	Limit [dB(μV/m)]	Unrestricted band emission [dB(μV/m)]	Margin [dB]
2399.987	4.8	-25.2	-27.2	2.0

Test result: Passed

Test equipment (please refer to chapter 7 for details)
1 – 2, 4, 6 – 9, 12, 14, 17

#### 5.7.4 Test setup (Band edge – restricted bands)

Test setup (Band edge – restricted bands)			
Used	Setup	See sub-clause	Comment
<input checked="" type="checkbox"/>	Radiated: 1 GHz to 40 GHz	5.1.3	-
<input type="checkbox"/>	Conducted: Antenna port	5.1.4	-

#### 5.7.5 Test method (Band edge – restricted bands)


Test method (Band edge – restricted bands)				
Used	Sub-Clause [1]	Name of method	Applicability	Comment
<input checked="" type="checkbox"/>	11.12.1	Standard method	No limitations	-
<input type="checkbox"/>	11.12.3.1	Marker-delta method	-	See 6.10.6 [3] 2 MHz from band
<input type="checkbox"/>	11.12.3.2	Integration method	-	2 MHz from band

#### 5.7.6 Test results (Band edge – restricted bands)

Ambient temperature:	22 °C
Relative humidity:	34 %

Date:	16.10.2024
Tested by:	D. BRUSCHINSKI

#### Worst case plot upper band edge (operation mode 12):



## Result tables:

### Upper band edge (operation mode 3):

Frequency [MHz]	Result (Pk) [dB(μV/m)]	Result (Av) [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
2,483.500	53.46	-	74.00	20.54
2,483.500	-	38.99	54.00	15.01
2,485.250	51.46	-	74.00	22.54
2,485.250	-	37.19	54.00	16.81

### Upper band edge (operation mode 6):

Frequency [MHz]	Result (Pk) [dB(μV/m)]	Result (Av) [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
2,483.500	54.64	-	74.00	19.36
2,483.500	-	39.05	54.00	14.95
2,486.750	51.15	-	74.00	22.85
2,486.750	-	35.55	54.00	18.45

### Upper band edge (operation mode 9):

Frequency [MHz]	Result (Pk) [dB(μV/m)]	Result (Av) [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
2,483.500	54.33	-	74.00	19.67
2,483.500	-	40.24	54.00	13.76
2,485.500	51.41	-	74.00	22.59
2,485.500	-	36.98	54.00	17.02
2,489.250	49.64	-	74.00	24.36
2,489.250	-	34.46	54.00	19.54



**Upper band edge (operation mode 12):**

Frequency [MHz]	Result (Pk) [dB(μV/m)]	Result (Av) [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
2,483.500	58.21	-	74.00	15.79
2,483.500	-	43.21	54.00	10.79
2,484.000	56.31	-	74.00	17.69
2,484.000	-	42.48	54.00	11.52
2,485.500	53.31	-	74.00	20.69
2,485.500	-	39.36	54.00	14.64
2,487.500	52.50	-	74.00	21.50
2,487.500	-	38.08	54.00	15.92

Test result: Passed

Test equipment (please refer to chapter 7 for details)

4, 6 – 9, 12, 14, 17

## 5.8 Radiated emissions

### 5.8.1 Test setup (Maximum unwanted emissions)

Test setup (Maximum unwanted emissions)			
Used	Setup	See sub-clause	Comment
<input checked="" type="checkbox"/>	Radiated: 9 kHz to 30 MHz / 30 MHz to 1 GHz / 1 GHz to 40 GHz	5.1.1 / 5.1.2 / 5.1.3	-
<input type="checkbox"/>	Conducted: Antenna port	5.1.4	-

### 5.8.2 Test method (Maximum unwanted emissions)

☒ Test method (radiated) see sub-clause 5.1 as described herein

### 5.8.3 Test results (Maximum unwanted emissions)

#### 5.8.3.1 Test results preliminary measurement 9 kHz to 30 MHz

Ambient temperature:	24 °C
Relative humidity:	65 %

Date:	16.08.2024
Tested by:	D. BRUSCHINSKI

Position of EUT: For tests for f between 9 kHz to 30 MHz, the EUT was set-up on a table with a height of 80 cm. The distance between EUT and antenna was 3 m.

Cable guide: For detail information of test set-up and the cable guide refer to the pictures in the annex A of the test report.

Test record: The measurement value was already corrected by 40 dB/decade as described in 47 CFR 15.31(f)(2) regarding to the measurement distance as requested in 47 CFR 15.209(a)

Remark: All 3 orthogonal planes were tested separately.  
The tests were only performed with a data rate of 500 kbps because pretests have shown that the emissions do not change significantly when varying the data rate.

Calculations:

Result @ norm. dist. [dBμV/m] = Reading [dBμV] + AF [dB/m] + Distance corr. fact. [dB]

Result @ norm. dist. [dBμA/m] = Result @ norm. dist. [dBμV/m] – 20 x log<sub>10</sub> (377 Ω)

Margin [dB] = Limit [dB(μV|μA)/m] - Result [dB(μV|μA)/m]

### Worst case plot:

Spurious emissions from 9 kHz to 30 MHz (operation mode 6, position 3):



Remark: No emissions closer than 20 dB to the limit, so no final measurement will be carried out.

Test result: Passed

Test equipment (please refer to chapter 7 for details)

3 - 9

### 5.8.3.2 Test results (30 MHz – 1 GHz)

Ambient temperature:	22 °C
Relative humidity:	52 %

Date:	12.08.2024
Tested by:	D. BRUSCHINSKI

Position of EUT: For tests for f between 30 MHz to 1 GHz, the EUT was set-up on a table with a height of 80 cm. The distance between EUT and antenna was 3 m.

Cable guide: For detail information of test set-up and the cable guide refer to the pictures in the annex A of the test report.

Test record: Plots for each frequency range are submitted below.

Remark: All 3 orthogonal planes were tested separately  
The tests were only performed with a data rate of 500 kbps because pretests have shown that the emissions do not change significantly when varying the data rate.

Calculations:

Result [dBμV/m] = Reading [dBμV] + Correction [dB/m]


Correction [dB/m] = AF [dB/m] + Cable attenuation [dB] + optional preamp gain [dB]

Margin [dB] = Limit [dBμV/m] - Result [dBμV/m]

The measured points and the limit line in the following diagram refer to the standard measurement of the emitted interference in compliance with the above-mentioned standard. The measured points marked with “♦” are the measured results of the standard subsequent measurement in a semi-anechoic chamber.

### Worst case plot:

Spurious emissions from 30 MHz to 1 GHz (operation mode 4, position 1):



### Result tables:

Operation mode 4:

Frequency [MHz]	Result (QP) [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Correction [dB/m]	Pol. (H/V)	Azimuth [deg]	Height [m]
30.690	26.14	40.00	13.86	26.24	H	71	1.59
32.820	37.55	40.00	2.45	24.92	H	133	1.50
37.470	36.64	40.00	3.36	21.98	H	18	1.99
37.470	36.64	40.00	3.36	21.98	H	18	1.99
42.030	29.00	40.00	11.00	18.94	V	359	1.01
48.060	14.38	40.00	25.62	14.87	V	41	1.03
66.060	30.55	40.00	9.45	13.61	V	183	1.03
144.120	21.09	43.50	22.41	15.63	H	127	1.80
240.240	23.13	46.00	22.87	17.00	H	133	1.00

Operation mode 5:

Frequency [MHz]	Result (QP) [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Correction [dB/m]	Pol. (H/V)	Azimuth [deg]	Height [m]
30.390	35.46	40.00	4.54	26.42	H	162	1.50
32.730	36.47	40.00	3.53	24.97	H	121	1.79
37.290	29.06	40.00	10.94	22.10	H	91	1.94
42.060	28.76	40.00	11.24	18.91	V	42	1.00
48.060	15.11	40.00	24.89	14.87	V	313	1.32
66.060	30.07	40.00	9.93	13.61	V	157	1.35
144.120	19.64	43.50	23.86	15.63	H	277	1.50
240.270	22.95	46.00	23.05	17.00	H	262	1.32
312.360	26.20	46.00	19.80	19.28	H	248	1.00

Operation mode 6:

Frequency [MHz]	Result (QP) [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Correction [dB/m]	Pol. (H/V)	Azimuth [deg]	Height [m]
30.000	33.64	40.00	6.36	26.66	H	191	1.55
32.760	35.99	40.00	4.01	24.95	H	283	1.78
37.470	35.66	40.00	4.34	21.98	H	329	2.00
42.060	30.85	40.00	9.15	18.91	V	10	1.02
48.060	16.53	40.00	23.47	14.87	V	340	1.37
66.090	31.08	40.00	8.92	13.62	V	184	1.33
144.150	22.05	43.50	21.45	15.63	H	264	1.50
210.900	22.56	43.50	20.94	16.23	H	322	1.62
312.360	25.69	46.00	20.31	19.28	H	246	1.01

Test result: Passed

Test equipment (please refer to chapter 7 for details)

4 - 12

### 5.8.3.3 Test results (radiated 1 GHz to 26.5 GHz)

Ambient temperature:	23 °C
Relative humidity:	63 % - 64 %

Date:	07.08.2024 / 09.08.2024
Tested by:	D. BRUSCHINSKI

Position of EUT: For tests for f between 1 GHz and the 10<sup>th</sup> harmonic, the EUT was set-up on a positioner device with a height of 150 cm. The distance between EUT and antenna was 3 m.

Cable guide: For detail information of test set-up and the cable guide refer to the pictures in the annex A of the test report.

Test record: Plots for each frequency range are submitted below.

Remark: The tests were only performed with a data rate of 500 kbps because pretests have shown that the emissions do not change significantly when varying the data rate.

#### Calculation:

Max Peak [dBμV/m] = Reading [dBμV] + Correction [dB/m]

Average [dBμV/m] = Reading [dBμV] + Correction [dB/m]

Correction [dB/m] = AF [dB/m] + Cable attenuation [dB] + optional preamp gain [dB] + DCCF\* [dB]  
\* (if applicable – only for Average values, that are fundamental related)


Margin [dB] = Limit [dBμV/m] – Max Peak | Average [dBμV/m]

The curves in the diagram only represent the maximum measured value for each frequency point of all preliminary measurements, which were carried out with various EUT and antenna positions.


The top measured curve represents the peak measurement. The measured points marked with "◇" are frequency points for the final peak detector measurement. These values are indicated in the following table. The bottom measured curve represents the average measurement. The measured points marked with "◇" are frequency points for the final average detector measurement.

## Worst case plots:

Spurious emissions from 1 GHz to 4 GHz (operation mode 5):




Spurious emissions from 4 GHz to 18 GHz (operation mode 4):





Spurious emissions from 18 GHz to 26.5 GHz (operation mode 4):



### Result tables:

Operation mode 4:

Frequency [MHz]	MaxPeak [dB(μV/m)]	Average [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Pol [H/V]	Azimuth [deg]	Elevation [deg]	Corr. [dB/m]
1016.000	37.75	-	74.00	36.25	V	66	90	25.75
1016.000	-	20.63	54.00	33.37	V	59	90	25.75
1071.250	37.71	-	74.00	36.29	V	72	90	26.24
1071.250	-	20.83	54.00	33.17	V	65	90	26.24
1113.750	44.14	-	74.00	29.86	V	74	90	26.44
1113.750	-	20.72	54.00	33.28	V	68	90	26.44
1204.500	40.68	-	74.00	33.32	V	64	150	27.27
1204.500	-	21.71	54.00	32.29	V	63	150	27.27
3451.000	54.64	-	74.00	19.36	H	102	150	40.40
3451.000	-	39.78	54.00	14.22	H	92	150	40.40
4804.000	58.95	-	74.00	15.05	V	216	90	9.69
4804.000	-	53.56	54.00	0.44	V	214	90	9.69
7206.500	59.50	-	74.00	14.50	H	276	90	13.56
7206.500	-	52.44	54.00	1.56	H	274	90	13.56
9608.750	56.79	-	74.00	17.21	V	272	90	18.83
9608.750	-	47.79	54.00	6.21	V	276	90	18.83
12011.000	55.99	-	74.00	18.01	V	270	60	23.46
12011.000	-	45.42	54.00	8.58	V	280	60	23.46
15208.000	54.54	-	74.00	19.46	V	52	120	27.11
15208.000	-	41.77	54.00	12.23	V	52	120	27.11
16748.000	58.25	-	74.00	15.75	H	178	150	29.54
16748.000	-	44.78	54.00	9.22	H	198	150	29.54
25165.750	46.73	-	74.00	27.27	H	73	0	11.50
25165.750	-	33.11	54.00	20.89	H	48	0	11.50

Operation mode 5:

Frequency [MHz]	MaxPeak [dB(μV/m)]	Average [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Pol [H/V]	Azimuth [deg]	Elevation [deg]	Corr. [dB/m]
1045.250	37.96	-	74.00	36.04	V	306	150	25.94
1045.250	-	20.62	54.00	33.38	V	299	150	25.94
1102.000	37.81	-	74.00	36.19	V	72	150	26.35
1102.000	-	21.02	54.00	32.98	V	71	150	26.35
2472.000	54.93	-	74.00	19.07	H	220	150	35.37
2472.000	-	38.34	54.00	15.66	H	220	150	35.37
3461.750	54.68	-	74.00	19.32	H	110	120	40.35
3461.750	-	39.72	54.00	14.28	H	113	120	40.35
3857.500	54.48	-	74.00	19.52	V	55	90	40.03
3857.500	-	39.67	54.00	14.33	V	61	90	40.03
4880.000	57.96	-	74.00	16.04	V	216	90	9.92
4880.000	-	53.13	54.00	0.87	V	214	90	9.92
7320.500	59.34	-	74.00	14.66	H	264	90	14.47
7320.500	-	52.53	54.00	1.47	H	270	90	14.47
9760.750	55.39	-	74.00	18.61	V	274	90	18.45
9760.750	-	45.67	54.00	8.33	V	278	90	18.45
12201.000	54.45	-	74.00	19.55	V	288	60	23.05
12201.000	-	43.00	54.00	11.00	V	288	60	23.05
14695.250	54.68	-	74.00	19.32	V	236	150	27.23
14695.250	-	42.25	54.00	11.75	V	250	150	27.23
16715.250	57.92	-	74.00	16.08	V	318	150	29.48
16715.250	-	44.81	54.00	9.19	V	319	150	29.48
25109.750	45.61	-	74.00	28.39	H	353	150	11.56
25109.750	-	32.98	54.00	21.02	H	12	150	11.56

Operation mode 6:

Frequency [MHz]	MaxPeak [dB(μV/m)]	Average [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Pol [H/V]	Azimuth [deg]	Elevation [deg]	Corr. [dB/m]
1100.500	37.60	-	74.00	36.40	V	66	150	26.33
1100.500	-	20.97	54.00	33.03	V	74	150	26.33
1351.250	40.29	-	74.00	33.71	H	278	120	28.43
1351.250	-	23.01	54.00	30.99	H	280	120	28.43
1566.750	42.03	-	74.00	31.97	V	31	30	30.49
1566.750	-	25.75	54.00	28.25	V	30	30	30.49
2351.750	52.06	-	74.00	21.94	H	225	150	35.27
2351.750	-	39.41	54.00	14.59	H	224	150	35.27
3669.750	53.81	-	74.00	20.19	H	211	60	39.44
3669.750	-	39.10	54.00	14.90	H	209	60	39.44
4960.000	56.23	-	74.00	17.77	H	274	60	10.06
4960.000	-	50.55	54.00	3.45	H	278	60	10.06
7440.500	60.12	-	74.00	13.88	H	278	90	15.14
7440.500	-	53.29	54.00	0.71	H	268	90	15.14
9920.750	55.76	-	74.00	18.24	V	274	90	19.69
9920.750	-	47.02	54.00	6.98	V	276	90	19.69
12401.000	56.22	-	74.00	17.78	V	278	90	23.52
12401.000	-	45.00	54.00	9.00	V	278	90	23.52
15788.250	56.09	-	74.00	17.91	H	23	60	28.19
15788.250	-	43.12	54.00	10.88	H	50	60	28.19
16688.750	56.99	-	74.00	17.01	H	351	120	29.35
16688.750	-	44.63	54.00	9.37	H	19	120	29.35
21463.250	45.06	-	74.00	28.94	V	79	150	11.42
21463.250	-	32.56	54.00	21.44	V	61	150	11.42

Test result: Passed

Test equipment (please refer to chapter 7 for details)

4 - 9, 12 - 18

## 6 Measurement Uncertainties

Conducted measurements		
Measurement method	Standard used for calculating measurement uncertainty	Expanded measurement uncertainty (95 %) $U_{lab}$
Frequency error	ETSI TR 100 028	$4.5 \times 10^{-8}$
Bandwidth measurements	-	$9.0 \times 10^{-8}$
Conducted emissions using a spectrum analyzer		
< 3.6 GHz	ETSI TR 100 028	2.3 dB
3.6 – 8 GHz	ETSI TR 100 028	2.8 dB
8 – 22 GHz	ETSI TR 100 028	3.2 dB
22 – 40 GHz	ETSI TR 100 028	3.6 dB
Power measurements		
Power meter	ETSI TR 100 028	0.9 dB
Conducted emissions from 150 kHz to 30 MHz with LISN		
	CISPR 16-4-2	2.8 dB

Radiated measurements		
Frequency error		
(Semi-) Anechoic chamber	ETSI TR 100 028	$4.5 \times 10^{-8}$
OATS	ETSI TR 100 028	$4.5 \times 10^{-8}$
Test fixture	ETSI TR 100 028	$4.5 \times 10^{-8}$
Bandwidth measurements		
(Semi-) Anechoic chamber	-	$9.0 \times 10^{-8}$
OATS	-	$9.0 \times 10^{-8}$
Test fixture	-	$9.1 \times 10^{-8}$
Radiated field strength M20		
CBL6112B @ 3 m 30 MHz – 1 GHz	CISPR 16-4-2	5.3 dB
R&S HL050 @ 3 m		
1 – 6 GHz	CISPR 16-4-2	5.1 dB
6 – 18 GHz	CISPR 16-4-2	5.4 dB
Flann Standard Gain Horns 12 – 40 GHz	-	5.9 dB
Radiated field strength M276		
R&S HL562E @ 3 m 30 MHz – 1 GHz	CISPR 16-4-2	4.8 dB
R&S HL050 @ 3 m	-	
1 – 6 GHz	CISPR 16-4-2	5.1 dB
6 – 18 GHz	CISPR 16-4-2	5.4 dB
Flann Standard Gain Horns 12 – 40 GHz	-	5.9 dB
OATS		
Field strength measurements below 30 MHz on OATS without ground plane	-	4.4 dB

## 7 Test Equipment used for Tests

No.	Test equipment	Type	Manufacturer	Serial No.	PM. No.	Cal. Date	Cal Due
1	Signal & spectrum analyzer	FSW43	Rohde & Schwarz	100586 & 100926	481720	17.03.2023	03.2025
2	RF cable	Sucoflex 104	Huber+Suhner	517402	482392	Calibration not necessary	
3	Loop antenna	HFH2-Z2	Rohde & Schwarz	832609/014	480059	21.02.2024	02.2026
4	EMC test software	Elektra V5.02.1	Rohde & Schwarz		483755	Calibration not necessary	
5	RF switch matrix	OSP220	Rohde & Schwarz	101391	482976	Calibration not necessary	
6	Turntable	TT3.0-3t	Maturo	825/2612/.01	483224	Calibration not necessary	
7	Controller	NCD	Maturo	474/2612.01	483226	Calibration not necessary	
8	Semi anechoic chamber M276	SAC5-2	Albatross Projects	C62128-A540-A138-10-0006	483227	Calibration not necessary	
9	EMI test receiver	ESW44	Rohde & Schwarz	101828	482979	21.02.2024	02.2026
10	Attenuator 6 dB	WA2-6	Weinschel		482793	Calibration not necessary	
11	Ultralog antenna	HL562E	Rohde & Schwarz	101079	482978	24.04.2024	04.2027
12	Antenna support	BAM 4.5-P-10kg	Maturo	222/2612.01	483225	Calibration not necessary	
13	Low noise amplifier 100 MHz - 18 GHz	LNA-30-00101800-25-10P	Narda-Miteq	2110917	482967	20.02.2024	02.2026
14	Log.-per. antenna	HL050	Rohde & Schwarz	100908	482977	22.09.2022	09.2025
15	Low noise amplifier 18 GHz - 26.5 GHz	LNA-30-18002650-20-10P	Narda-Miteq	2110911	482969	19.02.2024	02.2026
16	Standard gain horn 18 GHz – 26.5 GHz	20240-20	Flann	266399	483026	Calibration not necessary	
17	Positioner	TG1.5-10kg	Maturo	110/2648.01	483042	Calibration not necessary	
18	High-pass filter	WHKX4.0/18G-8SS	Wainwright	1	480587	Calibration not necessary	

## 8 Test site Verification

Test equipment	PM. No.	Frequency range	Type of validation	According to	Val. Date	Val Due
Semi anechoic chamber M276	483227	30 – 1000 MHz	NSA	ANSI C63.4-2014 ANSI C63.4a-2017	01.03.2023	28.02.2026
Semi anechoic chamber M276	483227	1 -18 GHz	SVSWR	CISPR 16-1-4 + Cor1:2010 + A1:2012 +A2:2017	28.02.2023	27.02.2026

## 9 Report History

Report Number	Date	Comment
F231413E3	09.01.2025	Initial Test Report
-	-	-

## 10 List of Annexes

Annex A	Test Setup Photos	18 pages
Annex B	EUT External Photos	7 pages
Annex C	EUT Internal Photos *	3 pages

\* The internal photographs were provided by the applicant.

--- end of test report ---