



Shenzhen Shuodian Electronic Technology Co.,Ltd
Page number 1-10

SPECIFICATION

for

HUB3 WIFI antenna

Customer No.

Product No.

WA-HUB3 WIFI ANT-FPC

Author: XiaofengZeng **Review:** Liming

Release Date: 2024.12.27

ShenZhen Shuodian Electronic Technology Co., Ltd

Room 201, Building 2, Nantaiyun Chuanggu Park, Tangwei Community, Fenghuang Street,
Guangming District, Shenzhen City, Guangdong Province

E-mail: **sz_shuodian@163.com**

Tel: 0755-86006322

Fax: 0755-86006323

Shenzhen Shuodian Electronic Technology Co.,Ltd



Contents

SPECIFICATION	1
SHENZHEN SHUODIAN ELECTRONIC TECHNOLOGY CO., LTD	1
CONTENTS	2
1. BILATERAL CONFIRMATION PAGE	3
2. GENERAL	4
3. GENERAL PRODUCT SPECIFICATIONS	4
4. SPECIFICATION DETIALS	5
4.1 MECHANICAL PROPERTIES	5
4.2 ELECTRIC PERFORMANCE	7
5. PRODUCT PACKAGING	10
6. DOCUMENT RESUME	10



1. Bilateral Confirmation page

1.1 Customer signature

Customer:

Seapartment/post	Sign	Date
Hardware Engineer/RD		
Mechanical/MD		
Project Manager/PM		
Commercial/Puchasing		
Checker		

1.2 Signature of ShuoDian Technology company

Seapartment/post	Sign	Date
Antenna Engineer/RD		
Mechanical/MD		
Project Manager/PM		
QA		
Checker		



2. General

2.1 Scope of application

This specification is only applicable to WOAN HUB3-WIFI antenna

2.2 Operating temperature range

Temperature range of this product: -20 ~ +65 °C

2.3 Storage temperature range:

This product is stored at - 30 ~ + 75 °C

3. General product specifications

NO.	ITEMS	DETAILS
1	Type	HUB3 WIFI antenna
2	Operating Frequency Band	2400-2500MHz
3	VSWR	≤ 2.0
4	Impedance	50 Ω
5	Antenna Type	PIFA
6	Antenna composition	FPC
7	Entity Picture	



4. Specification Detials

4.1 Mechanical Properties

4.11 Product Composition:


No.	Material	Size (MM)
1	FPC	22. 21*16. 24 Black

4.12 Apperance

Good appearance without scars 、 dirts、 protuberances, etc.

4.13 Antenna Picture and Structure Dimension

Productdrawings:






4.2 Electric Performance

4.21 Test condition

Environment:	Equipment:
Temperature: 10℃——+30℃	Network Analyzer: KEYSIGHT E5071C
Humidity: ≤80% (+40℃)	Multi-probe microwave anechoic chamber
Atmospher: 750mmkg±30mmkg	



4.22 Test Data for Electrical Performance:

WIFI matching parameters: (Match parameters added by chip factory)



4.22.1 S11 of the Antenna:

Marker	2400	2450	2500
Returnloss	-12.39	-17.43	-14.57
VSWR	1.62	1.32	1.46






4. 22. 2 Passive gain、 efficiency and Radiation Pattern:

Frequency (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain (dBi)	2.42	2.60	2.58	2.69	3.09	3.13	3.14	3.05	3.00	3.13	2.95
Efficiency (%)	46.74	49.10	51.17	52.17	54.51	54.49	54.05	52.40	49.07	47.12	45.23

Radiation Pattern 2450MHz

@2450MHz





5. Product Packaging

Manner of packing:

Packed in self sealed bags, 200 pcs each.

6. Document Resume

Document No.	
Release Date	2024/12/27
Author	XiofengZeng
Review	LiMing

Revised History

Date	Version	Revised Record
2024/12/27	1.00	New Project