

**RF EXPOSURE EVALUATION METHOD****FCC ID: 2ABWOCLP289****SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and  $\leq 50$  mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

WIFI:

<b>TX 802.11b Mode</b>				
Test Channe	Frequency	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	Maximum Conducted Output Power (AV)
	(MHz)	(dBm)	(dBm)	mW
CH01	2412	12.67	9.46	8.831
CH06	2437	12.53	9.31	8.531
CH11	2462	12.49	9.28	8.472
<b>TX 802.11g Mode</b>				
CH01	2412	11.29	8.15	6.531
CH06	2437	11.42	8.36	6.855
CH11	2462	11.35	8.29	6.745
<b>TX 802.11n20 Mode</b>				
CH01	2412	10.56	7.86	6.109
CH06	2437	10.71	7.91	6.180
CH11	2462	10.83	7.85	6.095
<b>TX 802.11n40 Mode</b>				
CH03	2422	10.22	7.19	5.236
CH06	2437	10.16	7.08	5.105
CH09	2452	10.28	7.24	5.297

Remark: The best case gain of the antenna is 1.0dBi.

1.0 dBi logarithmic terms convert to numeric result is nearly 1.26

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

WIFI:

Mode	[(max. power of channel, including tune-up tolerance, mW)]	(min. test separation distance,mm)]	[ $\sqrt{f}$ (GHz)]	Result	Limit
802.11b					
CH01	8.831	5	2.412	2.74	3
CH06	8.531	5	2.437	2.66	3
CH11	8.472	5	2.462	2.66	3
802.11g					
CH01	6.531	5	2.412	2.03	3
CH06	6.855	5	2.437	2.14	3
CH11	6.745	5	2.462	2.12	3
802.11n(20)					
CH01	6.109	5	2.412	1.90	3
CH06	6.180	5	2.437	1.93	3
CH11	6.095	5	2.462	1.91	3
802.11n(40)					
CH03	5.236	5	2.422	1.63	3
CH06	5.105	5	2.437	1.59	3
CH09	5.297	5	2.452	1.66	3

The test Result is less than 3.0 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

**Conclusion:** No SAR is required.