



RF exposure

FCC ID : 2ADTG-U3000

IC number : 12594A-U3000

According to FCC part 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time
(A) Limits for Occupational / Control Exposures				
300 – 1 500	--	--	f/300	6
1 500 - 100000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300 – 1 500	--	--	f/1500	6
1 500 – 100 000	--	--	<u>1</u>	<u>30</u>

f= frequency in MHz

Friis transmission formula: $P_d = (P_{out} \times G) / (4 \times \pi \times R^2)$

Where,

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Results

-2.4 GHz

Operation mode	Frequency (MHz)	Average maximum output power (dBm)	Antenna gain (dBi)	Power density at 20 cm (mW/cm ²)	Limit (mW/cm ²)
BLE 1 Mbps	2 402 ~ 2 480	0.9	2.24	0.000 410	1
802.11b	2 412 ~ 2 462	12.0		0.005 281	1
802.11g	2 412 ~ 2 462	11.0		0.004 195	1
802.11n_HT20	2 412 ~ 2 462	11.0		0.004 195	1
802.11n_HT40	2 422 ~ 2 452	11.0		0.004 195	1

-5 GHz (UNII-1)

Operation mode	Frequency (MHz)	Average maximum output power (dBm)	Antenna gain (dBi)	Power density at 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11a	5 180 ~ 5 240	11.5	3.20	0.005 871	1
802.11n_HT20	5 180 ~ 5 240	9.0		0.003 302	1
802.11n_HT40	5 190 ~ 5 230	10.0		0.004 157	1