

Page 1 of 25 JQA File No. : KL80050416 Issued Date : October 21, 2005

TEST REPORT

| APPLICANT ADDRESS | : | Panasonic Communications Co., Ltd. 1-62, 4-chome, Minoshima, Hakata-ku, Fukuoka, 812-8531, Japan |
|----------------------|---|---|
| PRODUCTS | : | 2.4GHz FHSS Cordless Teelphone(Base) |
| MODEL NO. | : | KX-TG2431 |
| SERIAL NO. | : | |
| FCC ID | : | ACJ96NKX-TG2431 |
| TEST STANDARD | : | CFR 47 FCC Rules and Regulations Part 15 |
| TESTING LOCATION | : | Japan Quality Assurance Organization KITA-KANSAI Testing Center 1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan |
| TEST RESULTS | : | Passed |
| DATE OF TEST | : | October 7, 2005 - October 11, 2005 |

4. Fukumoto

Yuichi Fukumoto Manager Japan Quality Assurance Organization KITA-KANSAI Testing Center Testing Dept. EMC Division 1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan

- The measurement values stated in Test Report was made with traceable to National Institute of Advanced Industrial Science and Technology (AIST) of Japan and National Institute of Information and Communications Technology (NICT) of Japan.
- The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
- The test results presented in this report relate only to the offered test sample.
- The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
- This test report shall not be reproduced except in full without the written approval of JQA.



Page 2 of 25

TABLE OF CONTENTS

Page

| Docum | nentation | |
|-------|--|----|
| 1 | Test Regulation | 3 |
| 2 | Test Location | 3 |
| 3 | Recognition of Test Laboratory | 3 |
| 4 | Description of the Equipment Under Test | 4 |
| 5 | Test Condition | 5 |
| 6 | Preliminary Test and Test Setup | 6 |
| 7 | Equipment Under Test Modification | 9 |
| 8 | Responsible Party | 9 |
| 9 | Deviation from Standard | 9 |
| 10 | Test Results | |
| 11 | Summary | 11 |
| 12 | Operating Condition | |
| 13 | Test Configuration | |
| 14 | Equipment Under Test Arrangement (Drawings) | 13 |
| 15 | Equipment Under Test Arrangement (Photographs) | 14 |
| Appen | dix A: Test Data | |
| A.1 | AC Powerline Conducted Emission | 16 |
| A.2 | Radiated Emission | 20 |
| Appen | dix B: Test Instruments | |

DEFINITIONS FOR ABBREVIATION AND SYMBOLS USED IN THIS TEST REPORT

- "EUT" means Equipment Under the Test.
- "N/A" means that Not Applicable.
- "N/T" means that Not Tested.
- \boxtimes indicates that the listed condition, standard or equipment is applicable for this report.
- indicates that the listed condition, standard or equipment is not applicable for this report.



Page 3 of 25

Documentation

1 Test Regulation

| Applied Standard | : | CFR 47 FCC Rules and Regulations Part 15 Subpart C – Intentional Radiators |
|-------------------|---|---|
| Test Requirements | : | §15.205, §15.207, §15.209 and §15.247 |

Test Procedure : ANSI C63.4–2003

Note) The test items requested by applicant are shown as follows:

- 1) AC Powerline Conducted Emission(§ 15.207)
- 2) Radiated Emission(§15.209)(30 1000MHz)

2 Test Location

KITA-KANSAI Testing Center 1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan KAMEOKA EMC Branch 9-1, Ozaki, Inukanno, Nishibetsuin-cho, Kameoka-shi, Kyoto 621-0126, Japan

3 Recognition of Test Laboratory

JQA KITA-KANSAI Testing Center Testing Department EMC Division is recognized under ISO/IEC 17025 by following accreditation bodies and the test facility of Testing Division is registered by the following bodies.

| VLAC Code | : | VLAC-001-2 (Effective through : April 3, 2006) |
|------------------------|---|--|
| NVLAP Lab Code | : | 200191-0 (Effective through : June 30, 2006) |
| BSMI Recognition No. | : | SL2-IS-E-6006, SL2-IN-E-6006, SL2-AI-E-6006 |
| | | (Effective through : September 14, 2007) |
| VCCI Registration No | • | R-006 R-008 R-1117 C-006 C-007 C-1674 C-2143 |
| voor negistration ivo. | • | (Effective through : April 3, 2006) |
| FCC Registration No. | : | 683630 (Effective through : June 30, 2006) |

Accredited as conformity assessment body for Japan electrical appliances and material law by METI. (Effective through : February 24, 2007)

Accredited as conformity assessment body for Article 2, Paragraph 8, Item 5 on law for implementation of the Mutual Recognition between Japan and the European Community by METI. (Effective through : August 7, 2007)



Page 4 of 25

4 Description of the Equipment Under Test

| 1. | Manufacturer | : | Panasonic Communications Co., Ltd. 1-62, 4-chome, Minoshima, Hakata-ku, Fukuoka, 812-8531 Japan | | | |
|-----|------------------------|---|--|--|--|--|
| 2. | Products | : | 2.4GHz FHSS Cordless Teelphone(Base) | | | |
| 3. | Model No. | : | KX-TG2431 | | | |
| 4. | Serial No. | : | | | | |
| 5. | Product Type | : | Pre-production | | | |
| 6. | Date of Manufacture | : | October, 2005 | | | |
| 7. | Transmitting Frequency | : | 2400.914355 MHz (01ch) - 2480.292773 MHz (90ch) | | | |
| 8. | Receiving Frequency | : | 2400.914355 MHz (01ch) - 2480.292773 MHz (90ch) | | | |
| 9. | Method/System | : | Frequency Hopping Spread Spectrum(FHSS) | | | |
| 10. | Type of Antenna | : | Dipole Antenna | | | |
| 11. | Antenna Gain | : | 2.15dBi(Rated) | | | |
| 12. | Power Rating | : | 100-240VAC50/ 60Hz200mA(AC Adaptor : PQLV255) | | | |
| | | | (Rated, Output DC6.5V1A) | | | |
| 13. | EUT Grounding | : | None | | | |
| 14. | Category | : | Intentional Radiator | | | |
| 15. | EUT Authorization | : | Certification | | | |
| 16. | Received Date of EUT | : | October 5, 2005 | | | |



Page 5 of 25

| Regulation : CFR 47 FCC Rules and Regulations Part 15 |
|---|
| Pag |
| 5 Test Condition |
| 5.1 AC Powerline Conducted Emission(§15.207) |
| The requirements are Applicable [Applicable - Tested Not tested by applicant request.] |
| Test site :KITA-KANSAIC- Shielded room- Anechoic chamberKAMEOKA- On 1st open site- Shielded room |
| Test instruments : Refer to Appendix B. |
| 5.2 Radiated Emission(§15.209) |
| 5.2.1 Radiated Emission 30 MHz – 1000 MHz |
| The requirements are 🛛 - Applicable [🖾 - Tested. 🔲 - Not tested by applicant request.] |
| Test site : - KITA-KANSAI 1st open site (3 m) - KAMEOKA 1st open site - 3 m - 10 m - 30 m - KAMEOKA 2nd open site - 3 m - 10 m |
| Test instruments : Refer to Appendix B. |
| |
| 5.2.2 Radiated Emission above 1 GHz |
| The requirements are 🛛 - Applicable [🗌 - Tested. 🖾 - Not tested by applicant request.] 🔲 - Not Applicable |
| Test site : - KITA-KANSAI 1st open site (3 m) - KITA-KANSAI Anechoic chamber (3 m) - KAMEOKA 1st open site - 3 m - 10 m - 30 m - KAMEOKA 2nd open site - 3 m - 10 m |
| Test instruments - Kefer to Appendix B. |



Page 6 of 25

6 Preliminary Test and Test Setup

6.1 AC Powerline Conducted Emission(§15.207)

The preliminary tests were carried out.

The preliminary tests were performed using the spectrum analyzer to observe the emissions characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for final tests.

- Side View -



* AMN : Artificial Mains Network



Page 7 of 25

6.2 Radiated Emission(§15.209)

6.2.1 Radiated Emission 30 MHz – 1000 MHz

The preliminary tests were carried out.

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

- Side View -





Page 8 of 25

6.2.2 Radiated Emission above 1 GHz

The preliminary tests were carried out.

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

- Side View -



* The antenna height H is scanned depending on the EUT's size and mounting height.



Page 9 of 25

7 Equipment Under Test Modification

- \boxtimes No modifications were conducted by JQA to achieve compliance to the limitations.
- □ To achieve compliance to the limitations, the following changes were made by JQA during the compliance test.

The modifications will be implemented in all production models of this equipment.

| Applicant | : Not Applicable |
|------------|------------------|
| Date | : Not Applicable |
| Typed Name | : Not Applicable |
| Position | : Not Applicable |

8 Responsible Party

Responsible Party of Test Item (Product)

Responsible Party \exists

Contact Person :

Signatory

9 Deviation from Standard

- \boxtimes No deviations from the standard described in clause 1.
- □ The following deviations were employed from the standard described in clause 1.





Page 11 of 25

11 Summary

General Remarks :

The EUT was tested according to the requirements of CFR 47 FCC Rules and Regulations Part 15 under the test configuration, as shown in clause 12 to 14. The conclusion for the test items of which are required by the applied regulation is indicated under the final judgment.

Final Judgment:

The "as received" sample;

- \boxtimes fulfill the test requirements of the regulation mentioned on clause 1.
- doesn't fulfill the test requirements of the regulation mentioned on clause 1.

Reviewed by:

Shigeru Kinoshita Deputy Manager Testing Dept. EMC Div. JQA KITA-KANSAI Testing Center

Tested by:

Tanaka

Yuzo Tanaka Engineer Testing Dept. EMC Div. JQA KITA-KANSAI Testing Center



Page 12 of 25

12 Operating Condition

Power Supply Voltage : 120VAC, 60Hz

Operation Mode

- 1. Transmitting/Receiving(CH45)
- 2. Charging

13 Test Configuration

The equipment under test (EUT) consists of :

| | Item | Manufacturer | Model No. | Serial No. | FCC ID | |
|---|---|---------------------------------------|-----------|------------|---------------------|--|
| А | 2.4GHz FHSS Cordless Telephone (Base) | Panasonic Communications Co., Ltd. | KX-TG2431 | | ACJ96NKX- TG2431 | |
| В | AC Adaptor | Panasonic Communications Co., Ltd. | PQLV255 | | N/A | |

The auxiliary equipment used for testing :

| | Item | Manufacturer | Model No. | Serial No. | FCC ID |
|---|--|---------------------------------------|-----------|------------|---------------------|
| С | Telephone Line Emulator | LSI JAPAN | TLE101 | 03144 | N/A |
| D | 2.4GHz FHSS Cordless Telephone (Handset) | Panasonic Communications Co., Ltd. | KX-TGA242 | | ACJ96NKX- TG2431 |

Type of Cable:

| No | Description | Identification | Connector | Cable | Ferrite | Length |
|------|----------------|----------------|-----------|----------|---------|--------|
| INO. | Description | (Manu. etc.) | Shielded | Shielded | Core | (m) |
| 1 | Telephone Line | | | NO | NO | 1.8 |
| 2 | DC Cable | | | NO | NO | 1.9 |



Page 13 of 25

14 Equipment Under Test Arrangement (Drawings)





Page 14 of 25

15 Equipment Under Test Arrangement (Photographs)

15.1 AC Powerline Conducted Emission(§15.207)



-Front View-



-SideView-

Photograph present configuration with maximum emission



Page 15 of 25

15.2 Radiated Emission(§15.209)



- Front View -



-Rear View-

Photograph present configuration with maximum emission



Page 16 of 25

Appendix A: Test Data

A.1 AC Powerline Conducted Emission(§15.207)

A.1.1 Transmitting/Receiving

Test condition : Transmitting/Receiving

Test Date: October 7, 2005 Temp.: 23 °C, Humi: 64 %

| Frequency | Corr. Factor | Me VA | eter Readiı A | ngs [dB(µV) Vl |)] B | Lin [dB() | nits µV)] | Res [dB(j | ults 1V)] | Margin [dB] | Remarks |
|-----------|-----------------|----------|------------------|-------------------|---------|--------------|--------------|--------------|--------------|----------------|---------|
| [MHz] | [dB] | QP | AVE | QP | AVE | QP | AVE | QP | AVE | | |
| 0.18 | 0.2 | 36.0 | | 35.0 | | 64.4 | 54.4 | 36.2 | | +28.2 | А |
| 0.27 | 0.1 | 37.0 | | 36.0 | | 61.2 | 51.2 | 37.1 | | +24.1 | А |
| 0.54 | 0.1 | 36.0 | | 35.0 | | 56.0 | 46.0 | 36.1 | | +19.9 | А |
| 1.06 | 0.1 | 28.0 | | 29.0 | | 56.0 | 46.0 | 29.1 | | +26.9 | А |
| 2.57 | 0.2 | 21.0 | | 22.0 | | 56.0 | 46.0 | 22.2 | | +33.8 | А |
| 7.73 | 0.5 | 34.0 | | 30.0 | | 60.0 | 50.0 | 34.5 | | +25.5 | А |
| 16.60 | 0.7 | 29.0 | | 26.0 | | 60.0 | 50.0 | 29.7 | | +30.3 | А |
| 25.00 | 0.9 | 25.0 | | 23.0 | | 60.0 | 50.0 | 25.9 | | +34.1 | А |

Calculated result at 0.54 MHz, as the worst point shown on underline: Corr. Factor = 0.1 dB +) Meter Reading = 36.0 dB(μ V) Result = 36.1 dB(μ V)

Minimum Margin: 56.0 - 36.1 = 19.9 (dB)

NOTES

- 1. The spectrum was checked from $0.15~\mathrm{MHz}$ to 30 MHz.
- 2. The correction factor includes the AMN insertion loss and the cable loss.
- 3. The symbol of "<" means "or less".
- 4. The symbol of ">" means "more than".
- 5. The symbol of "--" means "not applicable".
- 6. QP : Quasi-Peak Detector AVE : Average Detector
- 7. Setting of measuring instrument(s) :

| | Detector Function | IF Bandwidth |
|---|-------------------|------------------|
| А | CISPR QP | $9 \mathrm{kHz}$ |
| В | Average | 10 kHz |
| | | |



Page 17 of 25

Graph Data : AC Powerline Conducted Emission



JAPAN QUALITY ASSURANCE ORGANIZATION



Page 18 of 25

A.1.2 Charging

| Test condit | Test condition : ChargingTest October 7, 2005Temp.: 23 °C, Humi: 64 % | | | | | | | | | | |
|-------------|---|------|-------------|------------|---------|------|-------------|------|------|--------|---------|
| Frequency | Corr. | M | eter Readii | ngs [dB(µV |)] R | | nits V)] | Res | ults | Margin | Remarks |
| [MHz] | [dB] | QP | AVE | QP | AVE | QP | AVE | QP | AVE | լաքյ | |
| 0.19 | 0.2 | 39.0 | | 38.0 | | 64.2 | 54.2 | 39.2 | | +25.0 | А |
| 0.27 | 0.1 | 37.0 | | 35.0 | | 61.2 | 51.2 | 37.1 | | +24.1 | А |
| 0.41 | 0.1 | 38.0 | | 36.0 | | 57.8 | 47.8 | 38.1 | | +19.7 | А |
| 0.62 | 0.1 | 38.0 | | 36.0 | | 56.0 | 46.0 | 38.1 | | +17.9 | А |
| 1.09 | 0.1 | 32.0 | | 32.0 | | 56.0 | 46.0 | 32.1 | | +23.9 | А |
| 7.86 | 0.5 | 33.0 | | 29.0 | | 60.0 | 50.0 | 33.5 | | +26.5 | А |
| 17.20 | 0.7 | 28.0 | | 28.0 | | 60.0 | 50.0 | 28.7 | | +31.3 | А |
| 22.00 | 0.8 | 29.0 | | 31.0 | | 60.0 | 50.0 | 31.8 | | +28.2 | А |
| 25.00 | 0.9 | 30.0 | | 30.0 | | 60.0 | 50.0 | 30.9 | | +29.1 | А |
| 30.00 | 0.9 | 28.0 | | 26.0 | | 60.0 | 50.0 | 28.9 | | +31.1 | А |

Calculated result at 0.62 MHz, as the worst point shown on underline: Corr. Factor = 0.1 dB

+) Meter Reading = 38.0 dB(µV) Result = 38.1 dB(µV) Minimum Margin: 56.0 - 38.1 = 17.9 (dB)

NOTES

- 1. The spectrum was checked from 0.15 MHz to 30 MHz.
- 2. The correction factor includes the AMN insertion loss and the cable loss.
- 3. The symbol of "<" means "or less".
- 4. The symbol of ">" means "more than".
- 5. The symbol of "--" means "not applicable".
- 6. QP : Quasi-Peak Detector AVE : Average Detector
- 7. Setting of measuring instrument(s) :

| | Detector Function | IF Bandwidth |
|---|-------------------|--------------|
| А | CISPR QP | 9 kHz |
| В | Average | 10 kHz |



Page 19 of 25

Graph Data : AC Powerline Conducted Emission





Page 20 of 25

Test Date: October 11, 2005

A.2 Radiated Emission(§15.209)

A.2.1 Radiated Emission 30 MHz - 1000 MHz

A.2.1.1 Transmitting/Receiving

| Test condition : Transmitting/Receiving | | | | | | | Tem | o.∶23 °C, H | umi: 78 % |
|---|-------------------|---|--------|-----------------|----------------|---------|--------|-------------|-----------|
| Frequency | Antenna Factor | na Cable Meter Readings Limits Results r Loss [dB(µV)] [dB(µV/m)] [dB(µV/m)] | | sults [V/m)] | Margin [dB] | Remarks | | | |
| [MHz] | [dB(1/m)] | [dB] | Hori. | Vert. | | Hori. | Vert. | | |
| 33.0 | 17.5 | 0.8 | < 1.0 | < 7.0 | 40.0 | < 19.3 | < 25.3 | > +14.7 | А |
| 38.0 | 15.6 | 0.9 | < 3.0 | 9.0 | 40.0 | < 19.5 | 25.5 | +14.5 | А |
| 66.0 | 7.1 | 1.2 | < 9.0 | 14.0 | 40.0 | < 17.3 | 22.3 | +17.7 | А |
| 81.9 | 6.8 | 1.4 | < 19.0 | < 19.0 | 40.0 | < 27.2 | < 27.2 | > +12.8 | А |
| 124.4 | 13.4 | 1.7 | 3.0 | 10.0 | 43.5 | 18.1 | 25.1 | +18.4 | А |
| 163.8 | 15.4 | 2.0 | 9.0 | 10.0 | 43.5 | 26.4 | 27.4 | +16.1 | А |
| 248.9 | 17.1 | 2.5 | 4.0 | 4.0 | 46.0 | 23.6 | 23.6 | +22.4 | А |
| 327.7 | 15.7 | 2.9 | 21.0 | 18.0 | 46.0 | 39.6 | 36.6 | + б.4 | А |
| 655.4 | 21.9 | 4.3 | 2.0 | 0.0 | 46.0 | 28.2 | 26.2 | +17.8 | А |
| 819.2 | 22.6 | 4.8 | < 4.0 | < 10.0 | 46.0 | < 31.4 | < 37.4 | > + 8.6 | А |

| Calculated result at 327.7 MHz | , as | the wors | t point shown on underline | э: |
|--------------------------------|-------|----------|----------------------------|----|
| Antenna Factor | = | 15.7 | dB(1/m) | |
| Cable Loss | = | 2.9 | dB | |
| +) Meter Reading | = | 21.0 | dB(µV) | |
| Result | = | 39.6 | dB(µV/m) | |
| Minimum Margin: 46.0 - 39.6 - | = 6.4 | (dB) | | |

NOTES

1. Test Distance : 3 m

2. The spectrum was checked from 30 MHz to 1000 MHz.

3. The symbol of "<" means "or less".

4. The symbol of ">" means "more than".

5. Setting of measuring instrument(s) :

| Detector Function | IF Bandwidth | Antenna |
|-------------------|--|--|
| CISPR QP | 120 kHz | |
| Average | 120 kHz | Ducadhand |
| Average | $12 \mathrm{kHz}$ | Broadband |
| Average | $7.5~\mathrm{kHz}$ | |
| CISPR QP | 120 kHz | Tuned Dipole |
| | Detector Function CISPR QP Average Average Average CISPR QP | Detector FunctionIF BandwidthCISPR QP120 kHzAverage120 kHzAverage12 kHzAverage7.5 kHzCISPR QP120 kHz |



Page 21 of 25

Graph Data : Radiated Emission 30 MHz – 1000 MHz



Test condition : Transmitting/Receiving

<u>Test Date: October 11, 2005</u> <u>Temp.: 23 °C, Humi: 78 %</u>



Page 22 of 25

<u>Test Date: October 11, 2005</u> <u>Temp.: 23 °C, Humi: 78 %</u>

A.2.1.2 Charging

Test condition : Charging

| Frequency | Antenna Factor | Cable Loss | Meter R [dB(| Readings μV)] | Limits [dB(µV/m)] | Res [dB(µ | ults V/m)] | Margin [dB] | Remarks |
|-----------|-------------------|---------------|-----------------|------------------|----------------------|--------------|---------------|----------------|---------|
| [MHz] | [dB(1/m)] | [dB] | Hori. | Vert. | | Hori. | Vert. | | |
| 33.0 | 17.5 | 0.8 | 2.0 | 12.0 | 40.0 | 20.3 | 30.3 | + 9.7 | А |
| 66.0 | 7.1 | 1.2 | < 6.0 | 17.0 | 40.0 | < 14.3 | 25.3 | +14.7 | А |
| 81.9 | 6.8 | 1.4 | < 15.0 | < 15.0 | 40.0 | < 23.2 | < 23.2 | > +16.8 | А |
| 110.6 | 11.6 | 1.6 | 2.0 | 9.0 | 43.5 | 15.2 | 22.2 | +21.3 | А |
| 163.8 | 15.4 | 2.0 | 7.0 | 11.0 | 43.5 | 24.4 | 28.4 | +15.1 | А |
| 248.9 | 17.1 | 2.5 | 5.0 | 3.0 | 46.0 | 24.6 | 22.6 | +21.4 | А |
| 327.7 | 15.7 | 2.9 | 21.0 | 18.0 | 46.0 | 39.6 | 36.6 | + б.4 | А |
| 655.4 | 21.9 | 4.3 | 1.0 | 0.0 | 46.0 | 27.2 | 26.2 | +18.8 | А |
| 819.2 | 22.6 | 4.8 | < 6.0 | < 10.0 | 46.0 | < 33.4 | < 37.4 | > + 8.6 | А |
| 983.0 | 25.2 | 5.4 | < 0.0 | < 0.0 | 54.0 | < 30.6 | < 30.6 | > +23.4 | А |

| Calculated result at 327.7 MHz, as the worst point shown on underline: | | | | | | |
|--|---|---------------|--|--|--|--|
| Antenna Factor | = | 15.7 dB(1/m) | | | | |
| Cable Loss | = | 2.9 dB | | | | |
| +) Meter Reading | = | 21.0 dB(µV) | | | | |
| Result | = | 39.6 dB(µV/m) | | | | |
| Minimum Margin: 46.0 - 39.6 = 6.4 (dB) | | | | | | |

NOTES

1. Test Distance : 3 m $\,$

2. The spectrum was checked from 30 MHz to 1000 MHz.

3. The symbol of "<" means "or less".

4. The symbol of ">" means "more than".

5. Setting of measuring instrument(s) :

| A CISPR QP 120 kHz B Average 120 kHz C Average 12 kHz D Average 7.5 kHz | | Detector Function | IF Bandwidth | Antenna |
|---|---|-------------------|-------------------|-------------------|
| B Average 120 kHz C Average 12 kHz D Average 7.5 kHz | А | CISPR QP | 120 kHz | |
| C Average 12 kHz Broadband D Average 7.5 kHz 10 kHz | В | Average | 120 kHz | Due e ille e e il |
| D Average 7.5 kHz | С | Average | $12 \mathrm{kHz}$ | Broadband |
| | D | Average | 7.5 kHz | |
| E CISPR QP 120 kHz Tuned Dipole | Е | CISPR QP | 120 kHz | Tuned Dipole |



Page 23 of 25

Graph Data : Radiated Emission 30 MHz – 1000 MHz



JAPAN QUALITY ASSURANCE ORGANIZATION



Page 24 of 25 $\,$

A.2.2 Radiated Emission above 1 GHz

Not tested by applicant request.



Page 25 of 25 $\,$

Appendix B: Test Instruments

B.1 AC Powerline Conducted Emission(§15.207)

| Туре | Model | Manufacturer | ID No. | Last Cal. | Interval |
|---------------|---------|-----------------|--------|-----------|----------|
| Test Receiver | ESCS 30 | Rohde & Schwarz | A-1 | 2005/8 | 1 Year |
| AMN (main) | KNW-407 | Kyoritsu | D-6 | 2004/10 | 1 Year |
| RF Cable | | | H-8 | 2004/10 | 1 Year |

B.2 Radiated Emission(§15.209)

B.2.1 Radiated Emission 30 MHz – 1000 MHz

| Туре | Model | Manufacturer | ID No. | Last Cal. | Interval |
|----------------------|------------------|-----------------|--------|-----------|----------|
| Test Receiver | ESV | Rohde & Schwarz | A-6 | 2005/6 | 1 Year |
| Pre-Amplifier | ESV-Z3 | Rohde & Schwarz | A-20 | 2005/8 | 1 Year |
| Biconical Antenna | UHLP9103/BBA9106 | Schwarzbeck | C-43 | 2005/8 | 1 Year |
| Log-periodic Antenna | UHALP9107 | Schwarzbeck | C-42 | 2005/8 | 1 Year |
| RF Cable | | | H-5 | 2005/8 | 1 Year |
| Site Attenuation | | | H-17 | 2004/10 | 1 Year |

B.2.2 Radiated Emission above 1 GHz

Not tested by applicant request.