

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

|                     |                            |
|---------------------|----------------------------|
| Product Description | Dual band wireless adapter |
| Model Name          | XHT-6B12, XHT-6B10         |
| FCC ID              | 2AKC6XHT-6B12              |

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

According to the follow transmitter output power (  $P_t$  ) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

$P_t$ =transmitter output power in watts

$g_t$ =numeric gain of the transmitting antenna (unitless)

E=electric field strength in V/m

d=measurement distance in meters (m)

For 2.4G WIFI

$$P_t = 9.33\text{dBm} = 8.57\text{mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (8.57\text{mW} / 5\text{mm}) \cdot [\sqrt{2.462(\text{GHz})}] = 2.69 < 3.0 \text{ for 1-g SAR}$$

For 5G WIFI

$$P_t = 6.72\text{dBm} = 4.70\text{mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (4.70\text{mW} / 5\text{mm}) \cdot [\sqrt{5.825(\text{GHz})}] = 2.27 < 3.0 \text{ for 1-g SAR}$$

Note: The 2.4G and 5G WIFI can not transmit simultaneously.

### 4. CONCLUSION

The SAR evaluation is not required.