

● Radiated Emission Measurement (Supplement Test Data)

**Test Result: PASSED.** The test data please refer to the following pages.

All the emissions not reported below are too low against the FCC Part 15 Subpart C official limits.

Date of Test : May 18, 2004 Temperature : 18°C

EUT : Multi-Player Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Lie  
(Transmitting FM Radio Frequency 88.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Horizontal<br>dBμV | Emission Level<br>Horizontal<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-------------------------------|----------------------------------------|------------------|--------------|
| Fundamental Freq. (Average Value) |                           |                     |                               |                                        |                  |              |
| 88.100                            | 15.42                     | 2.00                | 19.30                         | 36.72                                  | 48.00            | 11.28        |
| Fundamental Freq. (Peak Value)    |                           |                     |                               |                                        |                  |              |
| 88.100                            | 15.42                     | 2.00                | 22.98                         | 40.40                                  | 68.00            | 27.60        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                               |                                        |                  |              |
| 176.200                           | 21.21                     | 2.90                | -3.63                         | 20.48                                  | 43.50            | 23.02        |
| 264.300                           | 24.62                     | 3.70                | -4.02                         | 24.30                                  | 46.00            | 21.70        |
| 352.400                           | 15.55                     | 4.30                | -3.45                         | 16.41                                  | 46.00            | 29.59        |
| 440.500                           | 17.60                     | 5.30                | -0.74                         | 22.17                                  | 46.00            | 23.83        |
| 528.600                           | 19.69                     | 6.90                | 3.99                          | 30.57                                  | 46.00            | 15.43        |
| 553.800                           | 19.40                     | 6.80                | 9.83                          | 36.03                                  | 46.00            | 9.97         |
| 616.700                           | 21.31                     | 6.30                | -4.82                         | 22.79                                  | 46.00            | 23.21        |
| 704.800                           | 23.56                     | 6.60                | -5.58                         | 24.58                                  | 46.00            | 21.42        |
| 709.000                           | 23.54                     | 6.60                | 5.52                          | 35.67                                  | 46.00            | 10.33        |
| 792.900                           | 23.95                     | 6.90                | -8.35                         | 22.50                                  | 46.00            | 23.50        |
| 881.000                           | 25.34                     | 7.30                | -8.62                         | 24.02                                  | 46.00            | 21.98        |

- Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.
2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Lie  
(Transmitting FM Radio Frequency 88.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Vertical<br>dBμV | Emission Level<br>Vertical<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-----------------------------|--------------------------------------|------------------|--------------|
| -----                             |                           |                     |                             |                                      |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                             |                                      |                  |              |
| 88.100                            | 15.46                     | 2.00                | 18.48                       | 35.94                                | 48.00            | 12.06        |
| Fundamental Freq. (Peak Value)    |                           |                     |                             |                                      |                  |              |
| 88.100                            | 15.46                     | 2.00                | 22.66                       | 40.12                                | 68.00            | 27.88        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                             |                                      |                  |              |
| 176.200                           | 20.66                     | 2.90                | -4.36                       | 19.20                                | 43.50            | 24.30        |
| 264.300                           | 25.20                     | 3.70                | -4.64                       | 24.25                                | 46.00            | 21.75        |
| 352.400                           | 15.78                     | 4.30                | -4.87                       | 15.21                                | 46.00            | 30.79        |
| 440.500                           | 17.38                     | 5.30                | -5.29                       | 17.39                                | 46.00            | 28.61        |
| 528.600                           | 20.22                     | 6.90                | -2.32                       | 24.81                                | 46.00            | 21.19        |
| 616.700                           | 21.29                     | 6.30                | -8.25                       | 19.34                                | 46.00            | 26.66        |
| 704.800                           | 22.25                     | 6.60                | -7.10                       | 21.75                                | 46.00            | 24.25        |
| 792.900                           | 25.42                     | 6.90                | -8.88                       | 23.44                                | 46.00            | 22.56        |
| 881.000                           | 25.34                     | 7.30                | -9.10                       | 23.54                                | 46.00            | 22.46        |

- Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Side  
(Transmitting FM Radio Frequency 88.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Horizontal<br>dBμV | Emission Level<br>Horizontal<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-------------------------------|----------------------------------------|------------------|--------------|
| -----                             |                           |                     |                               |                                        |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                               |                                        |                  |              |
| 88.100                            | 15.42                     | 2.00                | 17.27                         | 34.69                                  | 48.00            | 13.31        |
| Fundamental Freq. (Peak Value)    |                           |                     |                               |                                        |                  |              |
| 88.100                            | 15.42                     | 2.00                | 20.93                         | 38.35                                  | 68.00            | 29.65        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                               |                                        |                  |              |
| 176.200                           | 21.21                     | 2.90                | -4.19                         | 19.91                                  | 43.50            | 23.59        |
| 240.490                           | 23.10                     | 3.40                | 1.69                          | 28.19                                  | 46.00            | 17.81        |
| 264.300                           | 24.62                     | 3.70                | -5.51                         | 22.81                                  | 46.00            | 23.19        |
| 352.400                           | 15.55                     | 4.30                | -1.33                         | 18.53                                  | 46.00            | 27.47        |
| 440.500                           | 17.60                     | 5.30                | -2.54                         | 20.36                                  | 46.00            | 25.64        |
| 441.280                           | 17.63                     | 5.30                | 7.50                          | 30.43                                  | 46.00            | 15.57        |
| 528.600                           | 19.69                     | 6.90                | 1.22                          | 27.80                                  | 46.00            | 18.20        |
| 616.700                           | 21.31                     | 6.30                | -5.41                         | 22.20                                  | 46.00            | 23.80        |
| 704.800                           | 23.56                     | 6.60                | -1.91                         | 28.25                                  | 46.00            | 17.75        |
| 792.900                           | 23.95                     | 6.90                | -8.88                         | 21.98                                  | 46.00            | 24.02        |
| 881.000                           | 25.34                     | 7.30                | -9.27                         | 23.37                                  | 46.00            | 22.63        |

Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Side  
(Transmitting FM Radio Frequency 88.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Vertical<br>dBμV | Emission Level<br>Vertical<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-----------------------------|--------------------------------------|------------------|--------------|
| -----                             |                           |                     |                             |                                      |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                             |                                      |                  |              |
| 88.100                            | 15.46                     | 2.00                | 17.12                       | 34.58                                | 48.00            | 13.42        |
| Fundamental Freq. (Peak Value)    |                           |                     |                             |                                      |                  |              |
| 88.100                            | 15.46                     | 2.00                | 21.38                       | 38.84                                | 68.00            | 29.16        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                             |                                      |                  |              |
| 176.200                           | 20.66                     | 2.90                | -4.47                       | 19.09                                | 43.50            | 24.41        |
| 264.300                           | 25.20                     | 3.70                | -4.67                       | 24.22                                | 46.00            | 21.78        |
| 352.400                           | 15.78                     | 4.30                | -6.55                       | 13.53                                | 46.00            | 32.47        |
| 440.500                           | 17.38                     | 5.30                | -4.31                       | 18.37                                | 46.00            | 27.63        |
| 528.600                           | 20.22                     | 6.90                | 1.55                        | 28.68                                | 46.00            | 17.32        |
| 616.700                           | 21.29                     | 6.30                | -8.10                       | 19.48                                | 46.00            | 26.52        |
| 672.140                           | 23.07                     | 6.40                | 2.51                        | 31.99                                | 46.00            | 14.01        |
| 704.800                           | 22.25                     | 6.60                | -8.09                       | 20.76                                | 46.00            | 25.24        |
| 792.900                           | 25.42                     | 6.90                | -9.73                       | 22.59                                | 46.00            | 23.41        |
| 881.000                           | 25.34                     | 7.30                | -9.05                       | 23.59                                | 46.00            | 22.41        |
| -----                             |                           |                     |                             |                                      |                  |              |

Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004 Temperature : 18°C

EUT : Multi-Player Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Stand  
(Transmitting FM Radio Frequency 88.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Horizontal<br>dBμV | Emission Level<br>Horizontal<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-------------------------------|----------------------------------------|------------------|--------------|
| -----                             |                           |                     |                               |                                        |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                               |                                        |                  |              |
| 88.100                            | 15.42                     | 2.00                | 18.20                         | 35.62                                  | 48.00            | 12.38        |
| Fundamental Freq. (Peak Value)    |                           |                     |                               |                                        |                  |              |
| 88.100                            | 15.42                     | 2.00                | 21.49                         | 38.91                                  | 68.00            | 29.09        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                               |                                        |                  |              |
| 176.200                           | 21.21                     | 2.90                | -5.30                         | 18.81                                  | 43.50            | 24.69        |
| 264.300                           | 24.62                     | 3.70                | -5.51                         | 22.81                                  | 46.00            | 23.19        |
| 352.400                           | 15.55                     | 4.30                | -6.36                         | 13.50                                  | 46.00            | 32.50        |
| 440.500                           | 17.60                     | 5.30                | -5.90                         | 17.00                                  | 46.00            | 29.00        |
| 528.600                           | 19.69                     | 6.90                | -4.96                         | 21.62                                  | 46.00            | 24.38        |
| 616.700                           | 21.31                     | 6.30                | -7.91                         | 19.70                                  | 46.00            | 26.30        |
| 684.750                           | 23.11                     | 6.49                | -0.67                         | 28.93                                  | 46.00            | 17.07        |
| 704.800                           | 23.56                     | 6.60                | -7.63                         | 22.53                                  | 46.00            | 23.47        |
| 792.900                           | 23.95                     | 6.90                | -8.71                         | 22.15                                  | 46.00            | 23.85        |
| 881.000                           | 25.34                     | 7.30                | -9.23                         | 23.41                                  | 46.00            | 22.59        |
| -----                             |                           |                     |                               |                                        |                  |              |

Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Stand  
(Transmitting FM Radio Frequency 88.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Vertical<br>dBμV | Emission Level<br>Vertical<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-----------------------------|--------------------------------------|------------------|--------------|
| -----                             |                           |                     |                             |                                      |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                             |                                      |                  |              |
| 88.100                            | 15.46                     | 2.00                | 17.76                       | 35.22                                | 48.00            | 12.78        |
| Fundamental Freq. (Peak Value)    |                           |                     |                             |                                      |                  |              |
| 88.100                            | 15.46                     | 2.00                | 22.41                       | 39.87                                | 68.00            | 28.13        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                             |                                      |                  |              |
| 176.200                           | 20.66                     | 2.90                | -4.41                       | 19.15                                | 43.50            | 24.35        |
| 264.300                           | 25.20                     | 3.70                | -5.24                       | 23.66                                | 46.00            | 22.34        |
| 352.400                           | 15.78                     | 4.30                | -6.33                       | 13.75                                | 46.00            | 32.25        |
| 440.500                           | 17.38                     | 5.30                | -4.28                       | 18.39                                | 46.00            | 27.61        |
| 528.600                           | 20.22                     | 6.90                | -3.20                       | 23.93                                | 46.00            | 22.07        |
| 616.700                           | 21.29                     | 6.30                | -7.88                       | 19.70                                | 46.00            | 26.30        |
| 704.800                           | 22.25                     | 6.60                | -8.13                       | 20.72                                | 46.00            | 25.28        |
| 792.900                           | 25.42                     | 6.90                | -8.71                       | 23.61                                | 46.00            | 22.39        |
| 881.000                           | 25.34                     | 7.30                | -9.16                       | 23.48                                | 46.00            | 22.52        |
| -----                             |                           |                     |                             |                                      |                  |              |

- Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Lie  
(Transmitting FM Radio Frequency 98.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Horizontal<br>dBμV | Emission Level<br>Horizontal<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-------------------------------|----------------------------------------|------------------|--------------|
| -----                             |                           |                     |                               |                                        |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                               |                                        |                  |              |
| 98.100                            | 16.84                     | 2.10                | 17.48                         | 36.42                                  | 48.00            | 11.58        |
| Fundamental Freq. (Peak Value)    |                           |                     |                               |                                        |                  |              |
| 98.100                            | 16.84                     | 2.10                | 21.15                         | 40.09                                  | 68.00            | 27.10        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                               |                                        |                  |              |
| 196.200                           | 21.85                     | 3.00                | -4.86                         | 19.99                                  | 43.50            | 23.51        |
| 294.300                           | 26.33                     | 3.96                | -5.02                         | 25.26                                  | 46.00            | 20.74        |
| 392.400                           | 17.54                     | 4.70                | 0.46                          | 22.70                                  | 46.00            | 23.30        |
| 490.500                           | 18.58                     | 6.30                | 1.72                          | 26.60                                  | 46.00            | 19.40        |
| 528.580                           | 19.69                     | 6.90                | 6.77                          | 33.35                                  | 46.00            | 12.65        |
| 588.600                           | 21.02                     | 6.30                | 6.59                          | 33.91                                  | 46.00            | 12.09        |
| 679.900                           | 22.97                     | 6.40                | 4.14                          | 33.50                                  | 46.00            | 12.50        |
| 686.700                           | 23.18                     | 6.50                | -8.86                         | 20.82                                  | 46.00            | 25.18        |
| 733.250                           | 22.09                     | 6.70                | 3.88                          | 32.67                                  | 46.00            | 13.33        |
| 784.800                           | 23.87                     | 6.90                | -8.82                         | 21.95                                  | 46.00            | 24.05        |
| 882.900                           | 25.28                     | 7.30                | -9.29                         | 23.29                                  | 46.00            | 22.71        |
| 981.000                           | 25.74                     | 7.70                | -9.44                         | 24.00                                  | 54.00            | 30.00        |

Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Lie  
(Transmitting FM Radio Frequency 98.1MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Vertical<br>dBμV | Emission Level<br>Vertical<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-----------------------------|--------------------------------------|------------------|--------------|
| -----                             |                           |                     |                             |                                      |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                             |                                      |                  |              |
| 98.100                            | 17.54                     | 2.10                | 14.87                       | 34.51                                | 48.00            | 13.49        |
| Fundamental Freq. (Peak Value)    |                           |                     |                             |                                      |                  |              |
| 98.100                            | 17.54                     | 2.10                | 19.56                       | 39.20                                | 68.00            | 28.80        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                             |                                      |                  |              |
| 196.200                           | 22.50                     | 3.00                | -4.36                       | 21.14                                | 43.50            | 22.36        |
| 294.300                           | 26.47                     | 3.96                | -4.67                       | 25.75                                | 46.00            | 20.25        |
| 392.400                           | 17.73                     | 4.70                | -4.31                       | 18.12                                | 46.00            | 27.88        |
| 490.500                           | 18.53                     | 6.30                | -1.06                       | 23.78                                | 46.00            | 22.22        |
| 588.600                           | 21.52                     | 6.30                | 3.07                        | 30.88                                | 46.00            | 15.12        |
| 686.700                           | 23.55                     | 6.50                | -8.82                       | 21.23                                | 46.00            | 24.77        |
| 784.800                           | 25.40                     | 6.90                | -9.47                       | 22.83                                | 46.00            | 23.17        |
| 882.900                           | 25.42                     | 7.30                | -9.59                       | 23.13                                | 46.00            | 22.87        |
| 981.000                           | 26.26                     | 7.70                | -9.04                       | 24.92                                | 54.00            | 29.08        |
| -----                             |                           |                     |                             |                                      |                  |              |

Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Lie  
(Transmitting FM Radio Frequency 107.9MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Horizontal<br>dBμV | Emission Level<br>Horizontal<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-------------------------------|----------------------------------------|------------------|--------------|
| -----                             |                           |                     |                               |                                        |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                               |                                        |                  |              |
| 107.900                           | 17.87                     | 2.20                | 16.69                         | 36.76                                  | 48.00            | 11.24        |
| Fundamental Freq. (Peak Value)    |                           |                     |                               |                                        |                  |              |
| 107.900                           | 17.87                     | 2.20                | 20.46                         | 40.53                                  | 68.00            | 27.47        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                               |                                        |                  |              |
| 215.800                           | 21.86                     | 3.20                | -4.12                         | 20.94                                  | 43.50            | 22.56        |
| 323.700                           | 15.10                     | 4.14                | 10.45                         | 29.69                                  | 46.00            | 16.31        |
| 431.600                           | 17.27                     | 5.20                | -0.88                         | 21.59                                  | 46.00            | 24.41        |
| 539.500                           | 19.34                     | 7.10                | -3.00                         | 23.45                                  | 46.00            | 22.55        |
| 647.400                           | 21.29                     | 6.30                | -1.51                         | 26.09                                  | 46.00            | 19.91        |
| 755.300                           | 23.58                     | 6.70                | -7.29                         | 22.99                                  | 46.00            | 23.01        |
| 863.200                           | 26.09                     | 7.20                | -8.83                         | 24.46                                  | 46.00            | 21.54        |
| 971.100                           | 26.81                     | 7.70                | -9.61                         | 24.90                                  | 54.00            | 29.10        |
| -----                             |                           |                     |                               |                                        |                  |              |

Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

Date of Test : May 18, 2004      Temperature : 18°C

EUT : Multi-Player      Humidity : 54%

Test Mode : EUT w/Power Bank + Earphone, Set On Lie  
(Transmitting FM Radio Frequency 107.9MHz)

| Frequency<br>MHz                  | Antenna<br>Factor<br>dB/m | Cable<br>Loss<br>dB | Reading<br>Vertical<br>dBμV | Emission Level<br>Vertical<br>dBμV/m | Limits<br>dBμV/m | Margin<br>dB |
|-----------------------------------|---------------------------|---------------------|-----------------------------|--------------------------------------|------------------|--------------|
| -----                             |                           |                     |                             |                                      |                  |              |
| Fundamental Freq. (Average Value) |                           |                     |                             |                                      |                  |              |
| 107.900                           | 17.80                     | 2.20                | 15.52                       | 35.62                                | 48.00            | 12.38        |
| Fundamental Freq. (Peak Value)    |                           |                     |                             |                                      |                  |              |
| 107.900                           | 17.80                     | 2.20                | 19.71                       | 39.71                                | 68.00            | 28.29        |
| Spurious Freq. (Quasi-Peak Value) |                           |                     |                             |                                      |                  |              |
| 215.800                           | 22.37                     | 3.20                | -4.78                       | 20.79                                | 43.50            | 22.71        |
| 323.700                           | 15.54                     | 4.14                | 2.41                        | 22.09                                | 46.00            | 23.91        |
| 431.600                           | 17.16                     | 5.20                | -4.99                       | 17.37                                | 46.00            | 28.63        |
| 539.500                           | 20.31                     | 7.10                | -6.00                       | 21.42                                | 46.00            | 24.58        |
| 647.400                           | 21.69                     | 6.30                | -5.78                       | 22.21                                | 46.00            | 23.79        |
| 755.300                           | 24.74                     | 6.70                | -7.96                       | 23.47                                | 46.00            | 22.53        |
| 863.200                           | 25.46                     | 7.20                | -9.33                       | 23.33                                | 46.00            | 22.67        |
| 971.100                           | 26.84                     | 7.70                | -9.11                       | 25.43                                | 54.00            | 28.57        |
| -----                             |                           |                     |                             |                                      |                  |              |

Remark : 1. Emission Level = Antenna Factor + Cable Loss + Reading.  
 2. Measurement was up to 10<sup>th</sup> harmonics (from fundamental frequency), but the emissions level were too low against the official limit and not reported.

**Photos of Radiated Measurement at Semi-Anechoic Chamber**

Test Mode: EUT w/Power Bank + Earphone, Set On Lie



Test Mode: EUT w/Power Bank + Earphone, Set On Side



Test Mode: EUT w/Power Bank + Earphone, Set On Stand

