

FCC MPE Evaluation Report

Report No: WD-RF-R-240116-C0

Product Name : Furbo 3.5 Camera
Model Name : Furbo 3.5 Dog
Series Model Name : Furbo 3.5 Cat
FCC ID : 2AIBVTFFBV5
Applicant : Tomofun Co., Ltd.
Received Date : Mar. 19, 2024
Tested Date : Mar. 17, 2024 ~ May 31, 2024
Applicable Standard : 47 CFR FCC Part 2.1091
47 CFR FCC Part 1.1310
KDB 447498 D01
OET Bulletin 65 Supplement C



Wendell Industrial Co., Ltd
Wendell EMC & RF Laboratory

Caution:

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment.

Please note that the measurement uncertainty are provided for informational purpose only and are not used in determining the Pass/Fail results.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Wendell Industrial Co., Ltd..

Test Report

Issued Date: June 03, 2024

Project No.: 24Q031902

Product Name	Furbo 3.5 Camera
Trade Name	Furbo
Model Name	Furbo 3.5 Dog
Series Model Name	Furbo 3.5 Cat
FCC ID	2AIBVTFFBV5
Applicant	Tomofun Co., Ltd.
Manufacturer 1	Primax Electronics Ltd.
Manufacturer 2	Primax Electronics (Thailand) Co., Ltd
EUT Rated Voltage	DC 5V2A
EUT Test Voltage	AC 110V / 60Hz 、DC 5V
EUT Supports Radios Application	WLAN 802.11b/g 、WLAN 802.11n (HT20/HT40) Bluetooth LE
Applicable Standard	47 CFR FCC Part 2.1091 47 CFR FCC Part 1.1310 KDB 447498 D01 OET Bulletin 65 Supplement C
RF Evaluation	0.07281 mW/cm ²
Test Result	Complied

Documented :



(Specialist / Emma Lu)

Technical Engineer :



(Section Manager / Jack Chang)

Approved :



(Project Manager / Gary Wu)

Table of Contents

Document Revision History	4
Reference Testing Standard.....	5
1 Generation Information	6
1.1 Applicant.....	6
1.2 Manufacturer.....	6
1.3 Description of Equipment under Test.....	6
1.4 Test Facility	8
2 Mobile device Assessment Procedure.....	9
3 RF Exposure Assessment.....	9
4 Limit Requirement	10
5 Test Results.....	11

Document Revision History

Report No.	Issue date	Description
WD-RF-R-240116-C0	June 03, 2024	Initial report

Reference Testing Standard

Standard	Description	Version
47 CFR FCC Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.	--
47 CFR FCC Part 1.1310	Radiofrequency radiation exposure limits.	--
KDB 447498 D01	RF Exposure procedures and equipment authorization policies for mobile and portable devices.	V06
OET Bulletin 65 Supplement C	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields.	Edition 01-01

1 Generation Information

1.1 Applicant

Tomofun Co., Ltd.

4F, No.178, Sec. 3, Minquan E. Rd., SongShan Dist., Taipei City, Taiwan

1.2 Manufacturer

Primax Electronics Ltd.

No. 669, Ruiguang Rd., Neihu Dist., Taipei City 114, Taiwan

Primax Electronics (Thailand) Co., Ltd

888/8 Moo.7, Klongkiew Sub-district, Banbueng District, Chonburi, Thailand

1.3 Description of Equipment under Test

Product Name	Furbo 3.5 Camera
Model No.	Furbo 3.5 Dog
Series Model No.	Furbo 3.5 Cat
Model Difference	Refer to the table “Series Difference List”
FCC ID	2AIBVTFFBV5
Frequency Range	802.11b/g/n-20MHz: 2412~2462MHz 802.11n-40MHz: 2422~2452MHz Bluetooth: 2402-2480MHz
Antenna Information	Refer to the table “Antenna List”

The above equipment was tested by Wendell EMC & RF Laboratory For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties

Series Difference List

Model Difference	Main Model Furbo 3.5 Dog	Series Model Furbo 3.5 Cat
Circuit design, printed circuit boards	O	O
Antenna specifications, RF modules	O	O
Use components, wires, and materials	O	O
Use component location, routing, and structure	O	O
Product appearance	White	1. black 2. Add a holder for cat teaser
Other differences	--	Accessories include cat teaser

Note: The laboratory determines based on series differences. The differences are only in appearance color and shape, so there is no need to evaluate the output power/electric field strength +/-2dB requirements. The Furbo 2.5 Dog model is used as the main test.

Antenna List

No.	Manufacturer	Model No.	Antenna Type	Peak Gain
1	INPAQ TECHNOLOGY CO., LTD	RFFPA272206IMAB301	FPC antenna	2.71 dBi for 2.4GHz

1.4 Test Facility

Items	Required (IEC 60068-1)
Temperature (°C)	15-35
Humidity (% RH)	25-75
Barometric pressure (mbar)	860-1060

Description: Accredited by TAF

Accredited Number: 2965

Issued by: Wendell Industrial Co., Ltd

Company Address: 6F/6F-1, No.188, Baoqiao Rd., Xindian Dist.,
New Taipei City 23145, Taiwan R.O.C

Test Lab: Wendell EMC & RF Laboratory

Lab Address: 5F-1, No.188, Baoqiao Rd., Xindian Dist.,
New Taipei City 23145, Taiwan R.O.C

Test Location: No. 119, Wugong 3rd Rd., Wugu Dist.,
New Taipei City 248, Taiwan (R.O.C.)

Designation Number: TW0025

Test Firm Registration Number: 665221

2 Mobile device Assessment Procedure

In 47 CFR § 2.1091, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location.

3 RF Exposure Assessment

Estimation of the expected exposure in power density can be made with the following equation:

$$S = \frac{P \times G}{4\pi \times R^2} = \frac{\text{EIRP}}{4\pi \times R^2}$$

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.

EIRP: Effective Isotropic Radiated Power

4 Limit Requirement

In 47 CFR § 1.1310, use of the device as based upon the user's awareness and ability to exercise control over human exposure. The two categories defined are Occupational/Controlled Exposure and General Population/Uncontrolled. These two categories are defined as follow:

Occupational/Controlled Exposure:

Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

General Population/Uncontrolled:

General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1,842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f / 300	6
1,500-100,000	--	--	5	6

Note :

(1) f = frequency in MHz

(2) * = Plane-wave equivalent power density

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824 / f	2.19 / f	(180 / f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f / 1,500	30
1,500-100,000	--	--	1.0	30

Note :

(1) f = frequency in MHz

(2) * = Plane-wave equivalent power density

5 Test Results

Mode	Max. Power (E.I.R.P)		Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
	dBm	mW				
LE	12.05	16.03	20	0.00319	1	Pass
WLAN 2.4G	25.44	349.95	20	0.06962	1	Pass

Note:

- * Each Function of the max power which perform MPE of any configurations.
- * The total power of LE and WLAN 2.4G transmission at the same time is the largest.
- * The frequency (range) used by the radio frequency function is 1.5GHz~100GHz, the RF field strength limits is e.i.r.p. less than or equal to 1 mW/cm².
- * The limit is equal to the minimum value.
- * The Max total MPE = LE + WLAN 2.4G = 0.07281 (mW/cm²)

--- END ---