

Label

LED LUMINAIRE

Model: MXL1212S-14LED22K92750

Power: 120V 60Hz 22W

CONFORMS TO UL STD. 1598

CERTIFIED TO CSA STD. C22.2 No. 250.0

SUITABLE FOR DAMP LOCATIONS

MIN 90°C SUPPLY CONDUCTORS

CAUTION-RISK OF FIRE XXXX

CONVIENT AUX ENDROITS HUMIDES

LES FILS D'ALIMENTATION 90°C MIN

ATTENTION - RISQUE D'INCENDIE

FCC ID: 2AL76-121214 IC: 24219-121214



LED LUMINAIRE

Model: RGD-FM2/14/22W/MK/MS/2R

Power: 120V 60Hz 22W

CONFORMS TO UL STD. 1598

CERTIFIED TO CSA STD. C22.2 No. 250.0

SUITABLE FOR DAMP LOCATIONS

MIN 90°C SUPPLY CONDUCTORS

CAUTION-RISK OF FIRE XXXX

CONVIENT AUX ENDROITS HUMIDES

LES FILS D'ALIMENTATION 90°C MIN

ATTENTION - RISQUE D'INCENDIE

FCC ID: 2AL76-121214 IC: 24219-121214



LED LUMINAIRE

Model: FMBS14R16E92750

Power: 120V 60Hz 22W

CONFORMS TO UL STD. 1598

CERTIFIED TO CSA STD. C22.2 No. 250.0

SUITABLE FOR DAMP LOCATIONS

MIN 90°C SUPPLY CONDUCTORS

CAUTION-RISK OF FIRE XXXX

CONVIENT AUX ENDROITS HUMIDES

LES FILS D'ALIMENTATION 90°C MIN

ATTENTION - RISQUE D'INCENDIE

FCC ID: 2AL76-121214 IC: 24219-121214



LED LUMINAIRE

Model: MXL1214S-13LED22K92750
Power: 120V 60Hz 22W
CONFORMS TO UL STD. 1598
CERTIFIED TO CSA STD. C22.2 No. 250.0
SUITABLE FOR DAMP LOCATIONS
MIN 90°C SUPPLY CONDUCTORS
CAUTION-RISK OF FIRE XXXX
CONVIENT AUX ENDROITS HUMIDES
LES FILS D'ALIMENTATION 90°C MIN
ATTENTION - RISQUE D'INCENDIE
FCC ID: 2AL76-121214 IC: 24219-121214



Intertek
5005686

LED LUMINAIRE

Model: RGD-FM2/13/22W/MK/MS/PC
Power: 120V 60Hz 22W
CONFORMS TO UL STD. 1598
CERTIFIED TO CSA STD. C22.2 No. 250.0
SUITABLE FOR DAMP LOCATIONS
MIN 90°C SUPPLY CONDUCTORS
CAUTION-RISK OF FIRE XXXX
CONVIENT AUX ENDROITS HUMIDES
LES FILS D'ALIMENTATION 90°C MIN
ATTENTION - RISQUE D'INCENDIE
FCC ID: 2AL76-121214 IC: 24219-121214



Intertek
5005686

LED LUMINAIRE

Model: FMRS13R14E92750
Power: 120V 60Hz 22W
CONFORMS TO UL STD. 1598
CERTIFIED TO CSA STD. C22.2 No. 250.0
SUITABLE FOR DAMP LOCATIONS
MIN 90°C SUPPLY CONDUCTORS
CAUTION-RISK OF FIRE XXXX
CONVIENT AUX ENDROITS HUMIDES
LES FILS D'ALIMENTATION 90°C MIN
ATTENTION - RISQUE D'INCENDIE
FCC ID: 2AL76-121214 IC: 24219-121214



Intertek
5005686

