

## RF EXPOSURE REPORT

### FOR

<b>Applicant</b>	:	Kingstate Electronics (Dongguan) Co., Ltd
<b>Address</b>	:	Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai Town, Dong Guan City, Guang Dong Province, China.
<b>Equipment under Test</b>	:	Headphones
<b>Model No.</b>	:	YH-E500A
<b>Trade Mark</b>	:	YAMAHA
<b>FCC ID</b>	:	2AKMBYHE500A
<b>Manufacturer</b>	:	Kingstate Electronics (Dongguan) Co., Ltd
<b>Address</b>	:	Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai Town, Dong Guan City, Guang Dong Province, China.

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan  
City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## TABLE OF CONTENTS

	Test report declares.....	3
1.	General information.....	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory.....	5
2.	RF Exposure evaluation for FCC.....	5

## TEST REPORT DECLARE

<b>Applicant</b>	:	Kingstate Electronics (Dongguan) Co., Ltd
<b>Address</b>	:	Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai Town, Dong Guan City, Guang Dong Province, China.
<b>Equipment under Test</b>	:	Headphones
<b>Model No.</b>	:	YH-E500A
<b>Trade mark</b>	:	YAMAHA
<b>Manufacturer</b>	:	Kingstate Electronics (Dongguan) Co., Ltd
<b>Address</b>	:	Shi Chong Industrial Park, Shi Chong Avenue, Xiang Xi Village, Shi Pai Town, Dong Guan City, Guang Dong Province, China.

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R20011706-3E14		
<b>Date of Receipt:</b>	Mar. 12, 2020	<b>Date of Test:</b>	Mar. 12, 2020 ~ May 13, 2020

**Prepared By:**

*Talent Zhang*

**Talent Zhang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

## Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	May. 14, 2020	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: Headphones
Model Number	: YH-E500A
EUT function description	: Please reference user manual of this device
Power supply	: DC 5 V/0.5A from Charging case DC 3.7 V Polymer Li-ion built-in battery
Radio Specification	: Bluetooth V5.0
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: Broad antenna, maximum PK gain: 2.45 dBi
Sample Type	: Series production

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,  
Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### Estimation Result

Worse case is as below: [2402MHz, 6.88 dBm, 4.88 mW) output power]

$(4.88/5) \cdot [\sqrt{2.402(\text{GHz})}] = 1.513 < 3.0$  for 1-g SAR

Then SAR evaluation is not required

## END OF REPORT