

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Smart Phone

Trademark : ANT INTELLIGENT

Model Name : 1910

Family Model : N/A

Report No. : S20082800403001

FCC ID : 2AXNU-1910

Prepared for

Shenzhen KaiCheng Technology Co. Ltd
Room 2005, 20th floor, Block C, DaChong business center, No.5 Tong Gu road,
NanShan district, Shenzhen, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen 518126 P.R.China.
Tel.: 400-800-6106, 0755-3699 5508
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name.....: Shenzhen KaiCheng Technology Co. Ltd
Address.....: Room 2005, 20th floor, Block C, DaChong business center,
No.5 Tong Gu road, NanShan district, Shenzhen, China
Manufacturer's Name.....: Shenzhen KaiCheng Technology Co. Ltd
Address.....: Room 2005, 20th floor, Block C, DaChong business center,
No.5 Tong Gu road, NanShan district, Shenzhen, China

Product description


Product name.....: Smart Phone
Trademark: ANT INTELLIGENT
Model Name: 1910
Family Model.....: N/A
FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
Standards.....: IEEE Std 1528-2013
Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.....: Aug. 28, 2020 ~ Sep. 09, 2020
Date of Issue: Sep. 10, 2020
Test Result: **Pass**

Prepared By : 
(Test Engineer) :
(Cheng Jiawen)

Approved By : 
(Lab Manager) :
(Alex Li)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Sep. 10, 2020	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition.....	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe.....	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	18
3.1. Power Reference	18
3.2. Area scan & Zoom scan.....	18
3.3. Description of interpolation/extrapolation scheme	20
3.4. Volumetric Scan	20
3.5. Power Drift	20
4. System Verification Procedure	21
4.1. Tissue Verification	21
4.1.1. Tissue Dielectric Parameter Check Results	22
4.2. System Verification Procedure	23
4.2.1. System Verification Results	24
5. SAR Measurement variability and uncertainty	25
5.1. SAR measurement variability.....	25
5.2. SAR measurement uncertainty	25
6. RF Exposure Positions	26
6.1. Ear and handset reference point	26
6.2. Definition of the cheek position	26
6.3. Definition of the tilt position	28
6.4. Body Worn Accessory	28
6.5. Wireless Router Devices	29
7. RF Output Power	30
7.1. GSM Conducted Power	30
7.2. WCDMA Conducted Power	31
7.3. LTE Conducted Power	32

7.4. WLAN & Bluetooth Output Power	41
7.4.1. Output Power Results Of WLAN	41
7.4.2. Output Power Results Of Bluetooth.....	41
8. Antenna Location.....	42
9. Stand-alone SAR test exclusion.....	43
10. SAR Results	43
10.1. SAR measurement results	43
10.1.1. SAR measurement Result of GSM850.....	43
10.1.2. SAR measurement Result of GSM1900.....	44
10.1.3. SAR measurement Result of WCDMA Band 2.....	45
10.1.4. SAR measurement Result of WCDMA Band 4.....	46
10.1.5. SAR measurement Result of WCDMA Band 5.....	47
10.1.6. SAR measurement Result of LTE Band 2	48
10.1.7. SAR measurement Result of LTE Band 4	49
10.1.8. SAR measurement Result of LTE Band 5	51
10.1.9. SAR measurement Result of LTE Band 7	53
10.1.10. SAR measurement Result of LTE Band 12	55
10.1.11. SAR measurement Result of LTE Band 17	57
10.1.12. SAR measurement Result of WLAN 2.4G	58
10.2. SAR Summation Scenario.....	59
11. Appendix A. Photo documentation	69
12. Appendix B. System Check Plots.....	70
13. Appendix C. Plots of High SAR Measurement.....	95
14. Appendix D. Calibration Certificate	144

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE

HEAD AND TRUNK LIMIT

1.6 W/kg

APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for 1910 are as follows.

RF Exposure Conditions		Equipment Class -Highest Reported SAR (W/kg)			
		PCE	DTS	NII	DSS
1-g Head		0.496	0.576	N/A	N/A
1-g Body-Worn (Separation distance of 10mm)		0.901	0.165	N/A	N/A
1-g Hotspot (Separation distance of 10mm)		0.901	0.165	N/A	N/A
Max Simultaneous Tx	Head	1.072	1.072	N/A	0.601
	Body-Worn	1.066	1.066	N/A	0.954
	Hotspot	1.066	1.066	N/A	0.954

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name	Smart Phone		
Trade Name	ANT INTELLIGENT		
Model Name	1910		
Family Model	N/A		
FCC ID	2AXNU-1910		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna	FPC Antenna		
Battery Information	DC 3.85V, 4000mAh		
Device Operating Configurations			
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/4/5, LTE Band 2/4/5/7/12/17, WLAN 2.4G, Bluetooth		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990

	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	WLAN 2.4G	2412-2462	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 4)		
	3, tested with power control "all 1"(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		
Test Channels (low-mid-high)	128-189-251(GSM 850)		
	512-661-810(GSM 1900)		
	9262-9400-9538(WCDMA Band 2)		
	1312-1413-1513(WCDMA Band 4)		
	4132-4182-4233(WCDMA Band 5)		
	18607-18900-19193(LTE Band 2 BW=1.4MHz)		
	18615-18900-19185(LTE Band 2 BW=3MHz)		
	18625-18900-19175(LTE Band 2 BW=5MHz)		
	18650-18900-19150(LTE Band 2 BW=10MHz)		
	18675-18900-19125(LTE Band 2 BW=15MHz)		
	18700-18900-19100(LTE Band 2 BW=20MHz)		
	19957-20175-20393(LTE Band 4 BW=1.4MHz)		

19965-20175-20385(LTE Band 4 BW=3MHz)
19975-20175-20375(LTE Band 4 BW=5MHz)
20000-20175-20350(LTE Band 4 BW=10MHz)
20025-20175-20325(LTE Band 4 BW=15MHz)
20050-20175-20300(LTE Band 4 BW=20MHz)
20407-20525-20643(LTE Band 5 BW=1.4MHz)
20415-20525-20635(LTE Band 5 BW=3MHz)
20425-20525-20625(LTE Band 5 BW=5MHz)
20450-20525-20600(LTE Band 5 BW=10MHz)
20775-21100-21425(LTE Band 7 BW=5MHz)
20800-21100-21400(LTE Band 7 BW=10MHz)
20825-21100-21375(LTE Band 7 BW=15MHz)
20850-21100-21350(LTE Band 7 BW=20MHz)
23017-23095-23173 (LTE Band 12 BW=1.4MHz)
23025-23095-23165 (LTE Band 12 BW=3MHz)
23035-23095-23155 (LTE Band 12 BW=5MHz)
23060-23095-23130 (LTE Band 12 BW=10MHz)
23755-23790-23825(LTE Band 17 BW=5MHz)
23780-23790-23800(LTE Band 17 BW=10MHz)
1-3-6-9-11(WLAN 2.4G)

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPGO287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.08 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.08 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 7mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Dec. 27, 2019	Dec. 26, 2020
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Jul. 13, 2020	Jul. 12, 2021
☒	R&S	Wideband radio communication tester	CMW500	103917	Jul. 13, 2020	Jul. 12, 2021
☒	HP	Network Analyzer	8753D	3410J01136	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Jul. 13, 2020	Jul. 12, 2021

☒	Agilent	Power meter	E4419B	MY45102538	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	Power sensor	E9301A	MY41495644	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	Power sensor	E9301A	US39212148	Jul. 13, 2020	Jul. 12, 2021
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2020	Jul. 16, 2023

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	41.61	0.92	21.2 °C	Sep. 07, 2020
Body 750	750	55.55 (52.77~58.33)	0.96 (0.91~1.01)	55.54	0.97	21.2 °C	Sep. 08, 2020
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	40.84	0.92	21.5 °C	Sep. 04, 2020
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.02)	54.55	0.98	21.3 °C	Aug. 28, 2020
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.66	1.38	21.3 °C	Sep. 07, 2020
Body 1800	1800	53.30 (50.64~55.97)	1.52 (1.44~1.60)	54.10	1.51	21.2 °C	Sep. 09, 2020
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.70	1.43	21.4 °C	Sep. 04, 2020
Body 1900	1900	53.30 (50.64~55.97)	1.52 (1.44~1.60)	54.29	1.53	21.4 °C	Aug. 28, 2020
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.59	1.84	21.5 °C	Aug. 31, 2020
Body 2450	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	51.57	1.88	21.2 °C	Aug. 31, 2020
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.16	2.02	21.4 °C	Sep. 08, 2020
Body 2600	2600	52.51 (49.88~55.14)	2.16 (2.05~2.27)	52.86	2.21	21.6 °C	Sep. 09, 2020

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz Head	8.56 (7.70~9.42)	5.55 (5.00~6.11)	8.99	5.53	21.2 °C	Sep. 07, 2020
750MHz Body	8.85 (7.97~9.74)	5.91 (5.32~6.50)	9.25	6.02	21.2 °C	Sep. 08, 2020
835MHz Head	9.55 (8.60~10.51)	6.10 (5.49~6.71)	10.15	6.15	21.5 °C	Sep. 04, 2020
835MHz Body	9.83 (8.85~10.81)	6.45 (5.81~7.10)	9.40	6.62	21.3 °C	Aug. 28, 2020
1800MHz Head	38.11 (34.30~41.92)	20.05 (18.05~22.06)	38.91	20.97	21.3 °C	Sep. 07, 2020
1800MHz Body	38.13 (34.32~41.94)	20.65 (18.59~22.72)	39.30	19.82	21.2 °C	Sep. 09, 2020
1900MHz Head	38.92 (35.03~42.81)	20.09 (18.08~22.10)	37.62	20.32	21.4 °C	Sep. 04, 2020
1900MHz Body	39.02 (35.12~42.92)	20.57 (18.51~22.63)	38.30	20.81	21.4 °C	Aug. 28, 2020
2450MHz Head	53.76 (48.38~59.14)	24.12 (21.71~26.53)	56.89	24.54	21.5 °C	Aug. 31, 2020
2450MHz Body	52.90 (47.61~58.19)	24.09 (21.68~26.50)	51.01	24.07	21.2 °C	Aug. 31, 2020
2600MHz Head	55.60 (50.04~61.16)	24.60 (22.14~27.06)	55.31	23.29	21.4 °C	Sep. 08, 2020
2600MHz Body	52.49 (47.24~57.74)	23.74 (21.37~26.11)	56.12	23.34	21.6 °C	Sep. 09, 2020

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	33.00	32.77	32.72	32.66	23.97	23.74	23.69	23.63
GPRS(GMSK, 1 TS)	33.00	32.75	32.71	32.67	23.97	23.72	23.68	23.64
GPRS(GMSK, 2 TS)	32.00	31.83	31.80	31.70	25.98	25.81	25.78	25.68
GPRS(GMSK, 3 TS)	30.00	29.84	29.86	29.69	25.74	25.58	25.60	25.43
GPRS(GMSK, 4 TS)	29.00	28.78	28.81	28.64	25.99	25.77	25.80	25.63
EDGE(GMSK, 1 TS)	27.00	27.00	26.86	26.68	17.97	17.97	17.83	17.65
EDGE(GMSK, 2 TS)	27.00	25.39	26.26	26.04	20.98	19.37	20.24	20.02
EDGE(GMSK, 3 TS)	24.00	23.78	23.66	23.45	19.74	19.52	19.40	19.19
EDGE(GMSK, 4 TS)	23.00	22.51	22.59	22.38	19.99	19.50	19.58	19.37
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	31.00	29.96	30.06	29.88	21.97	20.93	21.03	20.85
GPRS(GMSK, 1 TS)	31.00	29.97	30.07	29.88	21.97	20.94	21.04	20.85
GPRS(GMSK, 2 TS)	30.00	29.04	29.16	28.97	23.98	23.02	23.14	22.95
GPRS(GMSK, 3 TS)	28.00	27.05	27.19	26.97	23.74	22.79	22.93	22.71
GPRS(GMSK, 4 TS)	27.00	26.00	26.11	25.90	23.99	22.99	23.10	22.89
EDGE(GMSK, 1 TS)	26.00	25.60	25.68	25.06	16.97	16.57	16.65	16.03
EDGE(GMSK, 2 TS)	25.00	24.16	24.28	24.21	18.98	18.14	18.26	18.19
EDGE(GMSK, 3 TS)	23.00	22.30	22.36	21.99	18.74	18.04	18.10	17.73
EDGE(GMSK, 4 TS)	22.00	21.13	21.09	20.79	18.99	18.12	18.08	17.78

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.
The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.2. WCDMA Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC 12.2Kbps	24.00	23.05	22.88	22.88
HSDPA Subtest-1	23.00	22.10	21.96	21.92
HSDPA Subtest-2	22.00	21.72	21.43	21.33
HSDPA Subtest-3	21.00	20.35	20.13	20.28
HSDPA Subtest-4	21.00	20.64	20.60	20.54
HSUPA Subtest-1	22.00	21.65	21.60	21.55
HSUPA Subtest-2	22.00	21.96	21.86	21.85
HSUPA Subtest-3	21.00	20.51	20.70	20.30
HSUPA Subtest-4	23.00	22.08	21.91	21.88
HSUPA Subtest-5	22.00	21.42	20.99	21.14
Band	WCDMA Band 4			
Tx Channel	Tune-up	1312	1413	1512
Frequency (MHz)		1712.4	1732.6	1752.6
RMC 12.2Kbps	23.00	22.68	22.71	22.82
HSDPA Subtest-1	22.00	20.66	21.74	21.87
HSDPA Subtest-2	22.00	21.28	21.07	21.42
HSDPA Subtest-3	21.00	20.21	20.02	20.29
HSDPA Subtest-4	21.00	20.38	20.31	20.53
HSUPA Subtest-1	22.00	21.27	21.37	21.22
HSUPA Subtest-2	22.00	21.68	21.61	21.74
HSUPA Subtest-3	21.00	20.37	20.43	20.47
HSUPA Subtest-4	22.00	21.70	21.74	21.86
HSUPA Subtest-5	22.00	20.79	21.09	21.09
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	24.00	23.09	23.07	23.22
HSDPA Subtest-1	23.00	22.19	22.10	22.24
HSDPA Subtest-2	22.00	21.61	21.30	21.87
HSDPA Subtest-3	21.00	20.63	20.41	20.77
HSDPA Subtest-4	21.00	20.75	20.84	20.79
HSUPA Subtest-1	22.00	21.14	21.69	21.86
HSUPA Subtest-2	23.00	22.02	21.98	22.17
HSUPA Subtest-3	22.00	21.16	21.03	21.07

HSUPA Subtest-4	23.00	22.16	22.07	22.21
HSUPA Subtest-5	22.00	21.34	21.28	21.38

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	23.00	22.19	22.52	22.44
			1	2	23.00	22.64	22.69	22.53
			1	5	23.00	22.66	22.50	22.44
			3	0	23.00	22.63	22.53	22.49
			3	1	23.00	22.67	22.56	22.52
			3	2	23.00	22.65	22.53	22.46
		16QAM	6	0	22.00	21.70	21.54	21.52
			1	0	22.00	21.46	21.63	21.58
			1	2	22.00	21.61	21.74	21.70
			1	5	22.00	21.44	21.61	21.59
			3	0	22.00	21.73	21.64	21.64
			3	1	22.00	21.71	21.69	21.64
			3	2	22.00	21.77	21.63	21.60
			6	0	21.00	20.81	20.71	20.62
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	23.00	22.74	22.58	22.47
			1	7	23.00	22.91	22.88	22.77
			1	14	23.00	22.74	22.51	22.45
			8	0	22.00	21.69	21.55	21.47
			8	4	22.00	21.70	21.59	21.53
			8	7	22.00	21.69	21.52	21.50
		16QAM	15	0	22.00	21.63	21.52	21.44
			1	0	23.00	21.53	21.91	21.63
			1	7	23.00	21.79	22.16	21.86
			1	14	23.00	21.47	21.87	21.63
			8	0	21.00	20.61	20.53	20.48
			8	4	21.00	20.63	20.53	20.48
			8	7	21.00	20.60	20.49	20.39
			15	0	21.00	20.60	20.45	20.36
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	23.00	22.59	22.43	22.40
			1	12	23.00	22.95	22.85	22.88
			1	24	23.00	22.57	22.42	22.39
			12	0	22.00	21.62	21.54	21.48
			12	6	22.00	21.66	21.56	21.52

			12	11	22.00	21.66	21.48	21.42
			25	0	22.00	21.61	21.51	21.44
		16QAM	1	0	23.00	21.84	21.69	21.87
			1	12	23.00	22.19	22.27	22.25
			1	24	23.00	21.76	21.68	21.84
			12	0	21.00	20.50	20.49	20.44
			12	6	21.00	20.54	20.52	20.45
			12	11	21.00	20.53	20.46	20.31
			25	0	21.00	20.61	20.42	20.37
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.00	22.76	22.55	22.44
			1	24	23.00	22.92	22.71	22.62
			1	49	23.00	22.73	22.50	22.50
			25	0	22.00	21.63	21.63	21.62
			25	12	22.00	21.66	21.57	21.52
			25	24	22.00	21.72	21.52	21.42
			50	0	22.00	21.63	21.57	21.50
		16QAM	1	0	23.00	21.49	21.92	21.55
			1	24	23.00	21.63	22.05	21.72
			1	49	23.00	21.47	21.83	21.59
			25	0	21.00	20.54	20.61	20.54
			25	12	21.00	20.57	20.50	20.46
			25	24	21.00	20.66	20.48	20.38
			50	0	21.00	20.57	20.53	20.49
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band 2	15MHz	QPSK	1	0	23.00	22.62	22.52	22.42
			1	37	23.00	22.88	22.82	22.71
			1	74	23.00	22.43	22.41	22.36
			36	0	22.00	21.67	21.69	21.52
			36	18	22.00	21.70	21.59	21.56
			36	37	22.00	21.72	21.56	21.48
			75	0	22.00	21.68	21.61	21.52
		16QAM	1	0	23.00	21.70	21.87	21.50
			1	37	23.00	21.97	22.16	21.89
			1	74	23.00	21.57	21.73	21.50
			36	0	21.00	20.56	20.65	20.50
			36	18	21.00	20.59	20.54	20.56
			36	37	21.00	20.58	20.50	20.46
			75	0	21.00	20.63	20.55	20.45
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.00	22.49	22.32	22.30
			1	49	23.00	22.76	22.68	22.58
			1	99	23.00	22.30	22.26	22.25

			50	0	22.00	21.45	21.68	21.36
			50	24	22.00	21.58	21.54	21.45
			50	49	22.00	21.54	21.50	21.26
			100	0	22.00	21.53	21.58	21.32
		16QAM	1	0	22.00	21.65	21.63	21.48
			1	49	22.00	21.93	21.89	21.77
			1	99	22.00	21.51	21.47	21.44
			50	0	21.00	20.46	20.66	20.30
			50	24	21.00	20.59	20.53	20.40
			50	49	21.00	20.57	20.47	20.24
			100	0	21.00	20.49	20.54	20.31

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.00	22.27	22.27	22.42
			1	2	23.00	22.43	22.45	22.55
			1	5	23.00	22.30	22.26	22.45
			3	0	23.00	22.34	22.38	22.49
			3	1	23.00	22.35	22.41	22.48
			3	2	23.00	22.32	22.41	22.47
			6	0	22.00	21.24	21.31	21.49
		16QAM	1	0	22.00	21.34	21.50	21.25
			1	2	22.00	21.42	21.63	21.42
			1	5	22.00	21.36	21.51	21.26
			3	0	22.00	21.41	21.60	21.60
			3	1	22.00	21.43	21.63	21.59
			3	2	22.00	21.41	21.61	21.61
			6	0	21.00	20.42	20.48	20.64
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	23.00	22.33	22.45	22.45
			1	7	23.00	22.72	22.73	22.74
			1	14	23.00	22.40	22.36	22.49
			8	0	22.00	21.36	21.38	21.53
			8	4	22.00	21.35	21.38	21.55
			8	7	22.00	21.36	21.35	21.51
			15	0	22.00	21.31	21.38	21.49
		16QAM	1	0	23.00	21.18	21.83	21.64
			1	7	23.00	21.33	22.06	21.95
			1	14	23.00	21.17	21.80	21.64
			8	0	21.00	20.28	20.44	20.54
			8	4	21.00	20.33	20.49	20.55
			8	7	21.00	20.36	20.44	20.50
			15	0	21.00	20.37	20.44	20.44
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5

LTE Band 4	5MHz	QPSK	1	0	23.00	22.24	22.27	22.40
			1	12	23.00	22.53	22.71	22.67
			1	24	23.00	22.29	22.31	22.39
			12	0	22.00	21.30	21.42	21.53
			12	6	22.00	21.38	21.45	21.56
			12	11	22.00	21.32	21.38	21.46
			25	0	22.00	21.29	21.39	21.54
		16QAM	1	0	23.00	21.68	21.66	21.68
			1	12	23.00	22.26	21.96	22.04
			1	24	23.00	21.69	21.61	21.69
			12	0	21.00	20.28	20.42	20.51
			12	6	21.00	20.35	20.45	20.56
			12	11	21.00	20.35	20.40	20.48
			25	0	21.00	20.28	20.46	20.44
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.00	22.36	22.40	22.42
			1	24	23.00	22.57	22.45	22.58
			1	49	23.00	22.42	22.44	22.48
			25	0	22.00	21.34	21.52	21.53
			25	12	22.00	21.37	21.42	21.47
			25	24	22.00	21.35	21.46	21.50
			50	0	22.00	21.35	21.47	21.49
		16QAM	1	0	22.00	21.12	21.78	21.54
			1	24	22.00	21.30	21.90	21.70
			1	49	22.00	21.19	21.79	21.61
			25	0	21.00	20.35	20.51	20.49
			25	12	21.00	20.37	20.48	20.47
			25	24	21.00	20.36	20.52	20.52
			50	0	21.00	20.30	20.49	20.54
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.00	22.26	22.27	22.38
			1	37	23.00	22.59	22.65	22.76
			1	74	23.00	22.26	22.27	22.39
			36	0	22.00	21.48	21.46	21.45
			36	18	22.00	21.53	21.42	21.56
			36	37	22.00	21.45	21.50	21.51
			75	0	22.00	21.47	21.49	21.50
		16QAM	1	0	23.00	21.35	21.47	21.74
			1	37	23.00	21.75	21.75	22.05
			1	74	23.00	21.43	21.42	21.74
			36	0	21.00	20.46	20.45	20.44
			36	18	21.00	20.53	20.40	20.52
			36	37	21.00	20.40	20.45	20.50
			75	0	21.00	20.43	20.53	20.40
Band	Band	Modulation	RB		Tune-up	Channel/Frequency(MHz)		

	Width		Configuration					
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.00	22.13	22.18	22.13
			1	49	23.00	22.52	22.48	22.60
			1	99	23.00	22.14	22.25	22.24
			50	0	22.00	21.39	21.47	21.41
			50	24	22.00	21.38	21.43	21.45
			50	49	22.00	21.30	21.49	21.45
			100	0	22.00	21.36	21.49	21.40
		16QAM	1	0	22.00	21.39	21.38	21.38
			1	49	22.00	21.73	21.77	21.80
			1	99	22.00	21.54	21.45	21.21
			50	0	21.00	20.40	20.51	20.46
			50	24	21.00	20.43	20.47	20.48
			50	49	21.00	20.38	20.49	20.50
			100	0	21.00	20.35	20.53	20.49

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	23.00	22.61	22.55	22.66
			1	2	23.00	22.74	22.67	22.77
			1	5	23.00	22.56	22.51	22.69
			3	0	23.00	22.62	22.61	22.67
			3	1	23.00	22.64	22.59	22.66
			3	2	23.00	22.60	22.60	22.61
			6	0	22.00	21.56	21.57	21.74
		16QAM	1	0	22.00	21.67	21.69	21.42
			1	2	22.00	21.78	21.87	21.57
			1	5	22.00	21.69	21.70	21.44
			3	0	22.00	21.74	21.81	21.71
			3	1	22.00	21.73	21.82	21.82
			3	2	22.00	21.70	21.81	21.73
			6	0	21.00	20.72	20.71	20.83
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	23.00	22.62	22.55	22.72
			1	7	23.00	22.85	22.96	23.00
			1	14	23.00	22.53	22.63	22.74
			8	0	22.00	21.52	21.53	21.73
			8	4	22.00	21.53	21.63	21.72
			8	7	22.00	21.53	21.62	21.69
			15	0	22.00	21.47	21.53	21.66
		16QAM	1	0	23.00	22.00	21.76	21.49
			1	7	23.00	22.28	22.05	21.74
			1	14	23.00	21.97	21.71	21.46
			8	0	21.00	20.54	20.54	20.65

			8	4	21.00	20.52	20.61	20.68
			8	7	21.00	20.52	20.60	20.63
			15	0	21.00	20.50	20.52	20.70
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	23.00	22.51	22.52	22.61
			1	12	23.00	22.84	22.89	23.00
			1	24	23.00	22.50	22.59	22.60
			12	0	22.00	21.43	21.52	21.69
			12	6	22.00	21.56	21.63	21.68
			12	11	22.00	21.46	21.66	21.64
			25	0	22.00	21.50	21.66	21.65
		16QAM	1	0	23.00	21.96	21.81	21.81
			1	12	23.00	22.46	22.20	22.18
			1	24	23.00	21.98	21.83	21.80
			12	0	21.00	20.47	20.44	20.64
			12	6	21.00	20.54	20.55	20.70
			12	11	21.00	20.50	20.59	20.65
			25	0	21.00	20.44	20.63	20.62
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band 5	10MHz	QPSK	1	0	23.00	22.55	22.59	22.65
			1	24	23.00	22.71	22.76	22.82
			1	49	23.00	22.63	22.70	22.69
			25	0	22.00	21.66	21.59	21.74
			25	12	22.00	21.53	21.64	21.71
			25	24	22.00	21.59	21.80	21.64
			50	0	22.00	21.59	21.71	21.69
		16QAM	1	0	23.00	21.72	21.45	22.00
			1	24	23.00	21.85	21.61	22.10
			1	49	23.00	21.78	21.50	22.03
			25	0	21.00	20.61	20.58	20.75
			25	12	21.00	20.57	20.58	20.68
			25	24	21.00	20.61	20.77	20.66
			50	0	21.00	20.63	20.65	20.68

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	23.00	22.82	22.76	22.26
			1	12	23.00	23.00	23.00	22.65
			1	24	23.00	22.84	22.71	22.23
			12	0	22.00	21.79	21.72	21.30
			12	6	22.00	21.87	21.79	21.39
			12	11	22.00	21.81	21.73	21.37
			25	0	22.00	21.80	21.73	21.31
			1	0	23.00	22.23	21.82	21.51
		16QAM	1	0	23.00	22.23	21.82	21.51

			1	12	23.00	22.65	22.19	21.78
			1	24	23.00	22.23	21.80	21.51
			12	0	21.00	20.73	20.58	20.27
			12	6	21.00	20.84	20.52	20.37
			12	11	21.00	20.80	20.48	20.35
			25	0	21.00	20.73	20.55	20.24
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	23.00	22.91	22.36	22.36
			1	24	23.00	23.00	22.48	22.42
			1	49	23.00	22.90	22.39	22.34
			25	0	22.00	21.88	21.35	21.37
			25	12	22.00	21.81	21.34	21.30
			25	24	22.00	21.92	21.39	21.46
			50	0	22.00	21.68	21.34	21.39
		16QAM	1	0	22.00	21.54	21.19	21.66
			1	24	22.00	21.62	21.29	21.80
			1	49	22.00	21.51	21.21	21.69
			25	0	21.00	20.38	20.37	20.39
			25	12	21.00	20.36	20.34	20.34
			25	24	21.00	20.45	20.39	20.47
			50	0	21.00	20.41	20.31	20.38
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	23.00	22.72	22.19	22.28
			1	37	23.00	22.62	22.50	22.68
			1	74	23.00	22.26	22.17	22.27
			36	0	22.00	21.39	21.36	21.40
			36	18	22.00	21.42	21.39	21.41
			36	37	22.00	21.50	21.42	21.46
			75	0	22.00	21.44	21.42	21.45
		16QAM	1	0	22.00	21.42	21.37	21.67
			1	37	22.00	21.72	21.70	22.00
			1	74	22.00	21.38	21.34	21.63
			36	0	21.00	20.40	20.27	20.39
			36	18	21.00	20.44	20.32	20.36
			36	37	21.00	20.50	20.32	20.45
			75	0	21.00	20.41	20.33	20.38
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.00	22.14	22.09	22.14
			1	49	23.00	22.51	22.45	22.48
			1	99	23.00	22.08	22.14	22.13
			50	0	22.00	21.29	21.25	21.36
			50	24	22.00	21.37	21.32	21.32

			50	49	22.00	21.36	21.34	21.43
			100	0	22.00	21.31	21.31	21.42
		16QAM	1	0	22.00	21.37	21.36	21.41
			1	49	22.00	21.76	21.67	21.64
			1	99	22.00	21.39	21.36	21.38
			50	0	21.00	20.33	20.26	20.42
			50	24	21.00	20.39	20.36	20.42
			50	49	21.00	20.43	20.35	20.43
			100	0	21.00	20.33	20.30	20.43

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	23.00	22.09	22.02	22.06
			1	2	23.00	22.22	22.11	22.17
			1	5	23.00	22.13	22.03	22.09
			3	0	23.00	22.20	22.14	22.17
			3	1	23.00	22.22	22.17	22.15
			3	2	23.00	22.19	22.13	22.14
		16QAM	6	0	22.00	21.01	21.00	21.09
			1	0	22.00	21.30	21.33	20.91
			1	2	22.00	21.38	21.37	21.13
			1	5	22.00	21.29	21.29	20.89
			3	0	22.00	21.39	21.38	21.30
			3	1	22.00	21.38	21.42	21.30
			3	2	22.00	21.40	21.39	21.31
			6	0	21.00	20.28	20.26	20.28
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	23.00	22.16	22.20	22.13
			1	7	23.00	22.48	22.41	22.45
			1	14	23.00	22.22	22.03	22.13
			8	0	22.00	21.08	21.12	21.19
			8	4	22.00	21.14	21.12	21.20
			8	7	22.00	21.12	21.13	21.15
			15	0	22.00	21.13	21.11	21.15
		16QAM	1	0	22.00	21.10	21.65	21.30
			1	7	22.00	21.11	21.89	21.69
			1	14	22.00	20.99	21.54	21.30
			8	0	21.00	20.11	20.18	20.24
			8	4	21.00	20.17	20.22	20.22
			8	7	21.00	20.12	20.18	20.20
			15	0	21.00	20.20	20.16	20.16
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band	5MHz	QPSK	1	0	23.00	21.98	22.01	22.03
			1	12	23.00	22.54	22.49	22.50

12			1	24	23.00	22.04	22.01	22.08
			12	0	22.00	21.18	21.11	21.24
			12	6	22.00	21.24	21.18	21.22
			12	11	22.00	21.13	21.20	21.15
			25	0	22.00	21.16	21.19	21.21
		16QAM	1	0	23.00	21.37	21.64	21.44
			1	12	23.00	21.84	22.09	21.73
			1	24	23.00	21.41	21.68	21.39
			12	0	21.00	20.25	20.12	20.23
			12	6	21.00	20.31	20.21	20.19
			12	11	21.00	20.15	20.24	20.11
			25	0	21.00	20.16	20.15	20.27
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	23.00	22.07	22.13	22.10
			1	24	23.00	22.20	22.26	22.26
			1	49	23.00	22.09	22.16	22.10
			25	0	22.00	21.26	21.21	21.10
			25	12	22.00	21.19	21.19	21.14
			25	24	22.00	21.26	21.28	21.07
			50	0	22.00	21.32	21.25	21.10
		16QAM	1	0	22.00	21.33	21.01	21.59
			1	24	22.00	21.43	21.17	21.68
			1	49	22.00	21.31	21.01	21.55
			25	0	21.00	20.34	20.22	20.15
			25	12	21.00	20.25	20.21	20.24
			25	24	21.00	20.30	20.29	20.14
			50	0	21.00	20.41	20.27	20.14

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	23.00	22.55	22.64	22.53
			1	12	23.00	22.99	22.93	22.90
			1	24	23.00	22.58	22.56	22.63
			12	0	22.00	21.66	21.70	21.79
			12	6	22.00	21.76	21.71	21.78
			12	11	22.00	21.74	21.67	21.72
			25	0	22.00	21.73	21.70	21.79
		16QAM	1	0	23.00	21.94	22.18	21.93
			1	12	23.00	22.39	22.62	22.41
			1	24	23.00	21.97	22.17	21.97
			12	0	21.00	20.71	20.72	20.75
			12	6	21.00	20.81	20.74	20.73
			12	11	21.00	20.78	20.69	20.65
			25	0	21.00	20.72	20.69	20.83
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	23.00	22.63	22.68	22.58
			1	24	23.00	22.75	22.82	22.77
			1	49	23.00	22.64	22.65	22.68
			25	0	22.00	21.65	21.68	21.67
			25	12	22.00	21.73	21.69	21.69
			25	24	22.00	21.71	21.65	21.66
			50	0	22.00	21.72	21.62	21.64
		16QAM	1	0	23.00	21.84	21.58	22.11
			1	24	23.00	22.01	21.69	22.25
			1	49	23.00	21.84	21.50	22.11
			25	0	21.00	20.70	20.65	20.74
			25	12	21.00	20.77	20.77	20.76
			25	24	21.00	20.76	20.67	20.70
			50	0	21.00	20.79	20.63	20.71

7.4. WLAN & Bluetooth Output Power

7.4.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	15.00	13.29
	6	2437	15.00	14.06
	11	2462	15.00	13.57
802.11g	1	2412	13.00	12.37
	6	2437	13.00	12.60
	11	2462	13.00	12.11
802.11n HT20	1	2412	13.00	12.49
	6	2437	13.00	12.62
	11	2462	13.00	12.00
802.11n HT40	3	2422	12.00	11.86
	6	2437	12.00	11.64
	9	2452	12.00	11.06

NOTE: Power measurement results of WLAN 2.4G.

7.4.2. Output Power Results Of Bluetooth


BR+EDR	Output Power (dBm)				
	Channel	Tune-up	Data Rates		
			1M	2M	3M
	0CH	4.000	3.867	3.217	2.905
	39CH	4.000	3.695	3.004	3.013
	78CH	4.000	3.954	3.481	3.437

BLE	Channel	Tune-up	Output Power (dBm)	
			Data Rates	
			1M	2M
	0CH	-6.000	-7.266	-7.388
	19CH	-6.000	-7.014	-6.432
	39CH	-6.000	-6.193	-6.316

8. Antenna Location

Right Side

150mm



Left Side

Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	NO	Yes	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	4	2.51	5	2.480	0.79	3.0	Yes

NOTE: Standalone SAR test exclusion for Bluetooth

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f_{\text{(GHz)}}}/x] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	4	2.51	5	2.480	7.5	0.105
Bluetooth	Body	4	2.51	10	2.480	7.5	0.053
Bluetooth	Hotspot	4	2.51	10	2.480	7.5	0.053

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift ($\pm 5\%$)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	189/836.4	GPRS(GMSK 2TS)	0.382	0.218	-2.31	31.80	32.00	0.400

Left Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.199	0.114	-4.41	31.80	32.00	0.208
Right Cheek	189/836.4	GPRS(GMSK 2TS)	0.348	0.199	-3.75	31.80	32.00	0.364
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.171	0.094	3.19	31.80	32.00	0.179

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 2TS)	0.374	0.272	-2.91	31.80	32.00	0.392
Back Side	189/836.4	GPRS(GMSK 2TS)	0.493	0.362	-0.39	31.80	32.00	0.516

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 2TS)	0.374	0.272	-2.91	31.80	32.00	0.392
Back Side	189/836.4	GPRS(GMSK 2TS)	0.493	0.362	-0.39	31.80	32.00	0.516
Left Side	189/836.4	GPRS(GMSK 2TS)	0.385	0.288	4.53	31.80	32.00	0.403
Right Side	189/836.4	GPRS(GMSK 2TS)	0.242	0.178	0.21	31.80	32.00	0.253
Bottom Side	189/836.4	GPRS(GMSK 2TS)	0.185	0.136	1.38	31.80	32.00	0.194

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	661/1880	GPRS(GMSK 2TS)	0.293	0.172	0.44	29.16	30.00	0.356
Left Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.154	0.089	3.22	29.16	30.00	0.187

Right Cheek	661/1880	GPRS(GMSK 2TS)	0.250	0.148	3.33	29.16	30.00	0.303
Right Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.128	0.079	-0.02	29.16	30.00	0.155

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 2TS)	0.319	0.190	-0.53	29.16	30.00	0.387
Back Side	661/1880	GPRS(GMSK 2TS)	0.421	0.256	2.70	29.16	30.00	0.511

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 2TS)	0.319	0.190	-0.53	29.16	30.00	0.387
Back Side	661/1880	GPRS(GMSK 2TS)	0.421	0.256	2.70	29.16	30.00	0.511
Left Side	661/1880	GPRS(GMSK 2TS)	0.320	0.195	1.22	29.16	30.00	0.388
Right Side	661/1880	GPRS(GMSK 2TS)	0.206	0.125	4.89	29.16	30.00	0.250
Bottom Side	661/1880	GPRS(GMSK 2TS)	0.155	0.094	-2.57	29.16	30.00	0.188

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	9400/1880	RMC12.2K	0.383	0.231	-0.32	22.88	24.00	0.496
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.195	0.115	1.95	22.88	24.00	0.252
Right Cheek	9400/1880	RMC12.2K	0.356	0.211	0.54	22.88	24.00	0.461
Right Tilt 15	9400/1880	RMC12.2K	0.177	0.105	4.60	22.88	24.00	0.229

Degree

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.494	0.269	2.90	22.88	24.00	0.639
Back Side	9400/1880	RMC12.2K	0.634	0.349	-3.09	22.88	24.00	0.821
Back Side	9262/1852.4	RMC12.2K	0.587	0.326	0.28	23.05	24.00	0.731
Back Side	9538/1907.6	RMC12.2K	0.596	0.338	0.17	22.88	24.00	0.771

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.494	0.269	2.90	22.88	24.00	0.639
Back Side	9400/1880	RMC12.2K	0.634	0.349	-3.09	22.88	24.00	0.821
Left Side	9400/1880	RMC12.2K	0.454	0.250	1.66	22.88	24.00	0.588
Right Side	9400/1880	RMC12.2K	0.275	0.156	1.09	22.88	24.00	0.356
Bottom Side	9400/1880	RMC12.2K	0.249	0.139	0.38	22.88	24.00	0.322
Back Side	9262/1852.4	RMC12.2K	0.587	0.326	0.28	23.05	24.00	0.731
Back Side	9538/1907.6	RMC12.2K	0.596	0.338	0.17	22.88	24.00	0.771

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	1413/1732.6	RMC12.2K	0.324	0.205	-1.95	22.71	23.00	0.346
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.175	0.113	-0.73	22.71	23.00	0.187
Right Cheek	1413/1732.6	RMC12.2K	0.297	0.186	-3.02	22.71	23.00	0.318
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.153	0.101	1.83	22.71	23.00	0.164

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g
			1g	10g				

								(W/Kg)
Front Side	1413/1732.6	RMC12.2K	0.536	0.320	-0.26	22.71	23.00	0.573
Back Side	1413/1732.6	RMC12.2K	0.664	0.401	-0.96	22.71	23.00	0.710

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.536	0.320	-0.26	22.71	23.00	0.573
Back Side	1413/1732.6	RMC12.2K	0.664	0.401	-0.96	22.71	23.00	0.710
Left Side	1413/1732.6	RMC12.2K	0.502	0.305	2.65	22.71	23.00	0.537
Right Side	1413/1732.6	RMC12.2K	0.310	0.188	-2.58	22.71	23.00	0.331
Bottom Side	1413/1732.6	RMC12.2K	0.259	0.161	-4.92	22.71	23.00	0.277

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	4182/836.4	RMC12.2K	0.113	0.089	-0.91	23.07	24.00	0.140
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.057	0.046	1.34	23.07	24.00	0.071
Right Cheek	4182/836.4	RMC12.2K	0.103	0.085	1.91	23.07	24.00	0.128
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.052	0.039	3.48	23.07	24.00	0.064

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.262	0.159	-0.24	23.07	24.00	0.325
Back Side	4182/836.4	RMC12.2K	0.327	0.194	-0.13	23.07	24.00	0.405

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.262	0.159	-0.24	23.07	24.00	0.325
Back Side	4182/836.4	RMC12.2K	0.327	0.194	-0.13	23.07	24.00	0.405

Left Side	4182/836.4	RMC12.2K	0.234	0.141	-0.67	23.07	24.00	0.290
Right Side	4182/836.4	RMC12.2K	0.162	0.091	-4.43	23.07	24.00	0.201
Bottom Side	4182/836.4	RMC12.2K	0.128	0.075	0.21	23.07	24.00	0.159

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	18900/1880	20M QPSK(1,49)	0.290	0.175	2.63	22.68	23.00	0.312
Left Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.161	0.098	-2.78	22.68	23.00	0.173
Right Cheek	18900/1880	20M QPSK(1,49)	0.273	0.163	4.40	22.68	23.00	0.294
Right Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.123	0.075	4.82	22.68	23.00	0.132
50%RB								
Left Cheek	18900/1880	1.4M QPSK(3,1)	0.266	0.160	2.68	22.56	23.00	0.294
Left Tilt 15 Degree	18900/1880	1.4M QPSK(3,1)	0.147	0.084	-3.15	22.56	23.00	0.163
Right Cheek	18900/1880	1.4M QPSK(3,1)	0.255	0.147	4.05	22.56	23.00	0.282
Right Tilt 15 Degree	18900/1880	1.4M QPSK(3,1)	0.105	0.069	-0.62	22.56	23.00	0.116

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tuned power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								

Front Side	18900/1880	20M QPSK(1,49)	0.400	0.220	-2.38	22.68	23.00	0.431
Back Side	18900/1880	20M QPSK(1,49)	0.480	0.266	-0.99	22.68	23.00	0.517
50%RB								
Front Side	18900/1880	1.4M QPSK(3,1)	0.344	0.201	4.08	22.56	23.00	0.381
Back Side	18900/1880	1.4M QPSK(3,1)	0.442	0.231	-0.35	22.56	23.00	0.489

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	20M QPSK(1,49)	0.400	0.220	-2.38	22.68	23.00	0.431
Back Side	18900/1880	20M QPSK(1,49)	0.480	0.266	-0.99	22.68	23.00	0.517
Left Side	18900/1880	20M QPSK(1,49)	0.381	0.215	-1.38	22.68	23.00	0.410
Right Side	18900/1880	20M QPSK(1,49)	0.223	0.124	-2.91	22.68	23.00	0.240
Bottom Side	18900/1880	20M QPSK(1,49)	0.191	0.110	3.96	22.68	23.00	0.206
50%RB								
Front Side	18900/1880	1.4M QPSK(3,1)	0.344	0.201	4.08	22.56	23.00	0.381
Back Side	18900/1880	1.4M QPSK(3,1)	0.442	0.231	-0.35	22.56	23.00	0.489
Left Side	18900/1880	1.4M QPSK(3,1)	0.360	0.188	2.98	22.56	23.00	0.398
Right Side	18900/1880	1.4M QPSK(3,1)	0.191	0.106	-1.39	22.56	23.00	0.211
Bottom Side	18900/1880	1.4M QPSK(3,1)	0.172	0.099	-3.64	22.56	23.00	0.190

NOTE: Hotspot SAR test results of LTE Band 2

10.1.7. SAR measurement Result of LTE Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20175/1732.5	20M QPSK(1,49)	0.283	0.179	0.68	22.48	23.00	0.319
Left Tilt	20175/1732.5	20M QPSK(1,49)	0.149	0.098	-0.71	22.48	23.00	0.168

15 Degree								
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.254	0.157	-4.71	22.48	23.00	0.286
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.135	0.087	2.71	22.48	23.00	0.152
50%RB								
Left Cheek	20175/1732.5	1.4M QPSK(3,0)	0.245	0.157	-2.82	22.38	23.00	0.283
Left Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,0)	0.137	0.086	2.18	22.38	23.00	0.158
Right Cheek	20175/1732.5	1.4M QPSK(3,0)	0.228	0.147	3.50	22.38	23.00	0.263
Right Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,0)	0.125	0.081	-3.52	22.38	23.00	0.144

NOTE: Head SAR test results of LTE Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tuned power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	20M QPSK(1,49)	0.415	0.262	-4.61	22.48	23.00	0.468
Back Side	20175/1732.5	20M QPSK(1,49)	0.509	0.326	-0.70	22.48	23.00	0.574
50%RB								
Front Side	20175/1732.5	1.4M QPSK(3,0)	0.371	0.244	1.19	22.38	23.00	0.428
Back Side	20175/1732.5	1.4M QPSK(3,0)	0.461	0.309	1.93	22.38	23.00	0.532

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								

NOTE: Hotspot SAR test results of LTE Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20525/836.5	10M QPSK(1,24)	0.121	0.077	0.05	22.76	23.00	0.128
Left Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.065	0.038	3.21	22.76	23.00	0.069
Right Cheek	20525/836.5	10M QPSK(1,24)	0.110	0.075	2.05	22.76	23.00	0.116
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.051	0.030	-2.04	22.76	23.00	0.054
50%RB								

Left Cheek	20525/836.5	1.4M QPSK(3,0)	0.115	0.072	0.54	22.61	23.00	0.126
Left Tilt 15 Degree	20525/836.5	1.4M QPSK(3,0)	0.061	0.032	-4.23	22.61	23.00	0.067
Right Cheek	20525/836.5	1.4M QPSK(3,0)	0.095	0.066	0.57	22.61	23.00	0.104
Right Tilt 15 Degree	20525/836.5	1.4M QPSK(3,0)	0.046	0.026	-2.49	22.61	23.00	0.050

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	10M QPSK(1,24)	0.190	0.134	-3.56	22.76	23.00	0.201
Back Side	20525/836.5	10M QPSK(1,24)	0.250	0.181	-0.04	22.76	23.00	0.264
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,0)	0.174	0.127	1.33	22.61	23.00	0.190
Back Side	20525/836.5	1.4M QPSK(3,0)	0.231	0.166	-2.26	22.61	23.00	0.253

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	10M QPSK(1,24)	0.190	0.134	-3.56	22.76	23.00	0.201
Back Side	20525/836.5	10M QPSK(1,24)	0.250	0.181	-0.04	22.76	23.00	0.264
Left Side	20525/836.5	10M QPSK(1,24)	0.186	0.136	-0.42	22.76	23.00	0.197
Right Side	20525/836.5	10M QPSK(1,24)	0.108	0.078	3.39	22.76	23.00	0.114
Bottom	20525/836.5	10M QPSK(1,24)	0.093	0.067	0.32	22.76	23.00	0.098

Side								
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,0)	0.174	0.127	1.33	22.61	23.00	0.190
Back Side	20525/836.5	1.4M QPSK(3,0)	0.231	0.166	-2.26	22.61	23.00	0.253
Left Side	20525/836.5	1.4M QPSK(3,0)	0.176	0.116	1.31	22.61	23.00	0.193
Right Side	20525/836.5	1.4M QPSK(3,0)	0.096	0.072	-2.49	22.61	23.00	0.105
Bottom Side	20525/836.5	1.4M QPSK(3,0)	0.085	0.060	1.38	22.61	23.00	0.093

NOTE: Hotspot SAR test results of LTE Band 5

10.1.9. SAR measurement Result of LTE Band 7

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	21100/2535	20M QPSK(1,49)	0.298	0.162	-0.68	22.45	23.00	0.338
Left Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.169	0.096	-3.34	22.45	23.00	0.192
Right Cheek	21100/2535	20M QPSK(1,49)	0.270	0.149	0.05	22.45	23.00	0.306
Right Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.123	0.071	-3.72	22.45	23.00	0.140
50%RB								
Left Cheek	21100/2535	20M QPSK(50,49)	0.260	0.153	-0.83	21.34	22.00	0.303
Left Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.150	0.089	1.88	21.34	22.00	0.175
Right Cheek	21100/2535	20M QPSK(50,49)	0.250	0.127	-2.63	21.34	22.00	0.291
Right Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.109	0.067	-3.85	21.34	22.00	0.127

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M QPSK(1,49)	0.666	0.321	-2.18	22.45	23.00	0.756
Back Side	21100/2535	20M QPSK(1,49)	0.794	0.379	-1.12	22.45	23.00	0.901
Back Side	21100/2535	20M QPSK(1,49)	0.765	0.359	0.23	22.51	23.00	0.856
Back Side	21100/2535	20M QPSK(1,49)	0.748	0.347	1.48	22.48	23.00	0.843
50%RB								
Front Side	21100/2535	20M QPSK(50,49)	0.394	0.168	-1.14	21.34	22.00	0.459
Back Side	21100/2535	20M QPSK(50,49)	0.462	0.217	3.80	21.34	22.00	0.538
100%RB								
Back Side	21100/2535	20M QPSK(100,0)	0.339	0.187	3.18	21.31	22.00	0.397

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M QPSK(1,49)	0.666	0.321	-2.18	22.45	23.00	0.756
Back Side	21100/2535	20M QPSK(1,49)	0.794	0.379	-1.12	22.45	23.00	0.901
Left Side	21100/2535	20M QPSK(1,49)	0.565	0.274	-3.48	22.45	23.00	0.641
Right Side	21100/2535	20M QPSK(1,49)	0.392	0.188	0.88	22.45	23.00	0.445
Bottom Side	21100/2535	20M QPSK(1,49)	0.302	0.140	-3.95	22.45	23.00	0.343
Back Side	21100/2535	20M QPSK(1,49)	0.765	0.359	0.23	22.51	23.00	0.856
Back Side	21100/2535	20M	0.748	0.347	1.48	22.48	23.00	0.843

		QPSK(1,49)						
50%RB								
Front Side	21100/2535	20M QPSK(50,49)	0.394	0.168	-1.14	21.34	22.00	0.459
Back Side	21100/2535	20M QPSK(50,49)	0.462	0.217	3.80	21.34	22.00	0.538
Left Side	21100/2535	20M QPSK(50,49)	0.304	0.155	-3.47	21.34	22.00	0.354
Right Side	21100/2535	20M QPSK(50,49)	0.207	0.110	-3.94	21.34	22.00	0.241
Bottom Side	21100/2535	20M QPSK(50,49)	0.175	0.081	-1.37	21.34	22.00	0.204
100%RB								
Back Side	21100/2535	20M QPSK(100,0)	0.339	0.187	3.18	21.31	22.00	0.397

NOTE: Hotspot SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23095/707.5	10M QPSK(1,24)	0.378	0.279	0.28	22.26	23.00	0.448
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.209	0.157	-4.67	22.26	23.00	0.248
Right Cheek	23095/707.5	10M QPSK(1,24)	0.330	0.242	-4.38	22.26	23.00	0.391
Right Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.162	0.123	-1.80	22.26	23.00	0.192
50%RB								
Left Cheek	23095/707.5	1.4M QPSK(3,1)	0.326	0.252	-2.05	22.17	23.00	0.395
Left Tilt 15 Degree	23095/707.5	1.4M QPSK(3,1)	0.191	0.136	3.90	22.17	23.00	0.231
Right	23095/707.5	1.4M QPSK(3,1)	0.307	0.207	3.08	22.17	23.00	0.372

Cheek								
Right Tilt 15 Degree	23095/707.5	1.4M QPSK(3,1)	0.146	0.114	0.65	22.17	23.00	0.177

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	10M QPSK(1,24)	0.163	0.130	-1.90	22.26	23.00	0.193
Back Side	23095/707.5	10M QPSK(1,24)	0.208	0.163	0.25	22.26	23.00	0.247
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,1)	0.139	0.112	3.18	22.17	23.00	0.168
Back Side	23095/707.5	1.4M QPSK(3,1)	0.190	0.151	2.37	22.17	23.00	0.230

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	10M QPSK(1,24)	0.163	0.130	-1.90	22.26	23.00	0.193
Back Side	23095/707.5	10M QPSK(1,24)	0.208	0.163	0.25	22.26	23.00	0.247
Left Side	23095/707.5	10M QPSK(1,24)	0.162	0.131	4.35	22.26	23.00	0.192
Right Side	23095/707.5	10M QPSK(1,24)	0.099	0.080	2.59	22.26	23.00	0.117
Bottom Side	23095/707.5	10M QPSK(1,24)	0.076	0.063	-1.20	22.26	23.00	0.090
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,1)	0.139	0.112	3.18	22.17	23.00	0.168
Back Side	23095/707.5	1.4M QPSK(3,1)	0.190	0.151	2.37	22.17	23.00	0.230
Left Side	23095/707.5	1.4M QPSK(3,1)	0.148	0.120	-0.75	22.17	23.00	0.179
Right	23095/707.5	1.4M QPSK(3,1)	0.094	0.069	1.42	22.17	23.00	0.114

Side								
Bottom Side	23095/707.5	1.4M QPSK(3,1)	0.070	0.056	2.16	22.17	23.00	0.085

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23790/710	10M QPSK(1,24)	0.373	0.273	0.04	22.82	23.00	0.389
Left Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.205	0.147	1.27	22.82	23.00	0.214
Right Cheek	23790/710	10M QPSK(1,24)	0.330	0.245	4.16	22.82	23.00	0.344
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.153	0.114	-0.12	22.82	23.00	0.159
50%RB								
Left Cheek	23790/710	10M QPSK(25,12)	0.336	0.232	-2.43	21.69	22.00	0.361
Left Tilt 15 Degree	23790/710	10M QPSK(25,12)	0.192	0.134	-2.41	21.69	22.00	0.206
Right Cheek	23790/710	10M QPSK(25,12)	0.313	0.216	3.17	21.69	22.00	0.336
Right Tilt 15 Degree	23790/710	10M QPSK(25,12)	0.130	0.101	-3.90	21.69	22.00	0.140

NOTE: Head SAR test results of LTE Band 17

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.159	0.129	-4.72	22.82	23.00	0.166

Back Side	23790/710	10M QPSK(1,24)	0.204	0.163	-0.62	22.82	23.00	0.213
50%RB								
Front Side	23790/710	10M QPSK(25,12)	0.146	0.112	-3.07	21.69	22.00	0.157
Back Side	23790/710	10M QPSK(25,12)	0.192	0.148	-2.65	21.69	22.00	0.206

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.159	0.129	-4.72	22.82	23.00	0.166
Back Side	23790/710	10M QPSK(1,24)	0.204	0.163	-0.62	22.82	23.00	0.213
Left Side	23790/710	10M QPSK(1,24)	0.154	0.126	2.82	22.82	23.00	0.161
Right Side	23790/710	10M QPSK(1,24)	0.098	0.083	-3.14	22.82	23.00	0.102
Bottom Side	23790/710	10M QPSK(1,24)	0.075	0.060	-0.04	22.82	23.00	0.078
50%RB								
Front Side	23790/710	10M QPSK(25,12)	0.146	0.112	-3.07	21.69	22.00	0.157
Back Side	23790/710	10M QPSK(25,12)	0.192	0.148	-2.65	21.69	22.00	0.206
Left Side	23790/710	10M QPSK(25,12)	0.145	0.113	2.89	21.69	22.00	0.156
Right Side	23790/710	10M QPSK(25,12)	0.085	0.078	-3.44	21.69	22.00	0.091
Bottom Side	23790/710	10M QPSK(25,12)	0.069	0.054	0.92	21.69	22.00	0.074

NOTE: Hotspot SAR test results of LTE Band 17

10.1.12. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel	Test Mode	SAR Value (W/kg)	Power Drift	Conducted power	Tune-up power	Scaled SAR
-----------------------	--------------	-----------	------------------	-------------	-----------------	---------------	------------

	/Freq.		1g	10g	(±5%)	(dBm)	(dBm)	1g (W/Kg)
Left Cheek	6/2437	802.11 b	0.464	0.236	-0.56	14.06	15.00	0.576
Left Tilt 15 Degree	6/2437	802.11 b	0.244	0.123	1.21	14.06	15.00	0.303
Right Cheek	6/2437	802.11 b	0.405	0.210	-2.13	14.06	15.00	0.503
Right Tilt 15 Degree	6/2437	802.11 b	0.183	0.094	1.65	14.06	15.00	0.227

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.083	0.049	-1.47	14.06	15.00	0.103
Back Side	6/2437	802.11 b	0.133	0.079	-4.21	14.06	15.00	0.165

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.083	0.049	-1.47	14.06	15.00	0.103
Back Side	6/2437	802.11 b	0.133	0.079	-4.21	14.06	15.00	0.165
Right Side	6/2437	802.11 b	0.033	0.017	0.60	14.06	15.00	0.041
Top Side	6/2437	802.11 b	0.045	0.026	2.80	14.06	15.00	0.056

NOTE: Hotspot SAR test results of WLAN 2.4G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 2.4G			
Head	Left Cheek	0.400	0.576	0.976	N/A	N/A
	Left Tilt 15 Degree	0.208	0.303	0.511	N/A	N/A

	Right Cheek	0.364	0.503	0.867	N/A	N/A
	Right Tilt 15 Degree	0.179	0.227	0.406	N/A	N/A
Body-Worn	Front Side	0.392	0.103	0.495	N/A	N/A
	Back Side	0.516	0.165	0.681	N/A	N/A
Hotspot	Front Side	0.392	0.103	0.495	N/A	N/A
	Back Side	0.516	0.165	0.681	N/A	N/A
	Left Side	0.403	N/A	0.403	N/A	N/A
	Right Side	0.253	0.041	0.294	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.194	N/A	0.194	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 2.4G			
Head	Left Cheek	0.356	0.576	0.932	N/A	N/A
	Left Tilt 15 Degree	0.187	0.303	0.490	N/A	N/A
	Right Cheek	0.303	0.503	0.806	N/A	N/A
	Right Tilt 15 Degree	0.155	0.227	0.382	N/A	N/A
Body-Worn	Front Side	0.387	0.103	0.490	N/A	N/A
	Back Side	0.511	0.165	0.676	N/A	N/A
Hotspot	Front Side	0.387	0.103	0.490	N/A	N/A
	Back Side	0.511	0.165	0.676	N/A	N/A
	Left Side	0.388	N/A	0.388	N/A	N/A
	Right Side	0.250	0.041	0.291	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.188	N/A	0.188	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 2.4G			
Head	Left Cheek	0.496	0.576	1.072	N/A	N/A
	Left Tilt 15 Degree	0.252	0.303	0.555	N/A	N/A
	Right Cheek	0.461	0.503	0.964	N/A	N/A
	Right Tilt 15 Degree	0.229	0.227	0.456	N/A	N/A
Body-Worn	Front Side	0.639	0.103	0.742	N/A	N/A
	Back Side	0.821	0.165	0.986	N/A	N/A
Hotspot	Front Side	0.639	0.103	0.742	N/A	N/A
	Back Side	0.821	0.165	0.986	N/A	N/A

	Left Side	0.588	N/A	0.588	N/A	N/A
	Right Side	0.356	0.041	0.397	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.322	N/A	0.322	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	WLAN 2.4G			
Head	Left Cheek	0.346	0.576	0.922	N/A	N/A
	Left Tilt 15 Degree	0.187	0.303	0.490	N/A	N/A
	Right Cheek	0.318	0.503	0.821	N/A	N/A
	Right Tilt 15 Degree	0.164	0.227	0.391	N/A	N/A
Body-Worn	Front Side	0.573	0.103	0.676	N/A	N/A
	Back Side	0.710	0.165	0.875	N/A	N/A
Hotspot	Front Side	0.573	0.103	0.676	N/A	N/A
	Back Side	0.710	0.165	0.875	N/A	N/A
	Left Side	0.537	N/A	0.537	N/A	N/A
	Right Side	0.331	0.041	0.372	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.277	N/A	0.277	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 2.4G			
Head	Left Cheek	0.140	0.576	0.716	N/A	N/A
	Left Tilt 15 Degree	0.071	0.303	0.374	N/A	N/A
	Right Cheek	0.128	0.503	0.631	N/A	N/A
	Right Tilt 15 Degree	0.064	0.227	0.291	N/A	N/A
Body-Worn	Front Side	0.325	0.103	0.428	N/A	N/A
	Back Side	0.405	0.165	0.570	N/A	N/A
Hotspot	Front Side	0.325	0.103	0.428	N/A	N/A
	Back Side	0.405	0.165	0.570	N/A	N/A
	Left Side	0.290	N/A	0.290	N/A	N/A
	Right Side	0.201	0.041	0.242	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.159	N/A	0.159	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 2.4G			
Head	Left Cheek	0.312	0.576	0.888	N/A	N/A
	Left Tilt 15 Degree	0.173	0.303	0.476	N/A	N/A
	Right Cheek	0.294	0.503	0.797	N/A	N/A
	Right Tilt 15 Degree	0.132	0.227	0.359	N/A	N/A
Body-Worn	Front Side	0.431	0.103	0.534	N/A	N/A
	Back Side	0.517	0.165	0.682	N/A	N/A
Hotspot	Front Side	0.431	0.103	0.534	N/A	N/A
	Back Side	0.517	0.165	0.682	N/A	N/A
	Left Side	0.410	N/A	0.410	N/A	N/A
	Right Side	0.240	0.041	0.281	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.206	N/A	0.206	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 2.4G			
Head	Left Cheek	0.319	0.576	0.895	N/A	N/A
	Left Tilt 15 Degree	0.168	0.303	0.471	N/A	N/A
	Right Cheek	0.286	0.503	0.789	N/A	N/A
	Right Tilt 15 Degree	0.152	0.227	0.379	N/A	N/A
Body-Worn	Front Side	0.468	0.103	0.571	N/A	N/A
	Back Side	0.574	0.165	0.739	N/A	N/A
Hotspot	Front Side	0.468	0.103	0.571	N/A	N/A
	Back Side	0.574	0.165	0.739	N/A	N/A
	Left Side	0.455	N/A	0.455	N/A	N/A
	Right Side	0.248	0.041	0.289	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.209	N/A	0.209	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 2.4G			
Head	Left Cheek	0.128	0.576	0.704	N/A	N/A
	Left Tilt 15 Degree	0.069	0.303	0.372	N/A	N/A
	Right Cheek	0.116	0.503	0.619	N/A	N/A
	Right Tilt 15 Degree	0.054	0.227	0.281	N/A	N/A

Body-Worn	Front Side	0.201	0.103	0.304	N/A	N/A
	Back Side	0.264	0.165	0.429	N/A	N/A
Hotspot	Front Side	0.201	0.103	0.304	N/A	N/A
	Back Side	0.264	0.165	0.429	N/A	N/A
	Left Side	0.197	N/A	0.197	N/A	N/A
	Right Side	0.114	0.041	0.155	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.098	N/A	0.098	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 2.4G			
Head	Left Cheek	0.338	0.576	0.914	N/A	N/A
	Left Tilt 15 Degree	0.192	0.303	0.495	N/A	N/A
	Right Cheek	0.306	0.503	0.809	N/A	N/A
	Right Tilt 15 Degree	0.140	0.227	0.367	N/A	N/A
Body-Worn	Front Side	0.756	0.103	0.859	N/A	N/A
	Back Side	0.901	0.165	1.066	N/A	N/A
Hotspot	Front Side	0.756	0.103	0.859	N/A	N/A
	Back Side	0.901	0.165	1.066	N/A	N/A
	Left Side	0.641	N/A	0.641	N/A	N/A
	Right Side	0.445	0.041	0.486	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.343	N/A	0.343	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	WLAN 2.4G			
Head	Left Cheek	0.448	0.576	1.024	N/A	N/A
	Left Tilt 15 Degree	0.248	0.303	0.551	N/A	N/A
	Right Cheek	0.391	0.503	0.894	N/A	N/A
	Right Tilt 15 Degree	0.192	0.227	0.419	N/A	N/A
Body-Worn	Front Side	0.193	0.103	0.296	N/A	N/A
	Back Side	0.247	0.165	0.412	N/A	N/A
Hotspot	Front Side	0.193	0.103	0.296	N/A	N/A
	Back Side	0.247	0.165	0.412	N/A	N/A
	Left Side	0.192	N/A	0.192	N/A	N/A
	Right Side	0.117	0.041	0.158	N/A	N/A

	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.090	N/A	0.090	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 2.4G			
Head	Left Cheek	0.389	0.576	0.965	N/A	N/A
	Left Tilt 15 Degree	0.214	0.303	0.517	N/A	N/A
	Right Cheek	0.344	0.503	0.847	N/A	N/A
	Right Tilt 15 Degree	0.159	0.227	0.386	N/A	N/A
Body-Worn	Front Side	0.166	0.103	0.269	N/A	N/A
	Back Side	0.213	0.165	0.378	N/A	N/A
Hotspot	Front Side	0.166	0.103	0.269	N/A	N/A
	Back Side	0.213	0.165	0.378	N/A	N/A
	Left Side	0.161	N/A	0.161	N/A	N/A
	Right Side	0.102	0.041	0.143	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.078	N/A	0.078	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	Bluetooth			
Head	Left Cheek	0.400	0.105	0.505	N/A	N/A
	Left Tilt 15 Degree	0.208	0.105	0.313	N/A	N/A
	Right Cheek	0.364	0.105	0.469	N/A	N/A
	Right Tilt 15 Degree	0.179	0.105	0.284	N/A	N/A
Body-Worn	Front Side	0.392	0.053	0.445	N/A	N/A
	Back Side	0.516	0.053	0.569	N/A	N/A
Hotspot	Front Side	0.392	0.053	0.445	N/A	N/A
	Back Side	0.516	0.053	0.569	N/A	N/A
	Left Side	0.403	N/A	0.403	N/A	N/A
	Right Side	0.253	0.053	0.306	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.194	N/A	0.194	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	Bluetooth			

Head	Left Cheek	0.356	0.105	0.461	N/A	N/A
	Left Tilt 15 Degree	0.187	0.105	0.292	N/A	N/A
	Right Cheek	0.303	0.105	0.408	N/A	N/A
	Right Tilt 15 Degree	0.155	0.105	0.260	N/A	N/A
Body-Worn	Front Side	0.387	0.053	0.440	N/A	N/A
	Back Side	0.511	0.053	0.564	N/A	N/A
Hotspot	Front Side	0.387	0.053	0.440	N/A	N/A
	Back Side	0.511	0.053	0.564	N/A	N/A
	Left Side	0.388	N/A	0.388	N/A	N/A
	Right Side	0.250	0.053	0.303	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.188	N/A	0.188	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	Bluetooth			
Head	Left Cheek	0.496	0.105	0.601	N/A	N/A
	Left Tilt 15 Degree	0.252	0.105	0.357	N/A	N/A
	Right Cheek	0.461	0.105	0.566	N/A	N/A
	Right Tilt 15 Degree	0.229	0.105	0.334	N/A	N/A
Body-Worn	Front Side	0.639	0.053	0.692	N/A	N/A
	Back Side	0.821	0.053	0.874	N/A	N/A
Hotspot	Front Side	0.639	0.053	0.692	N/A	N/A
	Back Side	0.821	0.053	0.874	N/A	N/A
	Left Side	0.588	N/A	0.588	N/A	N/A
	Right Side	0.356	0.053	0.409	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.322	N/A	0.322	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	Bluetooth			
Head	Left Cheek	0.346	0.105	0.451	N/A	N/A
	Left Tilt 15 Degree	0.187	0.105	0.292	N/A	N/A
	Right Cheek	0.318	0.105	0.423	N/A	N/A
	Right Tilt 15 Degree	0.164	0.105	0.269	N/A	N/A
Body-Worn	Front Side	0.573	0.053	0.626	N/A	N/A

	Back Side	0.710	0.053	0.763	N/A	N/A
Hotspot	Front Side	0.573	0.053	0.626	N/A	N/A
	Back Side	0.710	0.053	0.763	N/A	N/A
	Left Side	0.537	N/A	0.537	N/A	N/A
	Right Side	0.331	0.053	0.384	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.277	N/A	0.277	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	Bluetooth			
Head	Left Cheek	0.140	0.105	0.245	N/A	N/A
	Left Tilt 15 Degree	0.071	0.105	0.176	N/A	N/A
	Right Cheek	0.128	0.105	0.233	N/A	N/A
	Right Tilt 15 Degree	0.064	0.105	0.169	N/A	N/A
Body-Worn	Front Side	0.325	0.053	0.378	N/A	N/A
	Back Side	0.405	0.053	0.458	N/A	N/A
Hotspot	Front Side	0.325	0.053	0.378	N/A	N/A
	Back Side	0.405	0.053	0.458	N/A	N/A
	Left Side	0.290	N/A	0.290	N/A	N/A
	Right Side	0.201	0.053	0.254	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.159	N/A	0.159	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	Bluetooth			
Head	Left Cheek	0.312	0.105	0.417	N/A	N/A
	Left Tilt 15 Degree	0.173	0.105	0.278	N/A	N/A
	Right Cheek	0.294	0.105	0.399	N/A	N/A
	Right Tilt 15 Degree	0.132	0.105	0.237	N/A	N/A
Body-Worn	Front Side	0.431	0.053	0.484	N/A	N/A
	Back Side	0.517	0.053	0.570	N/A	N/A
Hotspot	Front Side	0.431	0.053	0.484	N/A	N/A
	Back Side	0.517	0.053	0.570	N/A	N/A
	Left Side	0.410	N/A	0.410	N/A	N/A
	Right Side	0.240	0.053	0.293	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A

	Bottom Side	0.206	N/A	0.206	N/A	N/A
--	-------------	-------	-----	-------	-----	-----

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	Bluetooth			
Head	Left Cheek	0.319	0.105	0.424	N/A	N/A
	Left Tilt 15 Degree	0.168	0.105	0.273	N/A	N/A
	Right Cheek	0.286	0.105	0.391	N/A	N/A
	Right Tilt 15 Degree	0.152	0.105	0.257	N/A	N/A
Body-Worn	Front Side	0.468	0.053	0.521	N/A	N/A
	Back Side	0.574	0.053	0.627	N/A	N/A
Hotspot	Front Side	0.468	0.053	0.521	N/A	N/A
	Back Side	0.574	0.053	0.627	N/A	N/A
	Left Side	0.455	N/A	0.455	N/A	N/A
	Right Side	0.248	0.053	0.301	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.209	N/A	0.209	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	Bluetooth			
Head	Left Cheek	0.128	0.105	0.233	N/A	N/A
	Left Tilt 15 Degree	0.069	0.105	0.174	N/A	N/A
	Right Cheek	0.116	0.105	0.221	N/A	N/A
	Right Tilt 15 Degree	0.054	0.105	0.159	N/A	N/A
Body-Worn	Front Side	0.201	0.053	0.254	N/A	N/A
	Back Side	0.264	0.053	0.317	N/A	N/A
Hotspot	Front Side	0.201	0.053	0.254	N/A	N/A
	Back Side	0.264	0.053	0.317	N/A	N/A
	Left Side	0.197	N/A	0.197	N/A	N/A
	Right Side	0.114	0.053	0.167	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.098	N/A	0.098	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	Bluetooth			
Head	Left Cheek	0.338	0.105	0.443	N/A	N/A

	Left Tilt 15 Degree	0.192	0.105	0.297	N/A	N/A
	Right Cheek	0.306	0.105	0.411	N/A	N/A
	Right Tilt 15 Degree	0.140	0.105	0.245	N/A	N/A
Body-Worn	Front Side	0.756	0.053	0.809	N/A	N/A
	Back Side	0.901	0.053	0.954	N/A	N/A
Hotspot	Front Side	0.756	0.053	0.809	N/A	N/A
	Back Side	0.901	0.053	0.954	N/A	N/A
	Left Side	0.641	N/A	0.641	N/A	N/A
	Right Side	0.445	0.053	0.498	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.343	N/A	0.343	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	Bluetooth			
Head	Left Cheek	0.448	0.105	0.553	N/A	N/A
	Left Tilt 15 Degree	0.248	0.105	0.353	N/A	N/A
	Right Cheek	0.391	0.105	0.496	N/A	N/A
	Right Tilt 15 Degree	0.192	0.105	0.297	N/A	N/A
Body-Worn	Front Side	0.193	0.053	0.246	N/A	N/A
	Back Side	0.247	0.053	0.300	N/A	N/A
Hotspot	Front Side	0.193	0.053	0.246	N/A	N/A
	Back Side	0.247	0.053	0.300	N/A	N/A
	Left Side	0.192	N/A	0.192	N/A	N/A
	Right Side	0.117	0.053	0.170	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.090	N/A	0.090	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	Bluetooth			
Head	Left Cheek	0.389	0.105	0.494	N/A	N/A
	Left Tilt 15 Degree	0.214	0.105	0.319	N/A	N/A
	Right Cheek	0.344	0.105	0.449	N/A	N/A
	Right Tilt 15 Degree	0.159	0.105	0.264	N/A	N/A
Body-Worn	Front Side	0.166	0.053	0.219	N/A	N/A

	Back Side	0.213	0.053	0.266	N/A	N/A
Hotspot	Front Side	0.166	0.053	0.219	N/A	N/A
	Back Side	0.213	0.053	0.266	N/A	N/A
	Left Side	0.161	N/A	0.161	N/A	N/A
	Right Side	0.102	0.053	0.155	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.078	N/A	0.078	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and Bluetooth.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - SID750 - Head
MEASUREMENT 2 System Performance Check - SID750 - Body
MEASUREMENT 3 System Performance Check - SID835 - Head
MEASUREMENT 4 System Performance Check - SID835 - Body
MEASUREMENT 5 System Performance Check - SID1800 - Head
MEASUREMENT 6 System Performance Check - SID1800 - Body
MEASUREMENT 7 System Performance Check - SID1900 - Head
MEASUREMENT 8 System Performance Check - SID1900 - Body
MEASUREMENT 9 System Performance Check - SID2450 - Head
MEASUREMENT 10 System Performance Check - SID2450 - Body
MEASUREMENT 11 System Performance Check - SID2600 - Head
MEASUREMENT 12 System Performance Check - SID2600 - Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	41.613162
Relative permittivity (imaginary part)	22.071263
Conductivity (S/m)	0.920362
Variation (%)	-1.810000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/Kg

SAR 10g (W/Kg)	0.553218
SAR 1g (W/Kg)	0.899062



MEASUREMENT 2


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW750</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	55.540248
Relative permittivity (imaginary part)	23.383842
Conductivity (S/m)	0.970318
Variation (%)	-0.490000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.602281
SAR 1g (W/Kg)	0.925263



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	40.843500
Relative permittivity (imaginary part)	19.921602
Conductivity (S/m)	0.920502
Variation (%)	1.870000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.615433
SAR 1g (W/Kg)	1.015035



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.551101
Relative permittivity (imaginary part)	21.173359
Conductivity (S/m)	0.981236
Variation (%)	-1.210000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.662123
SAR 1g (W/Kg)	0.940356



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.661237
Relative permittivity (imaginary part)	13.793229
Conductivity (S/m)	1.380365
Variation (%)	-2.113000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.097397
SAR 1g (W/Kg)	3.891451



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	54.103510
Relative permittivity (imaginary part)	15.110016
Conductivity (S/m)	1.513096
Variation (%)	1.510000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	1.982239
SAR 1g (W/Kg)	3.930268



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.701017
Relative permittivity (imaginary part)	13.583006
Conductivity (S/m)	1.430302
Variation (%)	-1.430000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg

SAR 10g (W/Kg)	2.032452
SAR 1g (W/Kg)	3.762361



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	54.293335
Relative permittivity (imaginary part)	14.473503
Conductivity (S/m)	1.533566
Variation (%)	0.120000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.39 W/kg

SAR 10g (W/Kg)	2.081329
SAR 1g (W/Kg)	3.830402



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.591421
Relative permittivity (imaginary part)	13.532631
Conductivity (S/m)	1.840663
Variation (%)	-3.350000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.454375
SAR 1g (W/Kg)	5.689435



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	51.571497
Relative permittivity (imaginary part)	13.813566
Conductivity (S/m)	1.882816
Variation (%)	0.420000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.46 W/kg

SAR 10g (W/Kg)	2.407285
SAR 1g (W/Kg)	5.101270



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.162638
Relative permittivity (imaginary part)	13.983997
Conductivity (S/m)	2.023631
Variation (%)	-0.040000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.329031
SAR 1g (W/Kg)	5.531267



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.860066
Relative permittivity (imaginary part)	15.330637
Conductivity (S/m)	2.213465
Variation (%)	-1.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.99 W/kg

SAR 10g (W/Kg)	2.334324
SAR 1g (W/Kg)	5.612188



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 2.4G Head
MEASUREMENT 12 WLAN 2.4G Body
MEASUREMENT 13 LTE Band 2 Head
MEASUREMENT 14 LTE Band 2 Body
MEASUREMENT 15 LTE Band 4 Head
MEASUREMENT 16 LTE Band 4 Body
MEASUREMENT 17 LTE Band 5 Head
MEASUREMENT 18 LTE Band 5 Body
MEASUREMENT 19 LTE Band 7 Head
MEASUREMENT 20 LTE Band 7 Body
MEASUREMENT 21 LTE Band 12 Head
MEASUREMENT 22 LTE Band 12 Body
MEASUREMENT 23 LTE Band 17 Head
MEASUREMENT 24 LTE Band 17 Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.750961
Relative permittivity (imaginary part)	19.941540
Conductivity (S/m)	0.926617
Variation (%)	-2.310000

SURFACE SAR





VOLUME SAR



Maximum location: X=-80.00, Y=-53.00

SAR Peak: 0.61 W/kg

SAR 10g (W/Kg)	0.218086
SAR 1g (W/Kg)	0.381879



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.559582
Relative permittivity (imaginary part)	21.152740
Conductivity (S/m)	0.982897
Variation (%)	-0.390000

SURFACE SAR





VOLUME SAR



Maximum location: X=-6.00, Y=-16.00

SAR Peak: 0.65 W/kg

SAR 10g (W/Kg)	0.361656
SAR 1g (W/Kg)	0.493459



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.077000
Relative permittivity (imaginary part)	13.230200
Conductivity (S/m)	1.381821
Variation (%)	0.440000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-53.00

SAR Peak: 0.47 W/kg

SAR 10g (W/Kg)	0.172434
SAR 1g (W/Kg)	0.293410



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.363899
Relative permittivity (imaginary part)	14.557700
Conductivity (S/m)	1.520471
Variation (%)	2.700000

SURFACE SAR





VOLUME SAR



Maximum location: X=-26.00, Y=19.00

SAR Peak: 0.65 W/kg

SAR 10g (W/Kg)	0.256330
SAR 1g (W/Kg)	0.421045



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.077000
Relative permittivity (imaginary part)	13.230200
Conductivity (S/m)	1.381821
Variation (%)	-0.320000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-52.00

SAR Peak: 0.58 W/kg

SAR 10g (W/Kg)	0.231301
SAR 1g (W/Kg)	0.382818



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.363899
Relative permittivity (imaginary part)	14.557700
Conductivity (S/m)	1.520471
Variation (%)	-3.090000

SURFACE SAR





VOLUME SAR



Maximum location: X=15.00, Y=16.00

SAR Peak: 1.06 W/kg

SAR 10g (W/Kg)	0.349461
SAR 1g (W/Kg)	0.633635



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.117390
Relative permittivity (imaginary part)	13.745742
Conductivity (S/m)	1.322646
Variation (%)	-1.950000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-52.00

SAR Peak: 0.47 W/kg

SAR 10g (W/Kg)	0.205233
SAR 1g (W/Kg)	0.324039



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	54.501167
Relative permittivity (imaginary part)	15.156370
Conductivity (S/m)	1.458380
Variation (%)	-0.960000

SURFACE SAR





VOLUME SAR



Maximum location: X=6.00, Y=22.00

SAR Peak: 1.05 W/kg

SAR 10g (W/Kg)	0.401457
SAR 1g (W/Kg)	0.663851



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.750961
Relative permittivity (imaginary part)	19.941540
Conductivity (S/m)	0.926617
Variation (%)	-0.910000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-25.00

SAR Peak: 0.13 W/kg

SAR 10g (W/Kg)	0.088930
SAR 1g (W/Kg)	0.113010



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.559582
Relative permittivity (imaginary part)	21.152740
Conductivity (S/m)	0.982897
Variation (%)	-0.130000

SURFACE SAR





VOLUME SAR



Maximum location: X=18.00, Y=1.00

SAR Peak: 0.52 W/kg

SAR 10g (W/Kg)	0.193808
SAR 1g (W/Kg)	0.326575



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	38.638000
Relative permittivity (imaginary part)	13.450300
Conductivity (S/m)	1.821021
Variation (%)	-0.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=-23.00, Y=13.00

SAR Peak: 0.80 W/kg

SAR 10g (W/Kg)	0.236031
SAR 1g (W/Kg)	0.463538



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	51.703701
Relative permittivity (imaginary part)	13.884400
Conductivity (S/m)	1.879793
Variation (%)	-4.210000

SURFACE SAR





VOLUME SAR



Maximum location: X=-24.00, Y=-5.00

SAR Peak: 0.24 W/kg

SAR 10g (W/Kg)	0.078757
SAR 1g (W/Kg)	0.133302



MEASUREMENT 13


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.077000
Relative permittivity (imaginary part)	13.230200
Conductivity (S/m)	1.381821
Variation (%)	2.630000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-52.00

SAR Peak: 0.44 W/kg

SAR 10g (W/Kg)	0.175128
SAR 1g (W/Kg)	0.289537



MEASUREMENT 14


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.363899
Relative permittivity (imaginary part)	14.557700
Conductivity (S/m)	1.520471
Variation (%)	-0.990000

SURFACE SAR





VOLUME SAR



Maximum location: X=18.00, Y=5.00

SAR Peak: 0.79 W/kg

SAR 10g (W/Kg)	0.265841
SAR 1g (W/Kg)	0.480328



MEASUREMENT 15


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.125290
Relative permittivity (imaginary part)	13.730592
Conductivity (S/m)	1.321569
Variation (%)	0.680000

SURFACE SAR






VOLUME SAR



Maximum location: X=-52.00, Y=-53.00

SAR Peak: 0.41 W/kg

SAR 10g (W/Kg)	0.178585
SAR 1g (W/Kg)	0.282574



MEASUREMENT 16


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	54.488365
Relative permittivity (imaginary part)	15.138220
Conductivity (S/m)	1.457054
Variation (%)	-0.700000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=20.00

SAR Peak: 0.78 W/kg

SAR 10g (W/Kg)	0.325838
SAR 1g (W/Kg)	0.508704



MEASUREMENT 17


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	40.753551
Relative permittivity (imaginary part)	19.940201
Conductivity (S/m)	0.926665
Variation (%)	0.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=-80.00, Y=-61.00

SAR Peak: 0.18 W/kg

SAR 10g (W/Kg)	0.076556
SAR 1g (W/Kg)	0.121300



MEASUREMENT 18


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	54.563499
Relative permittivity (imaginary part)	21.146999
Conductivity (S/m)	0.982748
Variation (%)	-0.040000

SURFACE SAR





VOLUME SAR



Maximum location: X=-7.00, Y=-14.00

SAR Peak: 0.32 W/kg

SAR 10g (W/Kg)	0.180719
SAR 1g (W/Kg)	0.249795



MEASUREMENT 19


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.492485
Relative permittivity (imaginary part)	13.851160
Conductivity (S/m)	1.950705
Variation (%)	-0.680000

SURFACE SAR





VOLUME SAR



Maximum location: X=-48.00, Y=-48.00

SAR Peak: 0.49 W/kg

SAR 10g (W/Kg)	0.161556
SAR 1g (W/Kg)	0.297997



MEASUREMENT 20


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	53.196945
Relative permittivity (imaginary part)	15.197840
Conductivity (S/m)	2.140362
Variation (%)	-1.120000

SURFACE SAR






VOLUME SAR



Maximum location: X=10.00, Y=-13.00

SAR Peak: 1.44 W/kg

SAR 10g (W/Kg)	0.379325
SAR 1g (W/Kg)	0.793543



MEASUREMENT 21


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	42.117962
Relative permittivity (imaginary part)	22.077780
Conductivity (S/m)	0.867779
Variation (%)	0.280000

SURFACE SAR





VOLUME SAR



Maximum location: X=-15.00, Y=-5.00

SAR Peak: 0.49 W/kg

SAR 10g (W/Kg)	0.278675
SAR 1g (W/Kg)	0.377766



MEASUREMENT 22


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	55.691662
Relative permittivity (imaginary part)	23.510851
Conductivity (S/m)	0.924107
Variation (%)	0.250000

SURFACE SAR



VOLUME SAR



Maximum location: X=3.00, Y=-19.00


SAR Peak: 0.26 W/kg

SAR 10g (W/Kg)	0.163159
SAR 1g (W/Kg)	0.208036

A line graph showing the relationship between SAR (W/kg) and Z (mm) for a 100 W CW antenna. The y-axis represents SAR (W/kg) and ranges from 0.057 to 0.253 with major grid lines every 0.025 units. The x-axis represents Z (mm) and ranges from 0.0 to 40.0 with major grid lines every 5.0 units. A red curve starts at (0.0, 0.253) and decreases monotonically, passing through approximately (10.0, 0.175) and (20.0, 0.100), ending at (32.5, 0.057).

Z (mm)	SAR (W/kg)
0.0	0.253
5.0	0.210
10.0	0.175
15.0	0.145
20.0	0.115
25.0	0.090
30.0	0.075
32.5	0.057

Hot spot position



MEASUREMENT 23


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	42.096710
Relative permittivity (imaginary part)	22.106178
Conductivity (S/m)	0.871966
Variation (%)	0.040000

SURFACE SAR





VOLUME SAR



Maximum location: X=-16.00, Y=-5.00

SAR Peak: 0.49 W/kg

SAR 10g (W/Kg)	0.273024
SAR 1g (W/Kg)	0.372857



MEASUREMENT 24


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	55.713760
Relative permittivity (imaginary part)	23.439501
Conductivity (S/m)	0.924558
Variation (%)	-0.620000

SURFACE SAR




VOLUME SAR




Maximum location: X=-7.00, Y=-40.00

SAR Peak: 0.25 W/kg

SAR 10g (W/Kg)	0.162878
SAR 1g (W/Kg)	0.204262



3D screen shot



Hot spot position

