

# RADIO TEST REPORT

Report ID:

**REP076382**

Project number:

**PRJ0067697**

Type of assessment:

**Final product testing**

Type of radio equipment:

**Spread Spectrum/Digital Device (2400–2483.5 MHz)**

Equipment class:

**DTS**

Product description:

**Neurotechnology-Brain Activity Sensing Device**

Applicant:

**Interaxon Inc.**

Product marketing name (PMN):

**Muse S Athena**

Model/HVIN:

**MS-03**

Variants P/Ns:

**MS-03-OP and MS-03-CB**

FCC identifier:

**FCC ID: 2ABZI-MS03**

ISED certification number:

**IC: 11834A-MS03**

Specifications:

- ◆ FCC 47 CFR Part 15 Subpart C, §15.247
- ◆ RSS-247, Issue 3, August 2023, Section 5

Date of issue: February 27, 2025

**Tarek Elkholy, EMC/RF Specialist**

Tested by

**Ketav Jani, EMC/RF Specialist**

Reviewed by



Signature



Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).  
The tests included in this report are within the scope of this accreditation.  
The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.

ANAB File Number: AT-3195 (Ottawa); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)

## Lab locations

Company name	Nemko Canada Inc.		
Facilities	<i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2  Tel: +1 613 737 9680 Fax: +1 613 737 9691	<i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8  Tel: +1 514 694 2684 Fax: +1 514 694 3528	<i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2  Tel: +1 519 650 4811
Test site identifier	CA2040	CA2041	CA0101
Website	<a href="http://www.nemko.com">www.nemko.com</a>		

## Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

## Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

## Table of Contents

<b>Table of Contents .....</b>	<b>3</b>
<b>Section 1      Report summary .....</b>	<b>4</b>
1.1    Test specifications .....	4
1.2    Test methods .....	4
1.3    Exclusions .....	4
1.4    Statement of compliance .....	4
1.5    Test report revision history .....	4
<b>Section 2      Engineering considerations .....</b>	<b>5</b>
2.1    Modifications incorporated in the EUT for compliance .....	5
2.2    Technical judgment .....	5
2.3    Model variant declaration .....	5
2.4    Deviations from laboratory tests procedures .....	5
<b>Section 3      Test conditions .....</b>	<b>6</b>
3.1    Atmospheric conditions .....	6
3.2    Power supply range .....	6
<b>Section 4      Information provided by the applicant .....</b>	<b>7</b>
4.1    Disclaimer .....	7
4.2    Applicant / Manufacturer .....	7
4.3    EUT information .....	7
4.4    Radio technical information .....	8
4.5    EUT setup details .....	8
<b>Section 5      Summary of test results .....</b>	<b>10</b>
5.1    Testing period .....	10
5.2    Sample information .....	10
5.3    FCC test results .....	11
5.4    ISED test results .....	11
<b>Section 6      Test equipment .....</b>	<b>12</b>
6.1    Test equipment list .....	12
<b>Section 7      Testing data .....</b>	<b>13</b>
7.1    Variation of power source .....	13
7.2    Number of frequencies .....	14
7.3    Antenna requirement .....	16
7.4    AC power line conducted emissions limits .....	17
7.5    Minimum 6 dB bandwidth for DTS systems .....	20
7.6    Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz .....	23
7.7    Spurious (out-of-band) unwanted emissions .....	26
7.8    Power spectral density for digitally modulated devices .....	36
<b>Section 8      Test setup diagrams .....</b>	<b>38</b>
8.1    Radiated emissions set-up for frequencies below 1 GHz .....	38
8.2    Radiated emissions set-up for frequencies above 1 GHz .....	38
8.3    AC mains conducted emissions set-up .....	39
8.4    Antenna port set-up .....	39

## Section 1 Report summary

### 1.1 Test specifications

FCC 47 CFR Part 15, Subpart C, Clause 15.247	Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz
RSS-247, Issue 3, August 2023, Section 5	Digital Transmission Systems (DTSSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

### 1.2 Test methods

558074 D01 15.247 Meas Guidance v05r02 (April 2, 2019)	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules.
RSS-Gen, Issue 5, April 2018	General Requirements for Compliance of Radio Apparatus
ANSI C63.10 v2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

### 1.3 Exclusions

None

### 1.4 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was performed against all relevant requirements of the test standard except as noted in section 1.3 above. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

Determining compliance is based on the results of the compliance measurement, not taking into account measurement uncertainty, in accordance with section 1.3 of ANSI C63.10 v2013.

See “Summary of test results” for full details.

### 1.5 Test report revision history

**Table 1.5-1: Test report revision history**

Revision #	Date of issue	Details of changes made to test report
REP076382	February 19, 2025	Original report issued

## Section 2 Engineering considerations

---

### 2.1 Modifications incorporated in the EUT for compliance

---

There were no modifications performed to the EUT during this assessment.

### 2.2 Technical judgment

---

None

### 2.3 Model variant declaration

---

As declared by the applicant, the EUT model MS-03 comes in two part numbers:

MS-03-OP and MS-03-CB

Both variations have the same PCB and FPC and hardware. The differences are in the fabric and paint color:

- MS-03-OP: Opal or light grey color
- MS-03-CB: Carbon or dark grey color

### 2.4 Deviations from laboratory tests procedures

---

No deviations were made from laboratory procedures.

## Section 3 Test conditions

---

### 3.1 Atmospheric conditions

---

Temperature	15 °C – 35 °C
Relative humidity	20 % – 75 %
Air pressure	86 kPa (860 mbar) – 106 kPa (1060 mbar)

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

### 3.2 Power supply range

---

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages  $\pm 5\%$ , for which the equipment was designed.

## Section 4 Information provided by the applicant

---

### 4.1 Disclaimer

---

This section contains information provided by the applicant and has been utilized to support the test plan. Inaccurate information provided by the applicant can affect the validity of the results contained within this test report. Nemko accepts no responsibility for the information contained within this section and the impact it may have on the test plan and resulting measurements.

### 4.2 Applicant / Manufacturer

---

Applicant name	Interaxon Inc.
Applicant address	555 Richmond St W suite 900, Toronto, ON M5V 3B1, Canada
Manufacturer name	Same as applicant
Manufacturer address	Same as applicant

### 4.3 EUT information

---

Product description	Neurotechnology-Brain Activity Sensing Device
Model / HVIN	MS-03
Brand	Muse S Athena
Part numbers	MS-03-OP, MS-03-CB
Serial number	Radiated sample: 7001-CKFM-F150 Conducted sample: 7000-PFX4-72BE
Power supply requirements	Internal battery: 3.7 V <sub>DC</sub>
Product description and theory of operation	The brain sensing headband is worn on the head, and measures brain activity through EEG using conductive fabric electrodes. The headband measures bloodflow in PPG and FNIR using an Optics system: 1 red and 1 dual IR LED in the center and 4 photodiodes symmetrically placed. The headband connects to the pod through pogo pins, and the signals are fed through an analog front-end featuring buffering, filtering and amplification then digitized and processed on a microcontroller to stream over BLE to a device (Smartphone, tablet or computer). The pod also features accelerometer and gyroscope sensors which are streamed over BLE.
Hardware revision	D

## 4.4 Radio technical information

Category of Wideband Data Transmission equipment	<input type="checkbox"/> Frequency Hopping Spread Spectrum (FHSS) equipment <input checked="" type="checkbox"/> Other types of Wideband Data Transmission equipment (e.g. DSSS, OFDM, etc.).
Frequency band	2400–2483.5 MHz
Frequency Min	2402 MHz
Frequency Max	2480 MHz
RF power Max, Conducted	4.1 mW and (6.1 dBm)
Measured BW, 99% OBW	1.03 MHz
Type of modulation	BLE (GFSK)
Emission classification	1M03F1D
Transmitter spurious, dBµV/m @ 3 m	At 2483.5 MHz, Average: 50.12 dBµV/m
Antenna information	Type: Ceramic chip SMD antenna Manufacturer: Johanson Model: 2450AT18B100E Gain: 0.5 dBi

## 4.5 EUT setup details

### 4.5.1 Radio exercise details

Operating conditions	<p>The EUT was loaded with FW v3.0.19, using USB-C cable and a serial connection between the EUT and a laptop loaded with (BlueNRG GUI v4.7.1) application the EUT was forced into BLE signal transmission at power level of 5 dBm at any of the available frequency channels.</p> <p>As per the EUT typical operation it is not operational while being charged, however for the testing purpose only the test sample was loaded with a firmware that enables transmission while connected to the charger to ensure maximum power transmission during the test.</p>
Transmitter state	Transmitter set into BLE modulated signal transmission mode.

## 4.5.2 EUT setup configuration

Table 4.5-1: EUT interface ports

Description	Qty.
USB-C charging/control port	1

Table 4.5-2: Support equipment

Description	Brand name	Serial number, Part number, Model, Revision level
Laptop	Dell	MN: Latitude E6420, DPN: VVF52 A01, SN: 28MCCS1
AC/DC adapter	BackBerry	PN: HDW-62391-001, MN: BB-C 0014ADU00

Table 4.5-3: Inter-connection cables

Cable description	From	To	Length (m)
USB-C charging cable	AC/DC adapter	EUT	> 3



Figure 4.5-1: Radiated testing block diagram




Figure 4.5-2: Antenna port testing block diagram

## Section 5 Summary of test results

---

### 5.1 Testing period

---

Test start date	January 9, 2025	Test end date	February 2, 2025
-----------------	-----------------	---------------	------------------

### 5.2 Sample information

---

Receipt date	December 23, 2024	Nemko sample ID number(s)	PRJ00676970007, PRJ00676970008
--------------	-------------------	---------------------------	--------------------------------

### 5.3 FCC test results

**Table 5.3-1: FCC requirements results**

Part	Test description	Verdict
<b>Generic requirements</b>		
§15.207(a)	Conducted limits	Pass
§15.31(e)	Variation of power source	Pass
§15.31(m)	Number of tested frequencies	Pass
§15.203	Antenna requirement	Pass
§15.247(c)(1)	Fixed point-to-point operation with directional antenna gains greater than 6 dBi	Not applicable
§15.247(c)(2)	Transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams	Not applicable
§15.247(d)	Spurious emissions	Pass
§15.247(f)	Time of occupancy for hybrid systems	Not applicable
<b>DTS specific requirements</b>		
§15.247(a)(2)	Minimum 6 dB bandwidth	Pass
§15.247(b)(3)	Maximum peak output power	Pass
§15.247(e)	Power spectral density	Pass

Notes: EUT is a battery-operated device, the testing was performed using fully charged batteries.

### 5.4 ISSED test results

**Table 5.4-1: ISSED requirements results**

Part	Test description	Verdict
<b>Generic requirements</b>		
RSS-Gen, 7.3	Receiver radiated emission limits	Not applicable
RSS-Gen, 7.4	Receiver conducted emission limits	Not applicable
RSS-Gen, 6.9	Operating bands and selection of test frequencies	Pass
RSS-Gen, 8.8	AC powerline conducted emissions limits	Pass
RSS-247, 5.5	Unwanted emissions	Pass
<b>RSS-247, 5.3 Hybrid Systems</b>		
RSS-247, 5.3 (a)	Digital modulation turned off	Not applicable
RSS-247, 5.3 (b)	Frequency hopping turned off	Not applicable
<b>DTS specific requirements</b>		
RSS-247, 5.2 (a)	Minimum 6 dB bandwidth	Pass
RSS-247, 5.2 (b)	Maximum power spectral density	Pass
RSS-247, 5.4 (d)	Transmitter output power and e.i.r.p. requirements for systems employing digital modulation techniques	Pass
RSS-247, 5.4 (e)	Transmitter e.i.r.p. requirements for point-to-point systems in 2400–2483.5 MHz and 5725–5850 MHz band	Not applicable
RSS-247, 5.4 (f)	Transmitter requirements for operation in the 2400–2483.5 MHz band with multiple directional beams	Not applicable

Notes: <sup>1</sup>According to sections 5.2 and 5.3 of RSS-Gen, Issue 5 the EUT does not have a stand-alone receiver neither scanner receiver, therefore exempt from receiver requirements.

EUT is a battery-operated device, the testing was performed using fully charged batteries.

## Section 6 Test equipment

### 6.1 Test equipment list

**Table 6.1-1: Equipment list**

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
3 m EMI test chamber	TDK	SAC-3	FA003012	1 year	April 22, 2025
Flush mount turntable	SUNAR	FM2022	FA003006	—	NCR
Controller	SUNAR	SC110V	FA002976	—	NCR
Antenna mast	SUNAR	TLT2	FA003007	—	NCR
Receiver/spectrum analyzer	Rohde & Schwarz	ESR26	FA002969	1 year	May 17, 2025
Bilog antenna (30–2000 MHz)	SUNAR	JB1	FA003009	1 year	April 24, 2025
Horn antenna (1–18 GHz)	ETS Lindgren	3117	FA002911	1 year	May 16, 2025
Preamp (1–18 GHz)	ETS Lindgren	124334	FA002956	1 year	April 2, 2025
Horn antenna (18–40 GHz)	EMCO	3116B	FA002948	1 year	April 4, 2025
Preamp 18-40 GHz	None	PA1840	FA003323	1 year	April 2, 2025
Notch filter (2.4-2.4835 GHz)	Microwave circuits	N0324413	FA003027	—	NCR
50 Ω coax cable	Huber + Suhner	None	FA003047	1 year	July 29, 2025
50 Ω coax cable	Huber + Suhner	None	FA003402	1 year	July 29, 2025
50 Ω SMA coax cable	Huber + Suhner	None	FA003056	1 year	March 1, 2025
Spectrum analyzer	Rohde & Schwarz	FSW43	FA002971	1 year	November 30, 2025
Signal generator	Rohde & Schwarz	SMB100A	FA002968	1 year	April 27, 2025
50 Ω SMA 10 dB attenuator	Weinschel	PN: WA7	FA003494	1 year	Mar 1, 2025
Two-line v-network	Rohde & Schwarz	ENV216	FA002965	1 year	November 30, 2025
50 Ω coax cable	Rohde & Schwarz	None	FA003074	1 year	July 29, 2025
AC Power source	Chroma	61605	FA003034	—	NCR

Note: NCR - no calibration required

All equipment related to the contribution of measurement has been included in this list. Such items include, but are not limited to, cables, attenuators, directional couplers, and pre-amps.

**Table 6.1-2: Automation software details**

Test description	Manufacturer of Software	Details
EMC/Radio test software	Rohde & Schwarz	EMC32, Software for EMC Measurements, Version 10.60.00

**Table 6.1-3: Measurement uncertainty calculations based on equipment list**

Measurement	Measurement uncertainty, ±dB
AC power line conducted emissions	3.33
Radiated spurious emissions (30 MHz to 1 GHz)	4.27
Radiated spurious emissions (1 GHz to 6 GHz)	4.74
Radiated spurious emissions (6 GHz to 18 GHz)	5.04
Radiated spurious emissions (18 GHz to 40 GHz)	4.78
RF Output power measurement using Spectrum Analyzer <sup>1</sup>	0.71
Conducted spurious emissions	1.15
Other antenna port measurements	0.81
Notes: UKAS Lab 34, TIA-603 and ETSI TR 100 028-1&2 have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products. Measurement uncertainty calculations assume a coverage factor of K = 2 with 95% certainty.	

## Section 7    Testing data

### 7.1    Variation of power source

#### 7.1.1    References, definitions and limits

##### **FCC §15.31 (e):**

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

#### 7.1.2    Test summary

Verdict	Pass		
Test date	January 9, 2025	Temperature	23 °C
Tested by	Tarek Elkholy	Air pressure	980 mbar
Test location	Cambridge	Relative humidity	35 %

#### 7.1.3    Observations, settings and special notes

The testing was performed as per ANSI C63.10 Section 5.13.

- Where the device is intended to be powered from an external power adapter, the voltage variations shall be applied to the input of the adapter provided with the device at the time of sale. If the device is not marketed or sold with a specific adapter, then a typical power adapter shall be used.
- For devices, where operating at a supply voltage deviating  $\pm 15\%$  from the nominal rated value may cause damages or loss of intended function, test to minimum and maximum allowable voltage per manufacturer's specification and document in the report.
- For devices with wide range of rated supply voltage, test at 15% below the lowest and 15% above the highest declared nominal rated supply voltage.
- For devices obtaining power from an input/output (I/O) port (USB, firewire, etc.), a test jig is necessary to apply voltage variation to the device from a support power supply, while maintaining the functionalities of the device.
- For battery-operated equipment, the equipment tests shall be performed using a variable power supply.

#### 7.1.4    Test data

EUT Power requirements:

	<input type="checkbox"/> AC	<input type="checkbox"/> DC	<input checked="" type="checkbox"/> Battery
If EUT is an AC or a DC powered, was the noticeable output power variation observed?	<input type="checkbox"/> YES	<input type="checkbox"/> NO	<input checked="" type="checkbox"/> N/A
If EUT is battery operated, was the testing performed using fresh batteries?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A
If EUT is rechargeable battery operated, was the testing performed using fully charged batteries?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A

## 7.2 Number of frequencies

### 7.2.1 References, definitions and limits

#### FCC §15.31:

- (m) Measurements on intentional radiators or receivers shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table.

#### RSS-Gen, Clause 6.9:

Except where otherwise specified, measurements shall be performed for each frequency band of operation for which the radio apparatus is to be certified, with the device operating at the frequencies in each band of operation shown in table below. The frequencies selected for measurements shall be reported in the test report.

**Table 7.2-1: Frequency Range of Operation**

Frequency range over which the device operates (in each band)	Number of test frequencies required	Location of measurement frequency inside the operating frequency range
1 MHz or less	1	Center (middle of the band)
1–10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near center and 1 near low end

Notes: “near” means as close as possible to or at the centre / low end / high end of the frequency range over which the device operates.

### 7.2.2 Test summary

Verdict	Pass		
Test date	January 9, 2025	Temperature	23 °C
Tested by	Tarek Elkholy	Air pressure	980 mbar
Test location	Cambridge	Relative humidity	35 %

### 7.2.3 Observations, settings and special notes

#### ANSI C63.10, Clause 5.6.2.1:

The number of channels tested can be reduced by measuring the center channel bandwidth first and then applying the following relaxations as appropriate:

- For each operating mode, if the measured channel bandwidth on the middle channel is at least 150% of the minimum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.
- For multiple-input multiple-output (MIMO) systems, if the measured channel bandwidth on testing the middle channel exceeds the minimum permitted bandwidth by more than 50% on one transmit chain, then it is not necessary to repeat testing on the other chains.
- If the measured channel bandwidth on the middle channel is less than 50% of the maximum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.

#### ANSI C63.10, Clause 5.6.2.2:

For devices with multiple operating modes, measurements on the middle channel can be used to determine the worst-case mode(s). The worst-case modes are as follows:

- Band edge requirements—Measurements on the mode with the widest bandwidth can be used to cover the same channel (center frequency) on modes with narrower bandwidth that have the same or lower output power for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- Spurious emissions—Measure the mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- In-band PSD—Measurements on the mode with the narrowest bandwidth can be used to cover all modes within the same modulation family of an equal or lower output power provided the result is less than 50% of the limit.

7.2.4      Test data

---

**Table 7.2-2:** *Test channels selection*

Start of Frequency range, MHz	End of Frequency range, MHz	Frequency range bandwidth, MHz	Low channel, MHz	Mid channel, MHz	High channel, MHz
2400	2483.5	83.5	2402	2442	2480

## 7.3 Antenna requirement

### 7.3.1 References, definitions and limits

#### FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### FCC §15.247:

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### RSS-Gen, Clause 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report.

### 7.3.2 Test summary

Verdict	Pass		
Test date	January 9, 2025	Temperature	23 °C
Tested by	Tarek Elkholy	Air pressure	980 mbar
Test location	Cambridge	Relative humidity	35 %

### 7.3.3 Observations, settings and special notes

None

### 7.3.4 Test data

- Must the EUT be professionally installed?      ☐ YES      ☒ NO  
 Does the EUT have detachable antenna(s)?      ☐ YES      ☒ NO  
     If detachable, is the antenna connector(s) non-standard?      ☐ YES      ☐ NO      ☒ N/A

**Table 7.3-1: Antenna information**

Antenna type	Manufacturer	Model number	Maximum gain	Connector type
Ceramic chip	Johanson	2450AT18B100E	0.5 dBi	SMD antenna

## 7.4 AC power line conducted emissions limits

### 7.4.1 References, definitions and limits

#### FCC §15.207:

- (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50  $\Omega$  line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

#### ANSI C63.10, Clause 6.2:

If the EUT normally receives power from another device that in turn connects to the public utility ac power lines, measurements shall be made on that device with the EUT in operation to demonstrate that the device continues to comply with the appropriate limits while providing the EUT with power. If the EUT is operated only from internal or dedicated batteries, with no provisions for connection to the public utility ac power lines (600 VAC or less) to operate the EUT (such as an adapter), then ac power-line conducted measurements are not required.

For direct current (dc) powered devices where the ac power adapter is not supplied with the device, an “off-the-shelf” unmodified ac power adapter shall be used. If the device is supposed to be installed in a host (e.g., the device is a module or PC card), then it is tested in a typical compliant host.

#### RSS-Gen, Clause 8.8:

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz, shall not exceed the limits in table below.

Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in table below. The more stringent limit applies at the frequency range boundaries.

**Table 7.4-1: Conducted emissions limit**

Frequency of emission, MHz	Conducted emissions limit, dB $\mu$ V	
	Quasi-peak	Average**
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

Notes:      \* - The level decreases linearly with the logarithm of the frequency.  
              \*\* - A linear average detector is required.

#### 7.4.2 Test summary

Verdict	Pass		
Test date	January 31, 2025	Temperature	24 °C
Tested by	Tarek Elkholy	Air pressure	971 mbar
Test location	Cambridge	Relative humidity	42 %


#### 7.4.3 Observations, settings and special notes

Port under test – Coupling device	AC/DC adapter AC power input – Artificial Mains Network (AMN)		
EUT power input during test	120 V <sub>AC</sub> , 60 Hz		
EUT setup configuration	Table top		
Measurement details	A preview measurement was generated with the receiver in continuous scan mode. Emissions detected within 10 dB or above the limit were re-measured with the appropriate detector against the correlating limit and recorded as the final measurement.		
Additional notes:	<ul style="list-style-type: none"> <li>– The EUT was set up as tabletop configuration per ANSI C63.10-2013 measurement procedure.</li> <li>– The spectral scan has been corrected with transducer factors (i.e. cable loss, LISN factors, and attenuators) for determination of compliance. Correction factor (dB) = LISN factor IL (dB) + cable loss (dB) + attenuator (dB)</li> <li>– Emissions that were continuously present for a minimum of 1 second and occurred more than once for every 15 seconds observation period were considered valid emissions. The maximum value of valid emissions has been recorded.</li> <li>– The test was performed during the charging mode.</li> </ul>		


##### Receiver settings:

Resolution bandwidth	9 kHz
Video bandwidth	30 kHz
Detector mode	Peak and Average (Preview), Quasi-peak and CAverage (Final)
Trace mode	Max Hold
Measurement time	100 ms (Preview), 160 ms (Final)

#### 7.4.4 Test data



**Plot 7.4-1:** *Conducted emissions on phase line*



**Plot 7.4-2:** *Conducted emissions on neutral line*

## 7.5 Minimum 6 dB bandwidth for DTS systems

### 7.5.1 References, definitions and limits

#### FCC §15.247:

- (a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:
- (2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### RSS-247, Clause 5.2:

DTSs include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902-928 MHz and 2400-2483.5 MHz:

- a. The minimum 6 dB bandwidth shall be 500 kHz.

#### RSS-Gen, Clause 6.7:

6 dB bandwidth is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 6 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

### 7.5.2 Test summary

Verdict	Pass		
Test date	February 2, 2025	Temperature	23 °C
Tested by	Tarek Elkholy	Air pressure	988 mbar
Test location	Cambridge	Relative humidity	31 %

### 7.5.3 Observations, settings and special notes

The test was performed as per KDB 558074, section 8.2 with reference to ANSI C63.10 subclause 11.8.  
Spectrum analyser settings:

Resolution bandwidth	6 dB BW: 100 kHz; 99% OBW: 1–5% of OBW
Video bandwidth	≥3 × RBW
Frequency span	4 MHz
Detector mode	Peak
Trace mode	Max Hold

## 7.5.4 Test data

**Table 7.5-1: 6 dB bandwidth results**


Frequency, MHz	6 dB bandwidth, MHz	Minimum limit, MHz	Margin, MHz
2402	0.758	0.500	0.258
2442	0.757	0.500	0.257
2480	0.740	0.500	0.240



**Figure 7.5-1: 6 dB bandwidth on low ch.**



**Figure 7.5-2: 6 dB bandwidth on mid ch.**




**Figure 7.5-3: 6 dB bandwidth on high ch.**

Test data, continued

**Table 7.5-2: 99% occupied bandwidth results**

Frequency, MHz	99% occupied bandwidth, MHz
2402	1.02
2442	1.03
2480	1.02


Notes: There is no 99% occupied bandwidth limit in the standard's requirements, the measurement results provided for information purposes only.



**Figure 7.5-4: 99% occupied bandwidth on low ch.**



**Figure 7.5-5: 99% occupied bandwidth on mid ch.**



**Figure 7.5-6: 99% occupied bandwidth on high ch.**

## 7.6 Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz

---

### 7.6.1 References, definitions and limits

---

#### **FCC §15.247:**

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (3) For systems using digital modulation in the 2400–2483.5 MHz band: 1 W (30 dBm). As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (c) Operation with directional antenna gains greater than 6 dBi.
  - (1) Fixed point-to-point operation:
    - (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
    - (iii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.
  - (2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
    - (i) Different information must be transmitted to each receiver.
    - (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
      - (A) The directional gain shall be calculated as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
      - (B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.
  - (iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.
  - (iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

## References, definitions and limits, continued

### RSS-247, Clause 5.4:

Devices shall comply with the following requirements, where applicable:

- d. For DTSs employing digital modulation techniques operating in the 2400–2483.5 MHz band,, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

- e. Fixed point-to-point systems in the 2400–2483.5 MHz band are permitted to have an e.i.r.p. higher than 4 W provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers. Point-to-multipoint systems, omnidirectional applications and multiple co-located transmitters transmitting the same information are prohibited from exceeding an e.i.r.p. of 4 W.
- f. Transmitters operating in the band 2400–2483.5 MHz, may employ antenna systems that emit multiple directional beams simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers, provided that the emissions comply with the following:
  - i. Different information must be transmitted to each receiver.
  - ii. If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit specified in sections 5.4(b) and 5.4(d). However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
  - iii. If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the applicable power limit specified in sections 5.4(b) and 5.4(d). If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the applicable limit specified in sections 5.4(b) and 5.4(d). In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the applicable limit specified in sections 5.4(b) and 5.4(d) by more than 8 dB.
  - iv. Transmitters that transmit a single directional beam shall operate under the provisions of sections 5.4(b), 5.4(d) and 5.4(e).

### 7.6.2 Test summary

Verdict	Pass		
Test date	February 2, 2025	Temperature	23 °C
Tested by	Tarek Elkholy	Air pressure	988 mbar
Test location	Cambridge	Relative humidity	31 %

### 7.6.3 Observations, settings and special notes

The test was performed as per KDB 558074, section 8.3 with reference to ANSI C63.10 subclause 11.9.1 (peak power) using method RBW≥DTS bandwidth (Maximum peak conducted output power)


Resolution bandwidth	3 MHz
Video bandwidth	≥3 × RBW
Frequency span	10 MHz
Detector mode	Peak
Trace mode	Max Hold

## 7.6.4 Test data


**Table 7.6-1: Output power and EIRP results (antenna port measurement)**

Frequency, MHz	Conducted output power, dBm	Output power limit, dBm	Output power margin, dB	Antenna gain, dBi	EIRP, dBm	EIRP limit, dBm	EIRP margin, dB
2402	6.1	30.0	23.9	0.5	6.6	36.0	29.4
2442	6.0	30.0	24.0	0.5	6.5	36.0	29.5
2480	6.0	30.0	24.0	0.5	6.5	36.0	29.5


Note: EIRP [dBm] = Conducted output power [dBm] + Antenna gain [dBi]



**Figure 7.6-1: Output power on low channel**



**Figure 7.6-2: Output power on mid channel**



**Figure 7.6-3: Output power on high channel**

## 7.7 Spurious (out-of-band) unwanted emissions

### 7.7.1 References, definitions and limits

#### FCC §15.247:

- (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### RSS-247, Clause 5.5:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

#### RSS-Gen:

- 8.9 Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table below.
- 8.10 Restricted frequency bands are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. The following conditions related to the restricted frequency bands apply:
- The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands.
  - Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table below.
  - Unwanted emissions that do not fall within the restricted frequency bands shall comply either with the limits specified in the applicable RSS or with those specified in table below.

**Table 7.7-1: FCC §15.209 and RSS-Gen – Radiated emission limits**

Frequency, MHz	Field strength of emissions		Measurement distance, m
	µV/m	dBµV/m	
0.009–0.490	2400/F	$67.6 - 20 \times \log_{10}(F)$	300
0.490–1.705	24000/F	$87.6 - 20 \times \log_{10}(F)$	30
1.705–30.0	30	29.5	30
30–88	100	40.0	3
88–216	150	43.5	3
216–960	200	46.0	3
above 960	500	54.0	3

Notes: In the emission table above, the tighter limit applies at the band edges.  
For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

## References, definitions and limits, continued

**Table 7.7-2: ISSED restricted frequency bands**

MHz	MHz	MHz	GHz
0.090–0.110	12.57675–12.57725	399.9–410	7.25–7.75
0.495–0.505	13.36–13.41	608–614	8.025–8.5
2.1735–2.1905	16.42–16.423	960–1427	9.0–9.2
3.020–3.026	16.69475–16.69525	1435–1626.5	9.3–9.5
4.125–4.128	16.80425–16.80475	1645.5–1646.5	10.6–12.7
4.17725–4.17775	25.5–25.67	1660–1710	13.25–13.4
4.20725–4.20775	37.5–38.25	1718.8–1722.2	14.47–14.5
5.677–5.683	73–74.6	2200–2300	15.35–16.2
6.215–6.218	74.8–75.2	2310–2390	17.7–21.4
6.26775–6.26825	108–138	2483.5–2500	22.01–23.12
6.31175–6.31225	149.9–150.05	2655–2900	23.6–24.0
8.291–8.294	156.52475–156.52525	3260–3267	31.2–31.8
8.362–8.366	156.7–156.9	3332–3339	36.43–36.5
8.37625–8.38675	162.0125–167.17	3345.8–3358	
8.41425–8.41475	167.72–173.2	3500–4400	Above 38.6
12.29–12.293	240–285	4500–5150	
12.51975–12.52025	322–335.4	5350–5460	

Note: Certain frequency bands listed in Table 7.7-2 and above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

**Table 7.7-3: FCC restricted frequency bands**

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	Above 38.6
13.36–13.41			

## 7.7.2 Test summary

Verdict	Pass		
Test date	January 31, 2025	Temperature	24 °C
Tested by	Tarek Elkholy	Air pressure	971 mbar
Test location	Cambridge	Relative humidity	42 %

### 7.7.3 Observations, settings and special notes

- As part of the current assessment, the test range of 9 kHz to 10<sup>th</sup> harmonic has been fully considered and compared to the actual frequencies utilized within the EUT. Since the EUT contains a transmitter in the GHz range, the EUT has been deemed compliant without formal testing in the 9 kHz to 30 MHz test range, therefore formal test results (tabular data and/or plots) are not provided within this test report.
- EUT was set to transmit with the typical duty cycle.
- Radiated measurements were performed at a distance of 3 m. except for 18-26 GHz it was scanned at distance of 1 m to maintain low noise floor.
- DTS emissions in non-restricted frequency bands test was performed as per KDB 558074, section 8.5 with reference to ANSI C63.10 subclause 11.11.
- Since fundamental power was tested using the maximum peak conducted output power procedure to demonstrate compliance, the spurious emissions limit is –20 dBc/100 kHz.
- DTS emissions in restricted frequency bands test was performed as per KDB 558074, section 8.6 with reference to ANSI C63.10 subclause 11.12.
- DTS band-edge emission measurements test was performed as per KDB 558074, section 8.7 with reference to ANSI C63.10 subclause 11.13.

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Detector mode:	Peak/RMS
Trace mode:	Max Hold/Average

Spectrum analyser settings for conducted spurious emissions measurements:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold


### 7.7.4 Test data

**Table 7.7-4: Radiated field strength measurement results**


Channel	Frequency, MHz	Peak Field strength, dBμV/m		Margin, dB	Average Field strength, dBμV/m		Margin, dB
		Measured	Limit		Measured	Limit	
Low	2390.0	59.14	74.00	14.86	49.43	54.00	4.57
Mid	7326.4	53.35	74.00	20.65	37.80	54.00	16.20
High	2483.5	60.13	74.00	13.87	50.12	54.00	3.88

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

## Test data, continued




**Figure 7.7-1:** Radiated spurious emissions 30-1000 MHz low channel




**Figure 7.7-2:** Radiated spurious emissions 30-1000 MHz mid channel

Test data, continued




**Figure 7.7-3:** Radiated spurious emissions 30-1000 MHz high channel




**Figure 7.7-4:** Radiated spurious emissions 1-18 GHz low channel

Test data, continued




**Figure 7.7-5:** Radiated spurious emissions 1-18 GHz mid channel




**Figure 7.7-6:** Radiated spurious emissions 1-18 GHz high channel

Test data, continued




**Figure 7.7-7:** Radiated spurious emissions 18-26 GHz low channel




**Figure 7.7-8:** Radiated spurious emissions 18-26 GHz mid channel

Test data, continued




**Figure 7.7-9:** Radiated spurious emissions 18-26 GHz high channel



Date: 31 JAN 2025 11:56:04


**Figure 7.7-10:** Radiated band edge spurious emissions at 2390 MHz Peak – Low ch.



Date: 31 JAN 2025 11:58:06


**Figure 7.7-11:** Radiated band edge spurious emissions at 2390 MHz Average – Low ch.

Test data, continued



Date: 31 JAN 2025 12:04:41

**Figure 7.7-12:** Radiated band edge spurious emissions at 2483.5 MHz Peak – High ch.




Date: 31 JAN 2025 12:03:44

**Figure 7.7-13:** Radiated band edge spurious emissions at 2483.5 MHz Average – High ch.



10:35:20 02.02.2025


**Figure 7.7-14:** Conducted non-restricted band edge spurious emissions at 2400 MHz, Low ch.




10:49:47 02.02.2025

**Figure 7.7-15:** Conducted non-restricted band edge spurious emissions at 2483.5 MHz, High ch.


## Test data, continued



**Figure 7.7-16:** Conducted non-restricted spurious emissions, Low ch.



**Figure 7.7-17:** Conducted non-restricted spurious emissions, Mid ch.



**Figure 7.7-18:** Conducted non-restricted spurious emissions, High ch.

## 7.8 Power spectral density for digitally modulated devices

### 7.8.1 References, definitions and limits

#### FCC §15.247:

- (e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
- (f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned-off, shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4. The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### RSS-247, Clause 5.2:

DTSS include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902-928 MHz and 2400-2483.5 MHz:

- b. The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

#### RSS-247, Clause 5.3:

Hybrid systems employ a combination of both frequency hopping and digital transmission techniques and shall comply with the following:

- b. With the frequency hopping turned off, the digital transmission operation shall comply with the power spectral density requirements for digital modulation systems set out in of section 5.2(b) or section 6.2.4 for hybrid devices operating in the band 5725–5850 MHz.

### 7.8.2 Test summary

Verdict	Pass		
Test date	February 2, 2025	Temperature	23 °C
Tested by	Tarek Elkholy	Air pressure	988 mbar
Test location	Cambridge	Relative humidity	31 %

### 7.8.3 Observations, settings and special notes

Power spectral density test was performed as per KDB 558074, section 8.4 with reference to ANSI C63.10 subclause 11.10.

The test was performed using method PKPSD (peak PSD).


Spectrum analyser settings:

Resolution bandwidth:	3 kHz
Video bandwidth:	$\geq 3 \times \text{RBW}$
Frequency span:	3 MHz
Detector mode:	Peak
Trace mode:	Max Hold


## 7.8.4 Test data

**Table 7.8-1: PSD results (antenna port measurement)**


Frequency, MHz	PSD, dBm/3 kHz	PSD limit, dBm/3 kHz	Margin, dB
2402	-8.4	8.0	16.4
2442	-8.5	8.0	16.5
2480	-8.5	8.0	16.5



**Figure 7.8-1: PSD on low channel**




**Figure 7.8-2: PSD on mid channel**




**Figure 7.8-3: PSD on high channel**

## Section 8 Test setup diagrams


### 8.1 Radiated emissions set-up for frequencies below 1 GHz




### 8.2 Radiated emissions set-up for frequencies above 1 GHz



### 8.3 AC mains conducted emissions set-up



### 8.4 Antenna port set-up



End of the test report