

FCC Test Report

Report No.: AGC01110241003FR01

FCC ID	:	2AOKB-A3005
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Wireless Headphone
BRAND NAME	:	soundcore
MODEL NAME	:	A3005
APPLICANT	:	Anker Innovations Limited
DATE OF ISSUE	:	Oct. 26, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Oct. 26, 2024	Valid	Initial Release



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Receiver Input Bandwidth	7
2.6 Equally Average Use of Frequencies and Behaviour	7
2.7 Pseudorandom Frequency Hopping Sequence	
2.8 Special Accessories	9
2.9 Equipment Modifications	9
2.10 Antenna Requirement	9
3. Test Environment	
3.1 Address of The Test Laboratory	
3.2 Test Facility	
3.3 Environmental Conditions	11
3.4 Measurement Uncertainty	
3.5 List of Equipment Used	
4.System Test Configuration	14
4.1 EUT Configuration	14
4.2 EUT Exercise	
4.3 Configuration of Tested System	14
4.4 Equipment Used in Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	
6. RF Output Power Measurement	
6.1 Provisions Applicable	
6.2 Measurement Procedure	
6.3 Measurement Setup (Block Diagram of Configuration)	
6.4 Measurement Result	
7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Results	
8. Conducted Band Edge and Out-of-Band Emissions	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Results	



9. Radiated Spurious Emission	51
9.1 Measurement Limit	51
9.2 Measurement Procedure	51
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Result	
10. Number of Hopping Frequency Measurement	
10.1 Provisions Applicable	
10.2 Measurement Procedure	67
10.3 Measurement Setup (Block Diagram of Configuration)	67
10.4 Measurement Result	67
11. Time of Occupancy (Dwell Time) Measurement	
11.1 Provisions Applicable	
11.2 Measurement Procedure	
11.3 Measurement Setup (Block Diagram of Configuration)	
11.4 Measurement Result	
12. Frequency Separation Measurement	73
12.1 Provisions Applicable	73
12.2 Measurement Procedure	73
12.3 Measurement Setup (Block Diagram of Configuration)	73
12.4 Measurement Result	73
13. AC Power Line Conducted Emission Test	
13.1 Measurement Limit	75
13.2 Measurement Setup (Block Diagram of Configuration)	75
13.3 Preliminary Procedure of Line Conducted Emission Test	
13.4 Final Procedure of Line Conducted Emission Test	
13.5 Measurement Results	
Appendix I: Photographs of Test Setup	77
Appendix II: Photographs of Test EUT	



1. General Information

Applicant	Anker Innovations Limited
Address	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Manufacturer	Anker Innovations Limited
Address	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Factory	N/A
Address	N/A
Product Designation	Wireless Headphone
Brand Name	soundcore
Test Model	A3005
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Oct. 09, 2024
Date of Test	Oct. 09, 2024 to Oct. 26, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BR_EDR-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Bibo zhang Prepared By Bibo Zhang Oct. 26, 2024 (Project Engineer) Calvin Lin **Reviewed By** Calvin Liu Oct. 26, 2024 (Reviewer) Max Zhang Approved By Max Zhang Oct. 26, 2024 (Authorized Officer)



2. Product Information

2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.3
Modulation Type	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK
Number of channels	79 Channels
Channel Separation	1 MHz
Maximum Transmitter Power	2.700 dBm
Hardware Version	V08, V09
Software Version	V01.10
Antenna Designation	Chip Antenna
Antenna Gain	2.7dBi
Power Supply	DC 3.7V by battery

Note:

The EUT includes two hardware designs, and the difference between them is that the V09 version adds

three test points (GND, NTC, 5V), while other layout and component designs remain unchanged. Only the test data of V08 version is recorded in the report.

2.2 Test Frequency List

Frequency Band	Channel Number	Frequency		
	0	2402 MHz		
	1	2403 MHz		
	:	:		
2400~2483.5MHz	39	2441MHz		
	:	:		
	77	2479 MHz		
	78	2480 MHz		
Note: f = 2402 + 1k MHz, k =	0,, 78 ; "f "is the operating frequency	(MHz); "k" is the operating channel.		



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2AOKB-A3005**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title	
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations	
2	2 FCC 47 CFR Part 15 Radio Frequency Devices		
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices	
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules	

2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.6 Equally Average Use of Frequencies and Behaviour.

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:


The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.



2.7 Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

44	35	78	03	20	76	02	19		21	64	75
								1	1		
			li						:		
						; ;			i i		
				i		<u></u>		1	i		

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



2.8 Special Accessories

Not available for this EUT intended for grant.

2.9 Equipment Modifications

Not available for this EUT intended for grant.

2.10 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2.7dBi.



3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.7V

3.4 Measurement Uncertainty

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



3.5 List of Equipment Used

• R	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23	
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31	
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31	
\boxtimes	AGC-EM-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20	
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22	
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	

• F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\square	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
\square	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
\square	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
\boxtimes	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
\square	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
\square	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• A	AC Power Line Conducted Emission								
Used Foundation I lest Foundation Manufacturer I Model No. 1 Serial No. 1							Next Cal. Date (YY-MM-DD)		
	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27		
	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08		
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27		



Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information		
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71		
\square	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A		
	AGC-EM-S004	RE Test System	Tonscend	TS⁺ Ver2.1(JS32-RE)	4.0.0.0		
\square	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6		
\square	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0		



4.System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable			
1	Control Box	RISYM	USB-TTL					
	Test Accessories Come From The Manufacturer							

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1				-	



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(1)	RF Output Power	Pass
3	§15.247 (a)(1)	20 dB Bandwidth	Pass
4	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
5	§15.209	Radiated Spurious Emission	Pass
6	§15.247 (a)(1)(iii)	Number of Hopping Frequency	Pass
7	§15.247 (a)(1)(iii)	Time of Occupancy	Pass
8	§15.247 (a)(1)	Frequency Separation	Pass
9	§15.207	AC Power Line Conducted Emission	Not applicable

Note: The BT function cannot transmit when charging.



5. Description of Test Modes

	Summary table of Test Cases				
	Data Rate / Modulation				
Test Item	Bluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK)				
Radiated & Conducted Test Cases	Aode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (Battery powered) Aode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (Battery powered) Aode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (Battery powered) Aode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (Battery powered) Aode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (Battery powered) Aode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (Battery powered) Aode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (Battery powered) Aode 7: Bluetooth Tx CH00_2402 MHz_3Mbps (Battery powered) Aode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered) Aode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered) Aode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered) Mode 10: Bluetooth Tx Hopping-1Mbps (Battery powered) Mode10: Bluetooth Tx Hopping-2Mbps (Battery powered) Mode11: Bluetooth Tx Hopping-3Mbps (Battery powered)				
AC Conducted Emission	N/A				
AC Conducted Emission N/A Note: 1. Only the result of the worst case was recorded in the report, if no other cases. 2. The battery is full-charged during the test. 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode. 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture Software Setting Diagram For Cascient 1.0.22 For Cascient 1.0.22 For Cascient 1.0.22 For the date 04 00 01 FC 00 For the mode 04 For the onder 04 01 01 FC 00 For the mode 04 01 01 FC 00 For the mode 04 For the onder 04 for 101 FC 00 For the for the onder 04 For th					
	清除日志				



6. RF Output Power Measurement

6.1 Provisions Applicable

The maximum out power permissible output power is 1 Watt for all frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

The maximum out power permissible output power is 0.125 watts for all other frequency hopping systems in the 2400-2483.5 MHz band.

6.2 Measurement Procedure

⊠For Peak power test:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW \geq RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

For Average power test:

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required


6.3 Measurement Setup (Block Diagram of Configuration)

For Average power test setup





For peak power test setup



6.4 Measurement Result


Test Data of Conducted Output Power							
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2402	1.736	≤21	Pass			
GFSK	2441	1.670	≤21	Pass			
	2480	0.893	≤21	Pass			
	2402	2.365	≤21	Pass			
π /4-DQPSK	2441	2.301	≤21	Pass			
	2480	1.520	≤21	Pass			
	2402	2.700	≤21	Pass			
8DPSK	2441	2.578	≤21	Pass			
	2480	1.781	≤21	Pass			






Test Graphs of Conducted Output Power





















7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement

7.1 Provisions Applicable


There is no corresponding limit requirement for this test item.

7.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 6.9.2 (20dB BW).

- The 20dB bandwidth spectrum analyzer setting reference is as follows:
- 1. Set RBW \geq 1% to 5% of the 20dB bandwidth
- 2. VBW = Approximately three times RBW
- 3. Span = Approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated
- 9. with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20
- 10. dB relative to the maximum level in the fundamental emission.
- The 99% bandwidth spectrum analyzer setting reference is as follows:
- 1. Span = 1.5 times to 5 times the OBW
- 2. Set RBW = 1% to 5% the OBW
- 3. VBW \geq 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace was allowed to stabilize

7.3 Measurement Setup (Block Diagram of Configuration)






7.4 Measurement Results

Test Data of Occupied Bandwidth and -20dB Bandwidth								
Test Mode	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail			
	2402	0.883	0.959	N/A	Pass			
GFSK	2441	0.884	1.000	N/A	Pass			
	2480	0.887	0.998	N/A	Pass			
	2402	1.185	1.311	N/A	Pass			
π /4-DQPSK	2441	1.188	1.313	N/A	Pass			
	2480	1.187	1.314	N/A	Pass			
	2402	1.190	1.301	N/A	Pass			
8DPSK	2441	1.196	1.302	N/A	Pass			
	2480	1.195	1.300	N/A	Pass			


Test Graphs of Occupied Bandwidth and -20 Bandwidth























8. Conducted Band Edge and Out-of-Band Emissions

8.1 Provisions Applicable


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.10.4 and 7.8.8:

- Reference level measurement
- 1. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- Emission level measurement
- 1. Span = Wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Trace was allowed to stabilize
- 8. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands






































































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands

























9. Radiated Spurious Emission

9.1 Measurement Limit

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

9.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average



absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
	1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

• Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

<u>Average Measurements above 1GHz</u>


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW \geq [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




9.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/




9.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

	Radia	ated Emission	Test Result	esults at 30MHz-1GHz					
EUT Name	Wireless Headpho	ne		Model N	Name	A3	005		
Temperature	22.9 ℃			Relative	e Humidity	57	.4 %		
Pressure	960hPa			Test Voltage			3.7V by battery		
Test Mode	Mode 7			Antenn	a Polarity	Ho	rizontal		
72.0	dBuV/m								
32		www.marthurde.hommind.sh	Marken Malanda			Limit: Margi			
-8	10 40 50 GO 70	80	(MHz)	300	400 500	600 70	1000.000		
				easure-	Linait	<u></u>			
	No.Mk. Freq. MHz	Level dBuV		ment BuV/m	Limit dBuV/m	Over dB	Detector		
	1 39.9942	5.62		19.52		20.48	peak		
	2 129.9226	6.84		22.64		20.40	peak peak		
	3 337.2155	5.88		22.90		23.10	peak		
	4 443.2943			30.12		15.88	peak		
	5 616.3718			31.10		14.90	peak		
	6 * 893.8567			37.60		.8.40	peak		
							·		





				Rad	iated E	Emiss	ion Test	Result	sults at 30MHz-1GHz						
EUT Name	Wi	reles	s He	eadph	one				Mode	el Nam	е		A30	005	
Temperature	ə 22	.9 °C	2						Relative Humidity				57.4 %		
Pressure	96	0hPa	a						Test	Voltag	е		DC	3.7\	/ by bat
Test Mode Mode 7							Ante	nna Po	olarit	y	Ver	tical			
72.	0 dBuV/	m													
													Limit: Margir	- r	
															ſ
					<u> </u>									_	ę
32											4	www.www.whe	Å	, Anna Ma	<i>v</i> ™
				1 X		2	whether the state	3 X		entrik der Alt	un a	Winter	"		
	Mr. Nobarra	alquiam	reneration	Auguraut	ntropped belong	VIL MANNA	hulus thet er of the helpipe	wer more while	wanter						
-8 3	0.000	40	50	60 7	0 90		(MHz	1	3	<u> </u>	400	500 G	00 70	0 1	000.000
						ading		-	easur						
	No.	Mk.	F	Freq.		evel	Facto		ment	Li	mit	Ov	er		
			1	MHz	d	ЭuV	dB	d	BuV/m	dB	uV/m	dE	Э	Dete	ctor
-	1		58.6	6126	7	'.92	17.09	3 2	25.01	40	.00	-14	.99	pe	ak
-	2	1	110.	5687	8	3.43	16.0	5 2	24.48	43	.50	-19.	.02	pe	ak
-	3		181.3	2834	E	3.07	18.40	3 2	24.53	43	.50	-18.	.97	pe:	
	4			5558		3.33	25.6		32.00		.00	-14		pe	
	5			6999		3.50	28.3		34.83	46		-11.		pe	
				7610							.00	-8.9		-	
	D	. 5	940.	1010	ť	3.37	30.6	, s	37.02	40	.00	-0.8	90	pe	aK

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 7 is the worst case and recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



UT N	lame	wireless Headphone			lphone		Model Name)	A3005		
empe	eratu	ure		23.1 ℃			Relative Hu	nidity	59.2%		
Press	ure			960hPa			Test Voltage	•	DC 3.7V by battery		
est N	Mode 7				Antenna Po	larity	Horizontal				
		130				FCC Part 15	C				
		120									
		110 100	Fun	damental Fred	quency						
		90 80									
	[m//li	70									
	_evel[dBµV/m]	60			λ			-A		ä	
	L.	50 40				na wata wata wata wata wata wata wata wa	MIL J. HUN HUT WHITH MAN AND AND AND AND AND AND AND AND AND A	Jamman and a stranger	AND THE MANY COMMENT		
		30 manut	Martinen M	whether a character and the second and the second	hile and a strand of a straight and the ball	and an addition of the stand of	i interneti i i i i i i i i i i i i i i i i i i	a blight	an Midden a		
		20									
		10		2G	36	4G	6G	8G		18G	
		10 0 -10 1G	< Limit		3G	4G Frequency[H		86			
		10 0 -10 1G * A	< Limit V Detector	— AV Limit — Ho				8G		18G	
PK D	Data	10 0 -10 1G * A		— AV Limit — Ho				8G		18G	
	Data	10 -10 16 List Freq.		AV Limit — He	Factor	Frequency[+	Margin	Heigh			
PK D NO.	Data	10 -10 16 — PP * A		- AV Limit - Ho	prizontal PK	Frequency[H	Margin	_	t Angle [°]	18G Polarity	
	21	List Freq. [MHz] 74.8174	V Detector	Level [dBµV/m] 38.39	Factor [dB] -12.99	Frequency(H Limit [dBµV/m 74.00	Margin [dB] 35.61	Heigh [cm] 150		Polarity Horizontal	
NO. 1 2	21 [°] 35	List Freq. [MHz] 74.8174 24.7524	V Detector 182 175	Level [dBµV/m]	Factor [dB]	Frequency[+ Limit [dBµV/m	Margin] [dB]	Heigh [cm]	[°]	Polarity	
NO. 1	21 [°] 35	List Freq. [MHz] 74.8174	V Detector 182 175	Level [dBµV/m] 38.39	Factor [dB] -12.99	Frequency(H Limit [dBµV/m 74.00	Margin [dB] 35.61	Heigh [cm] 150	[°] 351	Polarity Horizontal	
NO. 1 2	21 [°] 35 [°] 63	List Freq. [MHz] 74.8174 24.7524	V Detector 182 175 313	Level [dBµV/m] 38.39 39.60	Factor [dB] -12.99 -10.61	Frequency[F Limit [dBµV/m 74.00 74.00	Margin [dB] 35.61 34.40	Heigh [cm] 150	[°] 351 4	Polarity Horizontal Horizontal	
NO. 1 2 3	21 [°] 35 [°] 63 72 [°]	¹⁰ -10 -10 -10 -10 -10 -10 -10 -10 -10 -10	V Detector 182 175 313 732	Level [dBµV/m] 38.39 39.60 46.91	Factor [dB] -12.99 -10.61 -4.82	Frequency[F Limit [dBµV/m 74.00 74.00 74.00	Margin [dB] 35.61 34.40 27.09	Heigh [cm] 150 150 150	[[°]] 351 4 333	Polarity Horizontal Horizontal Horizontal	

RESULT: Pass



	-								
EUT N	lame	Wireless Hea	dphone	Mo	odel Name	/	\3005		
Tempe	erature	23.1 ℃		Relative Humidity			59.2%		
Press	ure	960hPa Test Voltage DC 3.7V by I			battery				
Test N	lode	Mode 7		Ar	itenna Polar	ity \	/ertical		
	130			FCC Part 15C					
	120								
	110								
	100 90								
	80								
	Гш 70 Пробенаторија 100 100 100 100 100 100 100 100 100 10						*	*	
	40	un and	A. martin a station of the states	mahan water a state of the stat	When the second and a second second	Manage Manager and the second	A STATISTICS OF A STATISTICS		
	30	how have been and the second and the second s	a na sa	a na na ana Abbana a a tao ka			- que - r		
	20								
	0								
	-10 1G	2G	3G	4G	6G	8G		18G	
	PK Lii	nit — AV Limit —	/ertical PK	Frequency[Hz]					
	# AV E								
PK C	Data List		-			1			
NO	Freq.	Level	Factor	Limit	Margin	Height	Angle	Delevite	
NO.	[MHz]	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	Polarity	
1	1207.42074	2 34.01	-18.01	74.00	39.99	150	190	Vertical	
2	2091.50915	1 40.31	-13.19	74.00	33.69	150	229	Vertical	
3	3742.37423	7 38.27	-10.32	74.00	35.73	150	214	Vertical	
4	6382.73827	4 46.80	-4.70	74.00	27.20	150	59	Vertical	
5	10940.89408	49.53	2.47	74.00	24.47	150	166	Vertical	
6	15874.78747	9 50.08	4.62	74.00	23.92	150	1	Vertical	

RESULT: Pass



	Jame	Wireless Head	nhone	Mc	del Name		3005	
Temp	erature	23.1 ℃		Relative Humidity			59.2%	
Press	ure	re 960hPa		Те	st Voltage	C	OC 3.7V by	battery
Test N	st Mode Mode 8			An	tenna Polar	ity ⊦	lorizontal	
	130			FCC Part 15C				
	120							
	100	Fundamental Fr	equency					
	90							
	[III] 70 GB1 60 S0 50				4		5	
	40		AMAN UMME MUMPER	K analuning jammar 1997 (1994)	In the second	Habert and the stand of the stand of the	WHAT IS A REAL PROPERTY OF	
	30 male 1	AND	and the second	a na mana dita ma mata ka	T			
	10							
	0							
	-10L 1G	2G	3G	4G Frequency[Hz]	6G	8G		18G
	PK Limit		izontal PK	(inclusion of the larger				
	ata List							
FNL		Laval	Fastar	L ins it	Manaia	L La la h t	Australia	
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2164.616462	37.54	-13.01	74.00	36.46	150	6	Horizontal
2	3325.832583	38.70	-11.10	74.00	35.30	150	1	Horizontal
3	6319.831983	46.28	-4.82	74.00	27.72	150	251	Horizontal
4	7322.932293	47.90	-3.68	74.00	26.10	150	16	Horizontal
5	10945.9946	49.70	2.48	74.00	24.30	150	280	Horizontal
6	16553.155316	49.82	5.68	74.00	24.18	150	266	Horizontal

RESULT: Pass



EUT Name Wireless Headphone Model Name A3005 Temperature 23.1 °C Relative Humidity 59.2% Pressure 960hPa Test Voltage DC 3.7V by batter Test Mode Mode 8 Antenna Polarity Vertical	ry
Pressure 960hPa Test Voltage DC 3.7V by batter Test Mode Mode 8 Antenna Polarity Vertical	ry
Test Mode Mode 8 Antenna Polarity Vertical 130 FCC Part 15C	ry
130 FCC Part 15C	
130	
120	
90	
80	
20	
-10	
1G 2G 3G 4G 6G 8G 18G Frequency[Hz]	i
PK Limit AV Limit Vertical PK AV Detector	
PK Data List	
NO. Freq. Level Factor Limit Margin Height Angle Po	larity
[MHz] [dBμV/m] [dB] [dBμV/m] [dB] [cm] [°]	lanty
1 1448.844885 33.58 -17.62 74.00 40.42 150 263 Ve	rtical
2 2089.808981 38.16 -13.19 74.00 35.84 150 132 Ve	rtical
3 3274.827483 38.68 -11.24 74.00 35.32 150 0 Ve	rtical
4 6318.131813 45.90 -4.82 74.00 28.10 150 349 Ve	rtical
5 10947.69477 48.91 2.49 74.00 25.09 150 69 Ve	rtical
6 16507.250725 49.54 5.63 74.00 24.46 150 1 Ve	rtical

RESULT: Pass



EUT N	Name	Wireless Head	phone	Мо	del Name	A	A3005		
Temp	erature	23.1 ℃		Re	lative Humi	dity 59	59.2%		
Press	sure	960hPa			st Voltage	D	DC 3.7V by battery		
Test N	Node	Mode 9			tenna Polar	ity He	orizontal		
	130 120 110 90 80 70 60 50 40 30 20 10 0 -10	ndamental Freq		FCC Part 15C		BG BG		183	
	PK Limit AV Detect	AV Limit Ho	rizontal PK	Frequency[Hz]					
PK [Data List								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
1	2103.410341	37.33	-13.16	74.00	36.67	150	358	Horizontal	
2	3526.452645	38.64	-10.60	74.00	35.36	150	12	Horizontal	
3	6319.831983	45.86	-4.82	74.00	28.14	150	127	Horizontal	
4	7440.244024	50.51	-3.71	74.00	23.49	150	30	Horizontal	
5	10971.49715	49.28	2.56	74.00	24.72	150	69	Horizontal	

RESULT: Pass



				_			~~~-		
EUT Na	ame	Wireless Head	phone	ľ	Model Name	A	A3005		
Temper	rature	23.1 ℃		F	Relative Humi	dity 5	59.2%		
Pressu	ire	960hPa			Fest Voltage	D	DC 3.7V by battery		
Test Mo	ode	Mode 9		ŀ	Antenna Polar	rity ∨	Vertical		
	130			FCC Part 15C					
	120 110 90 80 70 70 70 60 198 50								
	50 40 30 20 10 0 10 10 10	26	36	4G Frequency[Hz	6G	8G		186	
	40 30 20 10 0 -10 13 	2G — AV Limit — Ver		46	6G			18G	
	40 30 20 10 	2G — AV Limit — Ver	36	46	eG J Margin		Angle [°]	18G Polarity	
PK Da	40 30 20 10 10 13 	2G — AV Limit — Ver Level	3G tical PK Factor	4G Frequency[Hz	eG J Margin	BG			
PK Da	40 30 20 10 -10 13 	2G — AV Limit — Ver [dBµV/m]	rtical PK Factor [dB]	4G Frequency[Hz Limit [dBµV/m]	eg J Margin [dB]	BG Height [cm]	[°]	Polarity	
PK Da NO.	40 30 20 10 -10 -10 -10 -10 -10 -10 -10	2G 	rtcal PK Factor [dB] -18.06	4G Frequency[Hz Limit [dBµV/m] 74.00	^{6G} Margin [dB] 40.82	BG Height [cm] 150	[°] 36	Polarity Vertical	
PK Da NO.	40 30 20 10 10 13 	2G 	3G rtical PK Factor [dB] -18.06 -12.98	4G Frequency[Hz [dBµV/m] 74.00 74.00	^{6G} Margin [dB] 40.82 35.89	BG Height [cm] 150 150	[°] 36 287	Polarity Vertical Vertical	
PK Da NO. 1 2 3 4	40 20 10 1	2G — AV Limit — Ver [dBµV/m] 33.18 38.11 38.30	3G rical PK Factor [dB] -18.06 -12.98 -10.54	4G Frequency[Hz [dBµV/m] 74.00 74.00 74.00	^{6G} Margin [dB] 40.82 35.89 35.70	BG Height [cm] 150 150 150	[°] 36 287 41	Polarity Vertical Vertical Vertical	

RESULT: Pass

Note:

- 1. The amplitude of other spurious emissions from 18G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.




Band Edge Emission Test Results for Restricted Bands
--

EUT Name	Wireless Headphone	Model Name	A3005
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 7	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Wireless Headphone	Model Name	A3005
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 7	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Wireless Headphone	Model Name	A3005
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 9	Antenna Polarity	Horizontal





Test Graph for Average Measurement




RESULT: Pass




EUT Name	Wireless Headphone	Model Name	A3005
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 9	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



10. Number of Hopping Frequency Measurement

10.1 Provisions Applicable

This frequency hopping system must employ a minimum of 15 hopping channels.


10.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span = The frequency band of operation. Depending on the number of channels the device

- 2. supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- 3. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 4. VBW \geq RBW
- 5. Sweep time = Auto couple
- 6. Detector = Peak
- 7. Trace mode = Max hold
- 8. Allow the trace to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)



10.4 Measurement Result

Test Data of Number of Hopping Frequency							
Test Mode Number of Hopping Frequency Limits Pass or Fail							
8DPSK Hopping79>=15Pass							



		t orupno	er riun			ping i	10940		
📕 Keysight Spectrum Ar									
IXI RL RF	50 Ω AC	CORREC	SENSE	:INT		ALIGN AUTO		Oct 15, 2024	Frequency
Center Freq 2	.441750000		Trig: Free R	lun	Avg Type Avg Hold:	: Log-Pwr 100/100		E 1 2 3 4 5 6	
		PNO: Fast ++ IFGain:Low	#Atten: 40 c		Avginola.	100/100		PNNNN	
		IF Galli.Low							Auto Tune
						Mkr	1 2.410		Auto Func
10 dB/div Ref	30.00 dBm						1.7	57 dBm	
Log									
									Center Freq
20.0									2.441750000 GHz
									2.441730000 6112
10.0									
	1								Start Freq
0.00	1 A.M. A. A. A. M.	A ANDA R			A+0400-+	1011			2.400000000 GHz
~~~ AAAAAAAA	<u> የየ</u> ሰላ ተሳት የሚ	ᡃᠰᡇᢦᡶᠰᢣᡰ᠕ᡰ᠇ᠯᡟ	AAAAA MAAAAAA	ዛሞሚቅጥላ	<b>Լահ</b> ոռոհե	fy fy fy fy fy	<i>ቢ የዋላሞ</i> ዋላ	VVVVI	
-10.0									Stop Freq
									2.483500000 GHz
-20.0									2.483500000 GHZ
-20.0									
									CF Step
-30.0									8.350000 MHz
								<b>,</b>	Auto Man
-40.0									Auto Main
-40.0									
									Freq Offset
-50.0									
									0 Hz
-60.0									
-00.0									
Center 2.44175								3.50 MHz	
#Res BW 200 k	Hz	#VBW	/ 620 kHz			Sweep 1	.998 ms (	1000 pts)	
MSG						STATUS			
Te	st Grank	EDR H	OP AN	T1 N	A 3M	ops N	umber	of Hon	ping
10	Test_Graph_EDR_HOP_ANT1_NA_3Mbps_Number of Hopping								

## Test Graphs of Number of Hopping Frequency

Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.



# 11. Time of Occupancy (Dwell Time) Measurement

#### **11.1 Provisions Applicable**


The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

# **11.2 Measurement Procedure**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span = Zero span, centered on a hopping channel.
- 2. RBW shall be  $\leq$  channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. VBW  $\geq$  RBW
- 4. Sweep time = As necessary to capture the entire dwell time per hopping channel
- 5. Detector = Peak
- 6. Trace mode = Free Run
- 7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.


## 11.3 Measurement Setup (Block Diagram of Configuration)



#### **11.4 Measurement Result**

Test Data of Dwell Time							
Channel	Time of Pulse for 3DH5 (ms)	Number of hops in the period specified in the requirements	Dwell Time (ms)	Limit (ms)	Pass or Fail		
2402	2.892	26.0*4	300.768	400	Pass		
2441	2.892	29.0*4	335.472	400	Pass		
2480	2.892	26.0*4	300.768	400	Pass		





# **Test Graphs of Dwell Time**