FCC DFS TEST REPORT

FCC ID: 2BAWSRDG-XX

Sample : Dride4K

Trade Name : N/A

Main Model : DR4K1-RDG-XX

Additional Model : N/A

Report No.: 23032009ER-65

Prepared for

Dride Technology LTD Eliyahu Eitan 1, Rishon Letzion, Israel

Prepared by

Global United Technology Services Co. Ltd.

No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

TEST RESULT CERTIFICATION

Applicant	Dride Technology LTD		
Address	Eliyahu Eitan 1, Rishon Letzion, Israel		
Manufacturer	Dride Technology LTD		
Address	Eliyahu Eitan 1, Rishon Letzion, Israel		
Product description			
Product	Dride4K		
Trade Name:	N/A		
Model Name	DR4K1-RDG-XX		
Test Methods	FCC Rules and Regulations Part 15 Subpart C Section 15.407 ANSI C63.10: 2013		

This device described above has been tested by Global United Technology Services Co. Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of UNI, this document may be altered or revised by Global United Technology Services Co. Ltd., personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests:	Mar. 20, 2023 ~ May 31, 2023
Date of Issue:	Jul. 13, 2023
Test Result	Pass

Prepared By:	Insmille	Date:	2023-7-13	
	Project Engineer			
Check By:	Potisneronzier	Date:	2023-7-13	

Reviewer

Table of Contents	Pages
1 IEST SUMMARY	4
1.1 TEST PROCEDURES AND RESULTS	4
1.2 TEST FACILITY	5
1.3 MEASUREMENT UNCERTAINTY	6
1.4 ENVIRONMENTAL CONDITIONS	6
2 GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 CARRIER FREQUENCY OF CHANNELS	8
2.3 TEST MODE	9
2.4 DESCRIPTION OF THE TEST MODES	9
2.5 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	10
2.6 MEASUREMENT INSTRUMENTS LIST	11
3 DFS TEST INFORMATION	12
3.1 DFS TEST REQUIREMENT	12
3.2 TEST SETUP	13
3.3 LIMITS	13
3.4 RADAR TEST WAVEFORMS	15
3.5 TEST PROCEDURE	16
3.5 TEST RESULT	16
4 ANTENNA REQUIREMENT	26
5 PHOTO OF TEST	27

1 TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

1.1.1 Item	FCC Rules	Description Of Test	Result
1	FCC Part 15.407	DFS Detection Threshold	N/A
2	FCC Part 15.407	FCC Part 15.407 Channel Availability Check Time	
3	FCC Part 15.407	Channel Move Time	Pass
4	FCC Part 15.407	Channel Closing Transmission Time	Pass
5	FCC Part 15.407	Non- Occupancy Period	N/A
6	FCC Part 15.407	Uniform Spreading	N/A
7	FCC Part 15.407	U-NII Detection Bandwidth	N/A

Note:

"N/A" denotes test is not applicable in this Test Report.

1.2 TEST FACILITY

Test Firm	:	Global United Technology Services Co. Ltd.
Address	:	No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong,
		China 518102

The test facility is recognized, certified, or accredited by the following organizations:

• FCC—Registration No.: 381383

Designation Number: CN5029

Global United Technology Services Co., Ltd. Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

• IC — Registration No.: 9079A

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co. Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

• NVLAP (LAB CODE: 600179-0)

Global United Technology Services Co. Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

1.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)
UNI AN		9kHz ~ 150kHz	2.96
	ANOI	150kHz ~ 30MHz	2.44

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)
UNI ANSI	9kHz ~ 30MHz	2.50	
	ANSI	30MHz ~ 1000MHz	4.80
		1000MHz ~ 18000MHz	4.13

C. RF Conducted Method:

ltem	Measurement Uncertainty		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	$U_{c} = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_{c} = \pm 2 \%$		

1.4 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 °C
Relative Humidity:	30~60 %
Air Pressure:	950~1050 hPa

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product:	Dride4K
Trade Name:	N/A
Main Model:	DR4K1-RDG-XX
Additional Model:	N/A
Model Difference:	N/A
Operation Frequency:	Band 1: 5150 MHz ~ 5250MHz; Band 2: 5250 MHz ~ 5350MHz; Band 3: 5470 MHz ~ 5725MHz; Band 4: 5725 MHz ~ 5850MHz
Modulation Type:	BPSK, QPSK, 16QAM, 64QAM, 128QAM, 256QAM, OFDM
Antenna Type:	PCB Antenna
Antenna Gain:	Band 1: -10.49dBi; Band 2: -11.51dBi; Band 3: -4.35dBi; Band 4: -1.01dBi
Battery:	N/A
Adapter:	N/A
Power Source:	DC 12-24V from car charger

Note:

- 1. The EUT is designed as client devices without radar detection.
- 2. The device do not support TPC.

2.2 CARRIER FREQUENCY OF CHANNELS

Frequency Band	Channel Number	Frequency	Frequency Band	Channel Number	Frequency
	36	5180 MHz		112	5560 MHz
	38	5190 MHz		116	5580 MHz
	40	5200 MHz		118	5590 MHz
5150 MHz~ 5250MHz	42	5210 MHz		120	5600 MHz
	44	5220 MHz		122	5610 MHz
	46	5230 MHz	5470 MHz~	124	5620 MHz
	48	5240 MHz	5725MHz	126	5630 MHz
	52	5260 MHz		128	5640 MHz
	54	5270 MHz		132	5660 MHz
	56	5280 MHz		134	5670 MHz
5250 MHz~	58	5290 MHz		136	5680 MHz
	60	5300 MHz		140	5700 MHz
	62	5310 MHz		149	5745 MHz
	64	5320 MHz		151	5755 MHz
	100	5500 MHz	5725 MHz~ 5850MHz	153	5765 MHz
5470 MHz~ 5725MHz	102	5510 MHz		155	5775 MHz
	104	5520 MHz		157	5785 MHz
	106	5530 MHz		159	5795 MHz
	108	5540 MHz		165	5825MHz
	110	5550 MHz			

Note: For 20MHZ bandwidth system use Channel 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 149, 153, 157, 161, 165; For 40MHZ bandwidth system use Channel 38, 46, 54, 62, 102, 110, 118, 126, 134, 151, 159; For 80MHZ bandwidth system use Channel 42, 58, 106, 122, 155

Mode	Available channel	Tested channel	Modulation	Date
				rate(Mbps)
802.11a/n20/ac20	36, 40, 44, 48, 52, 56, 60, 64,	36, 40, 48, 52, 60,	OFDM	6Mbps/MCS0
	100, 104, 108, 112, 116, 120,	64, 100, 120, 140,		
	124, 128, 132, 136, 140, 149,	149, 157, 165		
	153, 157, 161, 165			
802.11n40/ac40	38, 46, 54, 62, 102, 110, 118,	38, 46, 54, 62, 102,	OFDM	MCS0
	126, 134, 151, 159;	118, 134, 151, 159		
802.11ac80	42, 58, 106, 122, 155	42, 58, 106, 122,	OFDM	MCS0
		155		

2.3 TEST MODE

Note:

- 1. The EUT has been set to operate continuously on tested channel individually, and the EUT is operating at its maximum duty cycle>or equal 98%.
- 2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
- 3. Restart time of the router and EUT network: 90s; Router FCC ID: Q78-ZXHNF670E.

2.4 DESCRIPTION OF THE TEST MODES

During the measurement the environmental conditions were within the listed ranges:

	Normal Voltage	DC 24V
Voltage	High Voltage	DC 26.4V
	Low Voltage	DC 21.6V
	Normal Temperature	24°C
Other	Relative Humidity	55 %
	Air Pressure	989 hPa

Note: All modes were test at Normal Voltage, High Voltage, and Low Voltage, only the worst results of Normal Voltage was reported in the test report.

2.5 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ltem	Equipment	Model No.	Cable Length(cm)	Remark
1	Dride4K	DR4K1-RDG-XX	3m	EUT
2	DC power supply			AE
3	AP(Master)	ZXHN F670		AE
4	PC	Lenovo		AE

Note:

- 1. The support equipment was authorized by Declaration of Confirmation.
- 2. All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

2.6 MEASUREMENT INSTRUMENTS LIST

ltem	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
		Radiated Emis	sions Measureme	ent	
1	Radiated Emission Test Software	EZ-EMC	Ver.CCS-03A1	N/A	N/A
2	Horn Antenna	Sunol	DRH-118	A101415	2023.09.27
3	Broadband Hybrid Antenna	Sunol	JB1	A090215	2024.02.26
4	PREAMP	HP	8449B	3008A00160	2023.09.22
5	PREAMP	HP	8447D	2944A07999	2023.05.17
6	EMI TEST RECEIVER	Rohde&Schwarz	ESR3	101891	2023.09.22
7	VECTOR Signal Generator	Rohde&Schwarz	SMU200A	101521	2023.09.22
8	Signal Generator	Agilent	E4421B	MY4335105	2023.09.22
9	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2023.09.22
10	MXA Signal Analyzer	Keysight	N9020A	MY51110104	2023.09.22
11	RF Power sensor	DARE	RPR3006W	15100041SNO88	2023.05.17
12	RF Power sensor	DARE	RPR3006W	15100041SNO89	2023.05.17
13	RF power divider	Anritsu	K241B	992289	2023.09.22
14	Wideband radio communication tester	Rohde&Schwarz	CMW500	154987	2023.09.22
15	Active Loop Antenna	Com-Power	AL-130R	10160009	2023.07.25
16	Broadband Hybrid Antennas	Schwarzbeck	VULB9163	VULB9163#958	2023.09.22
17	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1680	2023.05.23
18	Horn Antenna	A-INFOMW	LB-180400-KF	J211060660	2023.09.27
19	Microwave Broadband Preamplifier	Schwarzbeck	BBV 9721	100472	2023.09.22
20	Signal Generator	Agilent	N5183A	MY47420153	2023.09.22
21	Spctrum Analyzer	Rohde&Schwarz	FSP 40	100501	2023.09.22
22	Power Meter	KEYSIGHT	N1911A	MY50520168	2023.09.22
23	Frequency Meter	VICTOR	VC2000	997406086	2023.09.22
24	DC Power Source	HYELEC	HY5020E	055161818	2023.09.22

3 DFS TEST INFORMATION

3.1 DFS TEST REQUIREMENT

	Operational Mode					
Requirement		Client Without Radar				
		Detection	Detection			
Non-Occupancy Period	Yes	Not required	Yes			
DFS Detection Threshold	Yes	Not required	Yes			
Channel Availability Check Time	Yes	Not required	Not required			
Uniform Spreading	Yes	Not required	Not required			
U-NII Detection Bandwidth	Yes	Not required	Yes			

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Table 2: Applicability of DFS requirements during normal operation

	Operational Mode			
Requirement	☐ Master Device or Client with	🛛 Client Without Radar		
	Radar Detection	Detection		
DFS Detection Threshold	Yes	Not required		
Channel Closing Transmission Time	Yes	Yes		
Channel Move Time	Yes	Yes		
U-NII Detection Bandwidth	Yes	Not required		

Additional requirements for devices with multiple bandwidth modes	☐ Master Device or Client with Radar Detection	⊠Client Without Radar Detection					
U-NII Detection Bandwidth and	All BW modes must be tested	Not required					
Statistical Performance Check							
Channel Move Time and Channel	Test using widest BW mode	Test using the widest BW mode					
Closing Transmission Time	available	available for the link					
All other tests	Any single BW mode	Not required					
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several							
frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection							
bandwidth. For 802.11 devices it is s	bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz						

channels and the channel center frequency.

3.2 TEST SETUP



3.3 LIMITS

Table 3: DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value	
	(See Notes 1, 2, and 3)	
EIRP ≥ 200 milliwatt	-64 dBm	
EIRP < 200 milliwatt and	-62 dBm	
power spectral density < 10 dBm/MHz		
EIRP < 200 milliwatt that do not meet the power		
spectral density requirement	-64 dBm	
Note 1: This is the level at the input of the receiver as	suming a 0 dBi receive antenna.	

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

Parameter	Value			
Non-occupancy period	Minimum 30 minutes			
Channel Availability Check Time	60 seconds			
	10 seconds			
Channel Move Time	See Note 1.			
	200 milliseconds + an			
	aggregate of 60			
Channel Closing Transmission Time	milliseconds over remaining			
	10 second period.			
	See Notes 1 and 2.			
	Minimum 100% of the U-			
U-NII Detection Bandwidth	NII 99% transmission power bandwidth.			
	See Note 3.			

Table 4: DFS Response Requirement Values

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

3.4 RADAR TEST WAVEFORMS

Table 5 – Short Pulse Radar Test Waveforms

Radar	Pulse Width	PRI	Number of Pulses	Minimum	Minimum
Туре	(µsec)	(µsec)		Percentage of	Number of
				Successful	Trials
				Detection	
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 µsec, with a minimum increment of 1 µsec, excluding PRI values selected in Test A	$\operatorname{Roundup}\left\{ \begin{array}{c} \left(\frac{1}{360}\right) \\ \left(\frac{19 \cdot 10^{6}}{\mathrm{PRI}_{\mu sec}}\right) \end{array} \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (l	Radar Types 1-	4)		80%	120
Note 1: She time, and cl	ort Pulse Rada nannel closing	r Type 0 should be u time tests.	used for the detection ba	ndwidth test, ch	annel move

Table 6 – Long Pulse Radar Test Waveform

Radar	Pulse	Chirp	PRI	Number	Number	Minimum	Minimum
Туре	Width	Width	(µsec)	of Pulses	of <i>Bursts</i>	Percentage of	Number of
	(µsec)	(MHz)		per Burst		Successful	Trials
						Detection	
5	50-100	5-20	1000-	1-3	8-20	80%	30
			2000				

Table 7 – Frequency Hopping Radar Test Waveform

Radar	Pulse	PRI	Pulses	Hopping	Hopping	Minimum	Minimum
Туре	Width	(µsec)	per	Rate	Sequence	Percentage of	Number of
	(µsec)		Нор	(kHz)	Length	Successful	Trials
					(msec)	Detection	
6	1	333	9	0.333	300	70%	30

3.5 TEST PROCEDURE

1. When a Client Device without Radar Detection is the UUT, the Master Device is the Radar Detection Device.

- 2. A spectrum analyzer is used to establish the test signal level for each radar type.
- 3. During this process, there are no transmissions by either the Master Device or Client Device.
- 4. The spectrum analyzer is switched to the zero span (time domain) mode at the frequency of the Radar Waveform generator. The peak detector function of the spectrum analyzer is utilized. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) are set to at least 3 MHz.
- 5. The measured channels are 5530MHz in 80MHz Bandwidth and 5290MHz in 80MHz Bandwidth. The Radar signal was the same as transmitted channels, and injected into the antenna port of AP(master) ,measured the DFS parameters. The master transmitted the test data to client, the transmitted duty cycle is 30.8%.

3.5 TEST RESULT

3.5.1 Calibration of Radar Waveform

Calibration:

For a detection threshold level of -64dBm and the Client antenna gain is -4.35dBi, required detection threshold is -68.35dBm (= -64+(-4.35)).

Note: Maximum Transmit Power is greater than 200 milliwatt in this report, so detection threshold level is -64dBm.

Radar Type 0

🔤 Keysight Spectrum Analyzer - Swept SA 💿 🙆 💌								
(X) Contor	RF 50 Ω		SENSE:IN		ALIGN AUTO	03:34:45 PM TRACE	May 12, 2023	Frequency
10 dB/div	Ref -20.00 dl	PNO: Fast ↔ IFGain:High	Trig: Free Run #Atten: 0 dB	ונישייי		TYPE DET Mkr1 17 -69.5	.45 ms	Auto Tune
-30.0								Center Freq 5.260000000 GHz
-40.0								Start Freq 5.260000000 GHz
-60.0						∮ 1		Stop Freq 5.260000000 GHz
-80.0 <mark>- 111-141</mark>	leading filmene and a starting	Woltegeneles and Wildling Protocols	te olyphisedod of the	llande Mit Perlander be	ud), I., Alber	yı. Hayardılda		CF Step 3.000000 MHz <u>Auto</u> Man
- 100 - 100 A waa alayii ad udaala a kala kuu alayiin shayiin addi danki daaca makaasa ada yiddi ka bidu yiddaa kalada madu							u, da a tat	Freq Offset 0 Hz
Center 5 26000000 GHz Span 0 Hz								Scale Type
Res BW	3.0 MHz	VBW	3.0 MHz		Sweep 20	.00 ms (40	0000 pts)	
MSG					STATUS	1		

Radar Type 1



Radar Type 2



Radar Type 3



Radar Type 4



Radar Type 5



Radar Type 6

🔤 Keysight Spectrum Analyzer - Swept SA 💦 💿 🕑 💽														
<mark>LXI</mark>		RF	50 9	Ω AC	CORRE	C	SEN	SE:INT	A	ALIGN AUTO	03:48:12 P	May 12, 2023	Fr	equency
Cer	iter Fi	req 5	.2600	00000	J GHZ	Foot in b	Tria: Free	Run	Avgiyp	e: Log-Pwr	TYP	E WWW/WWW		1 ,
					IFGair	n:High	#Atten: 0	dB			DE			
											Mkr1 3	5 34 ms		Auto Tune
10 4	-69.38 dBm													
Log	Bruiv	KCI	-20.00	uBill					1					
	1													Center Fred
-30.0													E 26	
00.0													5.20	0000000 GH2
-40.0														Start From
													5.00	StartFrey
-50.0	L												5.26	0000000 GHZ
-60.0														Oton From
														StopFreq
70.0											•		5.26	0000000 GHz
-70.0														
			1		1		1		a status					CE Sten
-80.0									3	3.000000 MHz				
										Auto	Man			
-90.0														
-100														Freq Offset
	10 - 5	1 1		a de la	k. It		and the state		11		. a. 1	1.11.11		0 Hz
	վերի	10 - UN	al facilitation de la compacticación de la compacticación de la compacticación de la compacticación de la comp	i, ha li di sali	tu di di	ar tilldaði.	الالفاقيل الأق	n a fidd at	dal katalat	الانتهائية الأندية	الالار الملاء	ادل ان ان البان		
-110	MARKA					t u tin p it			a collin o			i si intii		
	111		ICT II	- P P.	1.1.1	- Jullin	11 11	n a l'Étér de				a status		scale Type
Con										Lin				
Pee	BIA 3		17 17	SIL		VBM	3.0 MHz			Sween A(0 ms (4	Pail 0 H2 0000 nts)		
ALC: N	Dw J	av IVII	12			0000	5-0 WH12			Sweep 40		oooo pisj		
MSG										STATU	S			

3.5.2 CHANNEL CLOSING TRANSMISSION AND CHANNEL MOVE TIME WLAN TRAFFIC

Channel Move Time and Channel Closing Transmission Time								
Test Frequency	Requirement	Measurement Level	Limit					
5260MHz	Channel Closing Transmission Time	0.041	≤0.26s					
	Channel Move Time	1.311	≤10s					
5500MHz	Channel Closing Transmission Time	0.009	≤0.26s					
	Channel Move Time	1.069	≤10s					
5290MHz	Channel Closing Transmission Time	0.008	≤0.26s					
	Channel Move Time	1.028	≤10s					
5530MHz	Channel Closing Transmission Time	0.02	≤0.26s					
	Channel Move Time	1.09	≤10s					



Note :

CMT: Channel Move Time

CCT: Channel Closing Transmission Time

T2 denote injected radar burst.



A20-5500MHz (Radar Type 0)

CMT: Channel Move Time

CCT: Channel Closing Transmission Time

T2 denote injected radar burst.

AC80-5290MHz (Radar Type 0)



CMT: Channel Move Time

CCT: Channel Closing Transmission Time

T2 denote injected radar burst.

AC80-5530MHz (Radar Type 0)



CMT: Channel Move Time

CCT: Channel Closing Transmission Time

T2 denote injected radar burst.

4 ANTENNA REQUIREMENT

Standard Applicable:

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Connected Construction

The antenna used in this product is a PCB Antenna.

ANTENNA:



5 PHOTO OF TEST

RF Conducted



End of Report