

TEST REPORT

Applicant Name: Dragino Technology Co., Limited.
Address: Room 202, BaoChengTai industrial park, No.8 CaiYun LongCheng Street, LongGang District, Shenzhen China
Report Number: SZ1240227-09487E-RF-00
FCC ID: ZHZ50V3NB

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: NB-IoT Sensor Node
Model No.: SN50v3-NB
Multiple Model(s) No.: D20-NB, D20S-NB, D22-NB, D23-NB, S31-NB, S31B-NB, SW3L-NB-004, SW3L-NB-006, SW3L-NB-010, WL03A-NB, DS03A-NB, CPL03-NB, TS01-NB
Trade Mark: DRAGINO
Date Received: 2024/02/27
Issue Date: 2024/05/15

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Gala Liu

Gala Liu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- MPE-BASED EXEMPTION	11
APPLICABLE STANDARD	11
RESULT	12
FCC §15.203 – ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.209, §15.205 & §15.247(D) – UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS14	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	16
FACTOR & OVER LIMIT/MARGIN CALCULATION	16
TEST DATA	16
FCC §15.247(A) (2) –6 DB EMISSION BANDWIDTH.....	31
STANDARD APPLICABLE	31
TEST PROCEDURE	31
TEST DATA	31
FCC §15.247(B) (3)- PEAK OUTPUT POWER MEASUREMENT	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(E) – POWER SPECTRAL DENSITY.....	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE34
 APPLICABLE STANDARD34
 TEST PROCEDURE34
 TEST DATA35

EUT PHOTOGRAPHS36

TEST SETUP PHOTOGRAPHS37

APPENDIX38
 APPENDIX A: DTS BANDWIDTH38
 APPENDIX B: OCCUPIED CHANNEL BANDWIDTH40
 APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER42
 APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY44
 APPENDIX E: DUTY CYCLE46

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	SZ1240227-09487E-RF-00	Original Report	2024/05/15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	NB-IoT Sensor Node
Tested Model	SN50v3-NB, D20-NB
Multiple Model(s)	D20S-NB,D22-NB,D23-NB,S31-NB,S31B-NB,SW3L-NB-004,SW3L-NB-006,SW3L-NB-010,WL03A-NB,DS03A-NB, CPL03-NB,TS01-NB
Frequency Range	BLE 1M: 2402-2480MHz
Maximum Conducted Peak Output Power	BLE: -2.66 dBm
Modulation Technique	BLE: GFSK
Antenna Specification [#]	0.37dBi (provided by the applicant)
Voltage Range	DC 3.60V from Battery
Sample serial number	SN50v3-NB: 2LT8-2 for Radiated Emissions Test 2LT8-1 for RF Conducted Test D20-NB: 2LT8-4, D20S-NB: 2LT8-6, D22-NB: 2LT8-7, D23-NB: 2LT8-8, S31-NB: 2LT8-11, S31B-NB: 2LT8-10, SW3L-NB-004: 2LT8-12, SW3L-NB-006: 2LT8-13, SW3L-NB-010: 2LT8-14, WL03A-NB: 2LT8-16, DS03A-NB: 2LT8-9, CPL03-NB: 2LT8-5, TS01-NB: 2LT8-15 (Assigned by BAACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A
<p>Note 1: The multiple models are electrically identical with the test model except for probe. Please refer to the declaration letter[#] for more detail, which was provided by manufacturer.</p> <p>Note 2: According to declaration letter[#], model D20-NB was selected as the worst case among the multiple models for testing “radiated emission for below 1GHz”, and model SN50v3-NB was selected for fully testing.</p>	

Objective

This report is in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209, 15.247 rules.

Test Methodology

All tests and measurements indicated in this document were performed in accordance ANSI C63.10-2013.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.94dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“Smart Snippets Toolbox V5.0.12”[#] exercise software was used and the power level is Default[#]. The software and power level was provided by the applicant.

Duty cycle

Please refer to the Appendix.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Temperature Probe	Unknown	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant

Not Applicable: The EUT cannot connect directly to the public power network.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2023/06/08	2024/06/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2024/07/19
ETS	Passive Loop Antenna	6512	29604	2023/07/07	2024/07/06
Unknown	Cable	Chamber Cable 1	F-03-EM236	2023/08/03	2024/08/02
Unknown	Cable	Chamber Cable 4	EC-007	2023/08/03	2024/08/02
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2023/04/18	2024/04/17
COM-POWER	Pre-amplifier	PA-122	181919	2023/06/29	2024/06/28
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2024/07/25
Unknown	RF Cable	KMSE	0735	2023/10/08	2024/10/07
Unknown	RF Cable	UFA147	219661	2023/10/08	2024/10/07
SNSD	2.4G Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
A.H.System	Pre-amplifier	PAM-1840VH	190	2023/08/03	2024/08/02
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
RF Conducted Test					
Tonscend	RF control Unit	JS0806-2	19D8060154	2023/09/06	2024/09/05
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2024/01/16	2025/01/15
Unknown	10dB Attenuator	Unknown	F-03-EM122	2023/07/04	2024/07/03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Result

For worst case:

Mode	Frequency (MHz)	Tune up conducted power [#]	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BLE	2402-2480	-2.00	0.37	-1.78	-3.78	0.42	0.2	768
NB-IoT Band 2	1850-1910	25.00	0.45	-1.70	23.3	213.80	0.2	768
NB-IoT Band 4	1710-1755	25.00	0.45	-1.70	23.3	213.80	0.2	768
NB-IoT Band 5	824-849	25.00	0.18	-1.97	23.03	200.91	0.2	422
NB-IoT Band 12	699-716	25.00	0.23	-1.92	23.08	203.24	0.2	358
NB-IoT Band 13	777-787	25.00	0.23	-1.92	23.08	203.24	0.2	398
NB-IoT Band 17	704-716	25.00	0.23	-1.92	23.08	203.24	0.2	360
NB-IoT Band 25	1850-1915	25.00	0.45	-1.70	23.3	213.80	0.2	768
NB-IoT Band 66	1710-1780	25.00	0.45	-1.70	23.3	213.80	0.2	768
NB-IoT Band 85	698-716	25.00	0.23	-1.92	23.08	203.24	0.2	357

Note 1: The tune-up power and antenna gain was declared by the applicant.

Note 2: 0dBd=2.15dBi.

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{BLE} / \text{limit} + ERP_{NB-IoT\ Band\ 85} / \text{limit} = 0.42/768 + 203.24/357 = 0.570 < 1.0$

To maintain compliance with the FCC’s RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to FCC § 15.203, the applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Antenna Connector Construction

The EUT has an internal antenna arrangement which was permanently attached and the maximum antenna gain[#] is 0.37dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant


FCC §15.209, §15.205 & §15.247(D) – UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup


9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.205, FCC 15.209, FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1-25 GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T_{on}$

Note: T_{on} is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23~25.3°C
Relative Humidity:	50~55 %
ATM Pressure:	101 kPa

The testing was performed by Anson Su from 2024-03-25 to 2024-05-15 for below 1GHz and Tyler Wu on 2024-04-07&2024-04-08 for above 1GHz.

EUT operation mode: Transmitting

Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.


9 kHz-30MHz: *Maximum output power mode, BLE 1M Low Channel*

For the radiated spurious emission below 30MHz, the emissions are 20dB below the limit or the noise floor which are not recorded.

30MHz-1GHz: (maximum output power mode BLE 1M, Low channel)

Model: SN50v3-NB


Horizontal



Site : Chamber A
 Condition : 3m Horizontal
 Project Number: SZ1240227-09487E-RF
 Note : BLE 1M
 Tester : Anson Su

	Freq Factor		Read Level		Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	41.59	-11.40	25.14	13.74	40.00	-26.26	QP
2	99.88	-13.76	24.24	10.48	43.50	-33.02	QP
3	122.57	-10.33	26.07	15.74	43.50	-27.76	QP
4	393.64	-7.68	25.06	17.38	46.00	-28.62	QP
5	678.47	-1.91	26.07	24.16	46.00	-21.84	QP
6	822.79	-0.22	26.00	25.78	46.00	-20.22	QP

Vertical




Site : Chamber A
 Condition : 3m Vertical
 Project Number: SZ1240227-09487E-RF
 Note : BLE 1M
 Tester : Anson Su

	Freq Factor		Read Level		Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.22	-12.01	23.54	11.53	40.00	-28.47	QP
2	95.55	-16.18	24.83	8.65	43.50	-34.85	QP
3	124.24	-10.77	25.96	15.19	43.50	-28.31	QP
4	392.96	-7.93	25.03	17.10	46.00	-28.90	QP
5	668.73	-2.50	26.65	24.15	46.00	-21.85	QP
6	875.63	0.26	25.21	25.47	46.00	-20.53	QP

Model: D20-NB


Horizontal



Site : Chamber A
 Condition : 3m Horizontal
 Project Number: SZ1240227-09487E-RF
 Test Mode : BLE 1M
 Tester : Anson Su

	Freq Factor		Read Level		Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.17	-11.63	23.18	11.55	40.00	-28.45	QP
2	99.79	-15.52	24.39	8.87	43.50	-34.63	QP
3	128.79	-12.10	25.89	13.79	43.50	-29.71	QP
4	399.73	-10.61	28.72	18.11	46.00	-27.89	QP
5	409.66	-10.40	31.24	20.84	46.00	-25.16	QP
6	838.08	-4.93	25.91	20.98	46.00	-25.02	QP

Vertical



Site : Chamber A
 Condition : 3m Vertical
 Project Number: SZ1240227-09487E-RF
 Test Mode : BLE 1M
 Tester : Anson Su

	Freq Factor		Read Level	Limit Level	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	40.10	-13.08	23.44	10.36	40.00	-29.64 QP
2	95.80	-17.77	25.50	7.73	43.50	-35.77 QP
3	129.75	-12.56	25.10	12.54	43.50	-30.96 QP
4	396.94	-10.90	27.18	16.28	46.00	-29.72 QP
5	691.08	-6.66	26.52	19.86	46.00	-26.14 QP
6	869.13	-5.02	25.94	20.92	46.00	-25.08 QP

1-25 GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave					
BLE 1M							
Low Channel 2402MHz							
2371.34	55.37	PK	H	-2.93	52.44	74	-21.56
2371.34	41.49	AV	H	-2.93	38.56	54	-15.44
2384.39	55.06	PK	V	-2.93	52.13	74	-21.87
2384.39	41.38	AV	V	-2.93	38.45	54	-15.55
4804.00	51.83	PK	H	2.42	54.25	74	-19.75
4804.00	46.62	AV	H	2.42	49.04	54	-4.96
4804.00	50.54	PK	V	2.42	52.96	74	-21.04
4804.00	45.08	AV	V	2.42	47.50	54	-6.50
Middle Channel 2440MHz							
4880.00	51.83	PK	H	2.56	54.39	74	-19.61
4880.00	47.09	AV	H	2.56	49.65	54	-4.35
4880.00	50.64	PK	V	2.56	53.20	74	-20.80
4880.00	46.52	AV	V	2.56	49.08	54	-4.92
High Channel 2480MHz							
4960.00	53.06	PK	H	2.68	55.74	74	-18.26
4960.00	48.31	AV	H	2.68	50.99	54	-3.01
4960.00	52.27	PK	V	2.68	54.95	74	-19.05
4960.00	47.05	AV	V	2.68	49.73	54	-4.27

Note:


Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude/Level= Corrected Factor + Reading


Margin = Corrected Amplitude/Level - Limit

The other spurious emission which is in the noise floor level was not recorded.

Test plots for Band Edge Measurements (Radiated):




BLE 1M			
Test Channel:	2480MHz	Ant. Polar. :	Vertical




Condition : Vertical
 Project No.: SZ1240227-09487E
 Tester : Tyler
 Note : BLE1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.613	-3.17	41.83	38.66	54.00	-15.34	Average
2	2483.613	-3.17	55.04	51.87	74.00	-22.13	peak

Listed with harmonic margin test plot:



Vertical




1-4GHz

Condition : Vertical
 Project No.: SZ1240227-09487E
 Tester : Tyler
 Note : BLE1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3911.875	-0.45	36.16	35.71	54.00	-18.29	Average
2	3911.875	-0.45	47.84	47.39	74.00	-26.61	Peak

Horizontal




4-18GHz

Condition : Horizontal
 Project No.: SZ1240227-09487E
 Tester : Tyler
 Note : BLE1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.68	48.31	50.99	54.00	-3.01	Average
2	4960.000	2.68	53.06	55.74	74.00	-18.26	Peak
3	17909.000	23.97	23.57	47.54	54.00	-6.46	Average
4	17909.000	23.97	36.81	60.78	74.00	-13.22	Peak

Vertical




4-18GHz

Condition : Vertical
 Project No.: SZ1240227-09487E
 Tester : Tyler
 Note : BLE1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.68	47.05	49.73	54.00	-4.27	Average
2	4960.000	2.68	52.27	54.95	74.00	-19.05	Peak
3	15100.250	15.85	31.53	47.38	54.00	-6.62	Average
4	15100.250	15.85	45.50	61.35	74.00	-12.65	Peak

Horizontal

18-25GHz




Condition : Horizontal
 Project No.: SZ1240227-09487E
 Tester : Tyler
 Note : BLE1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	24574.830	18.90	28.85	47.75	54.00	-6.25	Average
2	24574.830	18.90	42.44	61.34	74.00	-12.66	Peak

Vertical

18-25GHz



Condition : Vertical
 Project No.: SZ1240227-09487E
 Tester : Tyler
 Note : BLE1M_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	24408.580	18.79	28.88	47.67	54.00	-6.33	Average
2	24408.580	18.79	42.75	61.54	74.00	-12.46	Peak

FCC §15.247(a) (2) –6 dB EMISSION BANDWIDTH

Standard Applicable


According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	45 %
ATM Pressure:	101 kPa

The testing was performed by Tom Tan on 2024-03-28.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (3)- PEAK OUTPUT POWER MEASUREMENT


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.9.1.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	45 %
ATM Pressure:	101 kPa

The testing was performed by Tom Tan on 2024-03-28.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(e) – POWER SPECTRAL DENSITY

Applicable Standard


According to FCC §15.247(e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	45 %
ATM Pressure:	101 kPa

The testing was performed by Tom Tan on 2024-03-28.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

Test Procedure



Test Method: ANSI C63.10-2013 Clause 11.11

1. Set the RBW =100 kHz.
2. Set the VBW $\geq 3 \times$ RBW.
3. Detector = peak
4. Sweep time = auto couple.
5. Trace mode=max hold
6. All trace to fully stabilize
7. Use the peak marker function to determine the maximum amplitude level.
Ensure that amplitude of all unwanted emissions outside of the authorized frequency band(excluding restricted frequency bands) is attenuated by at least the minimum requirement specified in 11.11.
Report the three highest emissions relative to the limit.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	45 %
ATM Pressure:	101 kPa

The testing was performed by Tom Tan on 2024-03-28.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

EUT PHOTOGRAPHS

Please refer to the attachment SZ1240227-09487E-RF External photo and SZ1240227-09487E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment SZ1240227-09487E-RF Test Setup photo.


APPENDIX


Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.70	2401.63	2402.33	0.5	PASS
		2440	0.69	2439.64	2440.33	0.5	PASS
		2480	0.68	2479.64	2480.33	0.5	PASS

Test Graphs







Appendix B: Occupied Channel Bandwidth

Test Result

Test Mode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.047	2401.4685	2402.5155	---	---
		2440	1.051	2439.4645	2440.5155	---	---
		2480	1.047	2479.4685	2480.5155	---	---

Test Graphs







Appendix C: Maximum conducted output power

Test Result Peak

Test Mode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-2.66	≤30	PASS
		2440	-3.14	≤30	PASS
		2480	-2.99	≤30	PASS

Test Graphs Peak








Appendix D: Maximum power spectral density

Test Result

Test Mode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-17.52	≤8.00	PASS
		2440	-18.04	≤8.00	PASS
		2480	-18.21	≤8.00	PASS

Test Graphs






Appendix E: Duty Cycle

Test Result

Test Mode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]	1/Ton[Hz]	VBW setting [Hz]
BLE_1M	Ant1	2440	0.42	0.63	66.67	1.76	2381	3000

Test Graphs



***** END OF REPORT *****