

Setup photos for HAC RF Emissions and T-Coil Test Report

Test report no.:	HAC_Photo_RM-1128_03	Date of report:	2015-09-16
Template version:	4.0	Number of pages:	3
Testing laboratory:	TCC Microsoft Salo Laboratory P.O.Box 303 Joensuunkatu 7E FIN-24101 SALO, FINLAND Tel. +358 71 800 8000 Fax. +358 71 80 44122	Client:	Microsoft P.O. Box 68 Sinitaival 5 FIN-33721 TAMPERE, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 46880
Responsible test engineer:	Janne Hirsimäki	Product contact person:	Tero Huhtala
Measurements made by:	Sami Savela		
Tested devices:	RM-1128		
FCC ID:	PYARM-1128	IC:	661X-RM1128
Supplement reports:	RF_RM-1128_01, T-Coil_RM-1128_02		
Testing has been carried out in accordance with:	ANSI C63.19-2011 American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids CTIA Test Plan for Hearing Aid Compatibility, Revision 3.0, November 2013		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Microsoft.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		

Date and signatures:

For the contents:

CONTENTS

1.1	PICTURE OF DEVICE	3
1.2	TEST POSITIONS.....	3
1.2.1	<i>Scan area centered at the acoustic output.....</i>	3

1.1 Picture of Device



1.2 Test Positions

1.2.1 Scan area centered at the acoustic output

The device was positioned such that Device Reference plane was touching the bottom of the Test Arch. The scan is centered at the acoustic output by aligning the acoustic output with the intersection of the Test Arch's middle bar and dielectric wire.




Photo of the device positioned under Test Arch