Hanchett Entry Systems 10027 S. 51st Street, Ste 102 Phoenix, AZ 85044 Tel +1 623-582-4626



January 3, 2023

To: Federal Communications Commission

7435 Oakland Mills Road Columbia, MD 21046-1609

CC: Cetecom, Inc. TCB

Re: Single Limited Modular Approval Request

To Whom It May Concern:

We, Hanchett Entry Systems, are applying for a limited modular approval for our device with:

## FCC ID: VC3CRFM1

Please note that, this module is to be installed only by us in our end products and will not be marketed to any other party. Installation will be under our control and therefore full compliance of the end product will always be ensured.

The following information is being provided regarding **single limited modular approval** per the requirements of CFR 47 FCC 15.212(b).

This transceiver is a complete RF module with an integral reference oscillator. External connections are provided for power and data communication. Antennas are internal to our module.

The following numbered items correspond to requirements listed in 15.212 of the FCC rules:

- 1) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.
  - There is no shielding on the module PCB.
  - The module will be installed in the certified host by the grantee (HES) at their manufacturing plant.
  - Module installation outside of the grantee's manufacturing plant or module use outside of the intended host is not possible:
    - Host installations require controlled factory work instructions, unique regulatory labels, and regulatory reviews prior to any new host creation.
    - Host installations require unique security features within the module to be enabled for successful communication and host identification.
    - Factory manufacturing plant lines that assemble the hosts require performance checks on RFID and RF fundamental levels for each host using host specific hardware and fixtures.
    - Host specific manufacturing hardware and fixtures cannot be repurposed to create nonapproved variants.
  - HES does not, nor does it intend to, sell, or supply the module to any other divisions, factories, or plants within ASSA ABLOY.
- 2) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.
  - The module is designed using a 'System-on-Chip' (SoC) integrated circuit (IC). There are no exposed modulation inputs.

Hanchett Entry Systems 10027 S. 51st Street, Ste 102 Phoenix, AZ 85044 Tel +1 623-582-4626



- 3) The modular transmitter must have its own power supply regulation.
  - The module input power source is 3.3 VDC. The transmitter inside the SoC IC has its own internal regulated power supply to allow for this input.
- 4) The modular transmitter must comply with the antenna and transmission system requirements of Sec. Sec. 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a `unique" antenna coupler (at all connections between the module and the antenna, including the cable). The `professional installation" provision of Sec. 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.
  - The antenna is permanently attached to the module. The antenna is not detachable and therefore our module complies with this requirement.
- 5) The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Sec. 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Sec. 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Sec. 15.31(i)).
  - Our module was tested in the final host and the module will only ever be used in those approved hosts. This module is to be installed only by us in our end products and will not be marketed to any other party. Installation will be under our control and therefore full compliance of the end product will always be ensured.
- 6) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.
  - Our module has a label as described in the label exhibit that complies with this requirement. Endproduct labeling warnings can be found in the installation manual of the module.
- 7) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.
  - Our module complies with this requirement.
- 8) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.
  - Our module complies with this requirement. This module is to be installed only by us in our end

Hanchett Entry Systems 10027 S. 51st Street, Ste 102 Phoenix, AZ 85044 Tel +1 623-582-4626



products and will not be marketed to any other party. Installation will be under our control and therefore full compliance of the end product will always be ensured.

If you have any questions, please do not hesitate to contact us at +1 623-582-4626.

Sincerely,

Baruch Spence

Senior Electrical Design Engineer ASSA ABLOY EMS&OEM Group 10027 S. 51st Street, Suite 102

Phoenix, AZ 85044

Phone: +1 623-582-4626 x7137

Fax: +1 623-582-4626

Email: <u>baruch.spence@assaabloy.com</u>