



# FCC REPORT

Report Reference No. .... : **TRE1611005301** R/C.....: 73763

FCC ID..... : **ZSW-30-033**

Applicant's name..... : **b mobile HK Limited**

Address..... : Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

Manufacturer..... : **b mobile HK Limited**

Address..... : Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

Test item description ..... : **Mobile Phone**

Trade Mark ..... : Bmobile

Model/Type reference..... : AX1070

Listed Model(s) ..... : -

Standard ..... : **FCC Part 22: PUBLIC MOBILE SERVICES**  
**FCC Part 24: PERSONAL COMMUNICATIONS SERVICES**

Date of receipt of test sample..... : Nov. 09, 2016

Date of testing..... : Nov. 10, 2016 - Nov. 23, 2016

Date of issue..... : Nov. 24, 2016

Result..... : **Pass**

Compiled by  
( position+printed name+signature)...: File administrators Becky Liang

Supervised by  
( position+printed name+signature)...: Project Engineer Lion Cai

Approved by  
( position+printed name+signature)...: Manager Hans Hu

Testing Laboratory Name ..... : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

## Contents

<b><u>1.</u></b>	<b><u>TEST STANDARDS AND TEST DESCRIPTION</u></b>	<b><u>3</u></b>
1.1.	Test Standards	3
1.2.	Test Description	3
<b><u>2.</u></b>	<b><u>SUMMARY</u></b>	<b><u>4</u></b>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	EUT operation mode	5
2.4.	EUT configuration	5
2.5.	Modifications	5
<b><u>3.</u></b>	<b><u>TEST ENVIRONMENT</u></b>	<b><u>6</u></b>
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Statement of the measurement uncertainty	7
3.5.	Equipments Used during the Test	8
<b><u>4.</u></b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b><u>9</u></b>
4.1.	Conducted Output Power	9
4.2.	Occupy Bandwidth	11
4.3.	Out of band emission at antenna terminals	18
4.4.	Band Edge compliance	21
4.5.	Radiated Power Measurement	26
4.6.	Radiated Spurious Emssion	29
4.7.	Frequency stability V.S. Temperature measurement	35
4.8.	Frequency stability V.S. Voltage measurement	37
4.9.	Peak-Average Ratio	38
<b><u>5.</u></b>	<b><u>TEST SETUP PHOTOS OF THE EUT</u></b>	<b><u>41</u></b>
<b><u>6.</u></b>	<b><u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u></b>	<b><u>42</u></b>

## 1. TEST STANDARDS AND TEST DESCRIPTION

### 1.1. Test Standards

The tests were performed according to following standards:

[FCC Part 22 \(10-1-13 Edition\)](#): PRIVATE LAND MOBILE RADIO SERVICES.

[FCC Part 24\(10-1-13 Edition\)](#): PUBLIC MOBILE SERVICES

[TIA/EIA 603 D June 2010](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): - Unintentional Radiators

[FCC Part 2](#): FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[971168 D01 Power Meas License Digital Systems v02r02](#): provides a methodology for fully characterizing the fundamental power of wideband (> 1 MHz) digitally modulated RF signals acceptable to the FCC for demonstrating compliance for licensed transmitters.

### 1.2. Test Description

Test Item	Section in CFR 47	Result
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass
Peak-Average Ratio	Part 24.232 (d)	Pass

Remark: The measurement uncertainty is not included in the test result.

## 2. SUMMARY

### 2.1. Client Information

Applicant:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.
Manufacturer:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

### 2.2. Product Description

Name of EUT	Mobile Phone
Trade Mark:	Bmobile
Model No.:	AX1070
Listed Model(s):	-
IMEI :	358948060003876
Power supply:	DC 3.7V From internal battery
Adapter information:	Input: 100-240Va.c., 50-60Hz, 0.2A Output: 5Vd.c., 1A
<b>2G:</b>	
Support Network:	GSM, GPRS, EGPRS
Support Band:	GSM850, DCS1900
Modulation:	GSM/GPRS: GMSK EGPRS:GMSK/8PSK
Transmit Frequency:	GSM850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz
Receive Frequency:	GSM850: 869.20MHz-893.80MHz PCS1900: 1930.20MHz-1989.80MHz
GPRS Class:	12
EGPRS Class:	12
Antenna type:	Integral Antenna
Antenna gain:	GSM850: 1.0 dBi PCS1900: 1.0 dBi
Hardware version:	V1.0
Software version:	L18_C_G5018_BMB_V001
<b>3G:</b>	
Operation Band:	FDD Band II and FDD Band V
Power Class:	Power Class 3
Modulation Type:	QPSK/16QAM/64QAM/HSUPA/HSDPA
DC-HSUPA Release Version:	Not Supported
Antenna type:	Integral Antenna
Antenna gain:	-0.45 dBi

Test Frequency:

GSM 850		PCS1900	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20
190	836.60	661	1880.00
251	848.80	810	1909.80

FDD Band II		FDD Band V	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
9262	1852.4	4132	826.40
9400	1880.0	4183	836.60
9538	1907.6	4233	846.60

### 2.3. EUT operation mode

1.The EUT has been tested under typical operating condition. The Applicant provides software to control the EUT for staying in continuous transmitting and receiving mode for testing.

### 2.4. EUT configuration

**The following peripheral devices and interface cables were connected during the measurement:**

● - supplied by the manufacturer

○ - supplied by the lab

	Length (m) :	/
	Shield :	/
	Detachable :	/
	Manufacturer :	/
	Model No. :	/

### 2.5. Modifications

No modifications were implemented to meet testing criteria.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

##### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

##### **A2LA-Lab Cert. No. 3902.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until December 31, 2016.

##### **FCC-Registration No.: 317478**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date Jul. 18, 2014, valid time is until Jul. 18, 2017.

##### **IC-Registration No.: 5377A&5377B**

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on Dec.03, 2014, valid time is until Dec.03, 2017.

##### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

### 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature/Tnor:	15~35°C
Relative Humidity	30~60 %
Air Pressure	950-1050 hPa

### 3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Frequency stability	25 Hz	(1)
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-12.75 GHz	1.60 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)
Emission Mask	-----	(1)
Modulation Characteristic	-----	(1)
Transmitter Frequency Behavior	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

### 3.5. Equipments Used during the Test

<b>Output Power(Conducted) &amp; Occupied Bandwidth &amp; Emission Bandwidth &amp; Band Edge Compliance &amp; Conducted Spurious Emission</b>					
No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	11/13/2016
2	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	11/13/2016
3	Splitter	Mini-Circuit	ZAPD-4	400059	11/13/2016

<b>Frequency Stability</b>					
No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	11/13/2016
2	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	11/13/2016
3	Climate Chamber	ESPEC	EL-10KA	05107008	11/13/2016
4	Splitter	Mini-Circuit	ZAPD-4	400059	11/13/2016

<b>Output Power (Radiated) &amp; Radiated Spurious Emission</b>					
No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	11/13/2016
2	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	11/13/2016
3	HORN ANTENNA	ShwarzBeck	9120D	1012	11/13/2016
4	HORN ANTENNA	ShwarzBeck	9120D	1011	11/13/2016
5	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	11/13/2016
6	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	539	11/13/2016
7	TURNTABLE	MATURO	TT2.0	----	N/A
8	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
9	EMI Test Software	Audix	E3	N/A	N/A
10	EMI Test Receiver	Rohde&Schwarz	ESIB 26	100009	11/13/2016
11	RF Test Panel	Rohde&Schwarz	TS / RSP	335015/ 0017	11/13/2016
12	High pass filter	Compliance Direction systems	BSU-6	34202	11/13/2016
13	Splitter	Mini-Circuit	ZAPD-4	400059	11/13/2016
14	Horn Antenna	SCHWARZBECK	BBHA9170	25841	11/13/2016
15	Horn Antenna	SCHWARZBECK	BBHA9170	25842	11/13/2016
16	Preamplifier	ShwarzBeck	BBV 9718	BBV 9718	11/13/2016
17	Broadband Preamplifier	ShwarzBeck	BBV743	9743-0079	11/13/2016
18	Signal Generator	Rohde&Schwarz	SMF100A	101932	11/13/2016
19	Amplifier	Compliance Direction systems	PAP1-4060	120	11/13/2016
20	TURNTABLE	ETS	2088	2149	11/13/2016
21	ANTENNA MAST	ETS	2075	2346	11/13/2016
22	HORN ANTENNA	Rohde&Schwarz	HF906	100068	11/13/2016
23	HORN ANTENNA	Rohde&Schwarz	HF906	100039	11/13/2016


The calibration interval was one year.



## **4. TEST CONDITIONS AND RESULTS**

### **4.1. Conducted Output Power**

#### **TEST CONFIGURATION**



*Note: Measurement setup for testing on Antenna connector*

#### **TEST PROCEDURE**


1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power.

**TEST RESULTS**

EUT Mode	Channel	Frequency (MHz)	Power (dBm)
GSM 850 (GMSK)	128	824.20	31.85
	190	836.60	31.93
	251	848.80	31.79
GPRS850 (GMSK,1Slot)	128	824.20	31.12
	190	836.60	31.15
	251	848.80	31.08
EGPRS850 (8PSK,1Slot)	128	824.20	28.14
	190	836.60	28.22
	251	848.80	28.09
PCS1900 (GMSK)	512	1850.20	28.57
	661	1880.00	28.38
	810	1909.80	28.31
GPRS1900 (GMSK,1Slot)	512	1850.20	28.61
	661	1880.00	28.43
	810	1909.80	28.42
EGPRS1900 (8PSK,1Slot)	512	1850.20	26.81
	661	1880.00	26.92
	810	1909.80	26.85
WCDMA Band II	9262	1852.40	22.33
	9400	1880.00	22.10
	9538	1907.60	22.05
WCDMA Band V	4132	826.40	21.94
	4183	836.60	21.86
	4233	846.60	21.97

## 4.2. Occupy Bandwidth

### TEST CONFIGURATION




*Note: Measurement setup for testing on Antenna connector*

### TEST PROCEDURE


1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer
2. RBW was set to about 1% of emission BW, VBW= 3 times RBW.
3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

**TEST RESULTS**


EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
GSM 850 (GMSK)	128	824.20	243.76	320.80
	190	836.60	243.76	322.00
	251	848.80	244.76	319.20
GPRS850 (GMSK,1Slot)	128	824.20	245.75	324.10
	190	836.60	243.76	319.90
	251	848.80	244.76	320.50
EGPRS850 (8PSK,1Slot)	128	824.20	271.73	364.70
	190	836.60	268.73	364.00
	251	848.80	272.73	371.10
PCS1900 (GMSK)	512	1850.20	245.75	317.40
	661	1880.00	244.76	328.30
	810	1909.80	244.76	321.90
GPRS1900 (GMSK,1Slot)	512	1850.20	245.75	323.00
	661	1880.00	245.75	321.30
	810	1909.80	243.76	323.10
EGPRS1900 (8PSK,1Slot)	512	1850.20	292.71	397.20
	661	1880.00	294.71	404.10
	810	1909.80	292.71	401.70
WCDMA Band II	9262	1852.40	4195.80	4899.00
	9400	1880.00	4195.80	4867.00
	9538	1907.60	4195.80	4896.00
WCDMA Band V	4132	826.40	4215.78	4889.00
	4183	836.60	4205.79	4906.00
	4233	846.60	4195.80	4880.00

**GSM850 For GMSK Modulation****99% Occupy bandwidth&-26dB bandwidth**


Channel 128

**99% Occupy bandwidth&-26dB bandwidth**


Channel 190



Channel 251


**GPRS850 For GMSK Modulation****99% Occupy bandwidth&-26dB bandwidth**

Channel 128

**99% Occupy bandwidth&-26dB bandwidth**

Channel 190

## 99% Occupy bandwidth&amp;-26dB bandwidth




## 99% Occupy bandwidth&amp;-26dB bandwidth

Channel 251

## EGPRS850 For 8PSK Moudlation

## 99% Occupy bandwidth&amp;-26dB bandwidth




## 99% Occupy bandwidth&amp;-26dB bandwidth



Channel 128


Channel 190



Channel 251


## PCS1900 For GMSK Modulation

## 99% Occupancy bandwidth &amp; -26dB bandwidth




Channel 512

## 99% Occupancy bandwidth &amp; -26dB bandwidth




Channel 661



Channel 810


## GPRS1900 For GMSK Modulation

## 99% Occupancy bandwidth &amp; -26dB bandwidth




Channel 512

## 99% Occupancy bandwidth &amp; -26dB bandwidth




Channel 661

## 99% Occupy bandwidth&amp;-26dB bandwidth




Channel 810

## 99% Occupy bandwidth&amp;-26dB bandwidth




## EGPRS1900 For 8PSK Moudlation

## 99% Occupy bandwidth&amp;-26dB bandwidth




Channel 512

## 99% Occupy bandwidth&amp;-26dB bandwidth



Channel 661




Channel 810




## WCDMA Band II


## 99% Occupy bandwidth&amp;-26dB bandwidth




## 99% Occupy bandwidth&amp;-26dB bandwidth



## Channel 9262




## Channel 9400




## Channel 9538

## WCDMA Band V


## 99% Occupy bandwidth&amp;-26dB bandwidth




## 99% Occupy bandwidth&amp;-26dB bandwidth



## Channel 4132



## Channel 4183



## Channel 4233


### 4.3. Out of band emission at antenna terminals

#### LIMIT

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

#### TEST CONFIGURATION




#### TEST PROCEDURE

1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
2. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.
3. For the out of band: Set the RBW= 1MHz, VBW = 3MHz, Start=30MHz, Stop= 10th harmonic.


#### TEST RESULTS

Worst case at GSM850/DCS1800/WCDMA B2/B5


## GSM850



## CH128




## CH190




## CH251


## PCS1900




## CH512



## CH661



## CH810




#### 4.4. Band Edge compliance

##### LIMIT

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

##### TEST CONFIGURATION



##### TEST PROCEDURE

1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
2. For the bandedge: 2G: Set the RBW=3KHz, VBW = 10KHz, Sweep time= Auto  
3G: Set the RBW=100KHz, VBW = 300KHz, Sweep time= Auto

##### TEST RESULTS

GSM850					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
128	824.20	824	-15.19	-13.00	Pass
251	848.80	849	-14.42	-13.00	Pass

GPRS850					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
128	824.20	824	-14.95	-13.00	Pass
251	848.80	849	-14.03	-13.00	Pass

EGPRS850					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
128	824.20	824	-16.08	-13.00	Pass
251	848.80	849	-16.73	-13.00	Pass


PCS1900					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
512	1850.20	1850	-19.23	-13.00	Pass
810	1909.80	1910	-18.73	-13.00	Pass

GPRS1900					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
512	1850.20	1850	-19.6	-13.00	Pass
810	1909.80	1910	-18.5	-13.00	Pass


EGPRS1900					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
512	1850.20	1850	-16.87	-13.00	Pass
810	1909.80	1910	-21.12	-13.00	Pass

WCDMA Band II					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
9262	1852.4	1850	-14.99	-13.00	Pass
9538	1907.6	1910	-16.31	-13.00	Pass


WCDMA Band V					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
4132	826.4	824	-13.86	-13.00	Pass
4233	846.6	849	-14.80	-13.00	Pass

**GSM850 For GMSK Moudlation**

Channel 128




Channel 251

**GPRS850 For GMSK Moudlation**


Channel 128









Channel 251

**EGPRS850 For 8PSK Moudlation**

Channel 128




Channel 251


**PCS1900 For GMSK Moudlation****Channel 512****Channel 810****GPRS1900 For GMSK Moudlation****Channel 512****Channel 810****EGPRS1900 For 8PSK Moudlation****Channel 512****Channel 810**



WCDMA Band II




Channel 9262




Channel 9538

WCDMA Band V



Channel 4132



Channel 4233


## 4.5. Radiated Power Measurement

### LIMIT

GSM850/WCDMA Band V: 7W ERP

PCS1900/WCDMA Band II: 2W EIRP

### TEST CONFIGURATION



### TEST PROCEDURE

1. EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz,, And the maximum value of the receiver should be recorded as (Pr).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
6. The measurement results are obtained as described below:  
 $\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$   
 We used SMF100A microwave signal generator which signal level can up to 33dBm,so we not used power Amplifier for substitution test; The measurement results are amend as described below:  
 $\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$
7. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.  
 ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$ .

## **TEST RESULTS**

GSM:

Mode	Channel	Antenna Pol.	ERP	Limit (dBm)	Result
GSM850	128	V	30.22	38.45	Pass
		H	29.22		
	190	V	31.11		
		H	29.11		
	251	V	30.79		
		H	29.79		
GPRS850	128	V	30.21	38.45	Pass
		H	29.20		
	190	V	31.16		
		H	29.14		
	251	V	30.68		
		H	29.71		
EGPRS850	128	V	30.18	38.45	Pass
		H	29.08		
	190	V	31.06		
		H	29.09		
	251	V	30.64		
		H	29.68		

Mode	Channel	Antenna Pol.	EIRP	Limit (dBm)	Result
PCS1900	512	V	24.65	33.01	Pass
		H	22.81		
	661	V	23.96		
		H	21.97		
	810	V	24.68		
		H	22.64		
GPRS1900	512	V	24.45	33.01	Pass
		H	22.36		
	661	V	23.98		
		H	22.01		
	810	V	24.35		
		H	22.43		
EGPRS 1900	512	V	24.52	33.01	Pass
		H	22.64		
	661	V	23.99		
		H	22.06		
	810	V	24.47		
		H	22.69		

## WCDMA:

Mode	Channel	Antenna Pol.	EIRP	Limit (dBm)	Result
WCDMA Band II	9262	V	20.55	33.01	Pass
		H	18.45		
	9400	V	20.47		
		H	18.32		
	9538	V	20.16		
		H	18.36		


Mode	Channel	Antenna Pol.	ERP	Limit (dBm)	Result
WCDMA Band V	4132	V	21.24	38.45	Pass
		H	19.36		
	4183	V	21.43		
		H	19.52		
	4233	V	21.37		
		H	19.52		

## 4.6. Radiated Spurious Emssion

### LIMIT

-13dBm

### TEST CONFIGURATION



### TEST RESULTS

1. EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be

performed by rotating the test item and adjusting the receiving antenna polarization.

5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
6. The measurement results are obtained as described below:  
Power(EIRP)=PMea- PAg - Pcl + Ga  
We used SMF100A micowave signal generator which signal level can up to 33dBm,so we not used power Amplifier for substitution test; The measurement results are amend as described below:  
Power(EIRP)=PMea- Pcl + Ga
7. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.  
ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

## **TEST RESULTS**

Worst case at GSM850/DCS1800/WCDMA B2/B5

GSM850					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
128	156.091	Vertical	-60.16	-13.00	Pass
	233.887	V	-67.78		
	1648.505	V	-44.48		
	2282.013	V	-50.97		
	4113.730	V	-53.52		
	5734.148	V	-52.00		
	156.091	Horizontal	-63.83	-13.00	Pass
	259.910	H	-65.43		
	1674.056	H	-45.22		
	2262.044	H	-49.42		
	3825.990	H	-54.63		
	6219.277	H	-51.76		
190	156.091	Vertical	-63.83	-13.00	Pass
	259.910	V	-65.43		
	1674.056	V	-45.22		
	2262.044	V	-49.42		
	3825.990	V	-54.63		
	6219.277	V	-51.76		
	200.359	Horizontal	-66.20	-13.00	Pass
	259.910	H	-66.59		
	1013.271	H	-52.50		
	1672.217	H	-45.23		
	4593.075	H	-52.96		
	7992.857	H	-46.73		
251	156.091	Vertical	-62.73	-13.00	Pass
	390.821	V	-65.80		
	1013.271	V	-53.18		
	1698.136	V	-46.97		
	4113.730	V	-53.28		
	9067.719	V	-45.47		
	58.108	Horizontal	-75.03	-13.00	Pass
	233.887	H	-68.96		
	1698.136	H	-49.34		
	2345.558	H	-51.11		
	4113.730	H	-53.28		
	8457.962	H	-45.99		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of not record in the report are very lower than the limit and not show in test report.

PCS1900					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
512	41.459	Vertical	-75.22	-13.00	Pass
	182.211	V	-73.52		
	1716.895	V	-48.72		
	1901.586	V	-44.27		
	4119.700	V	-52.75		
	6834.070	V	-49.44		
	156.091	Horizontal	-65.17	-13.00	Pass
	259.910	H	-60.73		
	1305.992	H	-54.60		
	2597.876	H	-46.90		
	4119.700	H	-52.96		
	5554.084	H	-49.12		
661	259.910	Vertical	-59.15	-13.00	Pass
	414.897	V	-62.57		
	1013.271	V	-55.32		
	2606.452	V	-45.83		
	3831.542	V	-52.83		
	7652.562	V	-47.48		
	182.211	Horizontal	-72.73	-13.00	Pass
	442.007	H	-72.53		
	1753.109	H	-49.13		
	2577.974	H	-48.11		
	4119.700	H	-52.75		
	5643.398	H	-49.83		
810	156.091	Vertical	-69.32	-13.00	Pass
	414.897	V	-65.82		
	1575.898	V	-51.12		
	2448.239	V	-49.47		
	5725.838	V	-46.20		
	11823.840	V	-42.78		
	182.211	Horizontal	-64.06	-13.00	Pass
	414.897	H	-63.51		
	1577.631	H	-51.10		
	2497.135	H	-47.89		
	5725.838	H	-46.10		
	10901.530	H	-42.60		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of not record in the report are very lower than the limit and not show in test report.



WCDMA Band II					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
9262	41.459	Vertical	-63.91	-13.00	Pass
	266.387	V	-64.03		
	1197.424	V	-54.89		
	2883.666	V	-48.66		
	5554.084	V	-46.27		
	8976.130	V	-45.82		
	41.459	Horizontal	-68.06	-13.00	Pass
	414.897	H	-66.30		
	1196.109	H	-52.92		
	1575.898	H	-51.50		
	5554.084	H	-46.99		
	8924.210	H	-45.65		
9400	41.459	Vertical	-63.86	-13.00	Pass
	378.645	V	-62.93		
	1196.109	V	-53.54		
	2519.179	V	-46.23		
	4302.896	V	-55.20		
	6514.705	V	-52.34		
	41.459	Horizontal	-64.22	-13.00	Pass
	414.897	H	-64.56		
	1255.348	H	-55.75		
	2890.009	H	-48.74		
	5643.398	H	-48.28		
	10065.760	H	-44.17		
9538	184.144	Vertical	-67.37	-13.00	Pass
	307.700	V	-65.94		
	1198.740	V	-60.83		
	2342.982	V	-59.44		
	5098.612	V	-52.60		
	10109.650	V	-44.17		
	184.144	Horizontal	-70.03	-13.00	Pass
	414.897	H	-66.72		
	1196.109	H	-61.10		
	2287.032	H	-59.44		
	5717.540	H	-49.72		
	10869.960	H	-43.16		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of not record in the report are very lower than the limit and not show in test report.

WCDMA Band V					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
4132	156.091	Vertical	-67.85	-13.00	Pass
	259.910	V	-66.02		
	1648.505	V	-40.09		
	2497.135	V	-47.12		
	4113.730	V	-53.52		
	9457.217	V	-44.09		
	233.887	Horizontal	-67.78	-13.00	Pass
	469.237	H	-68.07		
	1646.695	H	-49.30		
	2282.013	H	-50.97		
	4113.730	H	-53.52		
	9054.577	H	-44.98		
4183	156.091	Vertical	-61.83	-13.00	Pass
	259.910	V	-63.43		
	1674.056	V	-45.22		
	2497.135	V	-48.19		
	5709.254	V	-51.98		
	10713.45	V	-43.33		
	199.656	Horizontal	-69.74	-13.00	Pass
	259.910	H	-66.59		
	1672.217	H	-41.23		
	2497.135	H	-47.50		
	3825.990	H	-54.63		
	9863.446	H	-43.98		
4233	156.091	Vertical	-59.73	-13.00	Pass
	259.910	V	-64.90		
	1694.409	V	-44.63		
	2183.902	V	-51.74		
	5143.171	V	-51.91		
	9067.719	V	-45.47		
	156.091	Horizontal	-68.35	-13.00	Pass
	200.359	H	-66.55		
	1297.411	H	-55.66		
	1698.136	H	-47.34		
	4974.445	H	-52.92		
	7487.887	H	-47.14		

Remark :


1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of not record in the report are very lower than the limit and not show in test report.

#### 4.7. Frequency stability V.S. Temperature measurement

##### LIMIT

2.5ppm

##### TEST CONFIGURATION



**Note :** Measurement setup for testing on Antenna connector

##### TEST PROCEDURE

1. The equipment under test was connected to an external DC power supply and input rated voltage.
2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators.
3. The EUT was placed inside the temperature chamber.
4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency.
5. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency.
6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

##### TEST RESULTS

Worst case at GSM850/DCS1800/WCDMA B2/B5 mid channel

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	24	0.029	2.5	Pass
	-20	23	0.027		
	-10	21	0.025		
	0	17	0.020		
	10	16	0.019		
	20	14	0.017		
	30	15	0.018		
	40	18	0.022		
	50	20	0.024		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	27	0.014	2.5	Pass
	-20	24	0.013		
	-10	23	0.012		
	0	20	0.011		
	10	22	0.012		
	20	18	0.010		
	30	19	0.010		
	40	21	0.011		
	50	22	0.012		


Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	22	0.012	2.5	Pass
	-20	16	0.009		
	-10	17	0.009		
	0	14	0.007		
	10	13	0.007		
	20	10	0.005		
	30	11	0.006		
	40	15	0.008		
	50	17	0.009		
Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	19	0.023	2.5	Pass
	-20	16	0.019		
	-10	14	0.017		
	0	15	0.018		
	10	13	0.016		
	20	8	0.010		
	30	10	0.012		
	40	13	0.016		
	50	16	0.019		

## 4.8. Frequency stability V.S. Voltage measurement

### LIMIT

2.5ppm

### TEST CONFIGURATION



Note : Measurement setup for testing on Antenna connector

### TEST PROCEDURE

1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage.
2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.
3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.

### TEST RESULTS

Worst case at GSM850/DCS1800/WCDMA B2/B5 mid channel


Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.35	10	0.012	2.5	Pass
	3.70	8	0.010		
	3.50	11	0.013		
Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.35	16	0.009	2.5	Pass
	3.70	15	0.008		
	3.50	18	0.010		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.35	18	0.010	2.5	Pass
	3.70	21	0.011		
	3.50	15	0.008		
Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.35	19	0.023	2.5	Pass
	3.70	21	0.025		
	3.50	16	0.019		

## 4.9. Peak-Average Ratio

### LIMIT

13dB

### TEST CONFIGURATION



### TEST PROCEDURE

According with KDB 971168

1. The signal analyzer' s CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals(>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal " RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the " on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power


### TEST RESULTS

#### Worst case GSM1900,EGPRS1900,WCDMA BAND1900


Band	Channel	Frequency(MHz)	PAR	Limit(dB)	Result
GSM1900	512	1850.2	9.54	13	Pass
	661	1880.0	9.58	13	Pass
	810	1909.8	9.60	13	Pass

Band	Channel	Frequency(MHz)	PAR	Limit(dB)	Result
8PSK1900	512	1850.2	9.54	13	Pass
	661	1880.0	9.56	13	Pass
	810	1909.8	9.52	13	Pass


Band	Channel	Frequency(MHz)	PAR	Limit(dB)	Result
WCDMA BAND II	9262	1852.4	2.52	13	Pass
	9400	1880.0	2.78	13	Pass
	9538	1907.6	2.68	13	Pass

**GSM1900**


Channel 512

**EGPRS1900 for 8PSK**


Channel 512




Channel 661




Channel 661



Channel 810





Channel 810





## 5. Test Setup Photos of the EUT

Radiated emission:



## 6. External and Internal Photos of the EUT

### External photos of the EUT















**Internal photos of the EUT**









-----End of Report-----