Bluetooth

Frequency: 2441 MHz; Duty Cycle: 1:2.98951; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used (interpolated): f = 2441 MHz; σ = 1.821 S/m; ϵ_r = 37.696; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1258; Calibrated: 3/18/2021

- Probe: EX3DV4 - SN3902; ConvF(7.82, 7.82, 7.82) @ 2441 MHz; Calibrated: 3/18/2021

- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: 1629

Right Touch Earpiece/ch 39/Area Scan (7x7x1): Measurement grid: dx=12mm, dy=12mm

Info: Interpolated medium parameters used for SAR evaluation. Maximum value of SAR (measured) = 0.164 W/kg

Right Touch Earpiece/ch 39/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,

dz=5mm

Reference Value = 7.706 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.700 W/kg

SAR(1 g) = 0.065 W/kg; SAR(10 g) = 0.021 W/kg

Smallest distance from peaks to all points 3 dB below = 2.8 mm

Ratio of SAR at M2 to SAR at M1 = 13.2%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.210 W/kg



0 dB = 0.210 W/kg = -6.78 dBW/kg

Bluetooth

Frequency: 2441 MHz; Duty Cycle: 1:2.98951; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used (interpolated): f = 2441 MHz; σ = 1.87 S/m; ϵ_r = 37.608; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1258; Calibrated: 3/18/2021

- Probe: EX3DV4 - SN3902; ConvF(7.82, 7.82, 7.82) @ 2441 MHz; Calibrated: 3/18/2021

- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: 1629

Right Flat/ch 39/Area Scan (7x7x1): Measurement grid: dx=12mm, dy=12mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.19 W/kg

Right Flat/ch 39/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.63 V/m; Power Drift = -0.19 dB Peak SAR (extrapolated) = 2.44 W/kg

SAR(1 g) = 0.601 W/kg; SAR(10 g) = 0.165 W/kg

Smallest distance from peaks to all points 3 dB below = 3.6 mm

Ratio of SAR at M2 to SAR at M1 = 27.9%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.53 W/kg



0 dB = 1.53 W/kg = 1.85 dBW/kg